

SkeleWAM: Skeleton World-Action Modeling for Efficient Robotic Manipulation

Juyi Sheng
Peking University

Logss2024@stu.pku.edu.cn

Hua Wang
Peking University

huawang@stu.pku.edu.cn

Mengyuan Liu
Peking University

liumengyuan@pku.edu.cn

Abstract

*World action models (WAMs) combine robot action generation with future state prediction. Existing WAMs typically predict videos or learned visual latents, which represent interaction geometry only implicitly and may retain appearance information unrelated to control. We introduce **SkeleWAM**, a compact WAM that represents a manipulation scene as a sparse 3D skeleton composed of robot joints, object centers, and interaction points. Constructed online from current RGB-D observations and robot proprioception, the skeleton provides a unified geometric state for action generation and future skeleton prediction. Future skeleton prediction provides additional geometric supervision for action learning without requiring visual reconstruction. At inference, SkeleWAM generates actions directly from the current skeleton and language instruction, while Medoid Action Consensus (MAC) serves as an auxiliary consensus strategy for stochastic action samples. On LIBERO-Plus, SkeleWAM achieves an overall success rate of 85.9% with 57.1M parameters, outperforming Cosmos-Policy by 3.7 percentage points. These results demonstrate that sparse 3D robot-object structure provides an effective state space for robust and parameter-efficient world action learning. The project is available at <https://skelewam-project.github.io/>.*

1. Introduction

Learning-based robotic manipulation has rapidly evolved from task-specific visuomotor policies to general-purpose robot foundation models. ACT learns action chunks from visual observations, while Diffusion Policy and DP3 model expressive action distributions using 2D and 3D visual representations, respectively [5, 21, 22]. As model pretraining and robot datasets continue to scale, generalist policies and vision-language-action (VLA) models, including RT-2, Octo, OpenVLA, π_0 , and $\pi_{0.5}$, have demonstrated increasingly broad capabilities across diverse manipulation tasks and environments [1, 2, 8, 9, 15]. World action models (WAMs) jointly model robot action generation and future

state prediction, where the latter provides additional supervision for learning how manipulation scenes evolve under robot actions [11, 12, 19, 20]. Many existing WAMs represent future states as generated videos or learned visual latents [4, 14, 19]. Although latent prediction reduces the computational cost of explicit video generation, the information retained by visual latents is largely shaped by the underlying visual encoder and its pretraining objective. More importantly, compressing visual observations does not by itself isolate the geometric variables that govern robot-object interactions, such as their spatial configurations and relative motions. This raises a fundamental question: *can a sparse representation of robot-object structure support effective world action learning while substantially reducing model complexity?*

Our key observation is that the aspects of a manipulation scene most relevant to control can be represented as a *skeleton* consisting of a sparse set of 3D landmarks on the robot and manipulated objects. The robot is represented by the 3D positions of its joints, while each object is represented by its center and a set of interaction points connected to that center. The object center captures its overall spatial location, whereas the interaction points identify locations relevant to robot contact and manipulation. Together, these landmarks provide a compact and explicit representation of the robot configuration and object interaction geometry. We use this unified skeleton as the state representation and jointly learn robot action generation and future skeleton prediction without reconstructing visual appearance.

Building on this representation, we introduce **SkeleWAM**, a compact world action model that operates on sparse skeleton states. Given current RGB-D observations and robot proprioception, SkeleWAM constructs the skeleton online and encodes it as a set of geometric tokens. During training, the model jointly learns robot action generation and future skeleton prediction, allowing future prediction to supervise the shared geometric representation. At inference, the future prediction branch is omitted, and actions are generated directly from the current skeleton and language instruction. To reduce sensitivity to stochastic sampling, SkeleWAM additionally uses Medoid Action Con-




Figure 1. **Sparse skeleton states enable efficient world action modeling.** Existing world action models represent future states as videos, visual latents, or dense 3D dynamics. In contrast, SkeleWAM converts RGB-D observations and robot states into a sparse 3D skeleton comprising robot joints, object centers, and interaction points. During training, it jointly learns robot action generation and future skeleton prediction. This explicit geometric representation achieves a favorable trade-off among task success, inference speed, model size, and computational cost.

sensus (MAC) as an auxiliary inference strategy. MAC selects the trajectory with the smallest average distance to other independently sampled candidates, without requiring a reward model or averaging multiple trajectories.

We evaluate SkeleWAM on the full LIBERO-Plus benchmark in a primary observation-based setting, where object landmarks are estimated from RGB-D observations. We additionally report SkeleWAM (sim-state), which replaces these estimates with privileged simulator coordinates solely as a diagnostic reference. In the primary setting, SkeleWAM achieves an overall success rate of 85.9% with 57.1M parameters, outperforming the strongest compared observation-based baseline, Cosmos-Policy, by 3.7 percentage points. Under camera perturbations, it achieves 93.4% success, exceeding Cosmos-Policy by 17.6 percentage points. The sim-state variant achieves 87.7% overall success, leaving a gap of only 1.8 percentage points from the primary setting. These results support our central hypothesis that sparse and explicit robot-object geometry provides an effective state representation for robust manipulation with a compact world action model.

The main contributions of this work are summarized as follows:

- We formulate world action modeling in a unified, sparse 3D skeleton state space composed of robot joints, object centers, and interaction points, providing an explicit representation of geometry relevant to manipulation.
- We introduce SkeleWAM, a compact model that jointly learns robot action generation and future skeleton prediction, with the latter serving as auxiliary supervision during training. SkeleWAM also employs MAC as an aux-

iliary inference strategy to improve sampling robustness without requiring a reward model.

- We conduct extensive evaluations on the full LIBERO-Plus benchmark, demonstrating the zero-shot robustness and parameter efficiency of SkeleWAM. Systematic ablations examine the effects of skeleton composition, future skeleton supervision, visual skeleton estimation, and MAC.

2. Related Work

2.1. Visuomotor and Vision-Language-Action Models

Visuomotor policies learn direct mappings from observations to robot actions. ACT predicts temporally coherent action chunks [22], while Diffusion Policy and DP3 model multimodal action distributions using image and 3D point-cloud observations, respectively [5, 21]. Vision-language-action (VLA) models extend this paradigm by incorporating pretrained vision-language representations for language-conditioned multitask control. RT-2 and OpenVLA adapt vision-language representations to action generation [2, 9], while π_0 and $\pi_{0.5}$ improve continuous control and generalization through flow matching and heterogeneous co-training [1, 8]. More recent methods improve policy adaptation, action encoding, and model compactness through OpenVLA-OFT, π_0 -FAST, and NORA, respectively [7, 10, 16]. Despite these advances, such policies primarily optimize action prediction and do not explicitly model how manipulation scenes evolve under robot actions.

2.2. World Action Models

To capture how manipulation scenes evolve under robot actions, world action models augment action learning with future state prediction. WorldVLA and UniVLA jointly model action generation and visual world evolution [3, 18], while DreamZero, GE-Act, and Cosmos-Policy leverage pretrained video models for robot control and planning [11, 13, 19]. VLA-JEPA replaces pixel reconstruction with the prediction of future latent target representations [17], whereas Fast-WAM retains future video prediction as a co-training objective but removes future generation at inference [20]. Although latent objectives reduce the computational cost and dependence on pixel reconstruction, both videos and visual latents represent interaction geometry only implicitly rather than parameterizing it as explicit state variables. In contrast, SkeleWAM defines both current and future states directly in a sparse 3D skeleton space composed of robot joints, object centers, and interaction points. It jointly learns action generation and future skeleton prediction, allowing future geometric prediction to supervise representation learning during training without being required for action generation at inference.

3. Method

3.1. Problem Formulation

Given a language instruction ℓ , the current RGB-D observation o_t , and the robot proprioceptive state q_t , our objective is to generate an action chunk

$$\mathbf{A}_t = [\mathbf{a}_t, \dots, \mathbf{a}_{t+H_a-1}] \in \mathbb{R}^{H_a \times d_a}, \quad (1)$$

where $\mathbf{a}_{t+i} \in \mathbb{R}^{d_a}$ denotes a single robot action, H_a is the action horizon, and d_a is the action dimension. SkeleWAM represents the current scene as a sparse 3D skeleton,

$$\mathbf{S}_t = \Phi_\psi(o_t, q_t, \ell) \in \mathbb{R}^{N \times 3}, \quad (2)$$

where N is the number of skeleton nodes and Φ_ψ is the skeleton extractor described in Section 3.2.

For training, we additionally define the future skeleton sequence

$$\mathbf{S}_t^+ = [\mathbf{S}_{t+\delta_1}, \dots, \mathbf{S}_{t+\delta_{H_s}}] \in \mathbb{R}^{H_s \times N \times 3}, \quad (3)$$

where H_s is the number of future states and $0 < \delta_1 < \dots < \delta_{H_s}$ are their temporal offsets. Conditioned on $\mathbf{S}_t$ and ℓ , we jointly learn the action and future skeleton distributions,

$$p_\theta^a(\mathbf{A}_t \mid \mathbf{S}_t, \ell), \quad p_\theta^s(\mathbf{S}_t^+ \mid \mathbf{S}_t, \ell), \quad (4)$$

where θ denotes the world action model parameters. Future skeleton prediction serves as auxiliary supervision during training and is omitted at inference.

3.2. Skeleton World Representation

The scene skeleton consists of robot keypoints and task-relevant object landmarks. For object m , we define

$$\mathbf{P}_{t,m} = [\mathbf{c}_{t,m}; \mathbf{u}_{t,m,1}; \dots; \mathbf{u}_{t,m,L_m}] \in \mathbb{R}^{(1+L_m) \times 3}, \quad (5)$$

where $\mathbf{c}_{t,m}$ denotes the object center and $\mathbf{u}_{t,m,j}$ denotes its j -th interaction point. The complete skeleton is

$$\begin{aligned} \mathbf{S}_t &= [\mathbf{J}_t; \mathbf{P}_{t,1}; \dots; \mathbf{P}_{t,M}], \\ N &= N_r + \sum_{m=1}^M (1 + L_m), \end{aligned} \quad (6)$$

where $\mathbf{J}_t \in \mathbb{R}^{N_r \times 3}$ contains robot joint and end-effector positions, M is the number of objects, and semicolons indicate concatenation along the node dimension.

Robot nodes follow the kinematic connectivity, while each object center connects to its associated interaction points. These connections define the skeletal organization; the model predicts node coordinates. Node identities, ordering, and connectivity remain consistent over time.

Robot keypoints are computed through forward kinematics, and object landmarks are estimated from RGB-D observations using a pretrained perception network that remains fixed during training. All coordinates are expressed in a shared robot-centric frame and normalized using training-set statistics. Future targets contain the corresponding nodes at the specified future times in the demonstration trajectories.

3.3. Skeleton World Action Model

The language instruction is encoded as $\mathbf{C}^\ell = \mathcal{E}_{\text{lang}}(\ell)$. Separate input adapters map the current skeleton, noisy action chunk, and noisy future skeleton sequence to tokens:

$$\begin{aligned} \mathbf{X}_t^c &= \phi_c(\mathbf{S}_t), \\ \mathbf{X}_{t,\tau_a}^a &= \phi_a(\tilde{\mathbf{A}}_{t,\tau_a}), \\ \mathbf{X}_{t,\tau_s}^s &= \phi_s(\tilde{\mathbf{S}}_{t,\tau_s}^+), \end{aligned} \quad (7)$$

where τ_a and τ_s denote noise times, distinct from the environment time step t . The noisy inputs are defined in Section 3.4; the current skeleton remains unperturbed by generative noise.

Following the two-expert Mixture-of-Transformers design of Fast-WAM [20], a world expert processes current and future skeleton tokens with shared parameters, while an action expert processes action tokens. Both experts are conditioned on $\mathbf{C}^\ell$.

For the three token groups ordered as $(\mathbf{X}_t^c, \mathbf{X}_{t,\tau_a}^a, \mathbf{X}_{t,\tau_s}^s)$, we define the block attention mask

$$\mathbf{M} = \begin{bmatrix} 1 & 0 & 0 \\ 1 & 1 & 0 \\ 1 & 0 & 1 \end{bmatrix}. \quad (8)$$




Figure 2. **Overview of SkeleWAM.** Frozen visual perception and forward kinematics construct the current skeleton. Action generation and future skeleton prediction are jointly trained with shared current-skeleton context. At inference, future skeleton prediction is omitted, and Medoid Action Consensus (MAC) selects a representative sampled action chunk. The robot executes its first H_e actions before observing and replanning.

Rows index query groups and columns index key and value groups, with 1 and 0 indicating allowed and blocked attention. Current skeleton tokens attend within their own group. Each prediction group attends to the current skeleton and itself, with no attention between action and future skeleton tokens. The output heads predict vector fields $\hat{v}_\theta^a \in \mathbb{R}^{H_a \times d_a}$ and $\hat{v}_\theta^s \in \mathbb{R}^{H_s \times N \times 3}$ in a single forward pass.

3.4. Training Objective

We train both prediction tasks using flow matching. Given a demonstration pair (A_t, S_t^+) , we sample independent standard Gaussian noise tensors ϵ^a and ϵ^s with matching shapes, and noise times $(\tau_a, \tau_s) \sim \rho$ on $[0, 1]^2$. The interpolation paths are

$$\begin{aligned} \tilde{A}_{t,\tau_a} &= (1 - \tau_a)A_t + \tau_a\epsilon^a, \\ \tilde{S}_{t,\tau_s}^+ &= (1 - \tau_s)S_t^+ + \tau_s\epsilon^s, \end{aligned} \quad (9)$$

where noise time 0 corresponds to data and 1 corresponds to Gaussian noise. The associated target vector fields are

$$v^a = \epsilon^a - A_t, \quad v^s = \epsilon^s - S_t^+. \quad (10)$$

The joint objective is

$$\begin{aligned} \mathcal{L}_{\text{action}} &= \mathbb{E} [\text{MSE}(\hat{v}_\theta^a, v^a)], \\ \mathcal{L}_{\text{skeleton}} &= \mathbb{E} [\text{MSE}(\hat{v}_\theta^s, v^s)], \\ \mathcal{L} &= \mathcal{L}_{\text{action}} + \lambda_s \mathcal{L}_{\text{skeleton}}, \end{aligned} \quad (11)$$

where MSE averages over tensor entries and λ_s weights skeleton supervision. The expectations cover demonstration samples, Gaussian noise, and noise times. Both losses

update the world expert: the skeleton loss supervises future geometric prediction, while the action loss propagates through the current skeleton context.

3.5. Inference and Medoid Action Consensus

At inference, we retain current skeleton processing and the action expert, while omitting future skeleton tokens. Starting from $\tilde{A}_{t,1} \sim \mathcal{N}(0, I)$, we integrate the learned action vector field:

$$\frac{d\tilde{A}_{t,\tau}}{d\tau} = \hat{v}_\theta^a(\tilde{A}_{t,\tau}, \tau; S_t, \ell), \quad \tau : 1 \rightarrow 0. \quad (12)$$

Here, the vector field is written as a function of the noisy action and current conditions. Integration yields the sampled action chunk $A_t = \tilde{A}_{t,0}$.

We employ Medoid Action Consensus (MAC) as an auxiliary strategy for selecting among stochastic action samples. Given $K \geq 2$ candidates $\{A_t^{(k)}\}_{k=1}^K$ generated from independent noise initializations, we compare their first $h \leq H_a$ steps over d_m continuous motion dimensions in normalized action space:

$$d_{ij} = \frac{1}{hd_m} \left\| (A_t^{(i)})_{1:h,1:d_m} - (A_t^{(j)})_{1:h,1:d_m} \right\|_F^2. \quad (13)$$

For notational convenience, the motion dimensions are indexed first. MAC selects the candidate with the smallest average dissimilarity:

$$c_i = \frac{1}{K-1} \sum_{j \neq i} d_{ij}, \quad i_{\text{sel}} = \arg \min_i c_i, \quad (14)$$

$$A_t^{\text{MAC}} = A_t^{(i_{\text{sel}})}.$$




Figure 3. **Qualitative real-world results.** Representative rollouts for opening a drawer, placing a block in a drawer, and stacking bowls. Each row shows the early, interaction, and late stages of a successful rollout, together with the corresponding sparse 3D skeleton. Success rates are computed over 20 trials per task.

The complete selected chunk is retained, including dimensions excluded from distance computation. MAC requires neither a reward nor a value model and avoids averaging potentially incompatible trajectories. For $K = 1$, the sole candidate is used directly. We execute the first $H_e \leq H_a$ actions, update the skeleton from the latest observation, and repeat. The execution horizon H_e controls replanning, while the consensus window h is used only for candidate selection.

4. Experiments

4.1. Simulation Setup

Benchmark and evaluation. We evaluate SkeleWAM on the full LIBERO-Plus benchmark [6], which contains 10,030 variants across seven perturbation categories. We report zero-shot task success rates without fine-tuning on the evaluation variants. Table 1 compares SkeleWAM with VLA policies and world-model-based methods.

Baselines. We compare SkeleWAM with representative VLA policies, including OpenVLA, OpenVLA-OFT, NORA, UniVLA, π_0 , π_0 -Fast, and $\pi_{0.5}$. We also include methods incorporating world modeling or future-state prediction, including WorldVLA, Fast-WAM, VLA-JEPA, GE-Act, and Cosmos-Policy. SkeleWAM uses a frozen pre-trained perception network to estimate object centers and

interaction points from RGB-D observations. These object nodes are combined with robot keypoints obtained through forward kinematics to form the current skeleton. SkeleWAM (sim-state) directly obtains the corresponding object coordinates from simulator states and serves as a privileged-input reference.

Implementation details. We train and evaluate SkeleWAM on an NVIDIA RTX 4090 GPU. Training runs for 60K steps with an effective batch size of 48, jointly predicting $H_a = 32$ action steps and eight future skeleton states. Action and future-skeleton tokens do not attend to each other. At inference, we use 10 flow-integration steps and execute $H_e = 16$ actions before replanning. MAC samples $K = 3$ action trajectories from independent Gaussian noise initializations and computes consensus over their first $h = 10$ motion steps. Future-skeleton prediction is omitted at inference. Additional implementation details are provided in the supplementary material.

4.2. Simulation Results

Zero-shot robustness. As shown in Table 1, SkeleWAM achieves 85.9% overall success with 57.1M parameters, outperforming the strongest compared observation-based baseline, Cosmos-Policy (82.2%), by 3.7 percentage points. Under camera perturbations, SkeleWAM reaches 93.4%, exceeding Cosmos-Policy by 17.6 points. It also achieves

Table 1. Zero-shot success rates (%) on LIBERO-Plus. Parameter counts are approximate. Best observation-based results are bolded; § denotes privileged simulator input.

Method	Params	Camera	Robot	Language	Light	Background	Noise	Layout	Overall
OpenVLA [9]	$\approx 7.5\text{B}$	0.8	3.5	23.0	8.1	34.8	15.2	28.5	15.6
OpenVLA-OFT [10]	$\approx 7.7\text{B}$	56.4	31.9	79.5	88.7	93.3	75.8	74.2	69.6
NORA [7]	$\approx 3.8\text{B}$	2.2	37.0	65.1	45.7	58.6	12.8	62.1	39.0
UniVLA [18]	$\approx 7\text{B}$	1.8	46.2	69.6	69.0	81.0	21.2	31.9	43.9
π_0 [1]	$\approx 3.5\text{B}$	13.8	6.0	58.8	85.0	81.4	79.0	68.9	53.6
π_0 -Fast [16]	$\approx 3\text{B}$	65.1	21.6	61.0	73.2	73.2	74.4	68.8	61.6
$\pi_{0.5}$ [8]	$\approx 3.6\text{B}$	70.6	50.5	84.4	95.7	93.4	87.4	84.1	79.7
WorldVLA [3]	$\approx 7\text{B}$	0.1	27.9	41.6	43.7	17.1	10.9	38.0	25.0
Fast-WAM [20]	$\approx 6.7\text{B}$	16.4	44.5	68.9	78.2	53.7	37.7	60.7	51.5
VLA-JEPA [17]	$\approx 2.3\text{B}$	64.2	67.7	88.1	91.8	93.4	65.8	83.9	77.9
GE-Act [13]	$\approx 2.5\text{B}$	60.7	77.0	77.4	95.8	86.0	90.9	80.2	80.3
Cosmos-Policy [11]	$\approx 2\text{B}$	75.8	63.3	81.7	96.5	88.9	92.7	82.2	82.2
SkeleWAM (ours)	$\approx 57.1\text{M}$	93.4	71.9	89.1	94.7	96.0	93.9	66.6	85.9
SkeleWAM (sim-state) §	$\approx 51.4\text{M}$	96.1	75.2	89.0	96.6	96.7	95.4	69.0	87.7

the best observation-based results under language, background, and noise perturbations, with success rates of 89.1%, 96.0%, and 93.9%, respectively. These results support our motivation to model interaction geometry explicitly: representing robot and object states in a shared robot-centric frame provides a compact state space that remains effective under viewpoint and appearance changes.

Performance under layout perturbations remains limited at 66.6%, compared with 84.1% for $\pi_{0.5}$. This result suggests that sparse geometric observations alone do not fully address generalization to substantially different spatial arrangements.

Simulator-derived skeletons. SkeleWAM (sim-state) achieves 87.7% overall success with 51.4M parameters, improving over RGB-D by 1.8 percentage points. Its success rates under camera and robot initial-state perturbations increase by 2.7 and 3.3 points, respectively, while language performance remains comparable (89.0% versus 89.1%). Since simulator-derived coordinates bypass visual object localization, this setting serves as a privileged-input reference. The relatively small overall gap shows that the frozen perception network provides effective skeleton estimates, while also leaving room for further improvement.

Layout success reaches only 69.0% even with simulator-derived coordinates. The remaining difficulty under layout perturbations therefore extends beyond visual localization and also reflects limitations in policy generalization to novel




Figure 4. **Real-world experimental setup.** An ARX R5 robot with external and wrist-mounted RealSense cameras operates in a tabletop workspace containing a drawer unit, blocks, and bowls.

spatial configurations.

4.3. Real-World Experiments

Experimental setup. We evaluate SkeleWAM on an ARX R5 robot with external and wrist-mounted RealSense cameras (Figure 4). We compare against Fast-WAM, $\pi_{0.5}$, and Cosmos-Policy on five real-world tasks, with 20 trials per task for each method. We report per-task success rates and their unweighted mean.

Table 2. Success rates (%) on five real-world manipulation tasks. Each method is evaluated over 20 trials per task. Average is the unweighted mean across tasks. Best results in each column, including ties, are bolded.

Method	Open Drawer	Close Drawer	Stack Blocks	Stack Bowls	Put Block in Drawer	Average $\uparrow$
Fast-WAM	80	85	80	85	85	83
$\pi_{0.5}$	80	80	70	75	75	76
Cosmos-Policy	85	85	90	90	85	87
SkeleWAM (ours)	80	90	90	95	90	89

Real-world performance. As shown in Table 2, SkeleWAM achieves 89% average success, exceeding Cosmos-Policy, Fast-WAM, and $\pi_{0.5}$ by 2, 6, and 13 percentage points, respectively. It achieves the highest or joint-highest success rate on four of the five tasks. Figure 3 visualizes representative successful rollouts at early, interaction, and late stages. The corresponding 3D skeletons compactly capture the evolving robot-object configurations used for action generation. Together, the quantitative and qualitative results demonstrate the effectiveness of SkeleWAM on the evaluated real-world manipulation tasks.

4.4. Ablation Studies

We ablate six design choices: object skeleton composition, future-skeleton supervision, cross-branch attention, action execution horizon, the number of MAC candidates, and the consensus window. All experiments use the RGB-D setting on the full LIBERO-Plus benchmark, with fixed training data, optimization settings, and evaluation variants. Unless varied explicitly, we use $H_a = 32$, $H_e = 16$, $K = 3$, and $h = 10$. Tables 3 and 4 summarize the model and inference ablations, respectively.

Object skeleton composition. Keeping robot keypoints unchanged, we compare object representations containing centers only, interaction points only, and both types of points. The combined representation achieves 85.9% success, outperforming centers only (82.3%) and interaction points only (77.7%) by 3.6 and 8.2 percentage points, respectively (Table 3, panel a). Object centers provide stable spatial references, while interaction points describe manipulation-relevant regions. Their combination therefore provides a more complete representation of object interaction geometry.

Contribution of future-skeleton prediction. Removing the future-skeleton loss and future tokens reduces success from 85.9% to 80.1%, while retaining the same current-skeleton processing and action-generation backbone (Table 3, panel b). Since both variants use the same action-only inference procedure, the 5.8-point improvement comes

from future-skeleton supervision during training. This result shows that predicting future geometric states helps the shared world expert learn representations that benefit action generation.

Cross-branch attention. We compare future-to-action ($S^+ \rightarrow A$), action-to-future ($A \rightarrow S^+$), and no cross-branch attention, while retaining the current-skeleton context and both training objectives. No cross-branch attention achieves 85.9% success, compared with 85.6% for $S^+ \rightarrow A$ and 84.8% for $A \rightarrow S^+$ (Table 3, panel c). These relatively small differences, together with the larger drop after removing future-skeleton supervision, indicate that the main benefit comes from co-training through the shared world expert rather than direct information exchange between the two prediction branches. We therefore use no cross-branch attention, which also allows the future-skeleton branch to be removed at inference.

Action execution horizon. With $H_a = 32$, $K = 3$, and $h = 10$, executing 5, 16, and 32 actions before replanning yields 80.7%, 85.9%, and 81.8% success, respectively (Table 4, panel a). The 16-step horizon improves over the shorter and longer settings by 5.2 and 4.1 percentage points. This intermediate horizon balances feedback from updated observations with temporally consistent action execution. We therefore use $H_e = 16$ by default.

Number of MAC candidates. We vary the number of independently sampled action candidates as $K \in \{1, 3, 5, 10\}$ while fixing $h = 10$. Here, $K = 1$ corresponds to single-trajectory sampling without MAC. Using three candidates improves success from 84.2% to 85.9% (Table 4, panel b). Increasing K to 5 or 10 yields 85.2% and 84.1%, showing that performance does not increase monotonically with the sampling budget. We therefore use $K = 3$, which achieves the best result with limited additional inference cost.

Consensus window. We vary the trajectory prefix used to compute MAC distances as $h \in \{3, 5, 10, 16\}$ while fixing $K = 3$ and $H_e = 16$. The corresponding success rates are

Table 3. Model ablations on the full LIBERO-Plus benchmark in the RGB-D setting. Each panel changes one design choice. Arrows indicate information flow between action tokens (A) and future-skeleton tokens (S^+). Inference uses $H_a = 32$, $H_e = 16$, $K = 3$, and $h = 10$.

Configuration	Success (%)
<i>(a) Object skeleton composition</i>	
Centers only	82.3
Interaction points only	77.7
Centers + interaction points (default)	85.9
<i>(b) Training objective</i>	
Action only	80.1
Action + future skeleton (default)	85.9
<i>(c) Cross-branch attention</i>	
$S^+ \rightarrow A$	85.6
$A \rightarrow S^+$	84.8
No cross-branch attention (default)	85.9

Table 4. Inference ablations on LIBERO-Plus in the RGB-D setting. We fix $H_a = 32$. Panel (a) varies H_e with $K = 3$ and $h = 10$; panel (b) varies K with $H_e = 16$ and $h = 10$; panel (c) varies h with $H_e = 16$ and $K = 3$.

Configuration	Success (%)
<i>(a) Action execution horizon</i>	
$H_e = 5$	80.7
$H_e = 16$ (default)	85.9
$H_e = 32$	81.8
<i>(b) Number of MAC candidates</i>	
$K = 1$ (without MAC)	84.2
$K = 3$ (default)	85.9
$K = 5$	85.2
$K = 10$	84.1
<i>(c) Consensus window</i>	
$h = 3$	85.3
$h = 5$	85.4
$h = 10$ (default)	85.9
$h = 16$	85.7

85.3%, 85.4%, 85.9%, and 85.7% (Table 4, panel c). Performance is relatively stable across the tested windows, with a maximum difference of 0.6 percentage points. The best result is obtained with $h = 10$, suggesting that a moderate temporal window captures sufficient trajectory consistency without placing excessive weight on more distant actions. We therefore use $h = 10$ by default.

5. Conclusion

We introduced SkeleWAM, a compact world action model that represents manipulation scenes as sparse 3D skeletons composed of robot joints, object centers, and interaction points. By jointly learning robot action generation and future skeleton prediction, SkeleWAM uses future geometric dynamics as auxiliary supervision during training without requiring visual reconstruction or additional world prediction at inference. We further introduced Medoid Action Consensus as a lightweight strategy for selecting a representative trajectory from stochastic action samples without relying on a reward model.

Experiments on the full LIBERO-Plus benchmark and five real-world manipulation tasks demonstrate that explicit robot-object geometry provides an effective and parameter-efficient state space for world action learning. SkeleWAM achieves strong zero-shot robustness with substantially fewer parameters than the compared VLA and world-model-based methods, while the ablations confirm the benefits of combining object centers with interaction points and of predicting future skeleton states during training. The remaining performance gap under large layout changes suggests that sparse geometry alone does not fully capture the variation required for spatial generalization. Future work may address this limitation by incorporating uncertainty-aware perception, adaptive interaction landmarks, and richer relational structure while preserving the compactness of the skeleton representation.

References

- [1] Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Lucy Xiaoyang Shi, James Tanner, Quan Vuong, Anna Walling, Haohuan Wang, and Ury Zhilinsky. π_0 : A vision-language-action flow model for general robot control. In *Proceedings of Robotics: Science and Systems (RSS)*, 2025. 1, 2, 6
- [2] Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Xi Chen, Krzysztof Choromanski, Tianli Ding, Danny Driess, Avinava Dubey, Chelsea Finn, Pete Florence, Chuyuan Fu, Montse Gonzalez Arenas, Keerthana Gopalakrishnan, Kehang Han, Karol Hausman, Alex Herzog, Jasmine Hsu, Brian Ichter, Alex Irpan, Nikhil Joshi, Ryan Julian, Dmitry Kalashnikov, Yuheng Kuang, Isabel Leal, Lisa Lee, Tsang-Wei Edward Lee, Sergey Levine, Yao Lu, Henryk Michalewski, Igor Mordatch, Karl Pertsch, Kanishk Rao, Krista Reymann, Michael Ryoo, Grecia Salazar, Pannag Sanketi, Pierre Sermanet, Jaspiar Singh, Anikait Singh, Radu Soricut, Huong Tran, Vincent Vanhoucke, Quan Vuong, Ayzaan Wahid, Stefan Welker, Paul Wohlhart, Jialin Wu, Fei Xia, Ted Xiao, Peng Xu, Sichun Xu, Tianhe Yu, and Brianna Zitkovich. Rt-2: Vision-language-action models

- transfer web knowledge to robotic control. In *arXiv preprint arXiv:2307.15818*, 2023. 1, 2
- [3] Jun Cen, Chaohui Yu, Hangjie Yuan, Yuming Jiang, Siteng Huang, Jiayan Guo, Xin Li, Yibing Song, Hao Luo, Fan Wang, Deli Zhao, and Hao Chen. Worldvla: Towards autoregressive action world model, 2025. 3, 6
 - [4] Jialei Chen, Kai Wang, Kang Chen, Shuaihang Chen, Feng Gao, Wenhao Tang, Zhiyuan Li, Weilin Liu, Zhuyu Yao, Boxun Li, Yuanbo Xu, and Chao Yu. Lawam: Latent world action models for efficient dynamics-aware robot policies, 2026. 1
 - [5] Cheng Chi, Siyuan Feng, Yilun Du, Zhenjia Xu, Eric Cousineau, Benjamin Burchfiel, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion. In *Proceedings of Robotics: Science and Systems (RSS)*, 2023. 1, 2
 - [6] Senyu Fei, Siyin Wang, Junhao Shi, Zihao Dai, Jikun Cai, Pengfang Qian, Li Ji, Xinzhe He, Shiduo Zhang, Zhaoye Fei, Jinlan Fu, Jingjing Gong, and Xipeng Qiu. Libero-plus: In-depth robustness analysis of vision-language-action models, 2025. 5
 - [7] Chia-Yu Hung, Qi Sun, Pengfei Hong, Amir Zadeh, Chuan Li, U Tan, Navonil Majumder, Soujanya Poria, et al. Nora: A small open-sourced generalist vision language action model for embodied tasks. *arXiv preprint arXiv:2504.19854*, 2025. 2, 6
 - [8] Physical Intelligence, Kevin Black, Noah Brown, James Darpinian, Karan Dhabalia, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Manuel Y. Gailiker, Dibya Ghosh, Lachy Groom, Karol Hausman, Brian Ichter, Szymon Jakubczak, Tim Jones, Liyiming Ke, Devin LeBlanc, Sergey Levine, Adrian Li-Bell, Mohith Mothukuri, Suraj Nair, Karl Pertsch, Allen Z. Ren, Lucy Xiaoyang Shi, Laura Smith, Jost Tobias Springenberg, Kyle Stachowicz, James Tanner, Quan Vuong, Homer Walke, Anna Walling, Haohuan Wang, Lili Yu, and Ury Zhilinsky. $\pi_{0.5}$: a vision-language-action model with open-world generalization, 2025. 1, 2, 6
 - [9] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, Quan Vuong, Thomas Kollar, Benjamin Burchfiel, Russ Tedrake, Dorsa Sadigh, Sergey Levine, Percy Liang, and Chelsea Finn. Openvla: An open-source vision-language-action model, 2024. 1, 2, 6
 - [10] Moo Jin Kim, Chelsea Finn, and Percy Liang. Fine-tuning vision-language-action models: Optimizing speed and success. In *Proceedings of Robotics: Science and Systems*, 2025. 2, 6
 - [11] Moo Jin Kim, Yihuai Gao, Tsung-Yi Lin, Yen-Chen Lin, Yunhao Ge, Grace Lam, Percy Liang, Shuran Song, Ming-Yu Liu, Chelsea Finn, et al. Cosmos policy: Fine-tuning video models for visuomotor control and planning. *arXiv preprint arXiv:2601.16163*, 2026. 1, 3, 6
 - [12] Lin Li, Qihang Zhang, Yiming Luo, Shuai Yang, Ruilin Wang, Fei Han, Mingrui Yu, Zelin Gao, Nan Xue, Xing Zhu, et al. Causal world modeling for robot control. In *Proceedings of Robotics: Science and Systems (RSS)*, 2026. 1
 - [13] Yue Liao, Pengfei Zhou, Siyuan Huang, Donglin Yang, Shengcong Chen, Yuxin Jiang, Yue Hu, Jingbin Cai, Si Liu, Jianlan Luo, Liliang Chen, Shuicheng Yan, Maoqing Yao, and Guanghui Ren. Genie envisioner: A unified world foundation platform for robotic manipulation, 2025. 3, 6
 - [14] Hao Luo, Wanpeng Zhang, Yicheng Feng, Sipeng Zheng, Haiweng Xu, Chaoyi Xu, Ziheng Xi, Yuhui Fu, and Zongqing Lu. Being-h0.7: A latent world-action model from egocentric videos, 2026. 1
 - [15] Octo Model Team, Dibya Ghosh, Homer Walke, Karl Pertsch, Kevin Black, Oier Mees, Sudeep Dasari, Joey Hejna, Charles Xu, Jianlan Luo, Tobias Kreiman, You Liang Tan, Lawrence Yunliang Chen, Pannag Sanketi, Quan Vuong, Ted Xiao, Dorsa Sadigh, Chelsea Finn, and Sergey Levine. Octo: An open-source generalist robot policy. In *Proceedings of Robotics: Science and Systems*, Delft, Netherlands, 2024. 1
 - [16] Karl Pertsch, Kyle Stachowicz, Brian Ichter, Danny Driess, Suraj Nair, Quan Vuong, Oier Mees, Chelsea Finn, and Sergey Levine. Fast: Efficient action tokenization for vision-language-action models. *arXiv preprint arXiv:2501.09747*, 2025. 2, 6
 - [17] Jingwen Sun, Wenyao Zhang, Zekun Qi, Shaojie Ren, Zezhi Liu, Hanxin Zhu, Guangzhong Sun, Xin Jin, and Zhibo Chen. Vla-jepa: Enhancing vision-language-action model with latent world model, 2026. 3, 6
 - [18] Yuqi Wang, Xinghang Li, Wenxuan Wang, Junbo Zhang, Yingyan Li, Yuntao Chen, Xinlong Wang, and Zhaoxiang Zhang. Unified vision-language-action model. In *International Conference on Learning Representations*, pages 80929–80944, 2026. 3, 6
 - [19] Seonghyeon Ye, Yunhao Ge, Kaiyuan Zheng, Shenyuan Gao, Sihyun Yu, George Kurian, Suneel Indupuru, You Liang Tan, Chuning Zhu, Jiannan Xiang, et al. World action models are zero-shot policies. *arXiv preprint arXiv:2602.15922*, 2026. 1, 3
 - [20] Tianyuan Yuan, Zibin Dong, Yicheng Liu, and Hang Zhao. Fast-wam: Do world action models need test-time future imagination? *arXiv preprint arXiv:2603.16666*, 2026. 1, 3, 6
 - [21] Yanjie Ze, Gu Zhang, Kangning Zhang, Chenyuan Hu, Muhan Wang, and Huazhe Xu. 3d diffusion policy: Generalizable visuomotor policy learning via simple 3d representations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2024. 1, 2
 - [22] Tony Z Zhao, Vikash Kumar, Sergey Levine, and Chelsea Finn. Learning fine-grained bimanual manipulation with low-cost hardware. In *Proceedings of Robotics: Science and Systems (RSS)*, 2023. 1, 2