

Fisheye-VLA: Decoupling Coverage and Acuity for Manipulation with a Single Fisheye Camera

fisheyevla.github.io

Ziang Ren^{1,2}, Zike Yan^{1,2}, Raymond Zhang^{3,4}, Xuguo He³, and Zhongyu Li^{1,2,*}

¹Hong Kong Embodied AI Lab

²The Chinese University of Hong Kong, Hong Kong SAR, China

³DeepCybo ⁴University of Washington, Seattle, WA, USA

*Corresponding author


Abstract

Manipulation requires both broad scene awareness and detailed local feedback, yet conventional camera rigs provide them through separate front and wrist cameras. We present Fisheye-VLA, a visual interface that brings these capabilities together using a single passive fisheye. A global view preserves the workspace, while local perspective crops direct detail toward the interaction. The key design question is where this local visual budget should go. We answer it through a controlled re-rendering study, comparing alternative crop directions on the same recorded observations. The study finds that end-effector-centered views capture most of the estimated benefit of a much larger candidate pool, motivating a compact allocation around both hands. Our interface uses calibrated end-effector projection and motion lead to track the crops, while a shared ray encoding preserves their spatial meaning as they move. Integrated with a pretrained VLA, it achieves 84% and 82% success in the two expanded tabletop regions, where some target placements extend beyond the front-camera coverage, and supports shelf and conveyor manipulation. Ablations show that local crops and their viewing directions become more important in the larger workspace regions. The results demonstrate that a single fisheye can support these manipulation tasks without physical wrist cameras.

(a) Robot and fisheye



(b) Policy views



(c) Scene coverage




Figure 1: Fisheye-VLA uses one fixed camera (boxed) to supply a global view and two interaction-centered crops, each 224×224 . White outlines mark the 90° front-camera field of view. Rendering local detail from the wider fisheye image supports manipulation without wrist cameras.

1. Introduction

A front-facing camera sees the workspace; a wrist camera sees the interaction up close. This division is a familiar and effective basis for learned manipulation [1]. It also makes a consequential design choice: coverage and acuity are tied to separate pieces of hardware. Once the rig is built, where a policy can see and where it can see in detail are largely fixed by camera placement. We argue that this coupling is an artifact of the rig, rather than a requirement of manipulation.

The distinction matters as vision-language-action (VLA) policies take on more varied tasks [2]. An object at the table’s edge, a mug on a shelf, and a moving object on a conveyor demand different combinations of scene context and local detail. A robot should be able to retain the whole workspace while spending detail where the current action needs it.

With a single passive fisheye, the robot records a wide field in one exposure and renders local perspective views from that image. The full scene remains available when a local view moves. We call this interface Fisheye-VLA (Fig. 1). Its local views concentrate the policy’s visual capacity around interaction using the same captured pixels. Figure 1c shows the coverage difference directly: the 90° front-camera footprint omits peripheral tabletop and elevated shelf areas that remain visible in the fisheye image.

The projection explains why a fisheye is particularly suited to this role. In the ideal equidistant model, image radius is $\rho = f\theta$, so radial angular sampling density $d\rho/d\theta = f$ is constant. Equal radial angular intervals therefore occupy equal source-pixel spans near the center and periphery. A rectilinear camera instead follows $\rho = f \tan \theta$, which diverges as θ approaches 90°; a finite perspective image cannot cover a full hemisphere [3]. Local crops can therefore move over a wide angular range with comparable radial sampling. Our renderer uses the calibrated lens model to account for departures from ideal equidistance.

The sensor alone does not determine the interface. Resizing the whole fisheye image to a fixed visual budget leaves an interaction region with few pixels. Rendering every possible close-up spends tokens on redundant observations. The central question is therefore *where the limited high-resolution budget should go*. Existing active-vision systems address this question through additional hardware, gaze supervision, or learned camera control [4; 5; 6]. A calibrated fisheye gives us another option: measure the value of an allocation before introducing a controller to choose it.

Re-rendering lets us compare local views while holding the scene, robot state, and crop count fixed. The study finds that end-effector placement improves on random allocation, with a smaller additional benefit from observing the second hand. This motivates the per-hand streams developed in Sec. 3 and evaluated in Sec. 5.

To implement this allocation, we need to place the crops and describe their changing viewing directions to the policy. The panorama remains available for target and scene context as the local streams follow the end-effectors. Calibrated end-effector projection places the crops, and causal motion lead keeps them ahead of a moving hand. A common spherical ray encoding tells the policy where each visual token originated as the crops move. The same rendering rule can also be driven by tracked handheld-gripper poses, making UMI-style collection a natural extension of the interface.

Our contributions are threefold. **Single-camera VLA manipulation over an extended workspace.** We develop a fisheye-based bimanual system and multi-task demonstration set supporting tabletop, shelf, and conveyor manipulation through one fixed sensor (Tables 3 and 4).

A shared geometric interface for global and local views. A persistent global stream and action-centered local streams share a geometric reference, allowing coverage and local acuity to be allocated

Table 1: Observation interfaces and view-construction requirements.

Interface	Supply of local detail	Allocation requirement	View cost	View rule / wrist dependence
Wrist + front [1]	Physical wrist images	Camera mounting	Separate capture streams	Rig-specific wrist views
EyeRobot [4]	Foveated mechanical eye	Learned BC-RL gaze	Camera actuation	Eye-centered observations
GIAVA [5]	Foveated active-camera images	Human gaze + learned gaze	Actuation + tokenization	Gaze-conditioned image grid
SaPaVe [6]	Actively redirected camera	Semantic camera learning	Camera actuation	Camera-conditioned policy
WristWorld [7]	Generated wrist-view video	Geometry + video model	Reconstruction + generation	Synthesized wrist viewpoints
EgoMimic [8]	Head and robot wrist views	Human/robot data alignment	Separate capture streams	Shared head view; robot wrists
Fisheye-VLA	Crops from one fisheye	Calibrated EE projection	Resampling: 1.3 ms	Shared renderer; no wrists

independently at the policy input (Table 3).

Controlled evaluation of visual allocation. Controlled re-rendering reveals where the extra visual budget is useful and motivates a compact end-effector prior, connecting the allocation study to a working closed-loop system (Tables 2 and 3).

2. Related Work

Camera placement determines which observations are available to a manipulation policy. We review how prior work obtains local detail and extends coverage, with the main interface differences summarized in Table 1.

Observation interfaces for VLA policies. OpenVLA provides an adaptable pretrained policy [9], while $\pi_{0.5}$ combines flow-based action generation with heterogeneous co-training for broader generalization [2]. Their observation interfaces still determine which information reaches control. Hand-centric observations improve learning when they preserve task observability [10], and cross-view fusion adds third-person context [1]. Wrist input raises CLASS success from 68% to 90% under changing global viewpoints [11]; wrist views also reduce action-prediction error relative to third-person views on several visuotactile manipulation tasks [12]. We retain hand-centered detail through local fisheye views.

Active visual allocation. Kim et al. combine low-resolution peripheral vision with high-resolution gaze-centered images for precise imitation learning [13]. EyeRobot learns gaze and manipulation with a mechanical eye and a BC-RL loop; its EyeGym renders eye observations from panoramic demonstrations [4]. GIAVA collects human gaze and camera actions to learn foveated processing [5]. SaPaVe learns semantic camera control and geometry-aware execution [6]. AV-ALOHA adds a dedicated arm to move a stereo camera [14]. These systems require additional gaze supervision, control learning, or camera actuation. Human gaze offers a broader motivation: visual sampling follows the information required by the task [15]. We use a fixed fisheye to compare crop directions

after recording, then evaluate whether end-effector positions provide a sufficient allocation rule for the tested tasks.

BFA++ learns inter-view and intra-view importance to prune supplied visual tokens [16]. We instead select which source pixels become local observations; view construction and token pruning are complementary.

Coverage beyond the current field of view. OmniDP uses panoramic LiDAR observations for large-workspace manipulation [17]. SOMA builds persistent spatial memory using a moving head camera [18]. We study the complementary case of persistent wide-field RGB coverage and the allocation of fine interaction detail within it.

Supplying local views without wrist cameras. WristWorld combines reconstruction and video generation to synthesize wrist views [7]. Imagination at Inference synthesizes in-hand views online with pose-conditioned diffusion [19]. Both seek the appearance of a displaced camera, including new parallax. Our renderer inexpensively resamples observed pixels from the existing optical center. Concurrent work outlines FK-projected hand ROIs cropped from a single perspective camera [20]. Such crops inherit the camera’s limited field of view and offer no explicit viewing-direction cue as they move. Fisheye-VLA differs in three respects: a 220° fisheye provides coverage beyond a rectilinear footprint, each local view is re-rendered as a calibrated perspective image rather than a pixel crop, and a shared ray encoding gives moving crops and the global view one geometric reference. We further ask *where* the local budget should go through a controlled allocation study, and validate the resulting interface in closed loop over expanding workspace extents.

Fisheye sensing and geometric conditioning. Rethinking Camera Choice studies wrist-mounted fisheye sensing through spatial localization, scene generalization, and camera transfer [21]. VISTA considers fisheye visual grounding together with the physical feasibility of handheld trajectories [22]. Fisheye3R identifies a geometric domain gap when perspective-trained reconstruction models encounter fisheye imagery [23]. Our fixed-camera interface addresses local appearance through perspective rendering while retaining the full fisheye for context. For camera geometry, PRoPE uses relative positional information [24], and camera-conditioned imitation learning uses ray embeddings for viewpoint robustness [25]. RayRoPE further conditions multi-view attention on projective ray geometry [26]. For our shared-center interface, ray features give dynamic local crops and the global image a common directional reference.

Human demonstration interfaces. UMI and FastUMI collect demonstrations with handheld devices rather than robot teleoperation [27; 28]. EgoMimic aligns human and robot observations for joint learning [8]. Our handheld extension reuses the fisheye view-construction rule with tracked gripper poses. This preserves the global/local observation structure across collection and deployment, while robot fine-tuning supplies embodiment-specific action supervision.

3. Method

In this section, we construct a global/local observation interface from the crop-placement study. The policy receives a source image I_t , an end-effector state s_t containing the current poses, and a language instruction ℓ , and predicts an action chunk $a_{t:t+H-1}$. A global view G_t preserves the complete scene, while n local views $\{C_{tj}\}_{j=1}^n$ retain interaction detail within a fixed visual budget. Figure 2 connects these observations to the policy and shows how tracked handheld poses reuse the same renderer.

3.1. Where to Place the Crops

Re-rendering a recorded image changes the local observation while holding the scene fixed. To compare possible allocations, we form a candidate set $\mathcal{C}_t$ with $K_t \leq K$ directions. Past, current, and future end-effector and instruction-referenced object positions are mapped to a shared grid of M anchor directions. Future positions broaden this retrospective diagnostic search; online tracking uses only states available at the current time.

A diagnostic policy is trained with independent Bernoulli dropout over candidate views, then frozen for evaluation. For a subset $S \subseteq \mathcal{C}_t$, let $E(S)$ denote action-chunk endpoint error and $g(S) = E(\text{global}) - E(S)$ its reduction from the global-only input. Comparing EE and random placements at equal crop counts separates the value of direction from the value of adding an image. A separate object-centered condition tests whether the instruction-referenced object is a better allocation cue.

The study motivates one local stream per end-effector: useful directions concentrate near interaction, and retaining both hands avoids a separate hand-selection rule. The placement and crop-count comparisons supporting this design are reported in Sec. 5.1.

3.2. Sensor Model and Focal Rendering

A calibrated camera projection $\mathcal{P}_\kappa$ maps physical rays to source pixels, so the renderer applies independently of image resolution and lens parameterization. The captured field of view sets the available directions. We resize I_t to obtain G_t and render local perspective views to retain more of the captured interaction detail. Let η_{tj} contain a virtual camera’s orientation and focal parameters. For virtual intrinsics A_η and orientation U_η , an output pixel with homogeneous coordinate $\bar{u}$ defines $r_\eta(u) = \text{normalize}(U_\eta A_\eta^{-1} \bar{u})$ in the physical camera frame. Its corresponding source pixel and rendered color are

$$m_{tj}(u) = \mathcal{P}_\kappa(r_{\eta_{tj}}(u)), \quad C_{tj}(u) = I_t(m_{tj}(u)). \quad (1)$$

Interpolation samples the source image at $m_{tj}(u)$. This inverse-warp construction performs cropping and distortion correction together, preserving a perspective image for the pretrained encoder. It also avoids resampling a globally rectified panorama before extracting the local view. Global-image rays are recovered from their source coordinates through $\mathcal{P}_\kappa^{-1}$, so every token can be expressed in the same camera frame.


3.3. Focal Tracking and Adaptive Extent

The observation provides the current end-effector poses (R_{tj}, x_{tj}) in the robot base frame. A fixed calibrated projection $\Pi_{\kappa,j}$ maps each pose to an image center, $p_{tj} = \Pi_{\kappa,j}(R_{tj}, x_{tj})$. The mapping is fitted offline from reference image observations paired with recorded end-effector poses. The renderer and policy both use these Cartesian states directly; crop placement requires no object detector.


A crop centered on the current hand can leave little detail ahead of a reach. Anticipatory gaze during manipulation motivates looking ahead of the current pose [29]. We predict $\hat{x}_{tj} = x_{tj} + \tau v_{tj}$, where v_{tj} is a causal backward-difference velocity and τ is the lead interval. Projecting $(R_{tj}, \hat{x}_{tj})$ sets the local viewing direction while retaining the current orientation. The virtual optical axis follows the source ray recovered at that projected center through $\mathcal{P}_\kappa^{-1}$, connecting pose tracking to the sampling map in Eq. 1.

Faster motion makes the predicted center less precise, so the viewport expands with speed. With reference speed v_{ref} and expansion coefficient β , we use $\alpha_{tj} = 1 + \beta \text{clip}(\|v_{tj}\|/v_{\text{ref}}, 0, 1)$ and local focal scale $f_{tj} = f_{0,tj}/\sqrt{\alpha_{tj}}$. The baseline focal scale $f_{0,tj}$ specifies the nominal extent; the motion term widens it during a reach.

(a) Online observation and action prediction



(b) Offline measurement candidates



(c) UMI-style handheld collection



Figure 2: Observation construction and policy integration. (a) Current end-effector (EE) poses and a causal velocity estimate predict the viewing centers. Calibrated projection locates these centers in the captured fisheye image; inverse perspective sampling extracts and rectifies each local view in one step. A resized global view retains the scene. The three views enter the vision encoder, and their source rays supply a common geometric reference before action prediction. The standalone sphere illustrates the shared optical center; the grid inset uses an equidistant fisheye projection. (b) Candidate-view footprints for the offline placement instrument, selected from a shared anchor bank. These are measurement candidates, not the deployed policy inputs; online crops follow the EE poses in (a). (c) Larger views of handheld collection and the matched grippers show how tracked human poses supply the same rendering input. This interface uses pose-dependent local views while preserving global coverage.

3.4. Spherical Ray Positional Encoding

The same local patch coordinate can refer to different physical directions as a crop moves. To preserve this spatial identity, we attach its source ray r to the visual token h :

$$\tilde{h} = h + e(r), \quad e(r) = W_2 \sigma(W_1 \gamma(r)). \quad (2)$$

The function γ combines the unit ray with Fourier features over L frequency bands. A shared network embeds rays from the global and local views, and its output projection is initialized to zero to preserve the pretrained features at initialization. Matching directions receive matching ray features even when their image coordinates differ.

3.5. Policy Integration and Deployment

The global view and local crops enter the VLA’s existing image pathways. The vision encoder produces appearance features, the ray residual supplies their viewing directions, and the policy conditions on

these tokens, s_t , and ℓ to predict $a_{t:t+H-1}$. The robot executes motion and gripper commands from this chunk. Training and deployment use the same view construction, so the policy learns to interpret the moving local inputs it will receive online.

3.6. UMI-Style Human Data Collection

We extend the interface to human demonstrations using the fixed fisheye camera and a mechanically matched handheld gripper. The wide field of view accommodates large hand movements, reducing tracking loss caused by hands leaving the image. We render auxiliary perspective views from the fisheye recordings for fiducial detection and gripper-pose estimation, while image-based recognition estimates the gripper’s open/closed state. The recovered poses drive the same global/local renderer used for robot observations (Fig. 2c), without requiring cameras on the handheld grippers. Keeping the table setup and camera placement consistent with robot deployment reduces the visual and spatial gap between the two data sources.

Short tracking gaps are interpolated, and trajectories are smoothed and aligned with video frames before motion targets are computed. Human pretraining is followed by robot fine-tuning, with domain-specific action normalization accommodating differences in motion statistics. Future extensions could use a tabletop calibration board to recover absolute gripper motion in a shared coordinate frame, reducing dependence on a matched collection setup.

4. Experimental Setup

The evaluation tests whether the allocation rule improves manipulation, whether its gains persist as the workspace expands, and whether the renderer supports both robot and handheld demonstrations. We separate the frozen-policy diagnostic from independently trained closed-loop policies to distinguish observation effects from learned control performance.

Platform and training. The robot uses two seven-axis Flexiv Rizon 4s arms with GN01 grippers and one fixed head-mounted 220° fisheye. The ordinary front-camera baseline has a 90° field of view, illustrated by the white outlines in Fig. 1c. Fisheye source images are 1944×1944 , and robot images and trajectories are sampled at 30 Hz. Policies start from $\pi_{0.5}$ [2] and predict 30-step chunks of 14-dimensional actions, with an end-effector delta and a gripper command per arm. Cartesian impedance control executes trajectories at 30 Hz. Each sensing configuration uses the same 300 teleoperated demonstrations per task and 20,000 training steps, on one NVIDIA RTX PRO 6000 with batch size 12. Random, object-centered, and EE crop policies are trained separately using their deployment crop rules and this shared budget.

Rendering and token budget. The global image and each local view are 224×224 , with bilinear sampling. Calibration uses the OpenCV fisheye model and fixed per-arm pose-to-image mappings. We set $\tau = 0.5$ s, $\beta = 0.5$, and $v_{\text{ref}} = 0.204$ m/s, the empirical high-percentile speed. The local area therefore expands by at most $1.5\times$. Ray encoding uses $L = 4$ Fourier bands. The encoder’s 14×14 patches produce 256 tokens per image: global plus two local views and the front camera plus two wrist cameras each supply 768 visual tokens. Ray features do not add tokens. Median deployment latency on an RTX 5090 is 87 ms, including 1.3 ms for rendering.

Placement diagnostic. We evaluate 1,500 held-out frames from 120 episodes. Candidate directions are snapped to a shared bank of $M = 30$ anchors, yielding at most $K = 16$ candidates per window. Figure 2b shows the source-image footprints of these anchor views used for the offline diagnostic. Conditions are paired using the same source frame and inference randomness within each packed batch.

We report endpoint-error reductions in millimeters with episode-clustered 95% bootstrap confidence intervals. Round 1 provides the EE-random contrast, while Round 2 provides the crop-count and object-centered contrasts in Table 2.




Figure 3: Evaluation geometry and crop-placement gains. (a) Top view of the tabletop: R1–R3 denote increasingly large placement extents, with the camera on the robot side. (b) Round 2 endpoint-error reductions relative to the global-only input, with 95% episode-clustered intervals; the diamond is the derived full-candidate reference. EE-centered views account for most of the estimated reduction.

Tasks and spatial protocol. Task A transfers an instructed fruit from ten categories into a box. Task B places a duck toy onto a shelf, and Task C transfers a mug from the shelf into a box. Task D transfers fruit between a conveyor and a bin in both directions. Success requires completing the transfer and leaving the object at its destination without dropping it. These task families test target selection, elevated placement, retrieval, and moving-object interaction (Fig. 4).

Task A uses predefined placement grids in nested tabletop extents: R1 is 80×50 cm, R2 is 130×70 cm, and R3 is 180×100 cm (Fig. 3a). Each configuration–region condition has 50 executed trials, and the table reports their observed success rates and arithmetic regional mean. Some target placements in R2 and R3 extend beyond the coverage of the front or wrist cameras; these conditions are evaluated with the same completion criterion as R1.

Handheld transfer. A separate fruit-to-shelf task tests pretraining with 300 human demonstrations before fine-tuning on 50 or 100 robot demonstrations. The collection device is a thumb-operated, GN01-shaped gripper with six AprilTags; its body can be 3D-printed at a material cost of approximately US\$1. A single fisheye image stream provides both visual observations and the inputs for gripper-pose and open/closed-state estimation, without additional cameras or motion-capture equipment. AprilTag detection in rectified views supplies poses for the shared renderer. The tripod-mounted fisheye matches the nominal robot camera placement, and each training condition is evaluated over 50 trials.

5. Results

We first assess crop placement, then compare camera configurations and interface components on the same regional scale. Task-suite and handheld-transfer results test whether the observation rule remains useful beyond the tabletop allocation experiment.

5.1. Crop Placement

At matched crop counts, an EE-centered view improves endpoint prediction over a random direction by 0.890 mm [0.520, 1.297] in Round 1 (Table 2). Round 2 gives reductions of 0.458 mm for a random crop and 1.339 mm for one EE crop, a point-estimate difference of 0.881 mm (Fig. 3). The placement change contributes more than simply adding a randomly directed local image.

A second EE crop adds 0.175mm [0.007, 0.346], bringing the reduction to 1.514mm. Adding the measured all-minus-one increment to the one-EE gain yields a 1.637mm full-candidate reference. The two-crop gain therefore corresponds to approximately 92.5% of this reference, a descriptive point estimate within the evaluated candidate pool. Separately, the Round 1 single-crop retention estimate is 81.9%, with a 95% confidence interval of [66.3%, 102.5%].

The oracle’s best direction falls within 20° of an EE in 69.9% of windows [61.3, 78.3], against a 28.4% chance rate computed from each window’s candidate distribution. Hit/chance rates of 30.1/8.1% at 10° and 78.8/47.6% at 30° show positive paired enrichment at each scale. Thus the EE concentration extends beyond a single cone threshold.

Motion alone is insufficient to choose a useful hand when both hands are stationary. In 37 such windows from 35 episodes, an independently evaluated oracle still obtains 2.427 mm [1.318, 3.825] of gain. Retaining one view per hand avoids this selection step. In the 0–30° off-axis subset, exact-ray placement reduces endpoint error by a further 0.293 mm [0.011, 0.622] relative to anchor-snapped placement.

The closed-loop crop block in Table 3 evaluates independently trained policies with two local views each. EE crops achieve a regional mean of 79.3%, compared with 33.3% for random and 45.3% for object-centered crops. EE placement leads in every region. Object-centered placement improves over random in closed loop, although its offline contrasts include zero: the frozen diagnostic evaluates endpoint prediction, whereas the separately trained policies must complete entire tasks.

5.2. Workspace Coverage and Ablations

Table 3 puts sensor configurations, component removals, and crop placements on the same Task A evaluation. The rig with a front camera and two wrist cameras is strongest in R1, at 92% against our 72%. Its success decreases to 58% in R2, where our interface reaches 84%. In R3, its success falls to 14%, while Fisheye-VLA succeeds in 82% of trials. Some placements in the expanded regions extend beyond the ordinary camera views, contributing to their lower success. The front camera alone reaches 44%, 38%, and 4%, and two wrist cameras reach 76%, 36%, and 0%.

The full interface remains competitive with fisheye plus two physical wrists, whose regional rates are 70%, 74%, and 78%. Rendered crops retain a common viewpoint and deterministic geometry while removing the wrist image streams. The observed differences are modest; the comparison supports a simpler sensing interface with similar task performance.

Table 2: Offline placement: paired gains with 95% CI.

Contrast	Round	Δ (mm)	95% CI
EE – random, one each	1	0.890	[0.520, 1.297]
Two EE – one EE	2	0.175	[0.007, 0.346]
All candidates – one EE	2	0.298	[−0.034, 0.626]
Object – random, one	2	−0.148	[−0.386, 0.126]
Object – random, three	2	0.030	[−0.298, 0.360]




Figure 4: Recorded execution sequences for the four task families. Columns show ordered stages from approach through transfer to completion; the same global/local rendering rule and multi-task policy serve every row. Shelf interaction requires keeping the elevated destination in context, and conveyor transfer requires following a moving object. The sequences illustrate reuse of the interface across different spatial and timing demands. Frame spacing indicates order, not equal elapsed time.

Keeping only the global image reduces R3 success from 82% to 30%, while the reduction in R1 is four points. The source still covers the target, but uniform resizing allocates little detail to its interaction region. Local crops both retain more local pixels and rectify the perspective view. Fisheye3R reports a mismatch when perspective-trained models receive fisheye imagery [23]; a related appearance mismatch could contribute here. These coupled changes explain why this ablation tests the entire local-view branch.

Removing ray encoding reduces R3 success by 42 points, compared with ten points in R1. Larger workspace extents expose the policy to a broader range of crop directions, making explicit source rays more useful. Removing motion lead gives smaller decreases of four, eight, and fourteen points. The observed trend favors leaving visual room ahead of a reach, while the crop and geometry ablations account for the largest outer-region losses.

5.3. Task Suite

The same multi-task policy completes tabletop transfer, shelf placement and retrieval, and conveyor transfer (Table 4). Shelf tasks require retaining a destination away from the central table while resolving the grasp or release. Conveyor transfer adds a timing requirement because the object moves during approach. Both conveyor directions have lower success than the static shelf tasks, consistent with this additional demand on tracking and control.

Table 3: Task A: regional success and mean (%).

Configuration	R1	R2	R3	Avg.
<i>Camera baselines</i>				
Global fisheye (w/o crops)	68	36	30	44.7
Front camera + two wrists	92	58	14	54.7
Front camera	44	38	4	28.7
Two wrist cameras	76	36	0	37.3
Fisheye + two wrists	70	74	78	74.0
<i>Interface ablations</i>				
w/o motion lead	68	76	68	70.7
w/o ray encoding	62	64	40	55.3
<i>Crop placement</i>				
Random crops	42	30	28	33.3
Object-centered crops	46	48	42	45.3
Fisheye-VLA	72	84	82	79.3

Every cell has 50 trials; Avg. is the mean over R1–R3. Global fisheye is also the no-focal-crop ablation.

Table 4: Four task families; Task D is evaluated in both directions.

Task	Success (%)
A Instructed fruit into box	79
B Duck toy onto shelf	88
C Mug from shelf into box	86
D Conveyor → bin	72
D' Bin → conveyor	68

Task A is the mean over three regions; each task–region condition has 50 trials.

Table 5: Handheld pretraining for fruit-to-shelf.

Human demos	Robot demos	Success (%)
0	50	36
300	50	48
0	100	46
300	100	72

Each condition has 50 trials.

5.4. Human Data

Handheld pretraining transfers the renderer to a separate fruit-to-shelf task (Table 5). At the 100-robot-demonstration budget, 300 human demonstrations improve success from 46% to 72%. At the 50-demonstration budget, the observed rates are 36% and 48%. The larger gain at the higher fine-tuning budget suggests that robot demonstrations help convert the pretrained motion representation into reliable gripper control.

6. Discussion

The placement study and closed-loop experiments support an end-effector prior for the tasks considered here. Retaining one local view per hand concentrates detail around interaction and avoids choosing a hand from motion alone. The region comparisons further show why coverage alone is insufficient: a global fisheye keeps the target visible, yet performs substantially worse without the local crops.

Shared-center crops cannot remove occlusion, and pose projection depends on calibration. Human pretraining also adds both data and optimization. Broader task evaluation and calibration transfer are natural next steps for this single-fisheye interface.

7. Conclusion

We presented Fisheye-VLA, a single-fisheye observation interface for bimanual VLA manipulation. A controlled re-rendering study motivated one local perspective view per end-effector, and the deployed interface tracks these views through calibrated end-effector projection. The shared ray encoding lets the policy use their changing viewing directions. Across the tested tasks, this input supports manipulation over a wider workspace than the rig with a front camera and two wrist cameras, using the same visual token budget. The handheld experiments also show that the renderer can be reused for demonstration collection. These results provide a practical basis for replacing a multi-camera rig with local views rendered from one fisheye.

Acknowledgment

This work was in part supported by the InnoHK initiative of the Innovation and Technology Commission of the Hong Kong Special Administrative Region Government via the Hong Kong Centre for Logistics Robotics. We also thank DeepCybo for its support, and Hualong Liu, Peize Li, and Zhekai Wang for their assistance.

References

- [1] Rishabh Jangir, Nicklas Hansen, Sambaran Ghosal, Mohit Jain, and Xiaolong Wang. Look closer: Bridging egocentric and third-person views with transformers for robotic manipulation. *IEEE Robotics and Automation Letters*, 7(2): 3046–3053, 2022. URL <https://arxiv.org/abs/2201.07779>.
- [2] Physical Intelligence, Kevin Black, Noah Brown, James Darpinian, Karan Dhabalia, Danny Driess, et al. $\pi_{0.5}$: A vision-language-action model with open-world generalization. In *Conference on Robot Learning*, 2025. URL <https://arxiv.org/abs/2504.16054>.
- [3] Juho Kannala and Sami S. Brandt. A generic camera model and calibration method for conventional, wide-angle, and fish-eye lenses. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(8):1335–1340, 2006. doi: 10.1109/TPAMI.2006.153.
- [4] Justin Kerr, Kush Hari, Ethan Weber, Chung Min Kim, Brent Yi, Tyler Bonnen, Ken Goldberg, and Angjoo Kanazawa. Eye, robot: Learning to look to act with a BC-RL perception-action loop. In *Conference on Robot Learning*, 2025. URL <https://arxiv.org/abs/2506.10968>.
- [5] Ian Chuang, Jinyu Zou, Andrew Lee, Dechen Gao, and Iman Soltani. Look, focus, act: Efficient and robust robot learning via human gaze and foveated vision transformers. In *IEEE International Conference on Robotics and Automation*, 2026. URL <https://arxiv.org/abs/2507.15833>.
- [6] Mengzhen Liu, Enshen Zhou, Cheng Chi, Yi Han, Shanyu Rong, Liming Chen, Pengwei Wang, Zhongyuan Wang, and Shanghang Zhang. SaPaVe: Towards active perception and manipulation in vision-language-action models for robotics. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2026. URL <https://arxiv.org/abs/2603.12193>.
- [7] Zezhong Qian, Xiaowei Chi, Yuming Li, Shizun Wang, Zhiyuan Qin, Xiaozhu Ju, Sirui Han, and Shanghang Zhang. WristWorld: Generating wrist-views via 4d world models for robotic manipulation. *arXiv preprint arXiv:2510.07313*, 2025. URL <https://arxiv.org/abs/2510.07313>.

- [8] Simar Kareer, Dhruv Patel, Ryan Punamiya, Pranay Mathur, Shuo Cheng, Chen Wang, Judy Hoffman, and Danfei Xu. EgoMimic: Scaling imitation learning via egocentric video. *arXiv preprint arXiv:2410.24221*, 2024. URL <https://arxiv.org/abs/2410.24221>.
- [9] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, et al. OpenVLA: An open-source vision-language-action model. In *Conference on Robot Learning*, 2024. URL <https://arxiv.org/abs/2406.09246>.
- [10] Kyle Hsu, Moo Jin Kim, Rafael Rafailov, Jiajun Wu, and Chelsea Finn. Vision-based manipulators need to also see from their hands. In *International Conference on Learning Representations*, 2022. URL <https://arxiv.org/abs/2203.12677>.
- [11] Sung-Wook Lee, Xuhui Kang, Brandon Yang, and Yen-Ling Kuo. CLASS: Contrastive learning via action sequence supervision for robot manipulation. In *Conference on Robot Learning*, 2025. URL <https://arxiv.org/abs/2508.01600>.
- [12] Toru Lin, Yu Zhang, Qiyang Li, Haozhi Qi, Brent Yi, Sergey Levine, and Jitendra Malik. Learning visuotactile skills with two multifingered hands. In *IEEE International Conference on Robotics and Automation*, 2025. URL <https://arxiv.org/abs/2404.16823>.
- [13] Heecheol Kim, Yoshiyuki Ohmura, and Yasuo Kuniyoshi. Gaze-based dual resolution deep imitation learning for high-precision dexterous robot manipulation. *IEEE Robotics and Automation Letters*, 6(2), 2021. doi: 10.1109/LRA.2021.3059619. URL <https://arxiv.org/abs/2102.01295>.
- [14] Ian Chuang, Andrew Lee, Dechen Gao, M-Mahdi Naddaf-Sh, and Iman Soltani. Active vision might be all you need: Exploring active vision in bimanual robotic manipulation. In *IEEE International Conference on Robotics and Automation*, pages 7952–7959, 2025. URL <https://arxiv.org/abs/2409.17435>.
- [15] Mary Hayhoe and Dana Ballard. Eye movements in natural behavior. *Trends in Cognitive Sciences*, 9(4):188–194, 2005. doi: 10.1016/j.tics.2005.02.009.
- [16] Haosheng Li, Weixin Mao, Zihan Lan, Hongwei Xiong, Hongan Wang, Chenyang Si, Ziwei Liu, Xiaoming Deng, and Hua Chen. BFA++: Hierarchical best-feature-aware token prune for multi-view vision language action model. *arXiv preprint arXiv:2602.20566*, 2026. URL <https://arxiv.org/abs/2602.20566>.
- [17] Pei Qu, Zheng Li, Yufei Jia, Ziyun Liu, Liang Zhu, Haoang Li, Jinni Zhou, and Jun Ma. OmniDP: Beyond-FOV large-workspace humanoid manipulation with omnidirectional 3D perception. *arXiv preprint arXiv:2603.05355*, 2026. URL <https://arxiv.org/abs/2603.05355>.
- [18] Pengteng Li, Weiyu Guo, He Zhang, Tiefu Cai, Xiao He, Yandong Guo, and Hui Xiong. Spatial memory for out-of-vision manipulation in vision-language-action. In *International Conference on Machine Learning*, 2026. URL <https://arxiv.org/abs/2605.22283>.
- [19] Haoran Ding, Anqing Duan, Zezhou Sun, Dezhen Song, and Yoshihiko Nakamura. Imagination at inference: Synthesizing in-hand views for robust visuomotor policy inference. *arXiv preprint arXiv:2509.15717*, 2025. URL <https://arxiv.org/abs/2509.15717>.
- [20] Xinhai Sun, Xiang Shi, Menglin Zou, and Wenlong Huang. ROI-driven foveated attention for unified egocentric representations in vision-language-action systems. *arXiv preprint arXiv:2603.20668*, 2026. URL <https://arxiv.org/abs/2603.20668>.
- [21] Han Xue, Nan Min, Xiaotong Liu, Wendi Chen, Yuan Fang, Jun Lv, Cewu Lu, and Chuan Wen. Rethinking camera choice: An empirical study on fisheye camera properties in robotic manipulation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2026. URL <https://arxiv.org/abs/2603.02139>.
- [22] Siyuan Yang, Linzheng Guo, Ouyang Lu, Zhaxizhuoma, Daoran Zhang, Xinmiao Wang, et al. VISTA: Vision-grounded and physics-validated adaptation of UMI data for VLA training. *arXiv preprint arXiv:2606.04708*, 2026. URL <https://arxiv.org/abs/2606.04708>.
- [23] Ruxiao Duan, Erin Hong, Dongxu Zhao, Eric Turner, Alex Wong, and Yunwen Zhou. Fisheye3R: Adapting unified 3D feed-forward foundation models to fisheye lenses. *arXiv preprint arXiv:2603.28896*, 2026. URL <https://arxiv.org/abs/2603.28896>.
- [24] Ruilong Li, Brent Yi, Junchen Liu, Hang Gao, Yi Ma, and Angjoo Kanazawa. Cameras as relative positional encoding. In *Advances in Neural Information Processing Systems*, 2025. URL <https://arxiv.org/abs/2507.10496>.
- [25] Tianchong Jiang, Jingtian Ji, Xiangshan Tan, Jiading Fang, Anand Bhattad, Vitor Guizilini, and Matthew R. Walter. Do you know where your camera is? view-invariant policy learning with camera conditioning. *arXiv preprint arXiv:2510.02268*, 2025. URL <https://arxiv.org/abs/2510.02268>.

- [26] Yu Wu, Minsik Jeon, Jen-Hao Rick Chang, Oncel Tuzel, and Shubham Tulsiani. RayRoPE: Projective ray positional encoding for multi-view attention. *arXiv preprint arXiv:2601.15275*, 2026. URL <https://arxiv.org/abs/2601.15275>.
- [27] Cheng Chi, Zhenjia Xu, Chuer Pan, Eric Cousineau, Benjamin Burchfiel, Siyuan Feng, Russ Tedrake, and Shuran Song. Universal manipulation interface: In-the-wild robot teaching without in-the-wild robots. In *Robotics: Science and Systems*, 2024. URL <https://arxiv.org/abs/2402.10329>.
- [28] Zhaxizhuoma, Kehui Liu, Chuyue Guan, Zhongjie Jia, Ziniu Wu, Xin Liu, et al. FastUMI: A scalable and hardware-independent universal manipulation interface with dataset. *arXiv preprint arXiv:2409.19499*, 2024. URL <https://arxiv.org/abs/2409.19499>.
- [29] Michael Land, Neil Mennie, and Jennifer Rusted. The roles of vision and eye movements in the control of activities of daily living. *Perception*, 28(11):1311–1328, 1999. doi: 10.1068/p2935.