EXP.NO:08

G-BURGER PROBLEM

PROBLEM STATEMENT:

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the perso
If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out
burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3$
But this is not the minimum, so need to try out other orders of consumption and choose the minimum value.
he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

CODE:

```c
#include<stdio.h>
#include<math.h>
int main(){
    int n;
    scanf("%d",&n);
    int cal[n];
    for(int i=0;i<n;i++){
        scanf("%d",&cal[i]);
    }
    for(int i=0;i<n;i++){
        for(int j=i+1;j<n;j++){
            if(cal[j]>cal[i]){
                int t=cal[i];
                cal[i]=cal[j];
                cal[j]=t;
            }
        }
    }
    int sum=0;
    for(int i=0;i<n;i++){
    sum+=cal[i]*pow(n,i);
    }
    printf("%d",sum);
    return 0;
}
```

EXP.NO:08

OUTPUT:



	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

RESULT:

The code is executed successfully.