Status	Finished
Started	Saturday, 17 October 2026, 6:03 PM
Completed	Saturday, 17 October 2026, 6:17 PM
Duration	13 mins 35 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. truncate() ✓
b. reduce()
c. shrink()
d. resize()

The correct answer is: truncate()

Question **2**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓
False

The correct answer is 'True'.

Question **3**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The buffer size for the file operations ✓
b. The file's read/write position
c. The encoding of the file
d. The access mode of the file

The correct answer is: The buffer size for the file operations

Question **4**

Correct

Mark 1.00 out of 1.00

How can you read a file line by line efficiently in Python?

a. Using the readlines() method
b. Using the read() method
c. Using the readline() method
d. Using a for loop ✓

The correct answer is: Using a for loop

Question **5**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. r+ ✓
b. w
c. a
d. r

The correct answer is: r+

Question **6**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

a. The access mode in which the file was opened ✓
b. The current position of the file cursor
c. The name of the file
d. The size of the file

The correct answer is: The access mode in which the file was opened

Question **7**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

a. Moves the file cursor to the beginning
b. Flushes the internal buffer to the file ✓
c. Deletes the file content
d. Closes the file

The correct answer is: Flushes the internal buffer to the file

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

a. fseek()
b. seek() ✓
c. tell()
d. ftell()

The correct answer is: seek()

Question **9**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

a. Moves the file cursor to the specified position ✓
b. Writes data to the file
c. Deletes the file
d. Reads the file line by line

The correct answer is: Moves the file cursor to the specified position

Question **10**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

a. file.is_closed()
b. file.isclosed()
c. file.closed()
d. file.closed ✓

The correct answer is: file.closed

Question **11**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It does nothing
b. It raises an error
c. It appends data to the file
d. It clears the old data and starts fresh ✓

The correct answer is: It clears the old data and starts fresh

Question **12**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. 1
b. null
c. garbage
d. 2
e. 0 ✓

The correct answer is:
0

Question **13**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

a. writelist(list)
b. write(list)
c. writelines(list) ✓
d. None of the mentioned

The correct answer is: writelines(list)

Question **14**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use ____

a. outfile = open(file = "c:\\scores.txt", "w")
b. outfile = open(file = "c:\scores.txt", "w")
c. outfile = open("c:\\scores.txt", "w") ✓
d. outfile = open("c:\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **15**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

a. none of the mentioned
b. sets the file's current position at the offset ✓
c. sets the file's current position within the file
d. sets the file's previous position at the offset

The correct answer is:
sets the file's current position at the offset