HTML & CSS Material

Python Full Stack Development Course
Offered by ManiTechEd
Manikanta Machapalli
Contact Information: Manikanta Machapalli, 9886282230

Web development

- Web development refers to the process of creating, building, and maintaining websites and web applications. It involves a variety of tasks, from coding and programming to designing the layout and user interface, ensuring functionality, performance, and security.

Web Technologies:

- HTML5
- CSS3
- JAVASCRIPT

Web Page:

- Webpage is a collection of data or a information in a single page

Website:

- the collection of multiple webpages is called as website
- This is created using UI Technologies like HTML5,CSS3 and JavaScript
- Ui stands for user interface technologies hwere user is directly interacted with the webpages or websites

HTML (Hyper Text Markup Language) – 1991 [tim berners lee]

HTML is the standard markup language used for creating web pages. It structures the content on the web by using a series of elements and tags to define the different parts of the document, such as headings, paragraphs, links, images, and other multimedia.

HTML Tags

HTML tags are the building blocks of HTML that define the structure and content of web pages.
Tags are enclosed in angle brackets (< >) and typically come in pairs: an opening tag and a closing tag, with the content in between.

Paired Tag and Unpaired Tag

Definition: HTML tags can be either paired (having an opening and a closing tag) or unpaired (self-closing). Paired tags enclose content, whereas unpaired tags do not enclose content but perform a specific function on their own.

Paired Tag:

Definition: A paired tag consists of an opening tag and a closing tag, with content placed between them.

<html></html>
<head></head>
<body></body>
<title></title>

Unpaired Tag (Self-Closing Tag):

Definition: An unpaired tag, also known as a self-closing tag, does not have a closing tag and does not enclose any content.

<img>

<hr>
<meta>

Python Full Stack Development Course
Offered by ManiTechEd
Manikanta Machapalli
Contact Information: Manikanta Machapalli, 9886282230

Heading Tags

HTML heading tags are used to define headings and subheadings on a web page. They are organized from **<h1> to <h6>, with <h1> being the most important and <h6> the least.**

List of Heading Tags:

1. **<h1>**: Main heading (highest level)
2. **<h2>**: Subheading (second level)
3. **<h3>**: Subheading (third level)
4. **<h4>**: Subheading (fourth level)
5. **<h5>**: Subheading (fifth level)
6. **<h6>**: Subheading (sixth level)

```
<h1>Main Heading</h1>
<h2>Subheading Level 2</h2>
 <h3>Subheading Level 3</h3>
<h4>Subheading Level 4</h4>
<h5>Subheading Level 5</h5>
<h6>Subheading Level 6</h6>
```

Paragraph Tag

The paragraph tag (<p>) in HTML is used to define a block of text as a paragraph. It automatically adds space above and below the paragraph to separate it from other elements.

```
<p>This is the first paragraph of text.</p>
<p>This is the second paragraph of text.</p>
```

Lorem Ipsum

Definition: Lorem Ipsum is a placeholder text commonly used in the design and publishing industries to fill space in a document or webpage when the actual content is not yet available. It is derived from a scrambled version of a Latin text by Cicero and is used to demonstrate the visual form of a document without relying on meaningful content.

Text Formatting Tags

Definition: Text formatting tags in HTML are used to style and emphasize text in various ways. They can change the appearance of text, such as making it bold or italic, and can also impact how text is presented visually.

1. ****: **Bold Text** - Renders text in a bold font.
Bold text
2. ****: **Italic Text** - Renders text in an italic font.
Italic text
3. ****:
Strong Emphasis - Renders text in bold and indicates strong importance.
Strong emphasis

4. ****: **Emphasized Text** - Renders text in italic and indicates emphasized importance.
Emphasized text

5. **<u>**: **Underlined Text** - Renders text with an underline.
<u>Underlined text</u>

7. **<del>**: **Deleted Text** - Represents text that has been deleted or removed.
<del>Deleted text</del>

8. **<small>**: **Small Text** - Renders text in a smaller font size.
<small>Smaller text</small>

9. **<sub>**: **Subscript Text** – whenever u want to write content in below.
₂O

10. **<sup>**: **Superscript Text** – whenever u want to write content in above then we can use sup.
²

Text Formatting Tags
Definition: Text formatting tags in HTML are used to style and emphasize text in various ways. They can change the appearance of text, such as making it bold or italic, and can also impact how text is presented visually.

1.<i>: **Insert tag** - Renders text in a bold font.
Whenever a content has been deleted it should be replaced with similar type of content in the webpage
<ins></ins>

Image Tag

The <img> tag is used to embed images in an HTML document. It is an unpaired (self-closing) tag that contains attributes to specify the image source, alternative text, dimensions, and other properties.
Absolute path:
This is the path in which the image are inserted from the google directly
Relative Path:
In this we are going to insert the images from the devices files by selecting the path of the images

- **src**: Specifies the path to the image file.
- **alt**: Provides alternative text for the image if it cannot be displayed.
- **width**: Sets the width of the image.
- **height**: Sets the height of the image.

```
<img src="image.jpg" alt="Description of image">
```

```
<img src="image.jpg" alt="Description of image" width="500" height="600">
```

Anchor Tag:

The <a> tag, known as the anchor tag, is used to create hyperlinks in an HTML document. These links can navigate to other web pages, files, locations within the same page, email addresses, or any other URL.

Example:

1.Basic Hyperlink:

html

```
<a href="https://www.example.com">Visit Example.com</a>
```

2.Link to an Email Address:

html

```
<a href="mailto:someone@example.com">Send Email</a>
```

3.Link to an Anchor Within the Same Page:

html

```
<!-- Anchor tag --> <a href="#section1">Go to Section 1</a>
<!-- Target section --> <h2 id="section1">Section 1</h2>
 <p>Content of Section 1.</p>
```

Attributes:

•**href**: Specifies the URL of the page the link goes to.

•**target**: Specifies where to open the linked document. For example, _blank opens the link in a new tab or window.

•**title**: Provides additional information about the link, often displayed as a tooltip.

•**name**: (deprecated) Specifies a named anchor for linking within the same page.