



INSTITUTO POLITÉCNICO NACIONAL

Unidad Profesional Interdisciplinaria en
Ingeniería y Tecnologías Avanzadas
UPIITA



Asignatura: Aplicaciones Distribuidas

Profesor: Noe Sierra Romero

Grupo: 4TM3

Práctica 7:

Alumna: Bernal Aguilar Yuvia Abigail

1. Código dado por el profesor:

```
// npm install express
require("node:dns/promises").setServers(["1.1.1.1", "8.8.8.8"]);
var express = require("express");
var app = express(); //Contenedor de Endpoints o WS Restful
const { MongoClient } = require("mongodb");
var client = 0;

var dbName = "";
var collectionName = "";

// Create references to the database and collection in order to run
// operations on them.
var database = 0;
var collection = 0;

app.use(express.json());
app.use(express.urlencoded({ extended: true }));

function prepareDB() {
  dbName = "myDatabase";
  collectionName = "recipes";

  // Create references to the database and collection in order to run
  // operations on them.
  database = client.db(dbName);
  collection = database.collection(collectionName);
}

async function connectDB() {
  const uri =
    "mongodb+srv://yuviamixer111213_db_user:Kv39QDXgxpHKMqvD@cluster0.meslfq3.mongodb.net/?appName=Cluster0";

  client = new MongoClient(uri);

  // The connect() method does not attempt a connection; instead it instructs
  // the driver to connect using the settings provided when a connection
  // is required.
  await client.connect();
}

app.get("/", async function (request, response) {
  r = {
    message: "Nothing to send",
  };

  response.json(r);
});
```

```

/*
Calling this service sending payload as parameters in URL:
https://typesofwebservices.noesierra.repl.co/serv001?id=Nope&token=2345678dhuj435
67fgh&geo=123456789,1234567890
*/
app.get("/serv001", async function (req, res) {
  const user_id = req.query.id;
  const token = req.query.token;
  const geo = req.query.geo;

  r = {
    user_id: user_id,
    token: token,
    geo: geo,
  };

  res.json(r);
});

/*
Calling this service sending payload as parameters in URL:
https://typesofwebservices.noesierra.repl.co/serv001?id=Nope&token=2345678dhuj435
67fgh&geo=123456789,1234567890
*/
app.get("/serv0010", async function (req, res) {
  const user_id1 = req.query.id;
  const token1 = req.query.token;
  const geo1 = req.query.geo;

  r1 = {
    user_id: user_id1,
    token: token1,
    geo: geo1,
  };

  res.json(r1);
});

// Call this service sending payload in body: raw - json
/*
{
  "id": "nope",
  "token": "ertydfg456Dfgwerty",
  "geo": "12345678,34567890"
}
*/
app.post("/serv002", async function (req, res) {
  const user_id = req.body.id;
  const token = req.body.token;
  const geo = req.body.geo;

```

```

    r = {
      user_id: user_id,
      token: token,
      geo: geo,
    };

    res.json(r);
  });

  /*
  Call this service sending parameter as a part of the URL
  https://typesofwebservices.noesierra.repl.co/serv003/1234567
  */
  app.post("/serv003/:info", async function (req, res) {
    const info = req.params.info;
    let r = { info: info };
    res.json(r);
  });

  app.post("/receipt/insert", async function (req, res) {
    const recipes = [
      {
        name: "elotes cocidos",
        ingredients: [
          "corn",
          "mayonnaise",
          "cotija cheese",
          "sour cream",
          "lime",
        ],
        prepTimeInMinutes: 35,
      },
    ];

    let result = "";

    try {
      const insertManyResult = await collection.insertMany(recipes);
      console.log(
        `${insertManyResult.insertedCount} documents successfully inserted.\n`,
      );
      result = `${insertManyResult.insertedCount} documents successfully inserted.`;
    } catch (err) {
      console.error(
        `Something went wrong trying to insert the new documents: ${err}\n`,
      );
      result = `Something went wrong trying to insert the new documents: ${err}`;
    }
    let r = { result: result };
    res.json(r);
  });

```

```
app.listen(3000, async function () {  
  console.log("Aplicación ejemplo, escuchando el puerto 3000!");  
  await connectDB();  
  prepareDB();  
});
```

2. Usando postman /serv001:

The screenshot shows the Postman interface for a GET request. The URL bar contains `http://localhost:3000/serv001?id=nope&token=ertydfg456Dfgwerty&geo=12345678,34567890`. The 'Query Params' tab is active, displaying a table with the following data:

Key	Value	Description
id	nope	
token	ertydfg456Dfgwerty	
geo	12345678,34567890	

The 'Body' tab is also active, showing a JSON response:

```
{  
  "user_id": "nope",  
  "token": "ertydfg456Dfgwerty",  
  "geo": "12345678,34567890"  
}
```

The status bar at the bottom indicates a **200 OK** response with a time of 4 ms and a body size of 308 B.

3. Usando /serv002:

POST



http://localhost:3000/serv002

Docs Params Auth Headers (8) Body ● Scripts Set

Body ▼ 

{ } JSON ▼

 Preview

 Visualize ▼

```
1  {  
2    "user_id": "nope",  
3    "token": "ertydfg456Dfgwerty",  
4    "geo": "12345678,34567890"  
5  }
```