

RECURSION EXAMPLES

Factorial

```
#include <iostream>
using namespace std;

// Function to calculate factorial using recursion
long long factorial(int n) {
    if (n <= 1) return 1; // Base case
    return n * factorial(n - 1); // Recursive call
}

int main() {
    int n; cin >> n;
    cout << "Factorial of " << n << " is: " << factorial(n) << endl;
    return 0;
}
```

Java

```
import java.util.Scanner;

public class Factorial {

    // Function to calculate factorial using recursion
    public static long factorial(int n) {
        if (n <= 1) return 1; // Base case
        return n * factorial(n - 1); // Recursive call
    }

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = scanner.nextInt();
        System.out.println("Factorial of " + n + " is: " + factorial(n));
        scanner.close();
    }
}
```

Direct and indirect recursion

Direct Recursion Example display n to 1

In direct recursion, a function calls itself directly.

```
#include <iostream>
using namespace std;

void directRecursion(int n) {
    if (n == 0) return; // Base case
    cout << n << " ";
    directRecursion(n - 1); // Directly calling itself
}
```

```
int main() {
    cout << "Direct Recursion: ";
    directRecursion(5); // Example input
    return 0;
}
o/p
5 4 3 2 1
```

Java

display n to 1

```
public class DirectRecursion {
    static void directRecursion(int n) {
        if (n == 0) return; // Base case
        System.out.print(n + " ");
        directRecursion(n - 1); // Directly calling itself
    }

    public static void main(String[] args) {
        System.out.print("Direct Recursion: ");
        directRecursion(5); // Example input
    }
}

o/p
5 4 3 2 1
```

Indirect Recursion Example

In indirect recursion, a function calls another function, which then calls the first function.

```
#include <iostream>
using namespace std;

void functionA(int n);
void functionB(int n);

void functionA(int n) {
    if (n <= 0) return; // Base case
    cout << "A: " << n << " ";
    functionB(n - 1); // Calls functionB
}

void functionB(int n) {
    if (n <= 0) return; // Base case
    cout << "B: " << n << " ";
    functionA(n - 1); // Calls functionA
}

int main() {
    cout << "Indirect Recursion: ";
    functionA(5); // Example input
    return 0;
}
```

o/p

Indirect Recursion: A: 5 B: 4 A: 3 B: 2 A: 1

Java

```
public class IndirectRecursion {
    static void functionA(int n) {
        if (n <= 0) return; // Base case
        System.out.print("A: " + n + " ");
        functionB(n - 1); // Calls functionB
    }

    static void functionB(int n) {
        if (n <= 0) return; // Base case
        System.out.print("B: " + n + " ");
        functionA(n - 1); // Calls functionA
    }

    public static void main(String[] args) {
        System.out.print("Indirect Recursion: ");
        functionA(5); // Example input
    }
}
```

o/p

Indirect Recursion: A: 5 B: 4 A: 3 B: 2 A: 1

Tail recursion

In this approach, the recursive call is the last operation performed in the function.

Displaying 1 to 5 using Tail Recursion: 1 2 3 4 5

```
#include <iostream>
```

```
using namespace std;
```

```
void displayTail(int start, int n) {
    if (start > n) return; // Base case
    cout << start << " "; // Print before recursive call
    displayTail(start + 1, n); // Recursive call is the last operation
}
```

```
int main() {
    int n = 5;
    cout << "Displaying 1 to " << n << " using Tail Recursion: ";
    displayTail(1, n);
    return 0;
}
```

o/p

Displaying 1 to 5 using Tail Recursion: 1 2 3 4 5

Java

```
public class DisplayTailRecursion {
```

```

static void displayTail(int start, int n) {
    if (start > n) return; // Base case
    System.out.print(start + " "); // Print before recursive call
    displayTail(start + 1, n); // Recursive call is the last operation
}

public static void main(String[] args) {
    int n = 5;
    System.out.print("Displaying 1 to " + n + " using Tail Recursion: ");
    displayTail(1, n);
}
}
o/p
Displaying 1 to 5 using Tail Recursion: 1 2 3 4 5

```

Non Tail recursion

Displaying 1 to 5 using Non-Tail Recursion: 1 2 3 4 5

In this approach, the recursive call is not the last operation. There is a pending cout (in C++) or System.out.println (in Java) statement after the recursive call.

```

#include <iostream>
using namespace std;

void displayNonTail(int n) {
    if (n == 0) return; // Base case
    displayNonTail(n - 1); // Recursive call first
    cout << n << " "; // Print after recursive call
}

int main() {
    int n = 5;
    cout << "Displaying 1 to " << n << " using Non-Tail Recursion: ";
    displayNonTail(n);
    return 0;
}
o/p
Displaying 1 to 5 using Non-Tail Recursion: 1 2 3 4 5

```

Java

Displaying 1 to 5 using Non-Tail Recursion: 1 2 3 4 5

```

public class DisplayNonTailRecursion {

    static void displayNonTail(int n) {
        if (n == 0) return; // Base case
        displayNonTail(n - 1); // Recursive call first
        System.out.print(n + " "); // Print after recursive call
    }

    public static void main(String[] args) {
        int n = 5;

```

```

        System.out.print("Displaying 1 to " + n + " using Non-Tail Recursion: ");
        displayNonTail(n);
    }
}
o/p
Displaying 1 to 5 using Non-Tail Recursion: 1 2 3 4 5

```

Tail recursion for factorial

```

#include <iostream>
using namespace std;

```

```

// Tail-recursive function for factorial
void tailRecursion(int n, int result) {
    if (n == 0) {
        cout << "Result: " << result << endl;
        return;
    }
    tailRecursion(n - 1, n * result); // Recursive call is the last operation
}

```

```

int main() {
    int n = 5;
    cout << "Tail Recursion: Calculating factorial of " << n << endl;
    tailRecursion(n, 1); // Start with the result as 1
    return 0;
}
o/p

```

Tail Recursion: Calculating factorial of 5
Result: 120

Java

```

public class TailRecursion {

```

```

    // Tail-recursive function for factorial
    static void tailRecursion(int n, int result) {
        if (n == 0) {
            System.out.println("Result: " + result);
            return;
        }
        tailRecursion(n - 1, n * result); // Recursive call is the last operation
    }
}

```

```

    public static void main(String[] args) {
        int n = 5;
        System.out.println("Tail Recursion: Calculating factorial of " + n);
        tailRecursion(n, 1); // Start with the result as 1
    }
}
o/p

```

Tail Recursion: Calculating factorial of 5
Result: 120

Non tail recursion for factorial

C++

```
#include <iostream>
```

```
using namespace std;
```

```
// Non-tail-recursive function for factorial
```

```
int nonTailRecursion(int n) {
```

```
    if (n == 0) return 1; // Base case
```

```
    return n * nonTailRecursion(n - 1); // Recursive call is followed by multiplication
```

```
}
```

```
int main() {
```

```
    int n = 5;
```

```
    cout << "Non-Tail Recursion: Calculating factorial of " << n << endl;
```

```
    cout << "Result: " << nonTailRecursion(n) << endl;
```

```
    return 0;
```

```
}
```

o/p

Non-Tail Recursion: Calculating factorial of 5

Result: 120

Java

```
public class NonTailRecursion {
```

```
    // Non-tail-recursive function for factorial
```

```
    static int nonTailRecursion(int n) {
```

```
        if (n == 0) return 1; // Base case
```

```
        return n * nonTailRecursion(n - 1); // Recursive call is followed by multiplication
```

```
    }
```

```
    public static void main(String[] args) {
```

```
        int n = 5;
```

```
        System.out.println("Non-Tail Recursion: Calculating factorial of " + n);
```

```
        System.out.println("Result: " + nonTailRecursion(n));
```

```
    }
```

```
}
```

o/p

Non-Tail Recursion: Calculating factorial of 5

Result: 120

Q Sum of 1 to n using recursion

Sample Input

5

Sample Output

15

Sample Input

10

Sample Output

55

Input

17

Output

153

```
#include <iostream>
using namespace std;
```

```
// Recursive function to calculate the sum from 1 to n
```

```
int sum(int n) {
    if (n == 0) return 0; // Base case
    return n + sum(n - 1); // Recursive case
}
```

```
int main() {
    int n;
    cin >> n;
```

```
    cout << "Sum of numbers from 1 to " << n << " is: " << sum(n) << endl;
    return 0;
}
```

Java

```
import java.util.Scanner;
```

```
public class SumOfNumbers {
    // Recursive function to calculate the sum from 1 to n
    public static int sum(int n) {
        if (n == 0) return 0; // Base case
        return n + sum(n - 1); // Recursive case
    }
```

```
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = scanner.nextInt();
        System.out.println("Sum of numbers from 1 to " + n + " is: " + sum(n));
        scanner.close();
    }
}
```

QPrint Numbers in Reverse (n to 1)

Print numbers from n to 1 using recursion.

Sample Input

5

Sample Output

5 4 3 2 1

Input

7

Output

7 6 5 4 3 2 1

Input

1

Output

1

```
#include <iostream>
using namespace std;
```

```
void printReverse(int n) {
    if (n == 0) return; // Base case
    cout << n << " "; // Print current number
    printReverse(n - 1); // Recursive call
}
```

```
int main() {
    int n = 5;
    printReverse(n);
    return 0;
}
```

```
class Main {
    static void printReverse(int n) {
        if (n == 0) return; // Base case
        System.out.print(n + " "); // Print current number
        printReverse(n - 1); // Recursive call
    }

    public static void main(String[] args) {
        int n = 5;
        printReverse(n);
    }
}
```

Q Calculate Power

This is a great way to explain how recursion works with mathematical problems.

Problem:

Calculate x^n using recursion.

Code (C++):

```
#include <iostream>
using namespace std;
```

```
int power(int x, int n) {
    if (n == 0) return 1; // Base case:  $x^0 = 1$ 
    return x * power(x, n - 1); // Recursive case
}
```



```

int main() {
    int x = 2, n = 3;
    cout << x << " raised to the power " << n << " is: " << power(x, n) << endl;
    return 0;
}

```

Java

```

class Main {
    static int power(int x, int n) {
        if (n == 0) return 1; // Base case:  $x^0 = 1$ 
        return x * power(x, n - 1); // Recursive case
    }

    public static void main(String[] args) {
        int x = 2, n = 3;
        System.out.println(x + " raised to the power " + n + " is: " + power(x, n));
    }
}

```

Problem:

Count the number of digits in an integer n.

Code (C++):

```

#include <iostream>
using namespace std;

```

```

int countDigits(int n) {
    if (n == 0) return 0; // Base case
    return 1 + countDigits(n / 10); // Recursive case
}

```

```

int main() {
    int n = 12345;
    cout << "Number of digits in " << n << " is: " << countDigits(n) << endl;
    return 0;
}

```

Java

```

class Main {
    static int countDigits(int n) {
        if (n == 0) return 0; // Base case
        return 1 + countDigits(n / 10); // Recursive case
    }

    public static void main(String[] args) {
        int n = 12345;
        System.out.println("Number of digits in " + n + " is: " + countDigits(n));
    }
}

```

QPalindrome Check

Check whether a given string is a palindrome using recursion.

```
#include <iostream>
#include <string>
using namespace std;

bool isPalindrome(string str, int start, int end) {
    if (start >= end) return true; // Base case
    if (str[start] != str[end]) return false; // Mismatch found
    return isPalindrome(str, start + 1, end - 1); // Recursive call
}

int main() {
    string str = "radar";
    cout << str << " is " << (isPalindrome(str, 0, str.length() - 1) ? "a palindrome" : "not a palindrome") <<
endl;
    return 0;
}

class Main {
    static boolean isPalindrome(String str, int start, int end) {
        if (start >= end) return true; // Base case
        if (str.charAt(start) != str.charAt(end)) return false; // Mismatch found
        return isPalindrome(str, start + 1, end - 1); // Recursive call
    }

    public static void main(String[] args) {
        String str = "radar";
        System.out.println(str + " is " + (isPalindrome(str, 0, str.length() - 1) ? "a palindrome" : "not a
palindrome"));
    }
}
```

Q Problem Statement

Write a program to find the maximum element in a 1D array using recursion. The program should accept an array of integers from the user and find the maximum value using a recursive function. The array size and elements should be provided by the user in the main function.

Sample Input

6

3 1 4 1 5 9

Output:

Maximum Element: 9

Sample Input

5

-10 -20 -30 -5 -15

Output:

Maximum Element: -5

Sample Input:

5

100 200 300 400 500

Output:

Maximum Element: 500

C++ Implementation

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
// Recursive function to find the maximum element
```

```
int findMax(const vector<int>& arr, int n) {
```

```
    if (n == 1) {
```

```
        return arr[0];
```

```
    }
```

```
    return max(arr[n - 1], findMax(arr, n - 1));
```

```
}
```

```
int main() {
```

```
    int size;
```

```
    cin >> size;
```

```
    vector<int> arr(size);
```

```
    for (int i = 0; i < size; i++) {
```

```
        cin >> arr[i];
```

```
    }
```

```
    int maxElement = findMax(arr, size);
```

```
    cout << maxElement << endl;
```

```
    return 0;
```

```
}
```

Java Implementation

```
import java.util.Scanner;
```

```
public class MaxElement {
```

```
    // Recursive function to find the maximum element
```

```
    public static int findMax(int[] arr, int n) {
```

```
        if (n == 1) {
```

```
            return arr[0];
```

```
        }
```

```
        return Math.max(arr[n - 1], findMax(arr, n - 1));
```

```
    }
```

```
    public static void main(String[] args) {
```

```
        Scanner scanner = new Scanner(System.in);
```

```
        int size = scanner.nextInt();
```

```
        int[] arr = new int[size];
```

```

        for (int i = 0; i < size; i++) {
            arr[i] = scanner.nextInt();
        }

        int maxElement = findMax(arr, size);
        System.out.println(maxElement);

        scanner.close();
    }
}

```

Problem Statement

Write a program to print a given string in reverse order using recursion. The program should accept a string from the user in the main function and use a recursive function to print the string in reverse order, one character at a time.

Sample Input:

hello

Output:

olleh

Input:

OpenAI

Output:

IAnepO

Input:

12345

Output:

54321

C++ Implementation

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
// Recursive function to print string in reverse order
```

```
void printReverse(const string& str, int index) {
```

```
    if (index < 0) {
```

```
        return;
```

```
    }
```

```
    cout << str[index];
```

```
    printReverse(str, index - 1);
```

```
}
```

```
int main() {
```

```
    string input;
```

```
    cin >> input;
```

```

    printReverse(input, input.size() - 1);
    cout << endl;

    return 0;
}

```

Java Implementation

```

import java.util.Scanner;

public class ReverseString {
    // Recursive function to print string in reverse order
    public static void printReverse(String str, int index) {
        if (index < 0) {
            return;
        }
        System.out.print(str.charAt(index));
        printReverse(str, index - 1);
    }

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        String input = scanner.nextLine();

        printReverse(input, input.length() - 1);
        System.out.println();

        scanner.close();
    }
}

```

QWrite a program to reverse a given array using recursion. The program should accept an array of integers from the user in the main function, reverse it using a recursive function, and display the reversed array.

Sample Input:

5
1 2 3 4 5

Output:

5 4 3 2 1

Sample Input:

4
10 20 30 40

Output:

40 30 20 10

Sample Input:

1
7

Output:

C++ Implementation

```

#include <iostream>
#include <vector>
using namespace std;

// Recursive function to reverse an array
void reverseArray(vector<int>& arr, int start, int end) {
    if (start >= end) {
        return;
    }
    swap(arr[start], arr[end]);
    reverseArray(arr, start + 1, end - 1);
}

int main() {
    int size;
    cin >> size;

    vector<int> arr(size);
    for (int i = 0; i < size; i++) {
        cin >> arr[i];
    }

    reverseArray(arr, 0, size - 1);

    for (int i = 0; i < size; i++) {
        cout << arr[i] << " ";
    }
    cout << endl;

    return 0;
}

```

Java Implementation

```

import java.util.Scanner;

public class ReverseArray {
    // Recursive function to reverse an array
    public static void reverseArray(int[] arr, int start, int end) {
        if (start >= end) {
            return;
        }
        // Swap elements
        int temp = arr[start];
        arr[start] = arr[end];
        arr[end] = temp;
        reverseArray(arr, start + 1, end - 1);
    }

    public static void main(String[] args) {

```

```

Scanner scanner = new Scanner(System.in);

int size = scanner.nextInt();

int[] arr = new int[size];
for (int i = 0; i < size; i++) {
    arr[i] = scanner.nextInt();
}

reverseArray(arr, 0, size - 1);

for (int i = 0; i < size; i++) {
    System.out.print(arr[i] + " ");
}
System.out.println();

scanner.close();
}
}

```

Problem Statement

Write a program to calculate the sum of all elements in an array using recursion. The program should accept an array of integers from the user in the main function, compute the sum using a recursive function, and display the result.

Sample Input:

5
1 2 3 4 5

Output:

Sum of Elements: 15

Sample Input:

4
10 20 30 40

Output:

Sum of Elements: 100

Input:

4
-5 15 -10 20

Output:

Sum of Elements: 20

C++ Implementation

```

#include <iostream>
#include <vector>
using namespace std;

```

// Recursive function to calculate the sum of elements

```

int sumOfElements(const vector<int>& arr, int n) {
    if (n == 0) {

```

```

        return 0; // Base case: empty array
    }
    return arr[n - 1] + sumOfElements(arr, n - 1);
}

```

```

int main() {
    int size;
    //cout << "Enter the size of the array: ";
    cin >> size;

    vector<int> arr(size);
    //cout << "Enter the elements of the array: ";
    for (int i = 0; i < size; i++) {
        cin >> arr[i];
    }

    int sum = sumOfElements(arr, size);
    cout << sum << endl;

    return 0;
}

```

Java Implementation

```

import java.util.Scanner;

public class SumOfArray {
    // Recursive function to calculate the sum of elements
    public static int sumOfElements(int[] arr, int n) {
        if (n == 0) {
            return 0; // Base case: empty array
        }
        return arr[n - 1] + sumOfElements(arr, n - 1);
    }

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int size = scanner.nextInt();

        int[] arr = new int[size];
        for (int i = 0; i < size; i++) {
            arr[i] = scanner.nextInt();
        }

        int sum = sumOfElements(arr, size);
        System.out.println(sum);

        scanner.close();
    }
}

```

Problem Statement

Q Write a program to check whether a given array is sorted in non-decreasing order using recursion. The program should accept an array of integers from the user in the main function, and a recursive function should determine if the array is sorted. If the array is sorted, output true; otherwise, output false.

Test Cases

Test Case 1:

Input:

5

1 2 3 4 5

Output:

Is Sorted: true

Test Case 2:

4

10 20 15 40

Output:

Is Sorted: false

Test Case 3:

4

5 5 5 5

Output:

Is Sorted: true

C++ Implementation

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
// Recursive function to check if array is sorted
```

```
bool isSorted(const vector<int>& arr, int index) {
```

```
    if (index == arr.size() - 1 || arr.size() == 0) {
```

```
        return true; // Base case: single element or end of array
```

```
    }
```

```
    if (arr[index] > arr[index + 1]) {
```

```
        return false;
```

```
    }
```

```
    return isSorted(arr, index + 1);
```

```
}
```

```
int main() {
```

```
    int size;
```

```
    cin >> size;
```

```
    vector<int> arr(size);
```

```
    for (int i = 0; i < size; i++) {
```

```
        cin >> arr[i];
```

```
    }
```

```
    bool result = isSorted(arr, 0);
```

```
    cout << "Is Sorted: " << (result ? "true" : "false") << endl;
```

```
    return 0;
```

```
}
```

Java Implementation

```
import java.util.Scanner;

public class ArraySortedCheck {
    // Recursive function to check if array is sorted
    public static boolean isSorted(int[] arr, int index) {
        if (index == arr.length - 1 || arr.length == 0) {
            return true; // Base case: single element or end of array
        }
        if (arr[index] > arr[index + 1]) {
            return false;
        }
        return isSorted(arr, index + 1);
    }

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int size = scanner.nextInt();

        int[] arr = new int[size];
        for (int i = 0; i < size; i++) {
            arr[i] = scanner.nextInt();
        }

        boolean result = isSorted(arr, 0);
        System.out.println("Is Sorted: " + (result ? "true" : "false"));

        scanner.close();
    }
}
```

Problem Statement

Write a program to search for a given element in an array using recursion. The program should accept an array of integers and a target value from the user in the main function. A recursive function should return the index of the first occurrence of the target element in the array. If the target element is not found, the function should return -1.

Test Cases

Test Case 1:

Input:

5

10 20 30 40 50

30

Output:

2

Test Case 2:

Input:

5

5 8 7 8 9

8

Output:

1

Test Case 3:

5

1 2 3 4 5

10

Output:

-1

C++ Implementation

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
// Recursive function to search for an element
```

```
int searchElement(const vector<int>& arr, int index, int target) {
```

```
    if (index == arr.size()) {
```

```
        return -1; // Base case: reached end of the array
```

```
    }
```

```
    if (arr[index] == target) {
```

```
        return index; // Element found
```

```
    }
```

```
    return searchElement(arr, index + 1, target);
```

```
}
```

```
int main() {
```

```
    int size, target;
```

```
    cin >> size;
```

```
    vector<int> arr(size);
```

```
    for (int i = 0; i < size; i++) {
```

```
        cin >> arr[i];
```

```
    }
```

```
    cin >> target;
```

```
    int result = searchElement(arr, 0, target);
```

```
    cout << result << endl;
```

```
    return 0;
```

```
}
```

Java Implementation

```
import java.util.Scanner;
```

```
public class SearchElement {
```

```
    // Recursive function to search for an element
```

```
    public static int searchElement(int[] arr, int index, int target) {
```

```
        if (index == arr.length) {
```

```
            return -1; // Base case: reached end of the array
```

```
        }
```

```
        if (arr[index] == target) {
```

```

        return index; // Element found
    }
    return searchElement(arr, index + 1, target);
}

public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);

    int size = scanner.nextInt();

    int[] arr = new int[size];
    for (int i = 0; i < size; i++) {
        arr[i] = scanner.nextInt();
    }

    int target = scanner.nextInt();

    int result = searchElement(arr, 0, target);
    System.out.println(result);

    scanner.close();
}
}

```

Write a program to check whether a given string is a palindrome using recursion. A string is considered a palindrome if it reads the same backward as forward. The program should accept a string from the user and use a recursive function to check if the string is a palindrome.

Test Case 1:

Input:

String: radar

Output:

The string is a palindrome.

Test Case 2:

Input:

String: hello

Output:

The string is not a palindrome.

Test Case 3:

Input:

String: abba

Output:

The string is a palindrome.

C++ Implementation

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
// Recursive function to check if a string is a palindrome
```

```
bool isPalindrome(const string& str, int start, int end) {
```

```
    if (start >= end) {
```

```

        return true; // Base case: all characters checked
    }
    if (str[start] != str[end]) {
        return false; // Characters do not match
    }
    return isPalindrome(str, start + 1, end - 1);
}

int main() {
    string input;
    cin >> input;

    bool result = isPalindrome(input, 0, input.size() - 1);
    if (result) {
        cout << "The string is a palindrome." << endl;
    } else {
        cout << "The string is not a palindrome." << endl;
    }

    return 0;
}

```

Java Implementation

```

import java.util.Scanner;

public class PalindromeCheck {
    // Recursive function to check if a string is a palindrome
    public static boolean isPalindrome(String str, int start, int end) {
        if (start >= end) {
            return true; // Base case: all characters checked
        }
        if (str.charAt(start) != str.charAt(end)) {
            return false; // Characters do not match
        }
        return isPalindrome(str, start + 1, end - 1);
    }

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        String input = scanner.nextLine();

        boolean result = isPalindrome(input, 0, input.length() - 1);
        if (result) {
            System.out.println("The string is a palindrome.");
        } else {
            System.out.println("The string is not a palindrome.");
        }

        scanner.close();
    }
}

```

```
}
```

Problem Statement

Write a program to count the number of vowels in a given string using recursion. The program should accept a string from the user and use a recursive function to count the vowels. The vowels are a, e, i, o, u (case-insensitive).

Test Cases

Test Case 1:

Input:

hello

Output:

2

Test Case 2:

Input:

OpenAI

Output:

3

Test Case 3:

Input:

xyz

Output:

0

C++ Implementation

```
#include <iostream>
```

```
#include <string>
```

```
#include <cctype>
```

```
using namespace std;
```

```
// Recursive function to count vowels in a string
```

```
int countVowels(const string& str, int index) {
```

```
    if (index == str.size()) {
```

```
        return 0; // Base case: end of string
```

```
    }
```

```
    char ch = tolower(str[index]); // Convert character to lowercase
```

```
    int count = (ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u') ? 1 : 0;
```

```
    return count + countVowels(str, index + 1);
```

```
}
```

```
int main() {
```

```
    string input;
```

```
    cin >> input;
```

```
    int vowelCount = countVowels(input, 0);
```

```
    cout << vowelCount << endl;
```

```
    return 0;
```

```
}
```

Java Implementation

```
import java.util.Scanner;

public class VowelCount {
    // Recursive function to count vowels in a string
    public static int countVowels(String str, int index) {
        if (index == str.length()) {
            return 0; // Base case: end of string
        }
        char ch = Character.toLowerCase(str.charAt(index)); // Convert character to lowercase
        int count = (ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u') ? 1 : 0;
        return count + countVowels(str, index + 1);
    }

    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        String input = scanner.nextLine();

        int vowelCount = countVowels(input, 0);
        System.out.println(vowelCount);

        scanner.close();
    }
}
```

Problem Statement

Write a program to remove consecutive duplicate characters from a string using recursion. The program should accept a string from the user in the main function and use a recursive function to return a string where all consecutive duplicate characters are removed.

Test Cases

Test Case 1:

Input:

aaabbccdee

Output:

abcde

Test Case 2:

Input:

aabbbaa

Output:

aba

Test Case 3:

Input:

abcd

Output:

abcd

C++ Implementation

```
#include <iostream>
#include <string>
using namespace std;
```

```
// Recursive function to remove consecutive duplicate characters
string removeDuplicates(const string& str, int index = 0) {
    if (index == str.size() - 1 || str.empty()) {
        return str.substr(index, 1); // Base case: return the last character
    }
    if (str[index] == str[index + 1]) {
        return removeDuplicates(str, index + 1); // Skip duplicate character
    }
    return str[index] + removeDuplicates(str, index + 1);
}
```

```
int main() {
    string input;
    cin >> input;

    string result = removeDuplicates(input);
    cout << result << endl;

    return 0;
}
```

Java Implementation

```
import java.util.Scanner;
```

```
public class RemoveDuplicates {
    // Recursive function to remove consecutive duplicate characters
    public static String removeDuplicates(String str, int index) {
        if (index == str.length() - 1 || str.isEmpty()) {
            return str.substring(index); // Base case: return the last character
        }
        if (str.charAt(index) == str.charAt(index + 1)) {
            return removeDuplicates(str, index + 1); // Skip duplicate character
        }
        return str.charAt(index) + removeDuplicates(str, index + 1);
    }
}
```

```
public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);
    String input = scanner.nextLine();
    String result = removeDuplicates(input, 0);
    System.out.println(result);

    scanner.close();
}
}
```

<https://codeforces.com/problemset/problem/110/A>

A. Nearly Lucky Number

```
#include <iostream>
using namespace std;
```



```

int countLuckyDigits(long long n) {
    if (n == 0) {
        return 0;
    }
    int digit = n % 10;
    if (digit == 4 || digit == 7) {
        return 1 + countLuckyDigits(n / 10);
    }
    return countLuckyDigits(n / 10);
}

```

```

int main() {
    long long n;
    cin >> n;

    int count = countLuckyDigits(n);
    if (count == 4 || count == 7) {
        cout << "YES" << endl;
    } else {
        cout << "NO" << endl;
    }

    return 0;
}

```

Java

```

import java.util.Scanner;

```

```

public class Main {

```

```

    static int countLuckyDigits(long n) {
        if (n == 0) {
            return 0;
        }
        int digit = (int)(n % 10);
        if (digit == 4 || digit == 7) {
            return 1 + countLuckyDigits(n / 10);
        }
        return countLuckyDigits(n / 10);
    }
}

```

```

public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);
    long n = scanner.nextLong();

    int count = countLuckyDigits(n);
    if (count == 4 || count == 7) {
        System.out.println("YES");
    } else {
        System.out.println("NO");
    }
}

```

```
        scanner.close();  
    }  
}
```