

Switch Case :

```
Switch (expression)
{
```

```
    Case Constant:
```

\* Constant ke jagah pe variable nahi likh sakte hain. Sirf Integer and Character Constant likh sakte hain.

```
    Case Constant:
```

\* All Constant are different.

\* Switch & case is a keyword.

```
    Case Constant:
```

\* You can write all cases and default in any order.

\* When break keyword encounters, control moves outside the switch body.

Break and default :

```
#include <stdio.h>
```

```
int main()
{
```

```
    int x;
```

```
    printf("Enter a number: ");
```

```
    scanf("%d", &x);
```

```
    switch (x)
    {
```

```
        Case 1 ... 10:
```

```
            printf("Sunday\n");
            break;
```

```
        Case 11 ... 20:
```

```
            printf("Monday\n");
            break;
```

```
        default:
```

```
            printf("Holiday");
```

```
    }
}
```

NOTE! — (...) means ?

⇒ Triple dot use hota hai Range batane ke liye.

Ex:  $x \geq 1 \ \&\& \ x \leq 10$   
 ⇒ 1 ... 10

Subject: \_\_\_\_\_

Date: \_\_\_\_\_

## —: Menu driven Program :—

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int main()
```

```
{  
    int x, a, b;
```

```
    while (1)
```

```
    {  
        printf("\n 1. Addition");
```

```
        printf("\n 2. Subtraction");
```

```
        printf("\n 3. Multiplication");
```

```
        printf("\n 4. Division");
```

```
        printf("\n 5. Exit");
```

```
        printf("Enter a number: ");
```

```
        scanf("%d", &x);
```

```
        switch (x)
```

```
        {
```

Case 1:

```
            printf("Enter two number: ");
```

```
            scanf("%d %d", &a, &b);
```

```
            printf("Sum is %d", a+b);
```

```
            break;
```

Case 2:

```
            printf("Enter two number: ");
```

```
            scanf("%d %d", &a, &b);
```

```
            printf("Subtraction is %d", a-b);
```

```
            break;
```

Case 3:

```
            printf("Enter two number: ");
```

```
            scanf("%d %d", &a, &b);
```

Subject: \_\_\_\_\_

Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

```
printf("Multiplication is %d", a*b);  
break;
```

Case 4:

```
printf("Enter two number: ");  
scanf("%d %d", &a, &b);  
printf("Division is %d", a/b);  
break;
```

Case 5:

```
exit(0);
```

default:

```
printf("\n Invalid choice");
```

```
}  
}  
return 0;
```