



The 46th International Conference on Software Engineering (ICSE 2024)

Beyond a Joke: Dead Code Elimination Can Delete Live Code

Haoxin Tu, Lingxiao Jiang, Debin Gao (Singapore Management University)
He Jiang (Dalian University of Technology)

18/04/2024, Lisbon



❑ What is Dead Code Elimination (DCE)?

- A fundamental compiler optimization technique that removes dead code (e.g., unreachable or reachable but whose results are unused) in the program

Background: Dead Code Elimination

❑ What is Dead Code Elimination (DCE)?

- A fundamental compiler optimization technique that removes dead code (e.g., unreachable or reachable but whose results are unused) in the program

```
1  int foo(void) {  
2      int a = 24;  
3      int b = 25; /* Assignment to dead variable */  
4      int c;  
5      c = a * 4;  
6      return c;  
7      b = 24; /* Unreachable code */  
8      return 0;  
9  }
```

```
1  int main(void) {  
2      int a = 5, b = 6, c = 0;  
3      c = a * (b / 2);  
4      if (0) { /* DEBUG */  
5          int ret = foo();  
6          printf("%d\n", ret);  
7      }  
8      return c;  
9  }
```

Background: Dead Code Elimination

❑ What is Dead Code Elimination (DCE)?

- A fundamental compiler optimization technique that removes dead code (e.g., unreachable or reachable but whose results are unused) in the program

```
1  int foo(void) {  
2      int a = 24;  
3      int b = 25; /* Assignment to dead variable */  
4      int c;  
5      c = a * 4;  
6      return c;  
7      b = 24; /* Unreachable code */  
8      return 0;  
9  }
```

```
1  int main(void) {  
2      int a = 5, b = 6, c = 0;  
3      c = a * (b / 2);  
4      if (0) { /* DEBUG */  
5          int ret = foo();  
6          printf("%d\n", ret);  
7      }  
8      return c;  
9  }
```

Background: Dead Code Elimination

❑ What is Dead Code Elimination (DCE)?

- A fundamental compiler optimization technique that removes dead code (e.g., unreachable or reachable but whose results are unused) in the program

```
1  int foo(void) {  
2      int a = 24;  
3      int b = 25; /* Assignment to dead variable */  
4      int c;  
5      c = a * 4;  
6      return c;  
7      b = 24; /* Unreachable code */  
8      return 0;  
9  }
```

```
1  int main(void) {  
2      int a = 5, b = 6, c = 0;  
3      c = a * (b / 2);  
4      if (0) { /* DEBUG */  
5          int ret = foo();  
6          printf("%d\n", ret);  
7      }  
8      return c;  
9  }
```

Background: Dead Code Elimination

❑ What is Dead Code Elimination (DCE)?

- A fundamental compiler optimization technique that removes dead code (e.g., unreachable or reachable but whose results are unused) in the program

```
1  int foo(void) {  
2    int a = 24;  
3    int b = 25; /* Assignment to dead variable */  
4    int c;  
5    c = a * 4;  
6    return c;  
7    b = 24; /* Unreachable code */  
8    return 0;  
9  }
```

```
1  int main(void) {  
2    int a = 5, b = 6, c = 0;  
3    c = a * (b / 2);  
4    if (0) { /* DEBUG */  
5        int ret = foo();  
6        printf("%d\n", ret);  
7    }  
8    return c;  
9  }
```

- Benefits of DCE: produce **smaller** or **faster** executables
 - Many other applications and languages (Java, Go, and Rust, etc.)

Motivation

Motivation

Question: Can DCE happen to erroneously delete live code?

Question: Can DCE happen to erroneously delete live code?

Question: Can DCE happen to erroneously delete live code?

- **Motivating example**

Question: Can DCE happen to erroneously delete live code?

➤ Motivating example

```
int idx = 0;
int a = 0;
void __attribute__((noinline)) marker_2(){ ++idx; }
static void c() { marker_2(); }
void d(int j) { for (;;) ; } // infinite loop
void e() { for (int i = 0; i < 100; m++) d(i); }
void f() {
    e(); // live code here is erroneously deleted
    c();
}
void g() { if (a == 0x99)    f(); }

int main (int argc, char* argv[]) {
    // when a = 0x99, the bug triggers
    a = strtol(argv[1], NULL, 16);
    g();
    printf("%d", idx);
    return 0;
}
```

A *miscompilation* bug detected by our approach

Question: Can DCE happen to erroneously delete live code?

➤ Motivating example

```
int idx = 0;
int a = 0;
void __attribute__((noinline)) marker_2(){ ++idx; }
static void c() { marker_2(); }
void d(int j) { for (;;) ; } // infinite loop
void e() { for (int i = 0; i < 100; m++) d(i); }
void f() {
    e(); // live code here is erroneously deleted
    c();
}
void g() { if (a == 0x99)    f(); }

int main (int argc, char* argv[]) {
    // when a = 0x99, the bug triggers
    a = strtol(argv[1], NULL, 16);
    g();
    printf( "%d", idx);
    return 0;
}
```

A *miscompilation* bug detected by our approach

```
int idx = 0;
int a = 0;
void __attribute__((noinline)) marker_2(){ ++idx; }
static void c() { marker_2(); }
void d(int j) { for (;;) ; } // infinite loop
void e() { for (int i = 0; i < 100; m++) d(i); }
void f() {
    e(); // live code here is erroneously deleted
    c();
}
void g() { if (a == 0x99)    f(); }

int main (int argc, char* argv[]) {
    // when a = 0x99, the bug triggers
    a = strtol(argv[1], NULL, 16);
    g();
    printf("%d", idx);
    return 0;
}
```

Question: Can DCE happen to erroneously delete live code?

➤ Motivating example

```
int idx = 0;
int a = 0;
void __attribute__((noinline)) marker_2(){ ++idx; }
static void c() { marker_2(); }
void d(int j) { for (;;) ; } // infinite loop
void e() { for (int i = 0; i < 100; m++) d(i); }
void f() {
    e(); // live code here is erroneously deleted
    c();
}
void g() { if (a == 0x99)    f(); }

int main (int argc, char* argv[]) {
    // when a = 0x99, the bug triggers
    a = strtol(argv[1], NULL, 16);
    g();
    printf("%d", idx);
    return 0;
}
```

A *miscompilation* bug detected by our approach

	Executable 1
(Input)	0x99
(Output)	Killed - processing time exceeded Program terminated with signal: SIGKILL

	Executable 2
(Input)	0x99
(Output)	1

Wrong binary code

<https://godbolt.org/z/z7zxexfr1>

Question: Can DCE happen to erroneously delete live code?

➤ Motivating example

```
int idx = 0;
int a = 0;
void __attribute__((noinline)) marker_2(){ ++idx; }
static void c() { marker_2(); }
void d(int j) { for (;;) ; } // infinite loop
void e() { for (int i = 0; i < 100; m++) d(i); }
void f() {
    e(); // live code here is erroneously deleted
    c();
}
void g() { if (a == 0x99) f(); }


int main (int argc, char* argv[]) {
    // when a = 0x99, the bug triggers
    a = strtol(argv[1], NULL, 16);
    g();
    printf("%d", idx);
    return 0;
}
```

(Input)

(Output)

(Input)

(Output)



Executor x86-64 clang 12.0.0 (C, Editor #1)

A ▾ □ Wrap lines [Icons]


x86-64 clang 12.0.0 [Dropdown] [Checkmark] -O3 -std=c99

0x99

Program returned: 143
Program stderr

(Output) Killed - processing time exceeded
Program terminated with signal: SIGKILL

Executable 1



Executor x86-64 clang 11.0.1 (C, Editor #1)

A ▾ □ Wrap lines [Icons]

x86-64 clang 11.0.1 [Dropdown] [Checkmark] -O3 -std=c99

0x99

Program returned: 0
Program stdout

(Output) 1

Wrong binary code Executable 2

<https://godbolt.org/z/z7zxexfr1>

A *miscompilation* bug detected by our approach

Solution: Xdead


Solution: Xdead

- **Key insights: divergence indicates DCE bugs**
 - Identify the divergent portions in binary first
 - leverage symbolic execution to reveal the divergent portion

Solution: Xdead

- **Key insights: divergence indicates DCE bugs**
 - Identify the divergent portions in binary first
 - leverage symbolic execution to reveal the divergent portion


① Test Program Instrumentation



Solution: Xdead

- **Key insights: divergence indicates DCE bugs**
- Identify the divergent portions in binary first
 - leverage symbolic execution to reveal the divergent portion

① Test Program Instrumentation




The marker function:

```
void __attribute__((noinline)) marker_i() { ++idx; };
```

Solution: Xdead

- **Key insights: divergence indicates DCE bugs**
- Identify the divergent portions in binary first
 - leverage symbolic execution to reveal the divergent portion

① Test Program Instrumentation




The marker function:

```
void __attribute__((noinline)) marker_i() { ++idx; };
```

Solution: Xdead

➤ Key insights: divergence indicates DCE bugs

- Identify the divergent portions in binary first
- leverage symbolic execution to reveal the divergent portion




The marker function:

```
void __attribute__((noinline)) marker_i() { ++idx; };
```

Solution: Xdead

➤ Key insights: divergence indicates DCE bugs

- Identify the divergent portions in binary first
- leverage symbolic execution to reveal the divergent portion




The marker function:

```
void __attribute__((noinline)) marker_i() { ++idx; };
```

Solution: Xdead

➤ Key insights: divergence indicates DCE bugs

- Identify the divergent portions in binary first
- leverage symbolic execution to reveal the divergent portion



The marker function:

```
void __attribute__((noinline)) marker_i() { ++idx; };
```


Preliminary results

➤ Evaluation setup

- Benchmark
 - **10,000** seed program from Csmith
- Subjects
 - GCC and LLVM
- Running setting
 - four scenarios under “-O3”

➤ Metric

- Number of divergent markers
- Number of bugs

➤ Evaluation setup

- Benchmark
 - **10,000** seed program from Csmith
- Subjects
 - GCC and LLVM
- Running setting
 - four scenarios under “-O3”

Table 1: Statistics of divergent markers and test programs

Testing Scenarios	Num.Div.b1	Num.Div.b2	Num.TP	Per.TP	Ave.M
GCC-10/11 (-std=c99)	52,553	0	5,897	58.97%	8.91
GCC-10/11 (-std=c11)	49,431	0	5,758	57.58%	8.59
LLVM-11/12(-std=c99)	187	60	70	0.007%	4.12
LLVM-11/12 (-std=c11)	142	57	68	0.0068%	2.93

➤ Metric

- Number of divergent markers
- Number of bugs

➤ Evaluation setup

- Benchmark
 - **10,000** seed program from Csmith
- Subjects
 - GCC and LLVM
- Running setting
 - four scenarios under “-O3”

Table 1: Statistics of divergent markers and test programs

Testing Scenarios	Num.Div.b1	Num.Div.b2	Num.TP	Per.TP	Ave.M
GCC-10/11 (-std=c99)	52,553	0	5,897	58.97%	8.91
GCC-10/11 (-std=c11)	49,431	0	5,758	57.58%	8.59
LLVM-11/12(-std=c99)	187	60	70	0.007%	4.12
LLVM-11/12 (-std=c11)	142	57	68	0.0068%	2.93

➤ Metric

- Number of divergent markers
- Number of bugs

➤ Summary

- Found many divergent portions indicating erroneously deleted live code (i.e., wrong compiler optimization opportunities)
- Detected **Two** miscompilation bugs in LLVM compilers


Conclusion

Conclusion


Answer: DCE can erroneously delete live code sometimes (Solution: Xdead)

Conclusion

Answer: DCE can erroneously delete live code sometimes (Solution: Xdead)



Answer: DCE can erroneously delete live code sometimes (Solution: Xdead)



➤ Future work

- Utilize more fine-grained binary analysis to identify fine-grained divergent portions in **Part 1**
- Improve the efficiency of **Part 3**
 - efficient path exploration



Paper



Code



The 46th International Conference on Software Engineering (ICSE 2024)

Thank you & Questions?

Beyond a Joke: Dead Code Elimination Can Delete Live Code

Haoxin Tu, Lingxiao Jiang, Debin Gao (Singapore Management University)
He Jiang (Dalian University of Technology)

18/04/2024, Lisbon