



Scipy.org (<http://scipy.org/>) Docs (<http://docs.scipy.org/>)

NumPy v1.10 Manual ([../index.html](http://docs.scipy.org/doc/numpy/reference/generated/numpy.savetxt.html)) NumPy Reference ([../index.html](http://docs.scipy.org/doc/numpy/reference/))

Routines ([../routines.html](http://docs.scipy.org/doc/numpy/reference/routines.html)) Input and output ([../routines.io.html](http://docs.scipy.org/doc/numpy/reference/routines.io.html))

[index \(../genindex.html\)](http://docs.scipy.org/doc/numpy/reference/generated/numpy.savetxt.html) [next \(numpy.genfromtxt.html\)](http://docs.scipy.org/doc/numpy/reference/generated/numpy.genfromtxt.html) [previous \(numpy.loadtxt.html\)](http://docs.scipy.org/doc/numpy/reference/generated/numpy.loadtxt.html)

numpy.savetxt

`numpy.savetxt(fname, X, fmt='%.18e', delimiter=' ', newline='\n', header='', footer='', comments='# ')` (<http://github.com/numpy/numpy/blob/v1.10.1/numpy/lib/npio.py#L967-L1166>) [source]

Save an array to a text file.

用在调试代码的过程中保存ndarray格式的【中间变量】

Previous topic

[numpy.loadtxt](http://docs.scipy.org/doc/numpy/reference/generated/numpy.loadtxt.html)
([numpy.loadtxt.htm](http://docs.scipy.org/doc/numpy/reference/generated/numpy.loadtxt.html))

Next topic

[numpy.genfromtxt](http://docs.scipy.org/doc/numpy/reference/generated/numpy.genfromtxt.html)
([numpy.genfromtxt.](http://docs.scipy.org/doc/numpy/reference/generated/numpy.genfromtxt.html))

Parameters: **fname** : filename or file handle

If the filename ends in `.gz`, the file is automatically saved in compressed gzip format. loadtxt

([numpy.loadtxt.html#numpy.loadtxt](#))

understands gzipped files transparently.

后缀是啥？

X : array_like

Data to be saved to a text file.

fmt : str or sequence of strs, optional

A single format (`%10.5f`), a sequence of formats, or a multi-format string, e.g. `'Iteration %d - %10.5f'`, in which case delimiter is ignored. For complex `X`, the legal options for `fmt` are:

a. a single specifier, `fmt='%4e'`, resulting in numbers formatted like `'(%s+%sj)' % (fmt, fmt)`

b. a full string specifying every real and imaginary part, e.g.

`' %4e %+4j %4e %+4j`

`%4e %+4j'` for 3 columns

c. a list of specifiers, one per column - in this case, the real and imaginary part must have separate specifiers, e.g. `['%.3e + %.3ej', '(%15e%+.15ej)']` for 2 columns

delimiter : str, optional

String or character separating columns.

newline : str, optional

String or character separating lines.

New in version 1.5.0.

header : str, optional

String that will be written at the beginning of the file.

New in version 1.7.0.

footer : str, optional

String that will be written at the end of the file.

New in version 1.7.0.

comments : str, optional

String that will be prepended to the `header` and `footer` strings, to mark them as comments. Default: `'# '`, as expected by e.g. `numpy.loadtxt`.

New in version 1.7.0.

See also:

save ([numpy.save.html#numpy.save](#)) Save an array to a binary file in NumPy `.npy` format

savez ([numpy.savez.html#numpy.savez](#)) Save several arrays into an uncompressed `.npz` archive

```
savez_compressed  
(numpy.savez_compressed.html#numpy.savez_compressed)  
Save several arrays into a compressed .npz archive
```

Notes

Further explanation of the `fmt` parameter

(`%[flag]width[.precision]specifier`):

flags:

- : left justify
- + : Forces to precede result with + or -.
- 0 : Left pad the number with zeros instead of space (see width).

width:

Minimum number of characters to be printed. The value is not truncated if it has more characters.

precision:

- For integer specifiers (eg. `d`, `i`, `o`, `x`), the minimum number of digits.
- For `e`, `E` and `f` specifiers, the number of digits to print after the decimal point.
- For `g` and `G`, the maximum number of significant digits.
- For `s`, the maximum number of characters.

specifiers:

- `c` : character
- `d` or `i` : signed decimal integer
- `e` or `E` : scientific notation with `e` or `E`.
- `f` : decimal floating point
- `g`, `G` : use the shorter of `e`, `E` or `f`
- `o` : signed octal
- `s` : string of characters
- `u` : unsigned decimal integer
- `x`, `X` : unsigned hexadecimal integer

This explanation of `fmt` is not complete, for an exhaustive specification see [R280].

References

- [R280] (1, 2) Format Specification Mini-Language
(<http://docs.python.org/library/string.html#format-specification-mini-language>), Python Documentation.

Examples

>>>

```
>>> x = y = z = np.arange(0.0, 5.0, 1.0)
>>> np.savetxt('test.out', x, delimiter=',')    # X is an array
>>> np.savetxt('test.out', (x, y, z))    # x, y, z equal sized 1D a
rrays
>>> np.savetxt('test.out', x, fmt='%1.4e')    # use exponential
notation
```

后缀是.out

>>> type(x)
<type 'numpy.ndarray'>