

# Introduction to Machine Learning

## Lecture 8 Representation and Clustering - Data Clustering and Typical Methods

**Hongteng Xu**



**中國人民大學**  
RENMIN UNIVERSITY OF CHINA

**高瓴人工智能學院**  
Gaoling School of Artificial Intelligence

# Outline

## Review

- ▶ Manifold learning (MDS, ISOMAP, LLE, ...)
- ▶ Kernel method (Kernel PCA)
- ▶ Large-scale manifold learning (t-SNE)
- ▶ Autoencoders (briefly)

# Outline

## Review

- ▶ Manifold learning (MDS, ISOMAP, LLE, ...)
- ▶ Kernel method (Kernel PCA)
- ▶ Large-scale manifold learning (t-SNE)
- ▶ Autoencoders (briefly)

## Today

- ▶ Data clustering (Motivations and Applications)
- ▶ Typical methods: K-means and Spectral Clustering
- ▶ Evaluation measurements

# Data Clustering: Real-world Examples



# Data Clustering: Real-world Examples



Could you enumerate more real-world clustering problems?

# K-means: One of The Most Commonly-Used Clustering Methods

## **Motivation:**

- ▶ A sample should be closer to the centroid of its cluster than to the centroid of other clusters.

# K-means: One of The Most Commonly-Used Clustering Methods

## **Motivation:**

- ▶ A sample should be closer to the centroid of its cluster than to the centroid of other clusters.

## **Principle:**

- ▶ Find the centroids of the clusters in a heuristic way.

# K-means: One of The Most Commonly-Used Clustering Methods

## Motivation:

- ▶ A sample should be closer to the centroid of its cluster than to the centroid of other clusters.

## Principle:

- ▶ Find the centroids of the clusters in a heuristic way.
- 1 Initialize  $K$  centroids randomly from the observed data, e.g.,  $\{\mathbf{c}_k\}_{k=1}^K$ .



# K-means: One of The Most Commonly-Used Clustering Methods

## Motivation:

- ▶ A sample should be closer to the centroid of its cluster than to the centroid of other clusters.

## Principle:

- ▶ Find the centroids of the clusters in a heuristic way.
  - 1 Initialize  $K$  centroids randomly from the observed data, e.g.,  $\{\mathbf{c}_k\}_{k=1}^K$ .
  - 2 Repeat the following steps till converge
    - a Assign each data to the nearest cluster:  $\forall \mathbf{x}_n$

$$\mathbf{x}_n \in \mathcal{C}_k, \quad \text{if } k = \arg \min_{k \in \{1, \dots, K\}} d(\mathbf{x}_n, \mathbf{c}_k).$$

# K-means: One of The Most Commonly-Used Clustering Methods

## Motivation:

- ▶ A sample should be closer to the centroid of its cluster than to the centroid of other clusters.

## Principle:

- ▶ Find the centroids of the clusters in a heuristic way.
  - 1 Initialize  $K$  centroids randomly from the observed data, e.g.,  $\{\mathbf{c}_k\}_{k=1}^K$ .
  - 2 Repeat the following steps till converge
    - a Assign each data to the nearest cluster:  $\forall \mathbf{x}_n$

$$\mathbf{x}_n \in \mathcal{C}_k, \quad \text{if } k = \arg \min_{k \in \{1, \dots, K\}} d(\mathbf{x}_n, \mathbf{c}_k). \quad (1)$$

- b Update the centriods:

$$\mathbf{c}_k = \frac{1}{|\mathcal{C}_k|} \sum_{\mathbf{x}_n \in \mathcal{C}_k} \mathbf{x}_n. \quad (2)$$

# Extensions of K-means

**Classic K-means:** Consider the samples and the centroids in the Euclidean space

- ▶  $d(\mathbf{x}_n, \mathbf{c}_k)$  is the Euclidean distance.
- ▶ The new centroids are updated via averaging samples.

# Extensions of K-means

**Classic K-means:** Consider the samples and the centroids in the Euclidean space

- ▶  $d(\mathbf{x}_n, \mathbf{c}_k)$  is the Euclidean distance.
- ▶ The new centroids are updated via averaging samples.

**K-means defined in other spaces:**

- ▶  $d(\mathbf{x}_n, \mathbf{c}_k)$  can be other valid metrics.
- ▶ The new centroids correspond to the **barycenters** of clusters computed.

# Extensions of K-means

**Classic K-means:** Consider the samples and the centroids in the Euclidean space

- ▶  $d(\mathbf{x}_n, \mathbf{c}_k)$  is the Euclidean distance.
- ▶ The new centroids are updated via averaging samples.

**K-means defined in other spaces:**

- ▶  $d(\mathbf{x}_n, \mathbf{c}_k)$  can be other valid metrics.
- ▶ The new centroids correspond to the **barycenters** of clusters computed.

(Let's revisit the Euclidean average as the Euclidean barycenter.)

# Spectral Clustering

## **Motivations:**

- ▶ Overcome the drawbacks of (classic) K-means
  - ▶ Not work well for linearly inseparable data
  - ▶ Curse of dimensionality

# Spectral Clustering

## Motivations:

- ▶ Overcome the drawbacks of (classic) K-means
  - ▶ Not work well for linearly inseparable data
  - ▶ Curse of dimensionality

## Principle:

- ▶ Use the **spectrum** (eigenvalues) of the **similarity matrix** of the data to perform dimensionality reduction before clustering.

# Spectral Clustering

## Motivations:

- ▶ Overcome the drawbacks of (classic) K-means
  - ▶ Not work well for linearly inseparable data
  - ▶ Curse of dimensionality

## Principle:

- ▶ Use the **spectrum** (eigenvalues) of the **similarity matrix** of the data to perform dimensionality reduction before clustering.

**The spectrum of a symmetric matrix:** For a symmetric  $\mathbf{A} \in \mathbb{R}^{N \times N}$ :

$$\mathbf{A} = \mathbf{U}\mathbf{\Lambda}\mathbf{U}^T = \sum_{n=1}^N \lambda_n \mathbf{u}_n \mathbf{u}_n^T.$$



# Spectral Clustering

## Motivations:

- ▶ Overcome the drawbacks of (classic) K-means
  - ▶ Not work well for linearly inseparable data
  - ▶ Curse of dimensionality

## Principle:

- ▶ Use the **spectrum** (eigenvalues) of the **similarity matrix** of the data to perform dimensionality reduction before clustering.

**The spectrum of a symmetric matrix:** For a symmetric  $\mathbf{A} \in \mathbb{R}^{N \times N}$ :

$$\mathbf{A} = \mathbf{U} \mathbf{\Lambda} \mathbf{U}^T = \sum_{n=1}^N \lambda_n \mathbf{u}_n \mathbf{u}_n^T. \quad (3)$$

Question:

- ▶ What is the difference between the eigen-decomposition and the SVD of  $\mathbf{A}$ ?

# Spectral Clustering

## Motivations:

- ▶ Overcome the drawbacks of (classic) K-means
  - ▶ Not work well for linearly inseparable data
  - ▶ Curse of dimensionality

## Principle:

- ▶ Use the **spectrum** (eigenvalues) of the **similarity matrix** of the data to perform dimensionality reduction before clustering.

**The spectrum of a symmetric matrix:** For a symmetric  $\mathbf{A} \in \mathbb{R}^{N \times N}$ :

$$\mathbf{A} = \mathbf{U} \mathbf{\Lambda} \mathbf{U}^T = \sum_{n=1}^N \lambda_n \mathbf{u}_n \mathbf{u}_n^T. \quad (3)$$

Question:

- ▶ What is the difference between the eigen-decomposition and the SVD of  $\mathbf{A}$ ?
- ▶ When are they same?

# Spectral Clustering

**Solution:** Given a set of data  $\{\mathbf{x}_n\}_{n=1}^N$

- 1 Define a similarity matrix  $\mathbf{A} = [a(\mathbf{x}_n, \mathbf{x}_m)] \in \mathbb{R}^{N \times N}$ .

# Spectral Clustering

**Solution:** Given a set of data  $\{\mathbf{x}_n\}_{n=1}^N$

- 1 Define a similarity matrix  $\mathbf{A} = [a(\mathbf{x}_n, \mathbf{x}_m)] \in \mathbb{R}^{N \times N}$ .
- 2 Define a **Laplacian** matrix  $\mathbf{L} = \text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}$ .

# Spectral Clustering

**Solution:** Given a set of data  $\{\mathbf{x}_n\}_{n=1}^N$

- 1 Define a similarity matrix  $\mathbf{A} = [a(\mathbf{x}_n, \mathbf{x}_m)] \in \mathbb{R}^{N \times N}$ .
- 2 Define a **Laplacian** matrix  $\mathbf{L} = \text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}$ .
- 3 Apply the eigenvalue decomposition of  $\mathbf{L} = \mathbf{U}\mathbf{\Lambda}\mathbf{U}^T$ ,  $0 = \lambda_1 \leq \dots \leq \lambda_N$ .

# Spectral Clustering

**Solution:** Given a set of data  $\{\mathbf{x}_n\}_{n=1}^N$

- 1 Define a similarity matrix  $\mathbf{A} = [a(\mathbf{x}_n, \mathbf{x}_m)] \in \mathbb{R}^{N \times N}$ .
- 2 Define a **Laplacian** matrix  $\mathbf{L} = \text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}$ .
- 3 Apply the eigenvalue decomposition of  $\mathbf{L} = \mathbf{U}\mathbf{\Lambda}\mathbf{U}^T$ ,  $0 = \lambda_1 \leq \dots \leq \lambda_N$ .
- 4 Consider the eigenvectors corresponding to the top- $L$  smallest eigenvalues, e.g.,  $\mathbf{U}_L \in \mathbb{R}^{N \times L}$ .

# Spectral Clustering

**Solution:** Given a set of data  $\{\mathbf{x}_n\}_{n=1}^N$

- 1 Define a similarity matrix  $\mathbf{A} = [a(\mathbf{x}_n, \mathbf{x}_m)] \in \mathbb{R}^{N \times N}$ .
- 2 Define a **Laplacian** matrix  $\mathbf{L} = \text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}$ .
- 3 Apply the eigenvalue decomposition of  $\mathbf{L} = \mathbf{U}\mathbf{\Lambda}\mathbf{U}^T$ ,  $0 = \lambda_1 \leq \dots \leq \lambda_N$ .
- 4 Consider the eigenvectors corresponding to the top- $L$  smallest eigenvalues, e.g.,  $\mathbf{U}_L \in \mathbb{R}^{N \times L}$ .
- 5 Applying K-means to the rows of  $\mathbf{U}_L$ .

# Spectral Clustering

**Solution:** Given a set of data  $\{\mathbf{x}_n\}_{n=1}^N$

- 1 Define a similarity matrix  $\mathbf{A} = [a(\mathbf{x}_n, \mathbf{x}_m)] \in \mathbb{R}^{N \times N}$ .
- 2 Define a **Laplacian** matrix  $\mathbf{L} = \text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}$ .
- 3 Apply the eigenvalue decomposition of  $\mathbf{L} = \mathbf{U}\mathbf{\Lambda}\mathbf{U}^T$ ,  $0 = \lambda_1 \leq \dots \leq \lambda_N$ .
- 4 Consider the eigenvectors corresponding to the top- $L$  smallest eigenvalues, e.g.,  $\mathbf{U}_L \in \mathbb{R}^{N \times L}$ .
- 5 Applying K-means to the rows of  $\mathbf{U}_L$ .

**Spectral Clustering = Manifold Learning + K-means**, where the Manifold learning method is called **Laplacian Eigenmap**



# Connect Spectral Clustering with Laplacian Eigenmap

- Recall that we have define a similarity matrix  $\mathbf{A}$  for the samples, each element  $a(\mathbf{x}_m, \mathbf{x}_n) = a_{mn} \in [0, 1]$  measures the similarity between  $\mathbf{x}_m$  and  $\mathbf{x}_n$ .

# Connect Spectral Clustering with Laplacian Eigenmap

- ▶ Recall that we have define a similarity matrix  $\mathbf{A}$  for the samples, each element  $a(\mathbf{x}_m, \mathbf{x}_n) = a_{mn} \in [0, 1]$  measures the similarity between  $\mathbf{x}_m$  and  $\mathbf{x}_n$ .
- ▶ If we want to reduce the dimension of the data, i.e., obtaining low-dimensional representations  $\{\mathbf{z}_n\}_{n=1}^N$ , a reasonable criterion/objective is:

$$\min_{\mathbf{Z} \in \mathbb{R}^{N \times L}} \sum_{m,n=1}^N \|\mathbf{z}_m - \mathbf{z}_n\|^2 a(\mathbf{x}_m, \mathbf{x}_n) \quad (4)$$

(For the highly-similar paired samples, their representations should own a short distance)

# Connect Spectral Clustering with Laplacian Eigenmap

- Equivalent formulation:

$$\sum_{m,n=1}^N \|\mathbf{z}_m - \mathbf{z}_n\|^2 a_{mn} = \sum_{m,n=1}^N (\mathbf{z}_m^T \mathbf{z}_m + \mathbf{z}_n^T \mathbf{z}_n - 2\mathbf{z}_m^T \mathbf{z}_n) a_{mn}$$

# Connect Spectral Clustering with Laplacian Eigenmap

- Equivalent formulation:

$$\begin{aligned}\sum_{m,n=1}^N \|\mathbf{z}_m - \mathbf{z}_n\|^2 a_{mn} &= \sum_{m,n=1}^N (\mathbf{z}_m^T \mathbf{z}_m + \mathbf{z}_n^T \mathbf{z}_n - 2\mathbf{z}_m^T \mathbf{z}_n) a_{mn} \\ &= \sum_{m=1}^N \mathbf{z}_m^T \mathbf{z}_m \left( \sum_{n=1}^N a_{mn} \right) + \sum_{n=1}^N \mathbf{z}_n^T \mathbf{z}_n \left( \sum_{m=1}^N a_{mn} \right) - 2 \sum_{m,n=1}^N \mathbf{z}_m^T \mathbf{z}_n a_{mn}\end{aligned}$$

# Connect Spectral Clustering with Laplacian Eigenmap

- Equivalent formulation:

$$\begin{aligned}\sum_{m,n=1}^N \|\mathbf{z}_m - \mathbf{z}_n\|^2 a_{mn} &= \sum_{m,n=1}^N (\mathbf{z}_m^T \mathbf{z}_m + \mathbf{z}_n^T \mathbf{z}_n - 2\mathbf{z}_m^T \mathbf{z}_n) a_{mn} \\&= \sum_{m=1}^N \mathbf{z}_m^T \mathbf{z}_m \left( \sum_{n=1}^N a_{mn} \right) + \sum_{n=1}^N \mathbf{z}_n^T \mathbf{z}_n \left( \sum_{m=1}^N a_{mn} \right) - 2 \sum_{m,n=1}^N \mathbf{z}_m^T \mathbf{z}_n a_{mn} \\&= 2\text{trace}(\mathbf{Z}^T \text{diag}(\mathbf{A}\mathbf{1}_N)\mathbf{Z}) - 2\text{trace}(\mathbf{Z}^T \mathbf{A}\mathbf{Z})\end{aligned}$$

# Connect Spectral Clustering with Laplacian Eigenmap

- Equivalent formulation:

$$\begin{aligned}\sum_{m,n=1}^N \|\mathbf{z}_m - \mathbf{z}_n\|^2 a_{mn} &= \sum_{m,n=1}^N (\mathbf{z}_m^T \mathbf{z}_m + \mathbf{z}_n^T \mathbf{z}_n - 2\mathbf{z}_m^T \mathbf{z}_n) a_{mn} \\&= \sum_{m=1}^N \mathbf{z}_m^T \mathbf{z}_m \left( \sum_{n=1}^N a_{mn} \right) + \sum_{n=1}^N \mathbf{z}_n^T \mathbf{z}_n \left( \sum_{m=1}^N a_{mn} \right) - 2 \sum_{m,n=1}^N \mathbf{z}_m^T \mathbf{z}_n a_{mn} \\&= 2\text{trace}(\mathbf{Z}^T \text{diag}(\mathbf{A}\mathbf{1}_N) \mathbf{Z}) - 2\text{trace}(\mathbf{Z}^T \mathbf{A} \mathbf{Z}) \\&= 2\text{trace}(\mathbf{Z}^T (\text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}) \mathbf{Z}) = 2\text{trace}(\mathbf{Z}^T \mathbf{L} \mathbf{Z})\end{aligned}$$

# Connect Spectral Clustering with Laplacian Eigenmap

- ▶ Equivalent formulation:

$$\begin{aligned} \sum_{m,n=1}^N \|\mathbf{z}_m - \mathbf{z}_n\|^2 a_{mn} &= \sum_{m,n=1}^N (\mathbf{z}_m^T \mathbf{z}_m + \mathbf{z}_n^T \mathbf{z}_n - 2\mathbf{z}_m^T \mathbf{z}_n) a_{mn} \\ &= \sum_{m=1}^N \mathbf{z}_m^T \mathbf{z}_m \left( \sum_{n=1}^N a_{mn} \right) + \sum_{n=1}^N \mathbf{z}_n^T \mathbf{z}_n \left( \sum_{m=1}^N a_{mn} \right) - 2 \sum_{m,n=1}^N \mathbf{z}_m^T \mathbf{z}_n a_{mn} \quad (5) \\ &= 2\text{trace}(\mathbf{Z}^T \text{diag}(\mathbf{A}\mathbf{1}_N) \mathbf{Z}) - 2\text{trace}(\mathbf{Z}^T \mathbf{A} \mathbf{Z}) \\ &= 2\text{trace}(\mathbf{Z}^T (\text{diag}(\mathbf{A}\mathbf{1}_N) - \mathbf{A}) \mathbf{Z}) = 2\text{trace}(\mathbf{Z}^T \mathbf{L} \mathbf{Z}) \end{aligned}$$

- ▶ We can find that
  - ▶  $\mathbf{L}$  is positive semidefinite
  - ▶ 0 is the smallest eigenvalue of  $\mathbf{L}$  and the corresponding eigenvector is  $\frac{1}{N} \mathbf{1}_N$ .
- ▶ As a result, the Laplacian Eigenmap corresponds to

$$\min_{\mathbf{Z}^T \mathbf{Z} = \mathbf{I}_L} \text{trace}(\mathbf{Z}^T \mathbf{L} \mathbf{Z}) \quad \Rightarrow \quad \mathbf{Z}^* = \mathbf{U}_L, \text{ where } \mathbf{L} = \mathbf{U} \mathbf{\Lambda} \mathbf{U}^T. \quad (6)$$

# Connect Spectral Clustering with Kernel Methods

## The construction of similarity matrix

- In general, we can apply the Gram matrix of kernel function as the similarity matrix, e.g., the RBF kernel

$$a(\mathbf{x}_m, \mathbf{x}_n) := K(\mathbf{x}_m, \mathbf{x}_n) = \exp\left(-\frac{\|\mathbf{x}_m - \mathbf{x}_n\|_2^2}{h}\right).$$



# Connect Spectral Clustering with Kernel Methods

## The construction of similarity matrix

- ▶ In general, we can apply the Gram matrix of kernel function as the similarity matrix, e.g., the RBF kernel

$$a(\mathbf{x}_m, \mathbf{x}_n) := K(\mathbf{x}_m, \mathbf{x}_n) = \exp\left(-\frac{\|\mathbf{x}_m - \mathbf{x}_n\|_2^2}{h}\right). \quad (7)$$

- ▶ **Question:** Suppose that  $\mathbf{A}$  is a kernel, and define  $\mathbf{D} = \text{diag}(\mathbf{A}\mathbf{1}_N)$ .

# Connect Spectral Clustering with Kernel Methods

## The construction of similarity matrix

- ▶ In general, we can apply the Gram matrix of kernel function as the similarity matrix, e.g., the RBF kernel

$$\alpha(\mathbf{x}_m, \mathbf{x}_n) := K(\mathbf{x}_m, \mathbf{x}_n) = \exp\left(-\frac{\|\mathbf{x}_m - \mathbf{x}_n\|_2^2}{h}\right). \quad (7)$$

- ▶ **Question:** Suppose that  $\mathbf{A}$  is a kernel, and define  $\mathbf{D} = \text{diag}(\mathbf{A}\mathbf{1}_N)$ . A normalized Laplacian matrix is

$$\hat{\mathbf{L}} = \mathbf{D}^{-1/2} \mathbf{L} \mathbf{D}^{-1/2} = \mathbf{I} - \mathbf{D}^{-1/2} \mathbf{A} \mathbf{D}^{-1/2} = \mathbf{I} - \hat{\mathbf{A}}.$$

# Connect Spectral Clustering with Kernel Methods

## The construction of similarity matrix

- ▶ In general, we can apply the Gram matrix of kernel function as the similarity matrix, e.g., the RBF kernel

$$a(\mathbf{x}_m, \mathbf{x}_n) := K(\mathbf{x}_m, \mathbf{x}_n) = \exp\left(-\frac{\|\mathbf{x}_m - \mathbf{x}_n\|_2^2}{h}\right). \quad (7)$$

- ▶ **Question:** Suppose that  $\mathbf{A}$  is a kernel, and define  $\mathbf{D} = \text{diag}(\mathbf{A}\mathbf{1}_N)$ . A normalized Laplacian matrix is

$$\hat{\mathbf{L}} = \mathbf{D}^{-1/2} \mathbf{L} \mathbf{D}^{-1/2} = \mathbf{I} - \mathbf{D}^{-1/2} \mathbf{A} \mathbf{D}^{-1/2} = \mathbf{I} - \hat{\mathbf{A}}. \quad (8)$$

Is the Laplacian Eigenmap defined on  $\hat{\mathbf{L}}$  equivalent to the Kernel PCA defined on  $\hat{\mathbf{A}}$ ?

How to evaluate your clustering results?

# Evaluation: When Ground Truth Is Available

## Purity

- ▶  $\Omega = \{w_1, \dots, w_K\}$  is the set of  $K$  clusters, each  $w_k$  contains the indices of the samples in the  $k$ -th cluster.

# Evaluation: When Ground Truth Is Available

## Purity

- ▶  $\Omega = \{w_1, \dots, w_K\}$  is the set of  $K$  clusters, each  $w_k$  contains the indices of the samples in the  $k$ -th cluster.
- ▶  $\mathcal{C} = \{c_1, \dots, c_J\}$  is the set of  $J$  classes (ground truth), each  $c_j$  contains the indices of the samples in the  $j$ -th class.

# Evaluation: When Ground Truth Is Available

## Purity

- ▶  $\Omega = \{w_1, \dots, w_K\}$  is the set of  $K$  clusters, each  $w_k$  contains the indices of the samples in the  $k$ -th cluster.
- ▶  $\mathcal{C} = \{c_1, \dots, c_J\}$  is the set of  $J$  classes (ground truth), each  $c_j$  contains the indices of the samples in the  $j$ -th class.
- ▶ Purity: assign each cluster to the class which is most frequent in the cluster, and calculate the averaged accuracy of the assignment.

$$\text{Purity}(\Omega, \mathcal{C}) := \frac{1}{N} \sum_{k=1}^K \max_{j \in \{1, \dots, J\}} |w_k \cap c_j|, \quad (9)$$

where  $N$  is the number of samples.

# Evaluation: When Ground Truth Is Available

## Purity

- ▶  $\Omega = \{w_1, \dots, w_K\}$  is the set of  $K$  clusters, each  $w_k$  contains the indices of the samples in the  $k$ -th cluster.
- ▶  $\mathcal{C} = \{c_1, \dots, c_J\}$  is the set of  $J$  classes (ground truth), each  $c_j$  contains the indices of the samples in the  $j$ -th class.
- ▶ Purity: assign each cluster to the class which is most frequent in the cluster, and calculate the averaged accuracy of the assignment.

$$\text{Purity}(\Omega, \mathcal{C}) := \frac{1}{N} \sum_{k=1}^K \max_{j \in \{1, \dots, J\}} |w_k \cap c_j|, \quad (9)$$

where  $N$  is the number of samples.

- ▶ What is its drawback?



# Evaluation: When Ground Truth Is Available

## Purity

- ▶  $\Omega = \{w_1, \dots, w_K\}$  is the set of  $K$  clusters, each  $w_k$  contains the indices of the samples in the  $k$ -th cluster.
- ▶  $\mathcal{C} = \{c_1, \dots, c_J\}$  is the set of  $J$  classes (ground truth), each  $c_j$  contains the indices of the samples in the  $j$ -th class.
- ▶ Purity: assign each cluster to the class which is most frequent in the cluster, and calculate the averaged accuracy of the assignment.

$$\text{Purity}(\Omega, \mathcal{C}) := \frac{1}{N} \sum_{k=1}^K \max_{j \in \{1, \dots, J\}} |w_k \cap c_j|, \quad (9)$$

where  $N$  is the number of samples.

- ▶ What is its drawback? (Consider the case with  $K \geq J$ )

# Evaluation: When Ground Truth Is Available

## **Normalized Mutual Information (NMI)**

- ▶ Overcome the drawback of purity: achieve a trade-off between the quality of the clustering and the number of clusters.

# Evaluation: When Ground Truth Is Available

## Normalized Mutual Information (NMI)

- ▶ Overcome the drawback of purity: achieve a trade-off between the quality of the clustering and the number of clusters.
- ▶  $P(w_k) = \frac{|w_k|}{N}$  is the probability of a sample belonging to the  $k$ -th cluster.
- ▶  $P(c_j) = \frac{|c_j|}{N}$  is the probability of a sample belonging to the  $j$ -th class.

# Evaluation: When Ground Truth Is Available

## Normalized Mutual Information (NMI)

- ▶ Overcome the drawback of purity: achieve a trade-off between the quality of the clustering and the number of clusters.
- ▶  $P(w_k) = \frac{|w_k|}{N}$  is the probability of a sample belonging to the  $k$ -th cluster.
- ▶  $P(c_j) = \frac{|c_j|}{N}$  is the probability of a sample belonging to the  $j$ -th class.
- ▶  $P(w_k \cap c_j) = \frac{|w_k \cap c_j|}{N}$  is the probability of a sample belonging to both the  $k$ -th cluster and the  $j$ -th class.

# Evaluation: When Ground Truth Is Available

## Normalized Mutual Information (NMI)

- ▶ Overcome the drawback of purity: achieve a trade-off between the quality of the clustering and the number of clusters.
- ▶  $P(w_k) = \frac{|w_k|}{N}$  is the probability of a sample belonging to the  $k$ -th cluster.
- ▶  $P(c_j) = \frac{|c_j|}{N}$  is the probability of a sample belonging to the  $j$ -th class.
- ▶  $P(w_k \cap c_j) = \frac{|w_k \cap c_j|}{N}$  is the probability of a sample belonging to both the  $k$ -th cluster and the  $j$ -th class.
- ▶ NMI:

$$\text{NMI}(\Omega, \mathcal{C}) = \frac{2I(\Omega, \mathcal{C})}{H(\Omega) + H(\mathcal{C})}, \quad (10)$$

- ▶ **Mutual Information:**  $I(\Omega, \mathcal{C}) = \sum_{k,j} P(w_k \cap c_j) \log \frac{P(w_k \cap c_j)}{P(w_k)P(c_j)}$ .
- ▶ **Entropy:**  $H(\Omega) = - \sum_k P(w_k) \log P(w_k)$

## Evaluation: When Ground Truth Is Available

**Rand Index (RI):** The percentage of pairwise decision correctness.

# Evaluation: When Ground Truth Is Available

**Rand Index (RI):** The percentage of pairwise decision correctness.

- ▶ Consider  $N(N - 1)/2$  pairs of the samples.
  - ▶ **True Positive (TP):** The percentage of the paired samples in the **same** class assigned to the **same** cluster
  - ▶ **True Negative (TN):** The percentage of the paired samples in **different** classes assigned to **different** clusters

# Evaluation: When Ground Truth Is Available

**Rand Index (RI):** The percentage of pairwise decision correctness.

- ▶ Consider  $N(N - 1)/2$  pairs of the samples.
  - ▶ **True Positive (TP):** The percentage of the paired samples in the **same** class assigned to the **same** cluster
  - ▶ **True Negative (TN):** The percentage of the paired samples in **different** classes assigned to **different** clusters
  - ▶ **False Positive (FP):** The percentage of the paired samples in **different** classes assigned to the **same** cluster
  - ▶ **False Negative (FN):** The percentage of the paired samples in the **same** class assigned to **different** clusters



# Evaluation: When Ground Truth Is Available

**Rand Index (RI):** The percentage of pairwise decision correctness.

- ▶ Consider  $N(N - 1)/2$  pairs of the samples.
  - ▶ **True Positive (TP):** The percentage of the paired samples in the **same** class assigned to the **same** cluster
  - ▶ **True Negative (TN):** The percentage of the paired samples in **different** classes assigned to **different** clusters
  - ▶ **False Positive (FP):** The percentage of the paired samples in **different** classes assigned to the **same** cluster
  - ▶ **False Negative (FN):** The percentage of the paired samples in the **same** class assigned to **different** clusters
- ▶ Rand Index:

$$RI = \frac{TP + TN}{TP + TN + FP + FN} \quad (11)$$

# Evaluation: When Ground Truth Is Available

## Other measurements:

- Precision, recall, and F1 score:

$$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}, \quad F1 = \frac{2P \cdot R}{P + R}$$

# Evaluation: When Ground Truth Is Available

## Other measurements:

- Precision, recall, and F1 score:

$$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}, \quad F1 = \frac{2P \cdot R}{P + R} \quad (12)$$

- Jaccard index:

$$JI = \frac{TP}{TP + FP + FN}$$

# Evaluation: When Ground Truth Is Available

## Other measurements:

- Precision, recall, and F1 score:

$$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}, \quad F1 = \frac{2P \cdot R}{P + R} \quad (12)$$

- Jaccard index:

$$JI = \frac{TP}{TP + FP + FN} \quad (13)$$

- Dice index:

$$DI = \frac{2TP}{2TP + FP + FN}$$

# Evaluation: When Ground Truth Is Available

## Other measurements:

- Precision, recall, and F1 score:

$$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}, \quad F1 = \frac{2P \cdot R}{P + R} \quad (12)$$

- Jaccard index:

$$JI = \frac{TP}{TP + FP + FN} \quad (13)$$

- Dice index:

$$DI = \frac{2TP}{2TP + FP + FN} \quad (14)$$

- Fowlkes-Mallows Index:

$$FMI = \sqrt{\frac{TP}{TP + FP} \cdot \frac{TP}{TP + FN}} = \sqrt{P \cdot R} \quad (15)$$

## Evaluation: When Ground Truth Is Unavailable

- ▶ The above measurements are called “external” evaluation methods because of using external ground truth information.
- ▶ The evaluation methods not relying on the ground truth are called “internal” measurements.

## Evaluation: When Ground Truth Is Unavailable

- ▶ The above measurements are called “external” evaluation methods because of using external ground truth information.
- ▶ The evaluation methods not relying on the ground truth are called “internal” measurements.

### Davies-Bouldin Index:

$$\text{DBI} = \frac{1}{K} \sum_{i=1}^K \max_{j \neq i} \frac{\sigma_i + \sigma_j}{d(\mathbf{c}_i, \mathbf{c}_j)} \quad (16)$$

- ▶  $\mathbf{c}_i$  is the centroid of the  $i$ -th cluster
- ▶  $\sigma_i$  is the average distance of all the samples in the  $i$ -th cluster to the centroid  $\mathbf{c}_i$ .

## Evaluation: When Ground Truth Is Unavailable

- ▶ The above measurements are called “external” evaluation methods because of using external ground truth information.
- ▶ The evaluation methods not relying on the ground truth are called “internal” measurements.

### Davies-Bouldin Index:

$$\text{DBI} = \frac{1}{K} \sum_{i=1}^K \max_{j \neq i} \frac{\sigma_i + \sigma_j}{d(\mathbf{c}_i, \mathbf{c}_j)} \quad (16)$$

- ▶  $\mathbf{c}_i$  is the centroid of the  $i$ -th cluster
- ▶  $\sigma_i$  is the average distance of all the samples in the  $i$ -th cluster to the centroid  $\mathbf{c}_i$ .

### Principle:

- ▶ Encourage low intra-cluster distances and high inter-cluster distance.
- ▶ In general, the lower DBI is, the better clustering result we have.



# Evaluation: When Ground Truth Is Unavailable

## Dunn Index:

- ▶ Aim at identifying dense and well-separated clusters.
- ▶ The ratio between the minimal inter-cluster distance to maximal intra-cluster distance

$$DI = \frac{\min_{1 \leq i < j \leq K} d(\mathbf{c}_i, \mathbf{c}_j)}{\max_{1 \leq i \leq K, \mathbf{x}_n \in c_i} d(\mathbf{c}_i, \mathbf{x}_n)} \quad (17)$$

# Evaluation: When Ground Truth Is Unavailable

## Silhouette:

- ▶ Given the  $i$ -th cluster  $\mathcal{C}_i$ , for the  $n$ -th sample in it, e.g.,  $n \in \mathcal{C}_i$ . The averaged distance of the sample to other samples in the same cluster is

$$a(n) = \frac{1}{|\mathcal{C}_i| - 1} \sum_{m \in \mathcal{C}_i, m \neq n} d(\mathbf{x}_m, \mathbf{x}_n)$$

# Evaluation: When Ground Truth Is Unavailable

## Silhouette:

- ▶ Given the  $i$ -th cluster  $\mathcal{C}_i$ , for the  $n$ -th sample in it, e.g.,  $n \in \mathcal{C}_i$ . The averaged distance of the sample to other samples in the same cluster is

$$a(n) = \frac{1}{|\mathcal{C}_i| - 1} \sum_{m \in \mathcal{C}_i, m \neq n} d(\mathbf{x}_m, \mathbf{x}_n) \quad (18)$$

- ▶ The smallest averaged distance to the samples in other clusters is

$$b(n) = \min_{j \in \{1, \dots, K\}, \text{ and } j \neq i} \frac{1}{|\mathcal{C}_j|} \sum_{m \in \mathcal{C}_j} d(\mathbf{x}_m, \mathbf{x}_n). \quad (19)$$

# Evaluation: When Ground Truth Is Unavailable

## Silhouette:

- The silhouette value of  $\mathbf{x}_n$  is defined as

$$s(n) = \begin{cases} 1 - a(n)/b(n), & a(n) < b(n) \\ 0, & a(n) = b(n) \\ b(n)/a(n) - 1, & a(n) > b(n) \end{cases}$$

# Evaluation: When Ground Truth Is Unavailable

## Silhouette:

- ▶ The silhouette value of  $\mathbf{x}_n$  is defined as

$$s(n) = \begin{cases} 1 - a(n)/b(n), & a(n) < b(n) \\ 0, & a(n) = b(n) \\ b(n)/a(n) - 1, & a(n) > b(n) \end{cases} \quad (20)$$

- ▶ Setting the number of clusters as  $k$ , the averaged silhouette value of all the data points measures the tightness of the clusters.

$$\bar{s}_k = \frac{1}{N} \sum_{n=1}^N s_k(n) \quad (21)$$

- ▶ Setting the number of clusters from 1 to  $K$ , the silhouette coefficient is defined as

$$\text{SC} = \max_{k \in \{1, \dots, K\}} \bar{s}_k \quad (22)$$

# In Summary

- ▶ The motivations and applications of data clustering
- ▶ K-means and Spectral Clustering
- ▶ Evaluation methods and challenges

## **Next...**

- ▶ Parametric Data Clustering: Gaussian Mixture Model
- ▶ EM algorithm
- ▶ Revisit K-means from a Statistical viewpoint

# Homework 3, DDL: April 27, 2022

## Python Programming

- 1 Lab # 5 (4 Pts, Done)
- 2 Lab # 6 (4 Pts)

## Questions for Tech Report (6 Pts, $\leq 3$ Pages)

- 1 **Alternating Optimization of RPCA.** When doing robust PCA (RPCA), if we assume  $\mathbf{X} = \mathbf{UV}^T$ , where  $\mathbf{U} \in \mathbb{R}^{N \times L}$  and  $\mathbf{V} \in \mathbb{R}^{D \times L}$ , the RPCA problem becomes

$$\min_{\mathbf{U}, \mathbf{V}} \|\mathbf{X}_{noisy} - \mathbf{UV}^T\|_1, \quad \text{where } \|\mathbf{A}\|_1 = \sum_{i,j} |a_{ij}|. \quad (23)$$

Can we solve this problem via alternating optimization? e.g.,

$$\mathbf{U}_t = \arg \min_{\mathbf{U}} \|\mathbf{X}_{noisy} - \mathbf{UV}_t^T\|_1, \quad \text{and} \quad \mathbf{V}_t = \arg \min_{\mathbf{V}} \|\mathbf{X}_{noisy} - \mathbf{U}_t \mathbf{V}^T\|_1. \quad (24)$$

If yes, derive the algorithm, otherwise, show your reason. (4 Pts)

- 2 Proof that ISOMAP, LLE, Kernel PCA, and Eigenmap lead to the same problem:  $\min_{\mathbf{Z} \in \mathbb{R}^{N \times L}} \text{tr}(\mathbf{Z}^T \Phi \mathbf{Z})$ , s.t.  $\mathbf{Z}^T \mathbf{Z} = \mathbf{I}_d$ , and derive the  $\Phi$ 's for the methods. (2 Pts)