


# Fundamentals Storytelling Framework



# Table of contents

<a href="#">Table of contents</a>	2
<a href="#">Fundamentals Storytelling Framework</a>	4
<a href="#">Download</a>	4
<a href="#">Getting started</a>	4
<a href="#">Creating your own scene</a>	6
<a href="#">Demonstration scene overview</a>	9
<a href="#">PlayerActivable Overview</a>	10
<a href="#">User guide</a>	11
<a href="#">Adding ProximityTriggers</a>	11
<a href="#">Adding SpawnPoints</a>	13
<a href="#">Starting a dialogue at start of the game</a>	15
<a href="#">Starting a dialogue from trigger</a>	17
<a href="#">Playing a sound</a>	18
<a href="#">Working with variables in script</a>	20
<a href="#">Setting variable in trigger</a>	21
<a href="#">Setting up a fetch quest</a>	23
<a href="#">Adding item to inventory from trigger</a>	33
<a href="#">Adding item to inventory from script</a>	35
<a href="#">Removing item from inventory from script</a>	37
<a href="#">Checking and removing item from inventory from trigger</a>	38
<a href="#">Checking for inventory item from script</a>	40
<a href="#">Creating and triggering animation from trigger</a>	40
<a href="#">Toggle animations</a>	44
<a href="#">Freezing/unfreezing the player</a>	51
<a href="#">Adding a speech bubble</a>	51
<a href="#">Making NPC walk somewhere</a>	52
<a href="#">Highlighting a path to somewhere</a>	53
<a href="#">Showing a UI screen</a>	54
<a href="#">Updating a variable in the HUD</a>	64
<a href="#">Starting a UnityEvent (Particle Effect)</a>	67
<a href="#">Showing a code lock and responding to it in a dialogue</a>	73
<a href="#">Function guide</a>	78
<a href="#">activate</a>	78
<a href="#">animate</a>	79
<a href="#">disable_controls</a>	80
<a href="#">enable_controls</a>	81
<a href="#">get_distance</a>	82
<a href="#">get_scene</a>	83
<a href="#">give_item</a>	83

<a href="#">has_item</a>	85
<a href="#">hide_path</a>	85
<a href="#">load_scene</a>	87
<a href="#">log</a>	88
<a href="#">play_animation</a>	89
<a href="#">playerpref_load_int</a>	
<a href="#">playerpref_load_string</a>	
<a href="#">playerpref_load_bool</a>	90
<a href="#">playerpref_save_string</a>	
<a href="#">playerpref_save_int</a>	
<a href="#">playerpref_save_bool</a>	91
<a href="#">playerpref_exists</a>	92
<a href="#">respawn</a>	93
<a href="#">say</a>	94
<a href="#">set_enabled</a>	95
<a href="#">set_spawn</a>	96
<a href="#">show_path</a>	97
<a href="#">take_item</a>	98
<a href="#">teleport</a>	99
<a href="#">toggle_animation</a>	100
<a href="#">walk_to</a>	101
<a href="#">wait_for_location</a>	102


# Fundamentals Storytelling Framework

This manual describes the framework in more detail. It is a live document and may be subject to updates throughout the year.


## Download

## Getting started

Open the project. Make sure you have a matching Unity version installed. *Do not downgrade the project, as that may lead to unexpected behavior.* If you open the project, you will see a scene:




At the top-right of the game window, you will see this icon. Use this to toggle gizmo visibility.




By default, the object names are shown. You can toggle this by disabling the ShowObjectNamesEditor in the Gizmo list. (The triangle next to the above icon)

If you press play, you will see an interactive tutorial showing the framework's features. To see the script for the tutorial, open the folder Dialogue in the Project window.



In this folder, there is a script called MyStoryScript.



Open the script by double-clicking it. You *may need to install Visual Studio Code to open it*.

The script is divided in scenes, such as these:

```
//-----  
//----- Start  
//-----  
0 references | Show in Graph View  
title: Start  
---  
<<declare $mission = "none">>  
<<set_enabled NPC false>>  
Hello, welcome to the framework.  
Would you like a demonstration of the features?  
->Yes  
|   <<jump DemonstrateFeatures>>  
->No  
====
```

*Note that I installed YarnSpinner scripting support in VS Code. That gives me syntax highlighting (the text color changes based on the semantics)*

Scenes contain a title and a body. The body is the part between --- and ===.


In the body, you will see all the dialogue that belongs to the scene, as well as commands for YarnSpinner/the framework. You can recognize commands because they are surrounded by <<< and >>>.

The lines that start with a -> are options the user can choose from. The lines directly under those show how the script will respond to this choice. So in the above example, if the player chooses “Yes”, the script will continue at the scene with the title “DemonstrateFeatures”.

## Creating your own scene


If you want to add your own scene, open the folder Assets/Scenes.

In there you will find a scene that is called Playground. This is a scene that contains a player, a camera and a terrain. Also, it has some light settings and the required UI elements set up.




To set up your own story, you can make a duplicate of this scene and open it.


Select the scene, then go to Edit->Duplicate (or press CMD/CTRL+D)




Then, rename the newly created scene and double-click it to open it.



In the Hierarchy window, select the Terrain gameobject. It can be found under SceneSetup:




Go to the Inspector window and scroll down. There you will see a button marked "Bake". Press it to bake the navigation mesh.



This is needed for the walk\_to and the show\_path functions.

If you want to add your own script, you can add it by right-clicking the Dialogue folder (1). Then go to Create (2), then Yarn Spinner->Yarn Script (3).



Any script you will add will be detected by the YarnSpinner project.

## Demonstration scene overview

SceneSetup	
Terrain	The Unity terrain
SpawnPoint	A player spawn
SpawnPoint	A player spawn
Location1	Transparent cube, used for walk_to example
Location2	Transparent cube, used for walk_to example
PlayerItems	
PlayerFollowCamera	A cinemachine virtual camera (that follows the player)
Player	The player GameObject
Interactables	
DialogueTrigger	Starts a certain dialogue node in YarnSpinner
Collectable	Adds item to inventory, plays audio and goes away
NPC	Can be talked to
SimpleAnimationTrigger	Checks inventory for item, activates one animation
UseInventoryItem	Animates only if used picked up the collectable
UnityEventTrigger	Can spawn any unity event (in this case, activates particles)
SimpleAudioTrigger	Plays an audio event
MenuTrigger	Shows a UI node (the letter)
MenuTrigger (CodeLock)	(CodeLock) shows a UI node (the code lock)
AnimationToggle	Can play multiple animation states
UI	
Inventory	Shows your inventory (press TAB)
Dialogue System (YarnSpinner)	System YarnSpinner root note
ProximityTriggerRoot	Used at runtime
Letter	The letter that is shown
HUD	Displays amount of items (a variable from YarnSpinner)
SpeechBubbleManager	Used at runtime to generate speech bubbles
CodeLock	The codelock puzzle (code = 1234), it contains an event that gets fired when right/wrong
PathVisualiser	Displays arrows on the terrain, used for navigating the player
Core	
Main Camera	
Directional Light	
PostFXVolume	

# PlayerActivable Overview

PlayerActivatables are scripts that are in the framework that allow player interaction with items. They can be activated by a ProximityTrigger (*The player must hold the “E” button for that*) or on collision. (When the players touches the item)  
These scripts that are located in the folder “Assets/Interaction Scripts”. You can use them to activate various things, such as sounds, animations, dialogues and particle effects.

Here is an overview of the PlayerActivatables in the folder:

## AddInventoryItem

This component will add an item to the inventory.

## AnimationToggle

This component will toggle between two animations.

## Collectable

This component will destroy the GameObject when the user activates it.

## DialogueTrigger

This component will start a certain scene in the YarnSpinner project.

## FMODEEventTrigger

This component will trigger an FMOD event.

## ShowMenu

This component will activate a UI object when activated.

## SimpleAnimationTrigger

This component will play a single animation when it is activated.

## SimpleAudioTrigger

This component will play a sound when it is activated.

## UnityEventTrigger

This component will fire a Unity Event.

## UseInventoryItem

This component will check if a certain item is in the inventory before it allows the other scripts to be activated.

## UseInventoryItemOnTarget

This component will do the same as UseInventoryItem, but it will activate scripts on another GameObject instead of itself.

## VariableSetter


This component will set a variable in the YarnSpinner project.

# User guide


## Adding ProximityTriggers

A Proximity Trigger is the E that shows up when you are close to a PlayerInteractable. You can use it to activate all the scripts on a GameObject.

1. Locate the prefab in the folder Assets/Interaction Prefabs




2. Ensure that in the hierarchy (i.e. under the UI node) there is a ProximityTriggerRoot.




If it is not there, add the ProximityTriggerRoot to the scene.


3. If you have no GameObject yet, go to the top bar menu in Unity and select GameObject->3D object->Cube first.



4. Drag the ProximityTrigger prefab to the GameObject you want to add it to.




5. Optionally, set the Long Press Duration property in the inspector:




If you add any PlayerInteractable scripts to the cube, it will be activated.

## Adding SpawnPoints

A SpawnPoint is a location where the player spawns. When the player touches a spawn point, it will be set as the next spawn position when the player dies.




SpawnPoints can be added from the “Assets/Interaction Prefabs” folder.



You can place them anywhere in your scene hierarchy.


To set the spawnpoint for the player, select the player in the hierarchy:



In the inspector window, locate the RespawnBehaviour component (scroll down for it).



You can drag your newly created SpawnPoint on the property that is called Spawn Point. That will ensure the player will spawn at this SpawnPoint at the start of the game, regardless of its initial position.




## Starting a dialogue at start of the game


When the framework starts, it is set up in such a way that YarnSpinner will automatically play the scene called “Start” in the YarnSpinner project, shown here:

```
//-----  
//----- Start  
//-----  
0 references | Show in Graph View  
title: Start  
---  
<<declare $mission = "none">>  
<<set_enabled NPC false>>  
Hello, welcome to the framework.  
Would you like a demonstration of the features?  
->Yes  
|   <<jump DemonstrateFeatures>>  
->No  
====
```

To change this behavior, locate the YarnSpinner GameObject in the hierarchy:




After selecting it, find the “Dialogue Runner” component in the inspector. Under *Behaviour* you will see a checkbox called “Start Automatically” and a text field called “Start Node” that currently says “Start”. Modify these properties to fit your needs.




## Starting a dialogue from trigger


You can also use a PlayerInteractive to activate a dialogue. For that, you need to add the script DialogueTrigger to the GameObject.




Next, locate the Dialogue Trigger component in the inspector and drag the GameObject Dialogue System (YarnSpinner) from the UI node onto the Dialogue Runner property of the component.



Finally, fill in the name of the scene you want to run from the interactable:




You can activate the PlayerInteractable using an ProximityTrigger (see the section “Adding ProximityTriggers” above) or by enabling the “Should Activate on Collision” property of the component.




## Playing a sound


There is a PlayerInteractable that is able to play a sound when it is activated. You need to import a sound file into Unity. You can drag the sound file onto your project window.




Locate the SimpleAudioTrigger script in the “Assets/Interaction Scripts” folder and drag it onto the GameObject that you want to apply it to.



Next, find the SimpleAudioTrigger component in the inspector and drag the sound from the project window onto the “Audio Clip” property of the component.



You can activate the SimpleAudioTrigger using a ProximityTrigger (see the section “Adding ProximityTriggers” above) or by enabling the “Should Activate on Collision” property of the component.



## Working with variables in script

YarnSpinner allows you to set a variable from a script. This can be done to keep track of things that the player has done. For instance, you can use variables to keep track of items that were collected (hasKey) or places that the user has visited (hasVisited). You can also use it to count certain things. For instance, you can count how often the player visited the NPC.

Here is an example script that uses a variable \$hasKey.

It can have two values: **true** or **false**. When it is “true”, the player has collected the key.


```
//  
//  
//-----  
0 references | Show in Graph View  
title: Start  
---  
<<declare $hasKey = false>>  
Hello, welcome to the framework.  
Find the key!  
===  
  
//  
//-----  
0 references | Show in Graph View  
title: GetKey  
---  
You found a key!  
<<set $hasKey to true>>  
===  
  
//  
//-----  
0 references | Show in Graph View  
title: OpenDoor  
---  
<<if $hasKey == true>>  
| Opening the door!  
<<else>>  
| You need a key for this>>  
<<endif>>  
==
```

More information about YarnSpinner variables can be found on their website:  
<https://docs.yarnspinner.dev/getting-started/writing-in-yarn/logic-and-variables>


## Setting variable in trigger

There is a PlayerInteractive that can set variables. When the component is activated it can alter a variable in the YarnSpinner script. You can set a variable to a certain value but also add or subtract an amount.


Locate the VariableSetter script in “Assets/Interaction Scripts” and drag it onto the GameObject you want to apply it to.



Drag the Dialogue Runner GameObject from the UI node in the hierarchy onto the VariableSetter component in the inspector:




In the YarnSpinner script, create a variable. This variable should be of the Number type. Currently that is the only type of variable supported by the VariableSetter component.



```
//-----
//-----                                         Start
//-----
0 references | Show in Graph View
title: Start
-----
<<declare $itemsFound = 0>>
=====
```

For testing purposes we can add a node that will display the variable in a dialogue.




```
//-----
//-----                                         ShowItemsFound
//-----
0 references | Show in Graph View
title: ShowItemsFound
-----
You found a {$itemsFound} items!
=====
```

Now when you run the dialogue scene, it will display the amount of items.

## Setting up a fetch quest

If you want to create a quest for the player, you can use a variable in the YarnSpinner script to set this up. This variable can keep track of that status of the quest. For instance, these states can be “unassigned”, “in progress” and “done”.

This tutorial will tell you how to set this up. It will show how to create the variable, how to add an item to the inventory from a pickup and check for it in the YarnSpinner script.




When the user interacts with an NPC, it will prompt the user to complete the first quest:


If the user is already doing the quest, talking to the NPC will give a friendly reminder.

When the user completes the quest, the NPC should reward the player.


Add two cubes to the game, name one of them “NPC” and the other one “Item”.




Add a DialogueTrigger to the NPC item.




From the UI node in the scene, drag the Dialogue System onto the DialogueTrigger.



In the properties of the DialogueTrigger component, add “QuestGiver” to the Dialog Node Name.




Check the box that says “Can Repeat”




This will make the YarnSpinner script play the scene called QuestGiver.


Drag a ProximityTrigger from the to folder “Assets/Interaction Prefabs” onto the NPC.




Next, drag the Collectable script onto the cube that is called Item.




Check the “Should Activate On Collision” checkbox on the Collectable component.




Add the AddInventoryItem script to the Item as well.




Drag the Player object from the PlayerItems node onto the "Inventory" property of the AddInventory component. This will ensure the items will end up in the Player's inventory.




Check the “Should Activate On Collision” checkbox on the component.




Open the folder Assets/InventoryItems and right-click the folder to create an InventoryItem. InventoryItems are used to define the name of the items and they define what icon should be shown in the inventory in the HUD.




Name the InventoryItem “item” and select it. The name will be used in the YarnSpinner script to reference the item.



In the inspector, assign a sprite to the Icon property. This is the sprite that will be shown in the inventory view in the HUD.



Drag the newly created item onto the “item” property of the AddInventoryItem component.




Now, when the player collects the item we created, it will appear in the inventory.

Now let's set up the script. Locate the script in the “Assets/Dialogue” folder and open it. In the first scene of the project, we'll add a variable called \$quest.


```
//-----  
//----- Start  
//-----  
0 references | Show in Graph View  
title: Start  
---  
=><<declare $quest = "unassigned">>  
====
```

The first value for the variable is “unassigned”. This will indicate the quest has not started yet. We will change it to “in progress” and “done” later on.


Add a TextMeshPro text object to the scene. This will be used to display the \$quest variable.




For this, go to the Unity's menu bar, then press GameObject->UI->Text - TextMeshPro.  
In the inspector, change the origin of the object to 0, 1. Change the Anchor Preset to the top-left setup. Finally, change the position of the object to (0, 0). These settings are highlighted in the screenshot.




Drag the HUDUpdateValue script from the folder "Assets/Interaction Prefabs" onto the newly created text object.



Drag the Dialogue System node from the UI node in the hierarchy onto the HUDUpdateValue component's field “variable storage behaviour”.



In the inspector, change the text field of the TextMeshPro Text component into: Quest: {\$quest} The part that reads {\$quest} will be replaced with the content of the variable from the YarnSpinner script. This will show the quest onto the screen for the player.



Open up the script again and add a new scene called QuestGiver. When the user interacts with the NPC, the DialogTrigger will trigger this scene.

In the QuestGiver scene, we will check if the user has the mission. If not, we will give the quest. If they have the quest, but not the Item in their inventory, we will give them a reminder.


```
//-----
//                                     QuestGiver
//-----
0 references | Show in Graph View
title: QuestGiver

<--if $quest == "unassigned">>
    NPC: Hello, traveler. Could you bring me the item?
    <<set $quest to "in progress">>
<<elseif $quest == "in progress">>
    <<if not has_item("Player", "item")>>
        NPC: Ah, did you fetch the item yet?
    <<else>>
        NPC: Thank you for doing the quest!
        <<set $quest to "done">>
    <<endif>>
<<elseif $quest == "done">>
    NPC: This quest is over.
<<endif>>
====
```


## Adding item to inventory from trigger

Add a cube to the scene and name it "Item".


For that, go to GameObject->3D Object->Cube




Rename the cube to "Item".




Drag the Player object from the PlayerItems node onto the “Inventory” property of the AddInventory component. This will ensure the items will end up in the Player’s inventory.




Check the “Should Activate On Collision” checkbox on the component.




Open the folder Assets/InventoryItems and right-click the folder to create an InventoryItem. InventoryItems are used to define the name of the items and they define what icon should be shown in the inventory in the HUD.




Name the InventoryItem “item” and select it. The name will be used in the YarnSpinner script to reference the item.



In the inspector, assign a sprite to the Icon property. This is the sprite that will be shown in the inventory view in the HUD.



Drag the newly created item onto the “item” property of the AddInventoryItem component.




Now, when the player collects the item we created, it will appear in the inventory.


## Adding item to inventory from script

Adding an inventory item from a script can be done with the give\_item command. The system will show the item in the inventory using an icon. You need to define the icon using a ScriptableObject in the InventoryItems folder.


Open the folder Assets/InventoryItems and right-click the folder to create an InventoryItem. InventoryItems are used to define the name of the items and they define what icon should be shown in the inventory in the HUD.



Name the InventoryItem “item” and select it. The name will be used in the YarnSpinner script to reference the item.



In the inspector, assign a sprite to the Icon property. This is the sprite that will be shown in the inventory view in the HUD.



In the scene where you want to give the item to the player, add the following script:


```
//-----  
//  
//-----  
0 references | Show in Graph View  
title: Start  
---  
<<give_item "Player" "item">>  
==
```

## Removing item from inventory from script

In the scene where you want to take an item from the inventory, add the following script:


```
//-----  
//  
//-----  
0 references | Show in Graph View  
title: QuestGiver  
---  
<<take_item "Player" "item">>  
==
```

Make sure the name of the item matches the one in the “Assets/InventoryItems” folder:




## Checking and removing item from inventory from trigger


Locate the script `UseInventoryItem` in the folder “Assets/Interaction Scripts” and drag it into the item that you want to use for checking the item in the inventory.




Drag the player GameObject from the PlayerItems node in the inventory onto the “Inventory” property of the `UseInventoryItem` component.



Locate the item that you want to check for in the “Assets/InventoryItems” folder and drag it onto the “Item” property of the component.



The `UseInventoryItem` component will disable all other PlayerInteractables until the user has the specified object in their inventory. Optionally, you can uncheck the box that says “Should remove from inventory”. This will keep the item in the inventory after usage.




The “Invert Item Check” box will make the component check the inventory for *not* having the item.

## Checking for inventory item from script

To check for an item in the script, you can use the “has\_item” function.


```
//  
//  
//-----  
QuestGiver  
0 references | Show in Graph View  
title: QuestGiver  
---  
  
=>  
<<if has_item("Player", "item")>>  
| NPC: You have the item!  
<<else>>  
| NPC: You don't have the item  
<<endif>>  
---
```

Make sure the name of the item matches the one in the "Assets/InventoryItems" folder:




## Creating and triggering animation from trigger


Select the gameobject that you want to animate in the hierarchy and open the Animation window. (CTRL/CMD+6)




In the Animation window, press the button that says “Create” and save the animation. Remember where you save the animation, because you need to locate it later on.



Press “Add Property”, select “Transform” and press the plus-sign that is on the right, next to position.




This will allow you to animate the object’s position.




Press the record button and move the play head to the second keyframe.


In the inspector, change the y-position of the GameObject.




Toggle the record button to stop recording and scrub the playhead to test the animation.




The GameObject should move between the old and new position as you scrub the playhead. Find the animation that you saved in the Assets folder and select it.



In the Inspector window, uncheck “Loop Time”. This will prevent the animation from looping.



Locate the SimpleAnimationTrigger in the folder “Assets/Interaction Script” and drag it onto the GameObject.




Drag the ProximityTrigger from the “Assets/Interaction Prefabs” onto the GameObject.  
Now when the player activates the item, the animation should play.

## Toggle animations

Toggling animations allows for multiple animations to be sequenced and repeated. For instance opening and closing a drawer: each time the player interacts with the drawer, it toggles between the open and close animation.


Create a new GameObject in the scene.




Select the item in the hierarchy and open the Animation window (CTRL/CMD+6)

Press the Create button to create an animation for the item and save it as OpenAnimation.


This animation should depict opening the door.



Press Add Property and add the rotation property.




Press the record button and move the playhead to the second keyframe.



In the inspector, rotate the GameObject 90°. For instance, this could be a door that opens.




Press the record button again to stop recording and scrub the playhead back to the start to verify the animation. The object should turn back into its original position.




In the animation window, click the name of the current animation and in the dropdown, press "Create New Clip". Save this animation as CloseAnimation.

This animation should depict closing the door.




Repeat the same steps as before: press the record button, move the playhead to the second keyframe and change the rotation in the inspector.




Press the record button again to end recording the animation.


Locate both animation clips in the Assets folder and select them. In the inspector disable “Loop time” for both of them.




Now go to Window->Animator.




In the Animator window, right-click the open area to create a new, empty animation state.




Right-click the newly created state and choose “Set as Layer Default State”




You can rearrange the layout a bit for clarity:




In the “Assets/Interaction Scripts” folder, locate the AnimationToggle script and drag it onto the GameObject in the hierarchy:




In the inspector, locate the AnimationToggle component and open the Animation States list. Use the plus sign on the right to add slots.



Fill in the names of the two animations you created before



Finally, locate a ProximityTrigger in the “Assets/Interaction Prefabs” folder and drag it onto the GameObject.



The object should now toggle between the two animation states.

## Freezing/unfreezing the player

It could be useful to temporarily disable the player movement. For instance if you want to show a cut scene. For that, two commands can be utilized in the script. Here is a short example how to use it:

```
//-----
//                                         Start
//-----
0 references | Show in Graph View
title: Start
--  

You will be stunned for 5 seconds.  

<<disable_controls Player>>  

<<wait 5>>  

<<enable_controls Player>>  


You can now move again.  

==
```

## Adding a speech bubble

To add a speech bubble, you can use the “say” command. For completion: speech bubbles are processed by the SpeechBubbleManager GameObject that must be placed in the scene. This is the default in the current project setup.

The speech bubble will be placed directly above the GameObject. If that is an NPC, the speech bubble would look as if it is placed at the center of its head. A typical setup would be to add a GameObject as a child to the NPC and use that for placing the speech bubbles.



In code, this item can be referred to by name:

```
//-----
//                                         Start
//-----
0 references | Show in Graph View
title: Start
<<say "Head" "Hello I am a speech bubble!">>
==
```


## Making NPC walk somewhere

In the current setup, there is an NPC. The NPC is a humanoid GameObject that has a “WalkToBehaviour” added to it. You can control this behavior from a script.

In order for this behavior to work properly you need to bake a NavMesh. That is data the Unity uses to navigate through the game world without running into obstacles.

### Baking the NavMeshSurface

In the hierarchy, locate the node “Terrain” in “SceneSetup”. In the inspector, locate the NavMeshSurface component and press the Bake button.



To make the NPC walk to a location, you can use this code:

```
//-----
//                                     Start
//-----
0 references | Show in Graph View
title: Start
-->
<<walk_to "NPC" "Location1">>
==
```

This will make the NPC walk towards the gameobject called “Location1”.

By default, the script will wait for it to finish. You can add an extra property to immediately continue your YarnSpinner script.

```
title: Start
---
<<walk_to "NPC" "Location1" 0 false>>
This message will show immediately
====
```

The number 0 in this script determines at what distance the NPC will stop walking when approaching the target.

## Highlighting a path to somewhere

It can be useful to show a path through the game world to guide the player. The show\_path helper function is made for that. You can show a path between two objects.

This command uses the NavMesh data, so you must first bake the NavMeshSurface as shown in the previous topic.

To show a path from one GameObject to another, you can use the following code:

```
//-----
//                                         Start
//-----
0 references | Show in Graph View
title: Start
---
<<show_path "Player" "Location1">>
====
```

By default, the path will disappear when the first object approaches the second one. However, if you want to explicitly hide the path, you can use the hide\_path command. If you want to use that, you should also set the “shouldWait” property to “false”.


```
//-----
//                                         Start
//-----
0 references | Show in Graph View
title: Start
---

Reach the location in 4 seconds!
<<show_path "Player" "Location1" false>>
<<wait 4>>
<<hide_path>>
<<if get_distance("Player", "Location1") < 1>>
    You are close!
<<else>>
    You are not close!
<<endif>>
```


## Showing a UI screen

It can be useful to show a UI screen when the user activates a trigger. This could for instance be a piece of paper that they pick up. The UI screen could show the item in close up.


First, we create a GameObject to hold this screen. Right-click the hierarchy and add a new GameObject. You can add it to the UI node if you prefer that.




Rename the newly created item to “Letter”.




In the inspector, right-click the Rect Transform component and reset its values.




Next, we add a Canvas component to it. Press the “Add Component” button in the inspector and add a Canvas component.






Change the Canvas Render Mode to “Screen Space - Overlay”. Optionally, check the “Vertex Color Always in Gamma Color Space” option to prevent the warning.

Then next, add a Canvas Scaler component the same way. Click the “Add Component” button again and add a Canvas Scaler.




Change the UI Scale Mode setting to “Scale With Screen Size”


Finally, add the “Graphic Raycaster” Component.



Now we add a UI Image. For this, go to GameObject->UI->Image.




Use the tab above the scene view to switch to Game view.




This will allow you to preview the image on screen.


You can adjust the scaling and anchoring in the inspector.




In the inspector, locate the Image component and press the small round icon on the right next to Source Image to select a new image.




Now, let's add a button to the screen. Press GameObject->UI->Button - TextMeshPro. We will set this button up so that it will close the UI once it is on screen.




Select the newly created button in the hierarchy. In the Inspector window, locate the Button component. A bit down there is the OnClick property. Press the plus sign on the right to add an Unity Event listener.




Next, drag the “Letter” GameObject from the hierarchy window onto the event listeners Object property.




Next, in the “Function” dropdown, select GameObject->SetActive (bool).




Leave the checkmark unchecked.



Select “Letter” in the hierarchy window.




Go to Inspector and uncheck the box that is on the left of the objects name at the top of the window.




Now we made a UI node that has a close button and that is hidden at the start of the game.

Let's now set up a GameObject that will activate the UI node.


First, create a cube. Go the GameObject->3D Object->Cube



In the “Assets/Interaction Scripts” folder, locate the “ShowMenu” script and drag it onto the cube in the hierarchy.




In the Inspector window, locate the ShowMenu component. Drag the Letter GameObject from the hierarchy onto the “Menu to activate” property of the component.



Finally, open the “Assets/Interaction Prefabs” folder and drag a ProximityTrigger onto the cube.

As a note: ensure that EventSystem is in the hierarchy and it is enabled. It is needed for buttons to interact.



If it is not there, you can add one by going to GameObject->UI->EventSystem.

## Updating a variable in the HUD

You can display a YarnSpinner variable in the HUD. This can be useful to show score or money. Variables can hold a number value or a string value. A string is a text between quotes.

In this example, we will make a variable in YarnSpinner, give it a value and display this value in the HUD. This is an edited excerpt from the “*Making a fetch quest*” tutorial above.


First, locate the script in the “Assets/Dialogue” folder and open it.

In the first scene of the project, we’ll add a variable called \$score.

```
title: Start  
---  
<<declare $score = 0>>  
---
```


The value for the variable is 0. We can change it later on.

Add a TextMeshPro text object to the scene. This will be used to display the \$quest variable.




For this, go to the Unity’s menu bar, then press GameObject->UI->Text - TextMeshPro.


In the inspector, change the origin of the object to 0, 1. Change the Anchor Preset to the top-left setup. Finally, change the position of the object to (0, 0). These settings are highlighted in the screenshot.




Drag the HUDUpdateValue script from the folder “Assets/Interaction Prefabs” onto the newly created text object.



Drag the Dialogue System node from the UI node in the hierarchy onto the HUDUpdateValue component’s field “variable storage behaviour”.



In the inspector, change the text field of the TextMeshPro Text component into: Score: {\$score}



The part that reads {\$score} will be replaced with the content of the variable from the YarnSpinner script. This will show the score onto the screen for the player.


For more information about YarnSpinner variables, see this article:

<https://docs.yarnspinner.dev/beginners-guide/syntax-basics#logic-and-variables>


## Starting a UnityEvent (Particle Effect)

The UnityEventTrigger component is a PlayerActivable that can trigger a Unity event. This gives low-level access to Unity's functionality. You can use it to trigger a wide range of things. You can enable/disable items, change their color, start/stop animations, sounds, music. Most of the functionality of the other PlayerActivatables can be achieved with only this script, and more. In this demonstration, we will make a particle effect and activate it.


Go to GameObject->3D Object->Cube to add a cube to your scene. Make sure to select it.




In the Inspector, press “Add Component”




In the box that appears, search for “Particle System”.




You can change the properties of the particle system. By default, the material is not compatible with the current pipeline, so it will look purple.




In the Inspector for the Particle System, find the property “Play on Awake” and disable it.




Locate the UnityEventTrigger script in the folder “Assets/Interaction Scripts” and drag it onto the cube.




In the Inspector for the UnityEventTrigger, locate the “Target Event()” property and add a slot using the “+” button on the bottom right of it.




Drag the cube onto the target property (that currently says “None”)



In the drop-down box on the right (the one that says “No Function”), select the Particle System script and select the “Play” method.




Locate the ProximityTrigger in the “Assets/Interaction Prefabs” folder and drag it onto the Cube.




Now when you activate the cube, the particle effect should show.

To change the material, you could look at the “Renderer” property of the ParticleSystem.




Click on Renderer in the inspector, edit the Material property and search for a material that contains the name “Particle”.




For more information about editing particle effects, please refer to the Unity documentation:  
<https://learn.unity.com/tutorial/introduction-to-particle-systems#>

## Showing a code lock and responding to it in a dialogue


Locate the CodeLock prefab under “Assets/Interaction Prefabs”



Drag it into the hierarchy.




In the Inspector, activate the GameObject by checking the checkbox next to the object's name.




You can do this from a PlayerActivatable by using the ShowMenu script (see “Showing a UI screen”).


Scroll down in the Inspector to find the “OnRightAnswer” and “OnWrongAnswer” properties.




Use the + sign to add an event to these. For this example, we will only add one for the OnRightAnswer property.




Drag the “DialogueRunner (YarnSpinner)” gameobject from the hierarchy onto the target field of the event. (The one the currently reads “None (Object)”).




In the dropdown box on the right (The one that currently reads “No Function”), locate the YarnSpinner script and find the StartDialogue function.



Select it and fill in the name of the YarnSpinner scene you want to play on a right answer.




Open the YarnSpinner dialogue script from “Assets/Dialogue”



Write the “WellDone” scene as follows. (Make sure to save the script)

```
0 references | Show in Graph View
✓ title: WellDone
---
Well done! The code was 1234!
==
```

Now, when the player guesses 1234, the script will show the message.



# Function guide

This section will show all commands and functions that are made available in YarnSpinner by the framework. They are sorted alphabetically.

## activate

### Syntax

```
<<activate target (PlayerActivatable)>>
```

### Description

This command activates all `PlayerActivatable` components on the specified `GameObject`. This is typically used to trigger certain interactive elements in the game, such as switches or buttons.

### Usage Example

```
// Example of activating an Elevator
<<activate "Elevator">>
```

In this example, the command activates all `PlayerActivatable` components on the `GameObject` named `Elevator`. This might trigger the elevator to move or become operational.

### See Also

- `set_enabled`: Enables or disables a `PlayerActivatable`.
- `toggle_animation`: Toggles an animation on a `GameObject`.

## animate

### Syntax

```
<<animate target (SimpleAnimationTrigger)>>
```

### Description

This command starts playing the animation associated with the specified GameObject's [SimpleAnimationTrigger](#) component.

### Usage Example

```
// Example of animating the Temple Gate
<<animate "TempleGate">>
```

In this example, the command starts the animation associated with the [TempleGate](#) GameObject.

### See Also

- [play\\_animation](#): Plays a specified animation state on a GameObject.
  - [toggle\\_animation](#): Toggles an animation on a GameObject.
-

## disable\_controls

### Syntax

```
<<disable_controls target (TogglePlayerControls)>>
```

### Description

This command disables the controls for the specified target, usually the player. You can use this during cutscenes.

### Usage Example

```
// Example of controlling player controls
<<disable_controls "Player">>
<<wait 7>>
<<enable_controls "Player">>
```

In this example, the command disables all controls for the player, preventing any input actions.

### See Also

- [enable\\_controls](#): Enables the controls for a target.
-

## enable\_controls

### Syntax

```
<<enable_controls target (TogglePlayerControls)>>
```

### Description

This command enables the controls for the specified target, usually the player. You can use this after the player controls were disabled using disable\_controls.

### Usage Example

```
// Example of enabling player controls
<<disable_controls "Player">>
<<wait 7>>
<<enable_controls "Player">>
```

In this example, the command re-enables all controls for the player, allowing input actions.

### See Also

- [disable\\_controls](#): Disables the controls for a target.
-

## get\_distance

### Syntax

```
<<if get_distance("object1", "object2") < value>>
    //code
<<else>>
    //code
<<endif>>
```

### Description

This command checks the distance between two gameobjects.

### Usage Example

```
<<if get_distance("Player", "Goal") < 5>>
    You are close to the goal
<<else>>
    You are not close to the goal
<<endif>>
```

In this example, the command checks the distance between the player and the goal and displays an appropriate message.

### See Also

- [show\\_path](#): Shows a path between two objects
  - [wait\\_for](#): Waits for an object to approach another object
-

## get\_scene

### Syntax

```
<<if get_scene() == "scene02">>  
..  
<<else>  
..  
<<endif>>
```

### Description

This command will read the current Unity scene name.

### Usage Example

```
<<set $currentSceneName to get_scene ()>>
```

In this example, the function loads the current scene name into a variable.

### See Also

- [set\\_scene](#): Loads another Unity scene.

## give\_item

### Syntax

```
<<give_item target (Inventory) id (string)>>
```

### Description

This command adds an item to the specified target's inventory.

### Usage Example

```
// Example of giving a golden coin to the player  
// coin should be defined in the folder Assets/InventoryItems  
// Resources  
<<give_item "Player" "coin">>
```

In this example, the command adds an item with the ID `coin` and the icon `goldencoin` to the player's inventory.

### See Also

- `take_item`: Removes an item from the inventory.
  - `has_item`: Checks if an item is in the inventory.
-

## has\_item

### Syntax

```
<<if has_item("tag")>>
    //code
<<else>>
    //code
<<endif>>
```

### Description

This command checks if a certain item is in the inventory.

### Usage Example

```
<<if has_item("coin")>>
    You have a coin.
<<else>>
    You don't have a coin.
<<endif>>
```

In this example, the command checks if the player has an item with the tag `coin` and displays an appropriate message.

### See Also

- [give\\_item](#): Adds an item to the inventory.
  - [take\\_item](#): Removes an item from the inventory.
-

## hide\_path

### Syntax

```
<<hide_path>>
```

### Description

This command hides the current navigation path that is being shown.

### Usage Example

```
// Example of hiding the navigation path
<<show_path "Player" "NPC">>
<<wait 7>>
<<hide_path>>
```

In this example, the command hides any navigation path that is currently displayed.

### See Also

- [show\\_path](#): Displays a navigation path between two GameObjects.
-

## load\_scene

### Syntax

```
<<load_scene name (string)>>
```

### Description

This command will load another Unity scene.

*Scenes must be added to File->Build Settings first.*

### Usage Example

```
<<load_scene "InsideTheHouse">>
<<stop>>
```

In this example, the command loads another scene and stops the script.

### See Also

- [get\\_scene](#): Reads the name of the current scene

log

### Syntax

```
<<log message (String)>>
```

### Description

This command will show a message in Unity's debug log.

### Usage Example

```
title: Start  
---  
<<log "Hello world">>  
====
```

In this example, the command shows “Hello world” in the debug log.  
If it is hidden, bring it up using Window->Panels->Console

## play\_animation

### Syntax

```
<<play_animation target (GameObject) name (string) [shouldWait (bool) = True]>>
```

### Description

This command plays a specified animation state on the target GameObject.

### Usage Example

```
// Example of playing the TurningAnimation on the Ferris Wheel without waiting
<<play_animation "FerrisWheel" "TurningAnimation" false>>
```

In this example, the command plays the `TurningAnimation` on the `FerrisWheel` GameObject and does not wait for the animation to complete.

### See Also

- `animate`: Starts an animation associated with a `SimpleAnimationTrigger`.
  - `toggle_animation`: Toggles an animation on a GameObject.
-

`playerpref_load_int`  
`playerpref_load_string`  
`playerpref_load_bool`

## Syntax

```
<<set $variable to playerpref_load_type(id)>>
```

## Description

Description This function loads a value from Unity's PlayerPrefs with the specified key (id) and type (type). The type can be string, int, or bool.

## Usage Example

```
<<playerpref_save_int "slot1" 16>>  
  
<<set $score=playerpref_load_int("slot1")>>
```

In this example, the player's score is saved to and loaded from PlayerPrefs.

## See Also

- `playerpref_save`: Saves a value to PlayerPrefs.
- `playerpref_exists`: Checks if a key exists in PlayerPrefs.

`playerpref_save_string`  
`playerpref_save_int`  
`playerpref_save_bool`

## Syntax

```
<<playerpref_save_type(id, value)>>
```

## Description

These functions save a value to Unity's PlayerPrefs with the specified key (id) and type (type). The type can be `string`, `int`, or `bool`.

## Usage Example

```
<<playerpref_save_int "slot1" 16>>

<<set $score=playerpref_load_int("slot1")>>
```

In this example, the player's score is saved to and loaded from PlayerPrefs.

## See Also

- `playerpref_load`: Loads a value from PlayerPrefs.
- `playerpref_exists`: Checks if a key exists in PlayerPrefs.

## playerpref\_exists

### Syntax

```
<<playerpref_exists id>>
```

**Description** This command checks if a key (**id**) exists in Unity's PlayerPrefs.

### Usage Example

```
// Check if player's name exists in PlayerPrefs
<<if playerpref_exists "player_name">>
    Player name exists!
<<else>>
    No player name found.
<<endif>>
```

In this example, the script checks if the player's name has been saved in PlayerPrefs and displays a message accordingly.

### See Also

- **playerpref\_save**: Saves a value to PlayerPrefs.
- **playerpref\_load**: Loads a value from PlayerPrefs.

## respawn

### Syntax

```
<<respawn target (RespawnBehaviour)>>
```

### Description

This command respawns the player at a specified location.

### Usage Example

```
// Example of respawning the player
<<respawn "Player">>
```

In this example, the command respawns the player at their designated respawn location.

### See Also

- [set\\_spawn](#): Sets the spawn point to a certain GameObject.
  - [teleport](#): Teleports a GameObject to a location.
-

**say**

### Syntax

```
<<say target (GameObject) message (String) [offset_y (number) = 0] [shouldWait (bool) = True]>>
```

### Description

This command shows a speech bubble with the specified message at the target GameObject.

### Usage Example

```
// Example of making the Tavern Keeper speak
<<say "TavernKeeperHead" "Welcome traveler, what can I get for you?">>
<<say "TavernKeeperHead" "We got some fine ale from the Royal Kingston brewery">>
```

In this example, the command displays the message "Welcome traveler, what can I get for you?" as a speech bubble above the **TavernKeeperHead** GameObject.

### See Also

- [wait\\_for](#): Waits for a condition to be met before continuing.
-

## set\_enabled

### Syntax

```
<<set_enabled target (PlayerActivatable) [mode (bool) = True]>>
```

### Description

This command enables or disables a `PlayerActivatable` component on the target `GameObject`. You can for instance disable objects at the start of the story and enable them later on in a dialogue.

### Usage Example

```
// Example of enabling an interactable NPC
<<set_enabled "InteractableNPC" false>>
<<wait 7>>
<<set_enabled "InteractableNPC" true>>
```

In this example, the command enables and disables the `PlayerActivatable` component on the `InteractableNPC` `GameObject`.

### See Also

- `activate`: Activates all `PlayerActivatable` components on a `GameObject`.
-

## set\_spawn

### Syntax

```
<<set_spawn target (RespawnBehaviour) spawnPoint (GameObject)>>
```

### Description

This command sets the spawn point to the specified GameObject.

### Usage Example

```
// Example of setting the spawn point to Chapter2Spawn  
<<set_spawn "Player" "Chapter2Spawn">>
```

In this example, the command sets the player's respawn point to the [Chapter2Spawn](#) GameObject.

### See Also

- [respawn](#): Respawns the player at a certain location.
-

## show\_path

### Syntax

```
<<show_path from (GameObject) to (GameObject) [shouldWait (bool) = True] [minDistance  
 (number) = 2]>>
```

### Description

This command shows a navigation path from one GameObject to another.

### Usage Example

```
// Example of showing a path from the Player to the Castle Gate  
<<show_path "Player" "CastleGate">>
```

In this example, the command shows a navigation path from the player to the [CastleGate](#) GameObject.

### See Also

- [hide\\_path](#): Hides the current path that is shown.
-

## take\_item

### Syntax

```
<<take_item target (Inventory) id (string)>>
```

### Description

This command removes an item from the specified target's inventory.

### Usage Example

```
// Example of taking a coin from the player
// The id can be set in give_item or in the AddInventoryItem component
<<take_item "Player" "coin">>
```

In this example, the command removes the item with the ID `coin` from the player's inventory.

### See Also

- `give_item`: Adds an item to the inventory.
  - `has_item`: Checks if an item is in the inventory.
-

# teleport

## Syntax

```
<<teleport target (RespawnBehaviour) destination (GameObject)>>
```

## Description

This command teleports the specified target to a destination GameObject.

## Usage Example

```
// Example of teleporting the player to the Dungeon Chapter  
<<teleport "Player" "DungeonChapter">>
```

In this example, the command teleports the player to the `DungeonChapter` GameObject.

## See Also

- `respawn`: Respawns the player at a certain location.
-

## toggle\_animation

### Syntax

```
<<toggle_animation target (AnimationToggle)>>
```

### Description

This command toggles the animation on the specified GameObject's [AnimationToggle](#) component.

### Usage Example

```
// Example of toggling the Boat animation
<<toggle_animation "Boat">>
```

In this example, the command toggles the animation associated with the [Boat](#) GameObject.

### See Also

- [play\\_animation](#): Plays a specified animation state on a GameObject.
  - [animate](#): Starts an animation associated with a [SimpleAnimationTrigger](#).
-

## walk\_to

### Syntax

```
<<walk_to target (WalkBehaviour) [destination (GameObject) = ] [distance (number) = 0]  
[shouldWait (bool) = True]>>
```

### Description

This command makes an NPC walk to a specified location.

### Usage Example

```
// Example of making an NPC walk to the Sword Puzzle  
<<walk_to "NPC" "SwordPuzzle">>
```

In this example, the command makes the **NPC** walk to the **SwordPuzzle** GameObject.

### See Also

- **wait\_for**: Waits for a condition to be met before continuing.
-

## wait\_for\_location

### Syntax

```
<<wait_for_location gameObject (GameObject) target (GameObject) [threshold (number) = 1.5]>>
```

### Description

This command waits for one GameObject to be within a certain distance of another GameObject.

### Usage Example

```
// Example of waiting for the player to approach an NPC  
<<wait_for_location "Player" "NPC">>
```

In this example, the command waits for the player to be within 1.5 units of the [NPC](#).

### See Also

- [walk\\_to](#): Makes an NPC walk to a location.
-