

ESD, REVERSE/BACKFEED PROTECTION

MCU, NATIVE USB, RESET/BOOT AND USER IO

RF MODULE INTERFACES – EXACT LOCKED VARIANTS

FOR – AP63203 REFERENCE COMPONENT SET

SOURCE DAMPING, RESET STATES AND TEST ACCESS

GPS, MICROSD, OLED AND EXPANSION

IDENT 1S BATTERY MONITOR INPUT

UTS – DEDICATED LOW-SIDE DRIVERS

MANUFACTURING / BRING-UP TEST POINTS

REV B IS PASSIVE-ONLY. NO JAMMER OR COUNTERMEASURE OUTPUT HARDWARE.

RX5808 module/lot and every reference-envelope model require qualification before fabrication.

All radio antenna paths and panel labels: see RF_COEXISTENCE.md.

GPL-3.0-only; open hardware design source Canonical MCU: ESP32-S3-WROOM-1-N8; native USB; four-layer carrier DESIGN IN PROGRESS – UNVALIDATED IN PHYSICAL HARDWARE – DO NOT ORDER SkySweep32 Project		
Sheet: / File: skysweep32_pro_rev_b.kicad_sch		
Title: SkySweep32 Pro Rev B Carrier		
Size: A3	Date: 2026-08-10	Rev:
KiCad E.D.A. 10.0.5		Id: 1/1