


# CSS

(Cascading Style Sheets)

Layouts


# Box model

Each element represented as a rectangular box for the rendering



```
<div class="box"><div class="content"></div></div>  
<div class="box"><div class="content"></div></div>
```

```
.box {  
  width: 50px;  
  height: 50px;  
  padding: 10px;  
  margin: 10px;  
  border: 5px solid blue;  
  background-color: #aaa;  
}  
.content {  
  height: 100%;  
  background-color: red;  
}
```



# Block elements

Start with a new line and stretch to the full width of the container

Could contain block and inline elements

Some properties could be applied only to block elements (such as width, height, margin, padding...)

```
<div>  
  text before  
  <div class="block">  
    block <span>element</span>  
    <div>inner block</div>  
  </div>  
  text after  
</div>
```

```
.block {  
  display: block;  
  border: 5px solid blue;  
}
```

text before  
block element  
inner block  
text after

# Inline elements

Have the size of the content

Could contain only text and other inline elements

Don't break the flow

**\*Inline-block** - creates a block element (could use all the properties from the block element) which behaves in the flow as inline

```
<div>
  text before
  <span class="inline">
    inline
    <span class="inlineBlock">element</span>
  </span>
  text after
</div>
```

```
.inline {
  display: inline;
  color: red;
}

.inlineBlock {
  display: inline-block;
  border: 5px solid blue;
}
```

text before inline element text after

# Display: none

Completely removes the element from the flow

```
<div>  
  text before  
  <div class="none">  
    removed block  
  </div>  
  text after  
</div>
```

```
.none {  
  display: none;  
}
```

text before text after

# Visibility

Change visibility of the element, but keep it in the flow

```
<div>  
  hide  
  <span class="visibility">the element</span>  
  and preserve the space  
</div>
```

```
.visibility {  
  visibility: hidden;  
}
```

hide  
space


and preserve the

# Float

Removes an element from the normal flow and puts it to the left/right of the container and allows to other inline elements wrap around it

```
<div>
  very very long long text
  
  more of very long long text
  more of very long long text
</div>
```

```
.float {
  float: left;
  width: 50px;
}
```

very very long long text  
 more of very long  
long text more of  
very long long text

# Static position

Positions an element based on the normal flow

Offset properties have no effect on it

The default value of the `position` property

```
<div class="container">  
  Shows  
  <span class="position">the position</span>  
  of the element  
</div>
```

```
.container {  
  position: relative;  
  border: 5px solid blue;  
  padding: 20px;  
}  
  
.position {  
  color: red;  
  position: static;  
  top: 20px;  
  left: 20px;  
}
```

Shows **the position** of the element



# Relative position

Positioned an element based on the normal flow

Offset properties will apply on it based on its default position

```
<div class="container">  
  Shows  
  <span class="position">the position</span>  
  of the element  
</div>
```

```
.container {  
  position: relative;  
  border: 5px solid blue;  
  padding: 20px;  
}  
  
.position {  
  color: red;  
  position: relative;  
  top: 20px;  
  left: 20px;  
}
```

Shows **the position** of the element

# Absolute position

Removes an element from the normal flow

It will be positioned by the offset properties based on the closest parent element with not static position

```
<div class="container">  
  Shows  
  <span class="position">the position</span>  
  of the element  
</div>
```

```
.container {  
  position: relative;  
  border: 5px solid blue;  
  padding: 20px;  
}  
  
.position {  
  color: red;  
  position: absolute;  
  top: 0;  
  left: 0;  
}
```

---

the position  
Shows of the element

# Fixed position

Removes an element from the normal flow

Offset properties will apply on it based on the viewport

```
<div class="container">  
  Shows  
  <span class="position">the position</span>  
  of the element  
</div>
```

```
.container {  
  position: relative;  
  border: 5px solid blue;  
  padding: 20px;  
}  
  
.position {  
  color: red;  
  position: fixed;  
  top: 0;  
  left: 0;  
}
```

the position

Shows of the element

# Overflow

Sets how an element will show its content when it overflows the edges

**visible** - content will be rendered outside the edges (default value)

**hidden** - hide the content outside the edges. Doesn't allow to scroll


**auto** - hide the content outside the edges, but allows scrolling to the hidden content

**scroll** - hide the content outside the edges. Always show scrollbars, even when content fits the element

```
<div class="overflow">  
  very very long long text  
  more of very long long text  
</div>
```


```
.overflow {  
  overflow: visible;  
  width: 100px;  
  height: 100px;  
  border: 5px solid blue;  
}
```

overflow: visible




very very  
long long  
text more  
of very  
long long  
text

overflow: hidden



very very  
long long  
text more  
of very

overflow: auto



long long  
text more  
of very

# Helpful links

- <https://www.w3.org/TR/CSS2/> - specification
- <https://caniuse.com> - checks the browsers support of the css properties
- <https://developer.mozilla.org/en-US/docs/Web/CSS/Reference> - documentation from Mozilla corporation
- <https://csstriggers.com> - checks what property triggers while rendering
- <https://css-tricks.com> - the portal with bunch of helpful tricks and articles