

/*Data Manipulation Using Correlated Subqueries*/

/*Subqueries are used heavily in update, delete, and insert statements as well, with correlated subqueries appearing frequently in update and delete statements.*/

```
desc rental;
```

```
UPDATE customer AS c
```

```
SET
```

```
    c.last_update = (SELECT  
                      MAX(r.rental_date)
```

```
    FROM
```

```
        rental r
```

```
    WHERE
```

```
        r.customer_id = c.customer_id)
```

```
WHERE
```

```
    EXISTS( SELECT
```

```
        1
```

```
    FROM
```

```
        rental r
```

```
    WHERE
```

```
        r.customer_id = c.customer_id);
```

/*DO NOT EXECUTE*/

DELETE FROM customer

WHERE

365 < ALL (SELECT

DATEDIFF(NOW(), r.rental_date) days_since_last_rental

FROM

rental r

WHERE

r.customer_id = customer.customer_id);

/*When using correlated subqueries with delete statements in MySQL,
keep in mind that, for whatever reason, table aliases are not allowed*/

/*When to Use Subqueries:

1. Subqueries as Data Sources

Since a subquery generates a result set containing rows and columns of data, it is perfectly valid to include subqueries in your from clause along with tables.*/

```
SELECT
    c.first_name, c.last_name, p.num_rentals, p.total_payments
FROM
    customer AS c
    INNER JOIN
    (SELECT
        customer_id,
        COUNT(*) AS num_rentals,
        SUM(amount) AS total_payments
    FROM
        payment
    GROUP BY customer_id) AS p ON c.customer_id = p.customer_id;
```

/*2. Data fabrication

Along with using subqueries to summarize existing data, you can use subqueries to generate data that doesn't exist in any form within your database.

For example, you may wish to group your customers by the amount of money spent on film rentals, but you want to use group definitions that are not stored in your database.*/

```
SELECT 'Small Fry' name, 0 low_limit, 74.99 high_limit
UNION ALL SELECT 'Average Joes' name, 75 low_limit, 149.99 high_limit
UNION ALL SELECT 'Heavy Hitters' name, 150 low_limit, 9999999.99
high_limit;
```

```

SELECT
    pymnt_grps.name, COUNT(*) num_customers
FROM
    (SELECT
        customer_id, COUNT(*) num_rentals, SUM(amount) tot_payments
    FROM
        payment
    GROUP BY customer_id) pymnt
INNER JOIN
    (SELECT 'Small Fry' name, 0 low_limit, 74.99 high_limit
    UNION ALL
    SELECT 'Average Joes' name, 75 low_limit, 149.99 high_limit
    UNION ALL
    SELECT 'Heavy Hitters' name, 150 low_limit, 9999999.99 high_limit
    ) pymnt_grps
ON pymnt.tot_payments
BETWEEN pymnt_grps.low_limit AND pymnt_grps.high_limit
GROUP BY pymnt_grps.name;

```

/*3. Task-oriented subqueries*/

```
SELECT
    c.first_name,
    c.last_name,
    ct.city,
    SUM(p.amount) AS total_payments,
    COUNT(*) AS total_rentals
FROM
    payment AS p
        INNER JOIN
    customer AS c ON p.customer_id = c.customer_id
        INNER JOIN
    address AS a ON c.address_id = a.address_id
        INNER JOIN
    city AS ct ON a.city_id = ct.city_id
GROUP BY c.first_name;
```

/*This query returns the desired data, but if you look at the query closely, you will see that the customer, address, and city tables are needed only for display purposes and that the payment table has everything needed to generate the groupings (customer_id and amount).*/

```
SELECT
    customer_id, COUNT(*) tot_rentals, SUM(amount) tot_payments
FROM
    payment
GROUP BY customer_id;
```

```
SELECT
    c.first_name,
    c.last_name,
    ct.city,
    pymnt.tot_payments,
    pymnt.tot_rentals
FROM
    (SELECT
        customer_id, COUNT(*) tot_rentals, SUM(amount) tot_payments
    FROM
        payment
    GROUP BY customer_id) AS pymnt
    INNER JOIN
    customer c ON pymnt.customer_id = c.customer_id
    INNER JOIN
    address a ON c.address_id = a.address_id
    INNER JOIN
    city ct ON a.city_id = ct.city_id;
```

/*Common table expressions (CTE)*/

```
WITH actors_s AS
(SELECT actor_id, first_name, last_name
FROM actor
WHERE last_name LIKE 'S%'
),
```

```
actors_s_pg AS
(SELECT s.actor_id, s.first_name, s.last_name,
f.film_id, f.title
FROM actors_s s
INNER JOIN film_actor fa
ON s.actor_id = fa.actor_id
INNER JOIN film f
ON f.film_id = fa.film_id
WHERE f.rating = 'PG'
),
```

```
actors_s_pg_revenue AS
(SELECT spg.first_name, spg.last_name, p.amount
FROM actors_s_pg spg
INNER JOIN inventory i
ON i.film_id = spg.film_id
INNER JOIN rental r
ON i.inventory_id = r.inventory_id
INNER JOIN payment p
ON r.rental_id = p.rental_id
) -- end of With clause
```

```
SELECT spg_rev.first_name, spg_rev.last_name,  
sum(spg_rev.amount) tot_revenue  
FROM actors_s_pg_revenue spg_rev  
GROUP BY spg_rev.first_name, spg_rev.last_name  
ORDER BY 3 desc;
```

/*Subqueries as Expression Generators*/

```
SELECT  
    (SELECT  
        c.first_name  
    FROM  
        customer c  
    WHERE  
        c.customer_id = p.customer_id) first_name,  
    (SELECT  
        c.last_name  
    FROM  
        customer c  
    WHERE  
        c.customer_id = p.customer_id) last_name,  
    (SELECT  
        ct.city  
    FROM  
        customer c  
        INNER JOIN  
        address a ON c.address_id = a.address_id  
        INNER JOIN  
        city ct ON a.city_id = ct.city_id  
    WHERE
```



```

        c.customer_id = p.customer_id) city,
    SUM(p.amount) tot_payments,
    COUNT(*) tot_rentals
FROM
    payment p
GROUP BY p.customer_id;

```

/*There are two main differences between this query and the earlier version using a subquery in the from clause:

- Instead of joining the customer, address, and city tables to the payment data, correlated scalar subqueries are used in the select clause to look up the customer's first/last names and city.
- The customer table is accessed three times (once in each of the three subqueries) rather than just once.

As previously noted, scalar subqueries can also appear in the order by clause.*/

```

SELECT
    a.actor_id, a.first_name, a.last_name
FROM
    actor a
ORDER BY (SELECT
    COUNT(*)
FROM
    film_actor fa
WHERE
    fa.actor_id = a.actor_id) DESC;

```

/*Along with using correlated scalar subqueries in select statements, you can use noncorrelated scalar subqueries to generate values for an insert statement.*/

```
INSERT INTO film_actor (actor_id, film_id, last_update)
VALUES (
(SELECT actor_id FROM actor
WHERE first_name = 'JENNIFER' AND last_name = 'DAVIS'),
(SELECT film_id FROM film
WHERE title = 'ACE GOLDFINGER'),
now()
);
```

/*Exercise - 1

Construct a query against the film table that uses a filter condition with a noncorrelated

subquery against the category table to find all action films (category.name =

'Action').*/

desc film;

desc category;

desc film_category;

SELECT

title

FROM

film

WHERE

film_id IN (SELECT

fc.film_id

FROM

film_category AS fc

INNER JOIN

category AS c ON fc.category_id = c.category_id

WHERE

c.name = 'Action');

/*Exercise - 2

Rework the query from Exercise 9-1 using a correlated subquery against the category and film_category tables to achieve the same results.*/

```
SELECT
    f.title
FROM
    film AS f
WHERE
    EXISTS( SELECT
        1
        FROM
            film_category AS fc
            INNER JOIN
                category AS c ON fc.category_id = c.category_id
        WHERE
            c.name = 'Action'
            AND fc.film_id = f.film_id);
```

/*Exercise - 3

Join the following query to a subquery against the film_actor table to show the level of each actor:

```
SELECT 'Hollywood Star' level, 30 min_roles, 99999 max_roles
```

```
UNION ALL
```

```
SELECT 'Prolific Actor' level, 20 min_roles, 29 max_roles
```

```
UNION ALL
```

```
SELECT 'Newcomer' level, 1 min_roles, 19 max_roles
```

The subquery against the film_actor table should count the number of rows for each actor using group by actor_id, and the count should be compared to the min_roles/max_roles columns to determine which level each actor belongs to.*/

```
SELECT
```

```
    actr.actor_id, grps.level
```

```
FROM
```

```
    (SELECT
```

```
        actor_id, COUNT(*) num_roles
```

```
    FROM
```

```
        film_actor
```

```
    GROUP BY actor_id) actr
```

```
    INNER JOIN
```

```
    (SELECT 'Hollywood Star' level, 30 min_roles, 99999 max_roles
```

```
    UNION ALL
```

```
    SELECT 'Prolific Actor' level, 20 min_roles, 29 max_roles
```

```
    UNION ALL
```

```
    SELECT 'Newcomer' level, 1 min_roles, 19 max_roles) grps
```

```
    ON actr.num_roles
```

```
    BETWEEN grps.min_roles AND grps.max_roles;
```