Alternative Splicing Analysis Tool Package (ASATP)

version 0.7

Content

1.	What is ASATP?	2
2.	How to install?	2
3.	Tools in ASATP	2
4.	How to use?	3
A	ASRecovist	3
	Input	3
	Output file	3
	Output graph	4
	Command example	5
A	ASQuantityDiff	5
	Input	5
	Output file	6
	Command example	6
A	ASAffectORF	6
	Input	7
	Output file	7
	Command example	7
r	runASATP	7
a	nsp2bit	8
b	pit2asp	8
	nlitCtf	0

1. What is ASATP?

Alternative splicing analysis tool package (ASATP), including a series of toolkits to analyze alternative splicing events, which could be used to

- detect and visualized alternative splicing events,
- check ORF changes,
- assess regulations of alternative splicing and
- do statistical analysis.

The users could either access this software from our webserver, or download it from GitHub.

2. How to install?

ASATP works under Linux. To use ASATP, you need install Perl (>5.10). Some Perl modules are needed:

Bioperl

Bio::Graphics GD::Image GD::SVG Statistics::R Math::BigInt

You can use CPAN command to install modules. For example:

```
perl -MCPAN -e 'install HTML::Template'
```

To check whether ASATP work well, you can run commands like:

```
perl ../runASATP.pl --gtf anno.gtf --trExpFile isoform_exp.txt --output output_svg --graph yes --graphFormat svg
perl ../runASATP.pl --gtf anno.gtf --trExpFile isoform_exp.txt --output output_png --graph yes --graphFormat png
```

3. Tools in ASATP

♦ ASRecovist

Alternative splicing recognition and visualization tool, which is a program to detect alternative splicing events from a gene annotation and classified them into different types (CE, IR, MXE, A3SS, A5SS, AFE, ALE and other). Alternative splicing events will be showed in tables and graphs.

♦ ASQuantityDiff

Alternative splicing quantity comparison between samples, which was used to detect expression regulations of alternative transcripts.

♦ ASAffectORF

Check AS event in CDS region, to identify the effect of alternative splicing event for ORFs.

♥ runASATP

Run Alternative splicing Analysis Tool Package, which was a combined pipeline including ASRecovist, ASQuantityDiff and ASAffectORF.

♦ asp2bit

Transform AS pattern to bit matrix.

bit2asp

Transform bit to ASP code.

Split a GTF file when it's too large to process. Then you can process them separately using multi-CPU to save time.

4. How to use?

ASRecovist

NAME					
Alternative splicing recog	Alternative splicing recognition and visualization tool				
SYNOPSIS					
Usage: perl ASRecov	vist.plgtf <gt< td=""><td>f_fortmat_file>output <output_fold> [graph no] [graphFormat SVG]</output_fold></td></gt<>	f_fortmat_file>output <output_fold> [graph no] [graphFormat SVG]</output_fold>			
Options:					
-help h					
gtf	STRING	Input gtf format file.			
output	STRING	Output folder.			
graph	no yes	Create graph or not. default [no]			
graphFormat	SVG png	Graph format. default [SVG]			

Input

GTF (Gene Transfer Format) is a refinement to GFF that tightens the specification. The first eight GTF fields are the same as GFF. The group field has been expanded into a list of attributes. For more information on this format, see https://genome.ucsc.edu/FAQ/FAQformat.html#format4

Output file

Four tab separated files (i.e. $AS_{\text{event.xls}}$, $AS_{\text{event.summary.xls}}$, $AS_{\text{event_group.xls}}$ and $AS_{\text{event_group.summary.xls}}$) were outputted.

AS_event.xls: alternative splicing event between transcripts of the same gene. Each column:

Column	Description	Example
Gene	gene id	G04034
Chromosome	chromosome/scaffold/contig id	contig6.12
Strand	gene strand	+
Transcript1	the 1st transcript in an alternative splicing event	G04034T0
Transcript2	the 2nd transcript in an alternative splicing event	G04034T1
AS Pattern	alternative splicing pattern (ASP) code	2
AS Event Type	alternative splicing type	IR
AS Event Span Unit	start and stop position of an alternative splicing event	1009411-1009632
ACD' C II'	span unit of an alternative splicing event, which corresponding bit	1000072 1000410
AS Bit Span Unit	matrix	1009272-1009410,

1009411-1009632,1009633-

1009680

AS_event.summary.xls: Summary of alternative splicing event. Each column:

Column	Description	Example
AS Pattern	alternative splicing pattern (ASP) code	8
AS Event Type	alternative splicing type	A5SS
AS Event Num	number of alternative splicing event	1
Gene with AS Event	gene number with alternative splicing event	1
Transcript with AS Event	transcript number with alternative splicing	2

AS_event_group.xls: alternative splicing events between different transcripts in a gene will be grouped when they are with the same ASP codes and the same span units of genome coordinates. Each column:


Column	Description	Example
Gene	gene id	G04034
Chromosome	chromosome/scaffold/contig id	contig6.12
Strand	gene strand	+
AS Event	alternative enlicing event energy in a con-	as al
Groups	alternative splicing event groups in a gene	as_g1
AS Pattern	alternative splicing pattern (ASP) code	2
AS Event Type	alternative splicing type	IR
AS Event Span	start and stan resition of an alternative calining event	1009411-1009632
Unit	start and stop position of an alternative splicing event	1009411-1009032
AS Bit Span	span unit of an alternative splicing event, which	1009272-1009410,1009411-
Unit	corresponding bit matrix	1009632,1009633-1009680
Transcript1	the 1st transcript in an alternative splicing event	G04034T0
Transcript2	the 2nd transcript in an alternative splicing event	G04034T1

AS_event_group.summary.xls: Summary of alternative splicing group. Each column:

Column	Description	Example
AS Pattern	alternative splicing pattern (ASP) code	8
AS Event Type	alternative splicing type	A5SS
AS Event Group Num	number of alternative splicing event groups	1
Gene with AS Event	gene number with alternative splicing event	1
Transcript with AS Event	transcript number with alternative splicing	2

Output graph

For each gene, a graphic structure of alternative splicing events could be produced. Gene structure in the genome is show in the top track. The other tracks represent groups of alternative splicing events in a gene. The group id, ASP code and alternative splicing type are labeled. For example,



ASRecovist support two graphic formats (i.e. png and svg).

Command example

perl ASRecovist.pl --gtf anno.gtf --output output_svg/ASRecovist_out --graph yes --graphFormat svg

ASQuantityDiff

```
NAME
    Alternative splicing quantity diff comparison between samples.
  SYNOPSIS
         Usage: perl ASQuantityDiff.pl --asEvent <AS_event.xls> --asGroup <AS_event_group.xls> --trExpFile
<transcript_expression_file> --output <output_fold>
         Options:
             -help|h
             --output
                            STRING
                                       Output folder.
             --asGroup
                           STRING
                                       Output of program ASRecovist, i.e. "AS_event_group.xls"
                          STRING
                                       Output of program ASRecovist or ASAffectORF, i.e. "AS_event.xls" or
             --asEvent
ASAffectORF_event.xls
             --trExpFile
                           STRING
                                        A file with expression levels of transcripts in different samples.
                            FLOAT
                                        q-vlaue cutoff [default: 0.05]
             --qvalue
             --expCutoff
                            FLOAT
                                       Expression level cutoff. A transcript will be considered to be not expressed if its
expression level less than this cutoff.
         Note:
             "--trExpFile" input file format (column separated by Tab):
                       Transcript Sample1 Sample2 ...
             g1 tr1 0.5 20 ...
             g1 tr2 53 19 ...
```

Input

The output file of ASRecovist will be as the input of ASQuantityDiff.

The expression information of each transcript in a gene is the input of ASQuantityDiff as well (--trExpFile).

The alternative splicing events significantly regulated between samples will be counted in outputted summary file (--qvalue).

Output file

ASQuantityDiff outputs four files, i.e. ASExpDiff_event.xls, ASExpDiff_event.summary.xls, ASExpDiff_event_group.xls and ASExpDiff_event_group.summary.xls, which are corresponding the four files outputted by ASRecovist.

Compared to AS_event.xls and AS_event_group.xls, some more columns are in ASExpDiff_event.xls and ASExpDiff_event_group.xls. Added column:

Column	Description	Example
Sample1	sample 1 name	Sample2
Sample2	sample 2 name	Sample3
Tr1_Sample1_Exp	expression of transcript 1 in sample 1	30.4259
Tr2_Sample1_Exp	expression of transcript 2 in sample 1	2
Tr1_Sample2_Exp	expression of transcript 1 in sample 2	49.581
Tr2_Sample2_Exp	expression of transcript 2 in sample 2	2
p-value	statistic p-value	1.00E+00
q-value	statistic q-value	1.00E+00

In an alternative splicing group, the expression of transcript 1 or 2 are the sum of transcripts in the group.

Compared with AS_event.summary.xls and AS_event_group.summary.xls, some more columns are in ASExpDiff_event.summary.xls and ASExpDiff_event_group.summary.xls. Added column in ASExpDiff_event.summary.xls:

Column	Description	Example
Sample1	sample 1	Sample2
Sample2	sample 2	Sample3
AS Event QuantityDiff	number of alternative splicing events significantly regulated	1
Gene with AS Event QuantityDiff	gene number	1
Transcript with AS Event QuantityDiff	transcript number	2
Sample1 Specific AS Event	alternative splicing event occurred in sample 1 only	1
Sample2 Specific AS Event	alternative splicing event occurred in sample 2 only	0

Columns added in ASExpDiff_event_group.summary.xls are similar.

Command example

 $perl\ ASQuantity Diff.pl\ -- as Event\ ASA ffect ORF_event.xls\ -- as Group\ AS_event_group.xls\ -- tr ExpFile\ is of orm_exp.txt\ -- output\ ASQuantity Diff_out$

ASAffectORF

NAME

Check AS event in CDS region.

SYNOPSIS

	Usage: perl ASA	ffectORF.plgtf <gt< th=""><th>f file with CDS annotation>asEvent <as event="" file="">output <output< th=""></output<></as></th></gt<>	f file with CDS annotation>asEvent <as event="" file="">output <output< th=""></output<></as>
folder>			
	Options:		
	-help h		
	gtf	STRING	Input gtf format file with CDS annoation
	output	STRING	Output folder.
	asEvent	STRING	Output of program ASRecovist , i.e. "AS_event.xls"

Input

The input of ASAffectORF are the GTF file with CDS annotation, and AS_event.xls, which was outputted by ASRecovist.

Output file

Two file ASAffectORF_event.xls outputted by ASAffectORF, i.e. and are ASAffectORF_event.summary.xls.

Compared with AS_event.xls, columns added in ASAffectORF_event.xls are:

Column	Description	Example
AS Event Location	alternative splicing event occurred region	G04034T0(CDS),G04034T1(CDS)
AS Event Frame Change	base number of frame change	0
Tr2_vs_T1 ORF Diff Tag	change tag of ORF	frame_full_same,start_same,stop_same

ASAffectORF_event.summary.xls: Summary of alternative splicing events in ASAffectORF_event.xls.

Command example

 $perl\ ASAffectORF.pl\ --gtf\ anno.gtf\ --asEvent\ output_svg/ASRecovist_out/AS_event.xls\ --output\ output_svg/ASAffectORF_output\ output\ outp$

runASATP

NAME Run Alternative splicing Analysis Tool Package. SYNOPSIS Usage: perl runASATP.pl --gtf <gtf file> --trExpFile <transcript_expression_file> --output <output_folder> [--graph no] [--graphFormat SVG] Options: -help|h --gtf **STRING** Input gtf format file. **STRING** Output folder. --output --trExpFile STRING A file with expression levels of transcripts in different samples. --graph no|yes Create graph or not. default [no] Graph format. default [SVG] --graphFormat SVG|png Note: "--gtf" input file should contain CDS annotation.

```
"--trExpFile" input file format (column separated by Tab):

Gene Transcript Sample1 Sample2 ...

g1 tr1 0.5 20 ...

g1 tr2 53 19 ...
```

runASATP is a pipeline to run ASRecovist, ASQuantityDiff and ASAffectORF. Therefore, the input and the output files were the same as ASRecovist, ASQuantityDiff and ASAffectORF.

asp2bit

```
NAME
  Transform AS pattern to bit matrix.
SYNOPSIS
  perl asp2bit.pl -asp aspCode --output <output_fold> [--graph no] [--graphFormat SVG]
       Options:
           -help|h
                                               Alternative splicing pattern code, e.g. 16
           --asp
                            no|yes
                                               Create graph or not. default [no]
           --graph
           --graphFormat
                           SVG|png
                                               Graph format. default [SVG]
                           STRING
           --output
                                               Output folder.
```

The input is the alternative splicing pattern (ASP) code. The output is the bit matrix corresponding to ASP code. Moreover, the graphic structure of an alternative splicing event can be drawn as well.

bit2asp

```
NAME
  Transform bit to ASP code.
SYNOPSIS
  perl bit2asp.pl --bit bitCode --output <output_fold> [--graph no]
  [--graphFormat SVG]
       Options:
            -help|h
            --bit
                                              Bit code, e.g. 10001,--101
            --graph
                            no|yes
                                              Create graph or not. default [no]
            --graphFormat SVG|png
                                              Graph format. default [SVG]
                           STRING
                                              Output folder.
            --output
```

The input of bit2asp is a bit matrix, and the output is ASP code. bit2asp can also draw graphic stricture of an alternative splicing event.

splitGtf

NAME

Split a gtf file when it's too large to process.

perl splitGtf.pl <file.gtf> <output_prefix>

The input is a large GTF file. The output is a series of small GTF files.

9