

SECURITY (COMP0141): UNIX PROCESSES



(MANY OF THESE SLIDES ARE TAKEN FROM ZAKIR DURUMERIC, THANKS ZAKIR!)

PROCESSES

Processes are isolated (cannot access each others' memory)

Processes run with the user ID (`uid`) of a specific user

- When you run a process, it's with the permissions of your `uid`
- Processes can access any files that you have access to

Processes started by `root` (`uid 0`) can reduce their privileges by changing to a less privileged `uid`

PROCESS USER IDS

Every process has three different user IDs:

Effective User ID (EUID): determines permissions for the process

Real User ID (RUID): determines the user that started the process

Saved User ID (SUID): EUID prior to any changes

3

These are typically all the same (the user that started the process)

CHANGING USER IDS

root can change EUID / RUID / SUID to arbitrary values

Unprivileged users can change EUID to RUID or SUID

`setuid(x)` changes all of EUID / RUID / SUID to x

`seteuid(x)` changes just EUID to x

4

SSH EXAMPLE

What if SSH runs as root and ran the following code?

```
→ if (authenticate(uid, passwd) == SUCCESS) {  
    seteuid(uid);  
    exec("/bin/bash");  
}  
                                euid = 0  
                                ruid = 0  
                                suid = 0
```

5

SSH EXAMPLE

What if SSH runs as root and ran the following code?

```
→ if (authenticate(uid, passwd) == SUCCESS) {  
    seteuid(uid);  
    exec("/bin/bash");  
}  
                                euid = 0uid  
                                ruid = 0  
                                suid = 0
```

6

SSH EXAMPLE

What if SSH runs as root and ran the following code?

```
if (authenticate(uid, passwd) == SUCCESS) {  
    seteuid(uid);  
    exec("/bin/bash");  
}  
  
euid = 0uid  
ruid = 0  
suid = 0
```

Unprivileged users can change EUID to RUID or SUID



setuid(0) ← get root privileges

7

SSH EXAMPLE

What if SSH runs as root and ran the following code?

```
if (authenticate(uid, passwd) == SUCCESS) {  
    seteuid(uid);  
    exec("/bin/bash");  
}  
  
euid = 0uid  
ruid = 0uid  
suid = 0uid
```

8

This is what we should do instead to prevent this attack

ELEVATING PRIVILEGES

Sometimes we need to elevate our own privileges


Example: Running `passwd` modifies `/etc/shadow`, which only root can read/write

UNIX allows you to set EUID of an executable to be the file owner rather than the executing user using the **setuid bit**

9

Can you think of another process that users would need to run with the setuid bit?

SETUID BIT



```
smeiklej@nocciola ~ % ls -l /usr/bin/sudo
-r-s--x--x 1 root wheel 460576 10 Aug 2020 /usr/bin/sudo
```

says that executing user
can run with the permissions
of the file owner (euid=root)


Question: When running `passwd`, how do we know **which** user's password can be modified?

Answer: The SUID (Saved User ID)


Question: What if `setuid` has a vulnerability?

10

Sudo is a classic example since this is all about temporarily elevating our privileges. But what if there is a vulnerability in the `setuid` process?



This is a classic example of (unauthorised) elevation of privilege



In summary, for the sake of functionality it is necessary for systems to allow both the (temporary) upgrade and downgrade of privileges

PRIVILEGES

Other architectures (like Windows) have differences but the themes are the same

Pros?

- Simple model provides protection for most situations
- Flexible enough to make most access control policies possible

Cons?


- ACLs are coarse-grained
- Can't differentiate processes run by a single user
- Nearly all systems operations require root access

13

PERMISSIONS

The past (and present!): one mainframe computer with many users

- Still highly relevant in large organisations
- Also the model we follow in platforms like Moodle



The present: many distributed personal devices

- Users need to make more decisions for themselves

14

This approach to permissions works well in a centralised filesystem but breaks down quickly in a more user-oriented computing ecosystem