


Threat Level: **GREEN**

Handler on Duty: [Jim Clausing](#)



## SANS ISC InfoSec Forums



Keyword, Domain, Port, IP or Head

**Search**

[Log In](#) or [Sign Up for Free!](#)

Contact Us

Diary

Podcasts

Jobs

Tools

Data

**FORUMS**

[← Next Thread](#) [Previous Thread →](#)

### ***Analysing meterpreter payload with Ghidra***



Yesterday I found a [powershell](#) script using [urlscan.io](#) which can be found. I didn't (and still don't) have any idea about the origins, being benign or malicious. Spoiler, it is (just) a meterpreter reverse-https payload being delivered using Metasploit's Web Delivery.

Urlscan is a great and powerfull tool to analyse webpages. It delivers reports about how the page loads, creates screenshots, stores interesting files and extracts all kind of indicators. Urls can be scanned manually or by the api. There are many automated

**Remco**



21 POSTS

ISC HANDLER

submissions, like links that have been included in emails or are suspicious. The service helps to find other domains running from the same ip, similar pages and campaigns.


[Searching](#) for 1.ps1 using urlscan delivers all kind of powershell scripts (many malicious), as also the one I found. Just to add some context, I searched for other occurrences of the ip address and file hash delivers, but found just one single result.

The powershell contains a base64 encoded payload which will be executed by starting a new powershell session with the script as argument. Using Cyberchef it is easy to decode the base64 payload as can be [shown](#) here. Multiple of my dear handler colleagues have [written](#) about this useful service already. Cyberchef (runs client side only) makes it easy to create recipes, that will transform the data by just dropping new operations (which are many predefined) to the recipe. This step only base64 decodes the payload, but the next [step](#) deflates the payload also.


Step 2 contains the encoded reverse-https Meterpreter payload that will be loaded and executed in memory. If we now extract the payload and extract it using another [recipe](#) we

have the shellcode and we'll load this into Ghidra. [Ghidra](#) is the Software Reverse Engineering (SRE) suite of tools which are developed (and now opened) by the NSA. Currently the github [repository](#) contains only a placeholder, but it says it will be made available opensource. There has been tweeted a lot about Ghidra and overall reactions are positive. Positive reactions are about the decompiler, the ability for collaborating with colleagues, support for adding multiple binaries to a single project, ability to undo, diffing, many supported processors and the analysis. Negative reactions are that it is based on java, supports no debugging and (steep) learning curve. A more thorough overview can be found in this article of [Joxean Koret](#).


Just to highlight a few features of Ghidra, we'll load the binary. After loading the file we have to pick the language, which is x86 32 bits and the binary can be analysed.



After importing it will show a small summary about the results.



The payload start address (0x0) needs to be disassembled manually, as it doesn't recognise the code. After disassembling the first bytes, the other code will follow and you'll get the this screen. The code can be annotated, functions created, diffed etc.



Ghidra will show the decompiled function next to the assembly view, a sample of decompiled function (the http request and response part) looks like this.

```
undefined4 UndefinedFunction_0000018c(void)
{
    undefined4 uVar1;
    int iVar2;
    int unaff_EBX;
    code *unaff_EBP;
    int iVar3;
    undefined *puStack48;
    int iStack44;
    int iStack40;
    undefined4 uStack16;
    undefined4 uStack8;

    uStack8 = 0xc69f8957;
    iStack40 = (*unaff_EBP)();
    uStack16 = 0x84e03200;
    iStack44 = 0x3b2e55eb;
    puStack48 = (undefined *)0x1a9;
    uVar1 = (*unaff_EBP)();
    iVar3 = 10;
    do {
        puStack48 = (undefined *)0x3380;
        (*unaff_EBP)(0x869e4675,uVar1,0x1f,&puStack48,4);
        iVar2 = (*unaff_EBP)(0x7b18062d,uVar1);
        if (iVar2 != 0) goto allocate_memory;
        (*unaff_EBP)(0xe035f044,5000);
        iVar3 = iVar3 + -1;
    } while (iVar3 != 0);
    do {
        puStack48 = (undefined *)0x1e5;
        exitfunk();
    } while (true);
    allocate_memory:
    unaff_EBX = (*unaff_EBP)(0xe553a458,unaff_EBX,0x400000,0x1000,0x40);
    iStack44 = unaff_EBX;
    iStack40 = unaff_EBX;
    while( true ) {
        puStack48 = (undefined *)&iStack44;
        iVar3 = (*unaff_EBP)(0xe2899612,uVar1,unaff_EBX,0x2000);
        if (iVar3 == 0) break;
        unaff_EBX = unaff_EBX + iStack44;
        if (iStack44 == 0) {
            return 0;
        }
    }
} while( true );
}
```

The payload uses a hashed functions to prevent presence of strings within the payload containing the system functions, which makes it less readable.

After analyses this is just a default Meterpreter payload where a reverse https shell will be opened to a Meterpreter handler.

Meterpreter http(s) handlers will use the default "It works" page we know from Apache, but only a bit different. As the default Apache [index.html](#) contains an extra `\n` (sha256: f2dcc96deec8bca2facba9ad0db55c89f3c4937cd6d2d28e5c4869216ffa81cf and 45 bytes), where [meterpreter](#) doesn't (sha256: 8f3ff2e2482468f3b9315a433b383f0cc0f9eb525889a34d4703b7681330a3fb and 44 bytes). If we search the meterpreter hash for [Censys](#) we'll find over two thousand suspected meterpreter servers. Maybe something to blacklist?

Remco Verhoef ([@remco\\_verhoef](#))  
ISC Handler - Founder of [DutchSec](#)  
[PGP Key](#)

Subscribe

Mar 8th 2019  
6 months ago

Great write-up, thank you for providing!

I think the Censys results show more servers  
however, over 53 thousand if I read correctly.

Quote

**Anonymous**

Mar 8th 2019  
6 months ago

[← Next Thread](#) [Previous Thread →](#)

[Sign Up for Free](#) or [Log In](#) to start participating in the conversation!

[Shop](#) [Link To Us](#) [About Us](#) [Handlers](#) [Privacy Policy](#) [Back To Top](#)

**Developers:** We have an [API](#) for you! 