



EK

Totally not a hacker

Email

Twitter

Github

Linux-Unix-IT Tips and Tricks #4

Different Linux / Unix / IT tips, notes, howto part 4

Other Parts

- [Part 1](#)
- [Part 2](#)
- [Part 3](#)

Who is writing to a mysql replica

```
# if you are using 5.6, you can do it!
# http://dev.mysql.com/doc/en/connection-summary-tables.html
mysql> desc performance_schema.events_statements_summary_by_user_by_event_name;
mysql> select user, event_name, count_star, sum_timer_wait, sum_rows_affected
->   from performance_schema.events_statements_summary_by_user_by_event_name
->   where sum_timer_wait > 0
->   order by user, sum_timer_wait desc;
mysql> select * from sys.user_summary_by_statement_type;
mysql> slave1 [localhost] {msandbox} (sys) > select * from user_summary
mysql> slave1 [localhost] {msandbox} (sys) > SELECT * FROM sys.user_summary
mysql> slave1 [localhost] {msandbox} (sys) > SELECT * FROM performance_
```

Display Mount FS in Nice Layout

CONTENTS

[Other Parts](#)[Who is writing to a mysql replica](#)[Display Mount FS in Nice Layout](#)[FreeBSD version](#)[Linux namespaces implementations](#)[Firewalld in CentOS7/RHEL](#)[Encrypt Linux Home Dir](#)[Moreutils](#)[Send Squid access_log to SIEM](#)[Send HP-UX syslogd to SIEM](#)[FreeBSD Vagrant](#)[LXC CentOS7 Container](#)[Systemd-nspawn CentOS7 Container](#)

```
$ mount | column -t
```

FreeBSD version

```
# to see the version and patch level of the installed kernel:
$ freebsd-version -k
# to see the version and patch level of the installed userland:
$ freebsd-version -u
# to find out if FreeBSD kernel is running in 32bit or 64bit mode:
$ getconf LONG_BIT
```

Linux namespaces implementations

```
# Linux namespaces implementations:
- mnt: mount points and filesystems isolation
- pid: process isolation
- net: network stack isolation (contains its own routes, network device)
- ipc: System V IPC isolation
- uts: hostname isolation
- user: user isolation by means of UIDs

# network namespace
$ ip netns add ns1
$ ip netns
$ ip netns exec ns1 ip link
```

Firewalld in CentOS7/RHEL

Simple Systemd

Manage logging in Systemd

Systemd cgroups

Systemd Targets/Run levels

DebTree – pkg dependency graphs

```
$ systemctl status firewalld
$ firewall-cmd --state
$ firewall-cmd --get-default-zone
$ firewall-cmd --get-active-zones
$ firewall-cmd --zone=public --list-all
$ firewall-cmd --reload
$ firewall-cmd --list-services
$ firewall-cmd --permanent --add-service=ssh
$ firewall-cmd --zone=public --add-port=514/udp
$ firewall-cmd --zone=public --add-forward-port=port=22:proto=tcp:topor
$ firewall-cmd --direct --add-rule ipv4 filter INPUT 0 -p tcp --dport 9
$ firewall-offline-cmd --direct --add-rule ipv4 filter INPUT 0 -p tcp -
$ systemctl disable firewalld
$ systemctl stop firewalld
```

Encrypt Linux Home Dir

```
$ apt-get install ecryptfs-utils
$ sudo ecryptfs-migrate-home -u <login>
# after login
$ ecryptfs-unwrap-passphrase
$ ecryptfs-add-passphrase
# change passpharase
$ ecryptfs-rewrap-passphrase /home/$USER/.ecryptfs/wrapped-passphrase
```

Moreutils

```
chronic - runs a command quietly unless it fails
$ 0 1 * * * chronic backup # instead of backup >/dev/null 2>&1

combine - combine sets of lines from two files using boolean operations
```

```
errno - look up errno names and descriptions
ifdata - get network interface info without parsing ifconfig output
ifne - Run command if the standard input is not empty
$ find . -name core | ifne mail -s "Core files found" root
isutf8 - check whether files are valid UTF-8
```

Send Squid access_log to SIEM

```
# http://wiki.squid-cache.org/Features/LogModules
# /etc/squid/squid.conf
access_log syslog:local6.info

# /etc/rsyslog.conf
local6.info @SIEMIP:514
$ systemctl restart squid.service
```

Send HP-UX syslogd to SIEM

```
# /etc/syslog.conf
*. * @<SIEM_IP>

$ kill -HUP `cat /etc/syslog.pid`
or
$ /sbin/init.d/syslog stop
$ /sbin/init.d/syslog start
```

FreeBSD Vagrant

```
# https://atlas.hashicorp.com/FreeBSD/

# Vagrantfile
Vagrant.configure("2") do |config|
  config.vm.synced_folder ".", "/vagrant", id: "vagrant-root", disabled: true
  config.vm.box = "freebsd/FreeBSD-11.0-CURRENT"
  config.ssh.shell = "sh"
  config.vm.base_mac = "080027D14C66"
end
$ vagrant up

or
$ vagrant init freebsd/FreeBSD-10.2-RELEASE; vagrant up --provider virt
```

LXC CentOS7 Container

```
$ yum -y install libvirt virt-install
$ systemctl start libvirtd

$ yum -y --installroot=/var/lib/libvirt/filesystems/centos7 \
--releasever=7 install systemd passwd yum \
centos-release vim-minimal procps-ng iproute \
net-tools dhclient policycoreutils

$ chroot /var/lib/libvirt/filesystems/centos7/
$ passwd root
$ echo "pts/0" >> /var/lib/libvirt/filesystems/centos7/etc/securetty

$ virt-install --connect lxc:// --name centos7 --ram 256 --filesystem /
Escape character is ^]
$ virsh --connect lxc:// console centos7
```

Systemd-nspawn CentOS7 Container

```
$ yum -y --installroot=/var/lib/libvirt/filesystems/centos7 \
--releasever=7 install systemd passwd yum \
centos-release vim-minimal procps-ng iproute \
net-tools dhclient policycoreutils

$ systemd-nspawn -D /var/lib/libvirt/filesystems/centos7 --machine cent
$ machinectl login centos_container
$ systemctl stop machine-centos_container.scope
```

Simple Systemd

```
# http://rus-linux.net/MyLDE/boot/img/systemd/systemd4_1.png
# get service states
$ systemctl list-unit-files -t service
$ systemctl list-units -t service --all
$ systemctl is-enabled sshd.service; echo $?

# enable service
systemctl enable clamd@scan.service

# systemd analyze speed
$ systemd-analyze blame

# check service depends
systemctl list-dependencies firewalld.service

# reload all daemons
systemctl daemon-reload
```

Manage logging in Systemd

```
# set timedate
$ timedatectl list-timezones
$ timedatectl set-timezone Europe/Moscow
$ timedatectl status

# to watch all logs
$ journalctl

# logs from last boot
$ journalctl -b

# filter logs with datetime
$ journalctl --since "2015-07-20 17:15:00"
$ journalctl --since yesterday
$ journalctl --since 09:00 --until now
$ journalctl --since 10:00 --until "1 hour ago"

# filter logs with service name
$ journalctl -u sshd.service
$ journalctl -u nginx.service --since yesterday
$ journalctl -u nginx.service -u php-fpm.service --since today

# filter logs with process, users or groups name
$ journalctl _PID=1229 (sshd)
$ journalctl _UID=99 (uid=99(nobody) gid=99(nobody) groups=99(nobody))
$ journalctl -F _UID
$ journalctl -F _GUID
$ man systemd.journal-fields

# filter logs with path
$ journalctl /usr/sbin/sshd

# see kernel logs
$ journalctl -k
```

```
# filter logs with error level
$ journalctl -p 3 -b
0 - EMERG
1 - ALERT
2 - CRIT
3 - ERR
4 - WARNING
5 - NOTICE
6 - INFO
7 -DEBUG

# write logs to stdout (default use less)
$ journalctl --no-pager

# write logs with formating
$ journalctl -u sshd.service -o json
$ journalctl -u sshd.service -o json-pretty

# formats:
cat
export
short
short-iso
short-monotonic
short-precise
verbose

# see new logs
$ journalctl -n
$ journalctl -n 20

# see logs in tail mode
$ journalctl -f

# count logs space usage
$ journalctl --disk-usage
```



```
# rotate logs
$ journalctl --vacuum-size=1G
$ journalctl --vacuum-time=1years

# write logs to syslog
# /etc/systemd/journald.conf
ForwardToSyslog=yes
```

Systemd cgroups

```
# To get the full hierarchy of control groups, type:
$ systemd-cgls

# To get the list of control group ordered by CPU, memory and disk I/O
$ systemd-cgtop

# To put resource limits on a service (here 500 CPUShares), type:
$ systemctl set-property httpd.service CPUShares=500
$ systemctl show -p CPUShares httpd.service
$ systemctl show httpd.service | grep CPUShares

# cgroup slices
systemctl status user-${UID}.slice

# For example, if we want to limit cpu.shares of all processes of user
$ systemctl set-property user-1000.slice CPUShares=100
$ systemctl daemon-reload
```

Systemd Targets/Run levels

```
# To get the current default run level, type:
$ systemctl get-default

# To move to maintenance mode, type:
$ systemctl rescue

# To set the default run level to non-graphical mode, type:
$ systemctl set-default multi-user.target

# To set the default run level to graphical mode, type:
$ systemctl set-default graphical.target

# To stop, reboot a server, suspend it or put it into hibernation, type:
$ systemctl poweroff
$ systemctl reboot
$ systemctl suspend
$ systemctl hibernate
```

DebTree – pkg dependency graphs

```
$ apt-get install debtree
$ debtree nginx
# Generate the dependency graph
$ debtree dpkg >dpkg.dot
# generate an SVG image from the '.dot'
$ dot -Tsvg -o dpkg.svg dpkg.dot
# Generate graph for package dpkg as PNG image
$ debtree dpkg | dot -Tpng >dpkg.png
```

Linux-Unix-IT Tips and Tricks #4 was published on August 17, 2015 and last modified on August 17, 2015.

0 Comments

EK BLOG

 Login ▾

 Recommend

 Tweet

 Share

Sort by Best ▾



Start the discussion...

LOG IN WITH

OR SIGN UP WITH DISQUS 



Name

Be the first to comment.

 Subscribe

 Add Disqus

 Disqus' Privacy Policy

DISQUS

YOU MIGHT ALSO ENJOY

(VIEW ALL POSTS)

- [Move from HDD to SSD with ArchLinux](#)
- [Linux SysAdm/DevOps Interview Questions](#)
- [ArchLinux Installation Guide](#)

