

WHISPER-LARGE-V3 GEOTECHNICAL INTELLIGENCE REPORT

SITUATIONAL ASSESSMENT: EXECUTIVE · NDMA / ICS-ALIGNED

Report ID:	DIR-20260917-DARJEELING-5443F	Generated:	2026-09-17 15:07
Target Zone:	Darjeeling Tea Garden Scarps	Audit Window:	Real-Time
Coordinates:	Lat 27.0360° · Lon 88.2627°	Elevation:	563 m
Risk Score:	72 / 100	Risk Level:	HIGH
Primary Threat:	Earthquake / Subsidence	Trend:	Deteriorating
State/Country:	West Bengal, India	AI Model:	WHISPER-LARGE-V3

1. WHISPER-LARGE-V3 INTELLIGENCE SYNTHESIS

The following geotechnical assessment was synthesised in real-time by the Whisper-Large-V3 deterministic AI pipeline, integrating live IoT telemetry, tectonic plate modelling, soil mechanics computation, and multi-hazard risk fusion.

Elevated multi-hazard risk at Lat 27.04, Lon 88.26. Current precipitation (0.0mm), soil saturation (30.2%), and tectonic stress (6.70mGal) combine to create severe geotechnical vulnerabilities.

2. OVERALL RISK SCORECARD

Hazard	Score	Level	Prob. %	Trigger Mechanism	Zone km²
LANDSLIDE	72	HIGH	77%	Sustained rainfall + antecedent soil moisture	5.8
FLOOD	54	MODERATE	57%	Peak hourly rainfall exceeding channel capacity	6.5
EARTHQUAKE	53	MODERATE	55%	Stress accumulation on mapped fault segment	7.9
CYCLONE	13	LOW	13%	Low pressure system intensification	3.9
VOLCANO	3	LOW	3%	Magma chamber overpressure	1.5

Multi-Hazard Severity Profile (0–100 Scale)



3. PER-HAZARD DEEP ANALYSIS & ROOT CAUSE DRIVERS

The following section provides a deterministic root-cause breakdown for each monitored hazard vector, computed from real-time sensor telemetry and Whisper-Large-V3 geophysical synthesis.

■ LANDSLIDE · Landslide

72/100 — HIGH

Contributing Factors:

- Rainfall 0.0mm saturating regolith
- Soil saturation 30.2%
- Factor of safety approaching critical threshold
- Steep slope with poor drainage

Trigger Mechanism: Sustained rainfall + antecedent soil moisture

Event Probability: 77% | **Estimated Evacuation Zone:** 5.8 km²

■ FLOOD · Flash Flood

54/100 — MODERATE

Contributing Factors:

- Surface runoff elevated at 0.0mm rainfall
- Impervious surface accumulation
- River bank stress indicators above normal
- Drainage capacity approaching saturation

Trigger Mechanism: Peak hourly rainfall exceeding channel capacity

Event Probability: 57% | **Estimated Evacuation Zone:** 6.5 km²

■ EARTHQUAKE · Seismic Event

53/100 — MODERATE

Contributing Factors:

- Tectonic stress 6.70mGal above regional baseline
- Fault proximity index elevated
- Lithological amplification factor present
- Recent microseismic cluster detected

Trigger Mechanism: Stress accumulation on mapped fault segment

Event Probability: 55% | **Estimated Evacuation Zone:** 7.9 km²

■ CYCLONE · Cyclone / High Wind

13/100 — LOW

Contributing Factors:

- Bay of Bengal SST anomaly monitoring active
- Pressure gradient within watch zone
- Wind shear indices within cyclogenesis range
- Track model convergence zone

Trigger Mechanism: Low pressure system intensification

Event Probability: 13% | **Estimated Evacuation Zone:** 3.9 km²

Contributing Factors:

- Magmatic SO₂ flux within baseline
- Ground deformation GPS: negligible
- Tremor frequency within normal range
- Thermal anomaly monitoring: nominal

Trigger Mechanism: Magma chamber overpressure

Event Probability: 3% | Estimated Evacuation Zone: 1.5 km²

4. VIRTUAL IoT SENSOR TELEMETRY

Real-time physical measurements ingested from the Virtual Sensor Network. Whisper-derived parameters are computed using deterministic geophysical simulation calibrated to the target GPS coordinates.

Sensor Name	Type	Recorded Value	Unit	Health Status	Data Source
Virtual Rainfall Array	Rainfall	0	mm	ONLINE	WHISPER-SIM
Virtual Seismic Array	Seismic	6.7	mGal	ONLINE	WHISPER-SIM
Virtual Soil Saturation	Soil Moisture	30.2	%	ONLINE	WHISPER-SIM
Virtual Temperature Sensor	Temperature	20	°C	ONLINE	Open-Meteo
Virtual Humidity Sensor	Humidity	65	%	ONLINE	Open-Meteo
Virtual Wind Speed Sensor	Wind Speed	10	km/h	ONLINE	Open-Meteo

5. GEOTECHNICAL ENGINEERING PARAMETERS

Slope stability analysis computed using Whisper-Large-V3 deterministic geomechanics engine. Parameters are derived from real-time pore pressure, lithological data, and tectonic proximity.

Parameter	Value	Parameter	Value
Slope Angle	48.4°	Soil Cohesion	34.4 kPa
Internal Friction Ang.	26.6°	Factor of Safety	0.6
Stability Status	UNSTABLE	Drainage Condition	Moderately drained
Infiltration Rate	32.9 mm/h	Groundwater Depth	9 m
Vegetation Cover	32.3%	Slope Curvature	Concave (accumulation zone)
Lithology	Quaternary alluvium over fractured granite	Slope Aspect	291.9°

6. 7-DAY PROBABILISTIC RISK FORECAST

Multi-day risk outlook computed by the Whisper-Large-V3 forecast module. Scores represent the expected composite hazard severity index for each 24-hour window.

Day	Date	Risk Score	Risk Level	Primary Threat	Confidence %
D+0	2026-09-18	—	MODERATE	—	95%
D+1	2026-09-19	—	MODERATE	—	89%
D+2	2026-09-20	—	MODERATE	—	83%
D+3	2026-09-21	—	LOW	—	77%
D+4	2026-09-22	—	LOW	—	71%
D+5	2026-09-23	—	LOW	—	65%
D+6	2026-09-24	—	LOW	—	59%

7. REMEDIAL MEASURES & TACTICAL RESPONSE PLAYBOOK

Response directives generated by the Whisper-Large-V3 SOP engine, aligned with NDMA Incident Command System (ICS) protocols and WHO/UN disaster preparedness guidelines.

7.1 IMMEDIATE RESPONSE (0–6 HOURS)

- Issue public hazard warnings
- Pre-position emergency response teams
- Activate Emergency Operations Centre (EOC) — Incident Command System Level 3
- Dispatch NDRF / SDRF rapid-response teams to all vulnerable quadrants
- Issue public broadcast alerts via NDMA Common Alerting Protocol
- Temporarily suspend all construction activities on slopes within 2km radius

7.2 SHORT-TERM ACTIONS (6H–7 DAYS)

- Audit structural integrity of bridges and slopes
- Activate early-warning siren network
- Conduct LiDAR-based slope displacement survey across the monitored sector
- Install additional real-time piezometers at soil saturation hotspots
- Review and upgrade drainage infrastructure — inspect all culverts and spillways
- Audit structural integrity of all load-bearing assets within exposure zone

7.3 LONG-TERM STRUCTURAL MEASURES

- Develop micro-zonation maps at 1:5000 scale for all high-risk wards
- Implement slope stabilisation works (soil nailing, retaining walls, bio-engineering)
- Establish permanent GPS + InSAR ground deformation monitoring network
- Update District Disaster Management Plan (DDMP) with revised hazard exposure data
- Commission detailed Probabilistic Seismic Hazard Analysis (PSHA) study
- Introduce land-use zoning bylaws restricting construction on class-III slopes

7.4 EARLY WARNING TRIGGER THRESHOLDS

- Rainfall threshold trigger: >40mm/hr → auto-alert
- Soil saturation trigger: >80% → pre-evacuation advisory
- Seismic trigger: >Mw 3.5 → structural inspection order
- Slope displacement trigger: >15mm/day → mandatory evacuation

8. POPULATION & INFRASTRUCTURE EXPOSURE

Estimated impact radius computed from Whisper-Large-V3 exposure modelling, incorporating risk score, geographic population density, and spatial hazard extent.

Infrastructure Category	Estimated Exposure	Infrastructure Category	Estimated Exposure
Roads Km	90.7	Bridges	7
Villages	32	Schools	4
Hospitals	2	Power Lines Km	45.4
Population At Risk	25920	Agricultural Ha	972
Telecom Towers	3	Water Sources	5

9. DATA PROVENANCE & SOURCE REGISTRY

All data streams ingested, validated, quality-checked, and fused by the Whisper-Large-V3 pipeline to produce this report.

Data Source	Type	Latency	Reliability
Open-Meteo API	Meteorological	15-min	99.2%
USGS Earthquake Catalog	Seismic	5-min	99.8%
IMD Rainfall Network	Hydrology	1-hour	96.4%
ISRO Bhuvan LISS-IV	Satellite Imagery	5-day	94.1%
GSI Geological Survey	Lithology	Annual	98.7%
WHISPER-LARGE-V3	AI Geotechnical Synthesis	Real-time	Deterministic