

NATIONAL DISASTER INTELLIGENCE AGENCY

WHISPER-LARGE-V3 GEOTECHNICAL INTELLIGENCE REPORT

SITUATIONAL ASSESSMENT: EXECUTIVE · NDMA / ICS-ALIGNED

Report ID:	TEST-HEADER-VISIBILITY	Generated:	2026-09-17 15:05
Target Zone:	Wayanad Chooralmala Escarpment	Audit Window:	Real-Time
Coordinates:	Lat 11.6050° · Lon 76.0830°	Elevation:	3459.0 m
Risk Score:	64 / 100	Risk Level:	MODERATE
Primary Threat:	Geotechnical Stress	Trend:	Stable / Watching
State/Country:	Kerala, India	AI Model:	WHISPER-LARGE-V3

1. WHISPER-LARGE-V3 INTELLIGENCE SYNTHESIS


The following geotechnical assessment was synthesised in real-time by the Whisper-Large-V3 deterministic AI pipeline, integrating live IoT telemetry, tectonic plate modelling, soil mechanics computation, and multi-hazard risk fusion.

Moderate environmental stress at Lat 11.61, Lon 76.08. Tectonic readings (4.92mGal) and surface moisture (28.5%) from current rainfall (0.0mm) require continuous automated monitoring.

2. OVERALL RISK SCORECARD

Hazard	Score	Level	Prob. %	Trigger Mechanism	Zone km²
LANDSLIDE	64	MODERATE	69%	Sustained rainfall + antecedent soil moisture	5.1
FLOOD	48	MODERATE	51%	Peak hourly rainfall exceeding channel capacity	5.8
EARTHQUAKE	39	LOW	41%	Stress accumulation on mapped fault segment	5.8
CYCLONE	6	LOW	6%	Low pressure system intensification	1.8
VOLCANO	23	LOW	23%	Magma chamber overpressure	11.5

Multi-Hazard Severity Profile (0–100 Scale)



3. PER-HAZARD DEEP ANALYSIS & ROOT CAUSE DRIVERS

The following section provides a deterministic root-cause breakdown for each monitored hazard vector, computed from real-time sensor telemetry and Whisper-Large-V3 geophysical synthesis.

■ LANDSLIDE · Landslide

64/100 — MODERATE

Contributing Factors:

- Rainfall 0.0mm saturating regolith
- Soil saturation 28.5%
- Factor of safety approaching critical threshold
- Steep slope with poor drainage

Trigger Mechanism: Sustained rainfall + antecedent soil moisture

Event Probability: 69% | **Estimated Evacuation Zone:** 5.1 km²

■ FLOOD · Flash Flood

48/100 — MODERATE

Contributing Factors:

- Surface runoff elevated at 0.0mm rainfall
- Impervious surface accumulation
- River bank stress indicators above normal
- Drainage capacity approaching saturation

Trigger Mechanism: Peak hourly rainfall exceeding channel capacity

Event Probability: 51% | **Estimated Evacuation Zone:** 5.8 km²

■ EARTHQUAKE · Seismic Event

39/100 — LOW

Contributing Factors:

- Tectonic stress 4.92mGal above regional baseline
- Fault proximity index elevated
- Lithological amplification factor present
- Recent microseismic cluster detected

Trigger Mechanism: Stress accumulation on mapped fault segment

Event Probability: 41% | **Estimated Evacuation Zone:** 5.8 km²

■ CYCLONE · Cyclone / High Wind

6/100 — LOW

Contributing Factors:

- Bay of Bengal SST anomaly monitoring active
- Pressure gradient within watch zone
- Wind shear indices within cyclogenesis range
- Track model convergence zone

Trigger Mechanism: Low pressure system intensification

Event Probability: 6% | **Estimated Evacuation Zone:** 1.8 km²

Contributing Factors:

- Magmatic SO₂ flux within baseline
- Ground deformation GPS: negligible
- Tremor frequency within normal range
- Thermal anomaly monitoring: nominal

Trigger Mechanism: Magma chamber overpressure

Event Probability: 23% | Estimated Evacuation Zone: 11.5 km²

4. VIRTUAL IoT SENSOR TELEMETRY

Real-time physical measurements ingested from the Virtual Sensor Network. Whisper-derived parameters are computed using deterministic geophysical simulation calibrated to the target GPS coordinates.

Sensor Name	Type	Recorded Value	Unit	Health Status	Data Source
Virtual Rainfall Array	Rainfall	0.0	mm	ONLINE	WHISPER-SIM
Virtual Seismic Array	Seismic	4.92	mGal	ONLINE	WHISPER-SIM
Virtual Soil Saturation	Soil Moisture	28.5	%	ONLINE	WHISPER-SIM
Virtual Temperature Sensor	Temperature	20.0	°C	ONLINE	Open-Meteo
Virtual Humidity Sensor	Humidity	65.0	%	ONLINE	Open-Meteo
Virtual Wind Speed Sensor	Wind Speed	10.0	km/h	ONLINE	Open-Meteo

5. GEOTECHNICAL ENGINEERING PARAMETERS

Slope stability analysis computed using Whisper-Large-V3 deterministic geomechanics engine. Parameters are derived from real-time pore pressure, lithological data, and tectonic proximity.

Parameter	Value	Parameter	Value
Slope Angle	38.8°	Soil Cohesion	35.0 kPa
Internal Friction Ang.	26.9°	Factor of Safety	0.6
Stability Status	UNSTABLE	Drainage Condition	Moderately drained
Infiltration Rate	33.6 mm/h	Groundwater Depth	9.2 m
Vegetation Cover	46.0%	Slope Curvature	Concave (accumulation zone)
Lithology	Quaternary alluvium over fractured granite	Slope Aspect	216.3°

6. 7-DAY PROBABILISTIC RISK FORECAST

Multi-day risk outlook computed by the Whisper-Large-V3 forecast module. Scores represent the expected composite hazard severity index for each 24-hour window.

Day	Date	Risk Score	Risk Level	Primary Threat	Confidence %
D+0	2026-09-18	—	MODERATE	—	95%
D+1	2026-09-19	—	MODERATE	—	89%
D+2	2026-09-20	—	MODERATE	—	83%
D+3	2026-09-21	—	LOW	—	77%
D+4	2026-09-22	—	LOW	—	71%
D+5	2026-09-23	—	LOW	—	65%
D+6	2026-09-24	—	LOW	—	59%

7. REMEDIAL MEASURES & TACTICAL RESPONSE PLAYBOOK

Response directives generated by the Whisper-Large-V3 SOP engine, aligned with NDMA Incident Command System (ICS) protocols and WHO/UN disaster preparedness guidelines.

7.1 IMMEDIATE RESPONSE (0–6 HOURS)

- Elevate monitoring frequency to 1Hz telemetry
- Activate Emergency Operations Centre (EOC) — Incident Command System Level 3
- Dispatch NDRF / SDRF rapid-response teams to all vulnerable quadrants
- Issue public broadcast alerts via NDMA Common Alerting Protocol
- Temporarily suspend all construction activities on slopes within 2km radius

7.2 SHORT-TERM ACTIONS (6H–7 DAYS)

- Inspect drainage infrastructure
- Review slope hazard maps
- Conduct LiDAR-based slope displacement survey across the monitored sector
- Install additional real-time piezometers at soil saturation hotspots
- Review and upgrade drainage infrastructure — inspect all culverts and spillways
- Audit structural integrity of all load-bearing assets within exposure zone

7.3 LONG-TERM STRUCTURAL MEASURES

- Develop micro-zonation maps at 1:5000 scale for all high-risk wards
- Implement slope stabilisation works (soil nailing, retaining walls, bio-engineering)
- Establish permanent GPS + InSAR ground deformation monitoring network
- Update District Disaster Management Plan (DDMP) with revised hazard exposure data
- Commission detailed Probabilistic Seismic Hazard Analysis (PSHA) study
- Introduce land-use zoning bylaws restricting construction on class-III slopes

7.4 EARLY WARNING TRIGGER THRESHOLDS

- Rainfall threshold trigger: >40mm/hr → auto-alert
- Soil saturation trigger: >80% → pre-evacuation advisory
- Seismic trigger: >Mw 3.5 → structural inspection order
- Slope displacement trigger: >15mm/day → mandatory evacuation

8. POPULATION & INFRASTRUCTURE EXPOSURE

Estimated impact radius computed from Whisper-Large-V3 exposure modelling, incorporating risk score, geographic population density, and spatial hazard extent.

Infrastructure Category	Estimated Exposure	Infrastructure Category	Estimated Exposure
Roads Km	44.8	Bridges	4
Villages	16	Schools	2
Hospitals	1	Power Lines Km	22.4
Population At Risk	12800	Agricultural Ha	480.0
Telecom Towers	2	Water Sources	3

9. DATA PROVENANCE & SOURCE REGISTRY

All data streams ingested, validated, quality-checked, and fused by the Whisper-Large-V3 pipeline to produce this report.

Data Source	Type	Latency	Reliability
Open-Meteo API	Meteorological	15-min	99.2%
USGS Earthquake Catalog	Seismic	5-min	99.8%
IMD Rainfall Network	Hydrology	1-hour	96.4%
ISRO Bhuvan LISS-IV	Satellite Imagery	5-day	94.1%
GSI Geological Survey	Lithology	Annual	98.7%
WHISPER-LARGE-V3	AI Geotechnical Synthesis	Real-time	Deterministic