

## Feature: Application Functional Testing

### # API Test Scenarios

@api

Scenario: Verify Debug Message Logging for Empty gherkinData

Given the application is running and accessible

And I have access to the application logs

When I trigger the application endpoint that processes entities

Then I should see a debug message in the logs indicating "7 entities discovered but gherkinData is empty for all"

@api

Scenario: Functional Test Generation from Java Source

Given access to the Java source code repository with at least one controller method defined

When I use the RoostGPT tool to trigger functional test generation

Then Gherkin files should be generated for each controller method, covering all endpoints

@api

Scenario Outline: Boundary Value Analysis for Endpoint Input Parameters

Given knowledge of the input parameters and their valid ranges for each endpoint

When I send a request to the '<endpoint>' with boundary value '<value>'

Then the response should be '<expected\_response>'

Examples:

| endpoint      | value     | expected_response |  |
|---------------|-----------|-------------------|--|
| /api/resource | min       | Success           |  |
| /api/resource | max       | Success           |  |
| /api/resource | below_min | Error             |  |
| /api/resource | above_max | Error             |  |

@api

Scenario Outline: Data Integrity and Refresh Logic Validation

Given access to the application and knowledge of data refresh triggers

When I trigger data changes in the system

And I access the '<endpoint>' to retrieve data

Then the data should reflect the latest changes and maintain integrity

Examples:

| endpoint     |  |
|--------------|--|
| /api/data    |  |
| /api/refresh |  |

@api

Scenario Outline: Alert Classification and Handling

Given knowledge of alert types and severity levels in the application  
When I trigger an alert of '<severity>' level  
Then the system should classify and handle the alert appropriately

Examples:

|          |
|----------|
| severity |
| low      |
| medium   |
| high     |

# UI Test Scenarios

@ui

Scenario Outline: Role-Based Access and Permissions

Given user accounts with different roles exist in the system

When I log in as a user with the '<role>' role

And I attempt to access the '<feature>' feature

Then access should be '<access>'

Examples:

|         |             |         |
|---------|-------------|---------|
| role    | feature     | access  |
| admin   | dashboard   | granted |
| user    | settings    | denied  |
| manager | reports     | granted |
| guest   | admin_panel | denied  |

@ui

Scenario Outline: State Transition Testing for Workflow Processes

Given knowledge of the workflow processes and their states

When I trigger a state transition from '<current\_state>' to '<next\_state>' through the application interface

Then the system should reflect the new state '<next\_state>'

Examples:

|               |            |
|---------------|------------|
| current_state | next_state |
| draft         | review     |
| review        | approved   |
| approved      | published  |