

Naïve Bayes in Numpy

CS114B Lab 1

Kenneth Lai

January 27, 2022

Goals of PA1

- ▶ You already implemented Naïve Bayes in CS114A

Goals of PA1

- ▶ You already implemented Naïve Bayes in CS114A
- ▶ Goals of PA1:

Goals of PA1

- ▶ You already implemented Naïve Bayes in CS114A
- ▶ Goals of PA1:
 - ▶ Learn about Numpy arrays and operations

Goals of PA1

- ▶ You already implemented Naïve Bayes in CS114A
- ▶ Goals of PA1:
 - ▶ Learn about Numpy arrays and operations
 - ▶ Learn how to represent documents/machine learning inputs in general as vectors

Naïve Bayes

```
function TRAIN NAIVE BAYES(D, C) returns  $\log P(c)$  and  $\log P(w|c)$ 

for each class  $c \in C$            # Calculate  $P(c)$  terms
     $N_{doc}$  = number of documents in D
     $N_c$  = number of documents from D in class c
     $\text{logprior}[c] \leftarrow \log \frac{N_c}{N_{doc}}$ 
     $V \leftarrow$  vocabulary of D
     $\text{bigdoc}[c] \leftarrow$  append(d) for  $d \in D$  with class c
    for each word  $w$  in  $V$            # Calculate  $P(w|c)$  terms
         $\text{count}(w, c) \leftarrow$  # of occurrences of  $w$  in  $\text{bigdoc}[c]$ 
         $\text{loglikelihood}[w, c] \leftarrow \log \frac{\text{count}(w, c) + 1}{\sum_{w' \text{ in } V} (\text{count}(w', c) + 1)}$ 
    return  $\text{logprior}, \text{loglikelihood}, V$ 

function TEST NAIVE BAYES( $\text{testdoc}, \text{logprior}, \text{loglikelihood}, C, V$ ) returns best  $c$ 

for each class  $c \in C$ 
     $\text{sum}[c] \leftarrow \text{logprior}[c]$ 
    for each position  $i$  in  $\text{testdoc}$ 
         $\text{word} \leftarrow \text{testdoc}[i]$ 
        if  $\text{word} \in V$ 
             $\text{sum}[c] \leftarrow \text{sum}[c] + \text{loglikelihood}[\text{word}, c]$ 
    return  $\text{argmax}_c \text{sum}[c]$ 
```

Figure 4.2 The naive Bayes algorithm, using add-1 smoothing. To use add- α smoothing instead, change the +1 to + α for loglikelihood counts in training.

Training Naïve Bayes

- ▶ Follow the pseudo-code/what you did in CS114A

Training Naïve Bayes

- ▶ Follow the pseudo-code/what you did in CS114A
 - ▶ By the end, the Numpy arrays `self.prior` and `self.likelihood` should be filled in

Training Naïve Bayes

- ▶ Follow the pseudo-code/what you did in CS114A
 - ▶ By the end, the Numpy arrays `self.prior` and `self.likelihood` should be filled in
- ▶ Use dictionaries (`self.class_dict` and `self.feature_dict`) to translate between class/feature names and indices

Training Naïve Bayes

- ▶ Follow the pseudo-code/what you did in CS114A
 - ▶ By the end, the Numpy arrays `self.prior` and `self.likelihood` should be filled in
- ▶ Use dictionaries (`self.class_dict` and `self.feature_dict`) to translate between class/feature names and indices
 - ▶ `self.class_dict` is given to you, while you will need to fill in `self.feature_dict` yourself

Training Naïve Bayes

► Training data:

document	class
just plain boring	negative
entirely predictable and lacks energy	negative
no surprises and very few laughs	negative
very powerful	positive
the most fun film of the summer	positive

Training Naïve Bayes

► `self.class_dict = {'neg': 0, 'pos': 1}`

Training Naïve Bayes

- ▶ `self.class_dict = {'neg': 0, 'pos': 1}`
- ▶ `self.feature_dict = {'predictable': 0,
 'no': 1,
 'fun': 2,
 'very': 3
 ::}`

Training Naïve Bayes

► `self.prior =` $\begin{bmatrix} \log(3/5) \\ \log(2/5) \end{bmatrix}$

Training Naïve Bayes

- ▶ `self.prior =` $\begin{bmatrix} \log(3/5) \\ \log(2/5) \end{bmatrix}$
- ▶ `self.likelihood =` $\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix}$

Training Naïve Bayes

- ▶ `self.prior =` $\begin{bmatrix} \log(3/5) \\ \log(2/5) \end{bmatrix}$
- ▶ `self.likelihood =` $\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix}$

Testing Naïve Bayes

- Suppose we observe a movie review $d = \text{"very very fun"}$. Is the review positive or negative?

Testing Naïve Bayes

$$\blacktriangleright c_{NB} = \operatorname{argmax}_{c \in C} \log(P(c)) + \sum_{i=1}^n \log(P(w_i|c))$$

Testing Naïve Bayes

- ▶ $c_{NB} = \operatorname{argmax}_{c \in C} \log(P(c)) + \sum_{i=1}^n \log(P(w_i|c))$
- ▶ Compare:
 - ▶ $\log(P(-)) + \log(P(\text{very}|-)) + \log(P(\text{very}|-)) + \log(P(\text{fun}|-))$
 - ▶ $\log(P(+)) + \log(P(\text{very}|+)) + \log(P(\text{very}|+)) + \log(P(\text{fun}|+))$

Testing Naïve Bayes

- ▶ $c_{NB} = \operatorname{argmax}_{c \in C} \log(P(c)) + \sum_{i=1}^n \log(P(w_i|c))$
- ▶ Compare:
 - ▶ $\log(3/5) + \log(1/17) + \log(1/17) + \log(1/34)$
 - ▶ $\log(2/5) + \log(2/29) + \log(2/29) + \log(2/29)$

Testing Naïve Bayes

► $d = \text{"very very fun"}$

Testing Naïve Bayes

- ▶ $d = \text{"very very fun"}$
- ▶ `self.feature_dict = {'predictable': 0,`
 `'no': 1,`
 `'fun': 2,`
 `'very': 3`
 `::}`

Testing Naïve Bayes

- ▶ $d = \text{"very very fun"}$
- ▶ `self.feature_dict = {'predictable': 0,`
 `'no': 1,`
 `'fun': 2,`
 `'very': 3`
 `::}`
- ▶ Create a feature vector

Testing Naïve Bayes

- ▶ $d = \text{"very very fun"}$
- ▶ `self.feature_dict = {`
 - `'predictable': 0,`
 - `'no': 1,`
 - `'fun': 2,`
 - `'very': 3`
 - `:`
 - `}`
- ▶ Create a feature vector
 - ▶ Features are words, values are counts

Testing Naïve Bayes

- ▶ $d = \text{"very very fun"}$
- ▶ `self.feature_dict = {`
 - `'predictable': 0,`
 - `'no': 1,`
 - `'fun': 2,`
 - `'very': 3`
 - `:`
 - `}`
- ▶ Create a feature vector
 - ▶ Features are words, values are counts

▶ `vector =`
$$\begin{bmatrix} 0 \\ 0 \\ 1 \\ 2 \\ \vdots \end{bmatrix}$$

Testing Naïve Bayes

- ▶ Take the matrix (`numpy.dot`) product of `self.likelihood` and our feature vector

Testing Naïve Bayes

- ▶ Take the matrix (`numpy.dot`) product of `self.likelihood` and our feature vector

- ▶
$$\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix} \cdot \begin{bmatrix} 0 \\ 0 \\ 1 \\ 2 \\ \vdots \end{bmatrix}$$

Testing Naïve Bayes

- ▶ Take the matrix (numpy.dot) product of `self.likelihood` and our feature vector

$$\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix} \cdot \begin{bmatrix} 0 \\ 0 \\ 1 \\ 2 \\ \vdots \end{bmatrix}$$

$$= \begin{bmatrix} 0 \log(1/17) + 0 \log(1/17) + 1 \log(1/34) + 2 \log(1/17) \\ 0 \log(1/29) + 0 \log(1/29) + 1 \log(2/29) + 2 \log(2/29) \end{bmatrix}$$

Testing Naïve Bayes

- ▶ Take the matrix (numpy.dot) product of self.likelihood and our feature vector

$$\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix} \cdot \begin{bmatrix} 0 \\ 0 \\ 1 \\ 2 \\ \vdots \end{bmatrix}$$

$$= \begin{bmatrix} \log(1/34) + 2 \log(1/17) \\ 3 \log(2/29) \end{bmatrix}$$

Testing Naïve Bayes

- ▶ Take the matrix (numpy.dot) product of `self.likelihood` and our feature vector

$$\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix} \cdot \begin{bmatrix} 0 \\ 0 \\ 1 \\ 2 \\ \vdots \end{bmatrix}$$

$$= \begin{bmatrix} \log(1/34) + 2 \log(1/17) \\ 3 \log(2/29) \end{bmatrix}$$

- ▶ This computes the log-likelihood of the document given each class

Testing Naïve Bayes

- ▶ Take the matrix (numpy.dot) product of `self.likelihood` and our feature vector

- ▶
$$\begin{bmatrix} \log(1/17) & \log(1/17) & \log(1/34) & \log(1/17) & \dots \\ \log(1/29) & \log(1/29) & \log(2/29) & \log(2/29) & \dots \end{bmatrix} \cdot \begin{bmatrix} 0 \\ 0 \\ 1 \\ 2 \\ \vdots \end{bmatrix}$$

$$= \begin{bmatrix} \log(1/34) + 2 \log(1/17) \\ 3 \log(2/29) \end{bmatrix}$$

- ▶ This computes the log-likelihood of the document given each class
 - ▶ All we need is `self.prior`

Testing Naïve Bayes

$$\begin{aligned} & \blacktriangleright \begin{bmatrix} \log(3/5) \\ \log(2/5) \end{bmatrix} + \begin{bmatrix} \log(1/34) + 2 \log(1/17) \\ 3 \log(2/29) \end{bmatrix} \\ &= \begin{bmatrix} \log(3/5) + \log(1/34) + 2 \log(1/17) \\ \log(2/5) + 3 \log(2/29) \end{bmatrix} \end{aligned}$$

Testing Naïve Bayes

$$\begin{aligned} &\blacktriangleright \begin{bmatrix} \log(3/5) \\ \log(2/5) \end{bmatrix} + \begin{bmatrix} \log(1/34) + 2 \log(1/17) \\ 3 \log(2/29) \end{bmatrix} \\ &= \begin{bmatrix} \log(3/5) + \log(1/34) + 2 \log(1/17) \\ \log(2/5) + 3 \log(2/29) \end{bmatrix} \end{aligned}$$

- Take the argmax: **positive**