

Contextualized Word Embeddings

CS114B Lab 12

Kenneth Lai

April 28, 2022

Contextualized Word Embeddings

CS114B Lab 12

Kenneth Lai

April 28, 2022



Source 1



Source 2

Contextualized Word Embeddings

CS114B Lab 12

Kenneth Lai

April 28, 2022



Source 1



Source 3

Distributed Representations of Words

- ▶ Representations of (contexts of) words as **embeddings** in some vector space
- ▶ Two approaches to distributed, distributional representations (Baroni et al. 2014):
 - ▶ Count-based
 - ▶ Count occurrences of words in contexts, optionally followed by some mathematical transformation (e.g. tf-idf, PPMI, SVD)
 - ▶ Prediction-based
 - ▶ Given some context vector(s) \mathbf{c} , predict some word \mathbf{x} (or vice versa)
 - ▶ a.k.a. **language modeling**-based

Language Models

- ▶ Given some context vector(s) \mathbf{c} , predict some word \mathbf{x} (or vice versa)
- ▶ Two approaches to language models:
 - ▶ **Generative** models
 - ▶ Model the joint probability distribution $P(\mathbf{x}, \mathbf{c})$
 - ▶ Examples: n-gram language models
 - ▶ Unigram: predict $P(\mathbf{x}_i)$
 - ▶ Bigram: predict $P(\mathbf{x}_i | \mathbf{x}_{i-1})$
 - ▶ Trigram: predict $P(\mathbf{x}_i | \mathbf{x}_{i-2}, \mathbf{x}_{i-1})$

Language Models

- ▶ Given some context vector(s) \mathbf{c} , predict some word \mathbf{x} (or vice versa)
- ▶ Two approaches to language models:
 - ▶ **Discriminative** models
 - ▶ Predict the conditional probability $P(\mathbf{x}|\mathbf{c})$ (or $P(\mathbf{c}|\mathbf{x})$) directly
 - ▶ Examples: neural network language models
 - ▶ Feedforward: word2vec (Mikolov et al. 2013a, 2013b)




- ▶ Recurrent: (Peters et al. 2018)




- ▶ Transformer: (Devlin et al. 2019)

word2vec

- Based on a feedforward neural network language model



CBOW



Skip-gram

- Continuous bag of words (**CBOW**): use context to predict current word
- **Skip-gram**: use current word to predict context

word2vec

- ▶ Input layer: one-hot word vectors
- ▶ Hidden (projection) layer: identity activation function, no bias
 - ▶ Input \rightarrow hidden = table lookup (in weight matrix)
- ▶ Output layer: softmax activation function

word2vec

- ▶ Skip-gram model: for each word, word2vec learns two word embeddings
 - ▶ Target word vector \mathbf{w} (row of \mathbf{W} , = output of hidden layer)
 - ▶ “Context” word vector \mathbf{c} (column of \mathbf{C})

word2vec

- ▶ Skip-gram model: for each word, word2vec learns two word embeddings
 - ▶ Target word vector \mathbf{w} (row of \mathbf{W} , = output of hidden layer)
 - ▶ “Context” word vector \mathbf{c} (column of \mathbf{C})
 - ▶ Note that there is a single context word vector for each word, that is an abstraction over all contexts


word2vec

- ▶ Skip-gram model: for each word, word2vec learns two word embeddings
 - ▶ Target word vector \mathbf{w} (row of \mathbf{W} , = output of hidden layer)
 - ▶ “Context” word vector \mathbf{c} (column of \mathbf{C})
 - ▶ Note that there is a single context word vector for each word, that is an abstraction over all contexts
- ▶ Common final word embeddings
 - ▶ Add $\mathbf{w} + \mathbf{c}$
 - ▶ Just \mathbf{w} (throw away \mathbf{c})

word2vec

- ▶ Skip-gram model: for each word, word2vec learns two word embeddings
 - ▶ Target word vector \mathbf{w} (row of \mathbf{W} , = output of hidden layer)
 - ▶ “Context” word vector \mathbf{c} (column of \mathbf{C})
 - ▶ Note that there is a single context word vector for each word, that is an abstraction over all contexts
- ▶ Common final word embeddings
 - ▶ Add $\mathbf{w} + \mathbf{c}$
 - ▶ Just \mathbf{w} (throw away \mathbf{c})

word embedding



word2vec

- ▶ Two issues with word2vec:

word2vec

- ▶ Two issues with word2vec:
 - ▶ One vector per word type

word2vec

- ▶ Two issues with word2vec:
 - ▶ One vector per word type
 - ▶ Limited (fixed-length) context

Polysemy

- ▶ One vector per word type

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ a **mouse**¹ controlling a computer system in 1968

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ a **mouse**¹ controlling a computer system in 1968
 - ▶ a quiet animal like a **mouse**²

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ a **mouse**¹ controlling a computer system in 1968
 - ▶ a quiet animal like a **mouse**²
- ▶ Should **mouse**¹ and **mouse**² have the same word embedding?

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ a **mouse**¹ controlling a computer system in 1968
 - ▶ a quiet animal like a **mouse**²
- ▶ Should **mouse**¹ and **mouse**² have the same word embedding?
 - ▶ Why not?

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ ... mouse¹ ... computer ...
 - ▶ ... animal ... mouse² ...
- ▶ Should mouse¹ and mouse² have the same word embedding?
 - ▶ Why not?
 - ▶ Syntagmatic association between mouse¹ and computer

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ ... mouse¹ ... computer ...
 - ▶ ... animal ... mouse² ...
- ▶ Should mouse¹ and mouse² have the same word embedding?
 - ▶ Why not?
 - ▶ Syntagmatic association between mouse¹ and computer
 - ▶ Syntagmatic association between mouse² and animal

Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ ... mouse¹ ... computer ...
 - ▶ ... animal ... mouse² ...
- ▶ Should mouse¹ and mouse² have the same word embedding?
 - ▶ Why not?
 - ▶ Syntagmatic association between mouse¹ and computer
 - ▶ Syntagmatic association between mouse² and animal
 - ▶ Paradigmatic association between computer and animal!


Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ ... mouse¹ ... computer ...
 - ▶ ... animal ... mouse² ...
- ▶ Should mouse¹ and mouse² have the same word embedding?
 - ▶ Why not?
 - ▶ Syntagmatic association between mouse¹ and computer
 - ▶ Syntagmatic association between mouse² and animal
 - ▶ Paradigmatic association between computer and animal!
- ▶ How can we distinguish between mouse¹ and mouse²?


Polysemy

- ▶ One vector per word type
- ▶ But words have multiple senses
 - ▶ ... mouse¹ ... computer ...
 - ▶ ... animal ... mouse² ...
- ▶ Should mouse¹ and mouse² have the same word embedding?
 - ▶ Why not?
 - ▶ Syntagmatic association between mouse¹ and computer
 - ▶ Syntagmatic association between mouse² and animal
 - ▶ Paradigmatic association between computer and animal!
- ▶ How can we distinguish between mouse¹ and mouse²?
 - ▶ Context!

Word Embeddings




Word Embeddings




- h is an embedding of x_i only

Word Embeddings




- ▶ h is an embedding of x_i only
 - ▶ How can we embed context information in h ?

Word Embeddings



- ▶ \mathbf{h} is an embedding of \mathbf{x}_i only
 - ▶ How can we embed context information in \mathbf{h} ?

Recurrent Neural Networks



- Neural networks in which the output of a layer in one time step is input to a layer in the next time step

Recurrent Neural Networks

- ▶ RNNs allow for contextualized word embeddings

Recurrent Neural Networks

- ▶ RNNs allow for contextualized word embeddings
 - ▶ Multiple word senses

Recurrent Neural Networks

- ▶ RNNs allow for contextualized word embeddings
 - ▶ Multiple word senses
 - ▶ Arbitrary-length context

Recurrent Neural Networks

- ▶ RNNs allow for **contextualized** word embeddings
 - ▶ Multiple word senses
 - ▶ Arbitrary-length context
- ▶ Is this enough?

Context and Long-Distance Dependencies

- ▶ \mathbf{h}_{i-1} encodes the context $\mathbf{x}_1, \dots, \mathbf{x}_{i-1}$

Context and Long-Distance Dependencies

- ▶ \mathbf{h}_{i-1} encodes the context $\mathbf{x}_1, \dots, \mathbf{x}_{i-1}$
 - ▶ But mostly \mathbf{x}_{i-1} , less \mathbf{x}_{i-2} , even less \mathbf{x}_{i-3}, \dots , very little \mathbf{x}_1

Context and Long-Distance Dependencies

- ▶ \mathbf{h}_{i-1} encodes the context $\mathbf{x}_1, \dots, \mathbf{x}_{i-1}$
 - ▶ But mostly \mathbf{x}_{i-1} , less \mathbf{x}_{i-2} , even less \mathbf{x}_{i-3}, \dots , very little \mathbf{x}_1
- ▶ Context is **local**

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement
- ▶ The flights the airline (was/were) cancelling (was/were) full.

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement
- ▶ The flights the **airline was** cancelling (was/were) full.

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement
- ▶ The flights the **airline was** cancelling (was/were) full.
 - ▶ The context for “**was**” is mostly “**airline**”

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement
- ▶ The **flights** the **airline** **was** cancelling **were** full.
 - ▶ The context for “**was**” is mostly “**airline**”

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement
- ▶ The **flights** the **airline** **was** cancelling **were** full.
 - ▶ The context for “**was**” is mostly “**airline**”
 - ▶ The context for “**were**” is mostly “cancelling”, “**was**”, “**airline**”

Context and Long-Distance Dependencies

- ▶ Example: subject-verb agreement
- ▶ The **flights** the **airline** **was** cancelling **were** full.
 - ▶ The context for “**was**” is mostly “**airline**”
 - ▶ The context for “**were**” is mostly “cancelling”, “**was**”, “**airline**”
 - ▶ Very little “**flights**”

Context and Long-Distance Dependencies

- ▶ Two approaches to handling long-distance dependencies:

Context and Long-Distance Dependencies

- ▶ Two approaches to handling long-distance dependencies:
 - ▶ Memory-based (e.g. long short-term)

Context and Long-Distance Dependencies

- ▶ Two approaches to handling long-distance dependencies:
 - ▶ Memory-based (e.g. long short-term)



- ▶  does this

Context and Long-Distance Dependencies

- ▶ Two approaches to handling long-distance dependencies:
 - ▶ Memory-based (e.g. long short-term)



- ▶ does this
 - ▶ Attention-based

Context and Long-Distance Dependencies

- ▶ Two approaches to handling long-distance dependencies:
 - ▶ Memory-based (e.g. long short-term)



- ▶ does this
- ▶ Attention-based
 - ▶ At each time step, the model explicitly computes which other words to pay attention to

Context and Long-Distance Dependencies

- ▶ Two approaches to handling long-distance dependencies:
 - ▶ Memory-based (e.g. long short-term)



- ▶ does this

- ▶ Attention-based

- ▶ At each time step, the model explicitly computes which other words to pay attention to



- ▶ does this




► Embeddings from Language Models




- ▶ Embeddings from Language Models
- ▶ Based on a bidirectional long short-term memory (LSTM) language model

Long Short-Term Memory




Source

Long Short-Term Memory



Source


Long Short-Term Memory



Source

- Separate memory (cell) state


Long Short-Term Memory



Source

- ▶ Separate memory (cell) state
 - ▶ Reading from and writing to memory controlled by **gates**


Long Short-Term Memory



Source

- ▶ Separate memory (cell) state
 - ▶ Reading from and writing to memory controlled by **gates**
 - ▶ Each gate contains one or two neural network layers


Long Short-Term Memory



Source

- ▶ Separate memory (cell) state
 - ▶ Reading from and writing to memory controlled by **gates**
 - ▶ Each gate contains one or two neural network layers
 - ▶ State **persists** across time


Long Short-Term Memory



Source

- ▶ Separate memory (cell) state
 - ▶ Reading from and writing to memory controlled by **gates**
 - ▶ Each gate contains one or two neural network layers
 - ▶ State **persists** across time
 - ▶ May remember information from long ago


Long Short-Term Memory



Source


- ▶ Separate memory (cell) state
 - ▶ Reading from and writing to memory controlled by **gates**
 - ▶ Each gate contains one or two neural network layers
 - ▶ State **persists** across time
 - ▶ May remember information from long ago
 - ▶ Gradients for memory don't decay with time

Long Short-Term Memory



Source

- ▶ Separate memory (cell) state
 - ▶ Reading from and writing to memory controlled by **gates**
 - ▶ Each gate contains one or two neural network layers
 - ▶ State **persists** across time
 - ▶ May remember information from long ago
 - ▶ Gradients for memory don't decay with time
- ▶ See Christopher Olah's [Understanding LSTM Networks](#) for more details!





- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)




- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)
- ▶ 2 bidirectional LSTM layers



- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)
- ▶ 2 bidirectional LSTM layers
- ▶ Output layer: softmax




- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)
- ▶ 2 bidirectional LSTM layers
- ▶ Output layer: softmax
- ▶ Word embeddings: weighted sum of outputs of input and LSTM layers (task dependent)





Embedding of “stick” in “Let’s stick to” - Step #2

1- Concatenate hidden layers



2- Multiply each vector by a weight based on the task




3- Sum the (now weighted) vectors




ELMo embedding of “stick” for this task in this context

Forward Language Model



Backward Language Model



Source



► Bidirectional Encoder Representations from Transformers



- ▶ Bidirectional Encoder Representations from Transformers
- ▶ Based on a transformer (“attention is all you need”) model

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector
 - ▶ Matrix multiplication

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector
 - ▶ Matrix multiplication
 - ▶ For each word i :

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector
 - ▶ Matrix multiplication
- ▶ For each word i :
 2. Compute the dot product of query q_i with key k_j for each word j

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector
 - ▶ Matrix multiplication
- ▶ For each word i :
 2. Compute the dot product of query q_i with key k_j for each word j
 3. Scale the dot product (e.g. Vaswani et al. (2017) divide by 8)
 - ▶ Leads to more stable gradients

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector
 - ▶ Matrix multiplication
- ▶ For each word i :
 2. Compute the dot product of query q_i with key k_j for each word j
 3. Scale the dot product (e.g. Vaswani et al. (2017) divide by 8)
 - ▶ Leads to more stable gradients
 4. Softmax

Attention

1. Compute **query**, **key**, and **value** vectors for each input vector
 - ▶ Matrix multiplication
- ▶ For each word i :
 2. Compute the dot product of query q_i with key k_j for each word j
 3. Scale the dot product (e.g. Vaswani et al. (2017) divide by 8)
 - ▶ Leads to more stable gradients
 4. Softmax
 5. Compute the weighted sum of values v_j for each word j
 - ▶ Weights = softmax output from previous step

Attention

Input

Embedding

Queries

Keys

Values

Score

Divide by $8 (\sqrt{d_k})$

Softmax


Softmax

X

Value

Sum

Thinking

x_1 

q_1 

k_1 

v_1 

$q_1 \cdot k_1 = 112$

14

0.88

v_1 

z_1 

Machines

x_2 

q_2 


k_2 

v_2 

$q_2 \cdot k_2 = 96$

12

0.12

v_2 

z_2 

Source

Attention

- ▶ Output: weighted sum of value vectors (modulo some more advanced topics)

Attention

- ▶ Output: weighted sum of value vectors (modulo some more advanced topics)
 - ▶ Multi-head attention
 - ▶ Positional encodings
 - ▶ Residual connections
 - ▶ Layer normalization

Attention

- ▶ Output: weighted sum of value vectors (modulo some more advanced topics)
 - ▶ Multi-head attention
 - ▶ Positional encodings
 - ▶ Residual connections
 - ▶ Layer normalization
- ▶ See Jay Alammar's [The Illustrated Transformer](#) for more details!

Transformers

- ▶ “Attention Is All You Need” (Vaswani et al. 2017)

Transformers

- ▶ “Attention Is All You Need” (Vaswani et al. 2017)
- ▶ No recurrence, relies entirely on attention (and feedforward layers) to capture global dependencies

Transformers

- ▶ “Attention Is All You Need” (Vaswani et al. 2017)
- ▶ No recurrence, relies entirely on attention (and feedforward layers) to capture global dependencies
 - ▶ Recurrent neural networks are inherently sequential, processing one word at a time

Transformers

- ▶ “Attention Is All You Need” (Vaswani et al. 2017)
- ▶ No recurrence, relies entirely on attention (and feedforward layers) to capture global dependencies
 - ▶ Recurrent neural networks are inherently sequential, processing one word at a time
 - ▶ Transformers are more parallel, looking at the entire sequence at once

Transformers

- ▶ “Attention Is All You Need” (Vaswani et al. 2017)
- ▶ No recurrence, relies entirely on attention (and feedforward layers) to capture global dependencies
 - ▶ Recurrent neural networks are inherently sequential, processing one word at a time
 - ▶ Transformers are more parallel, looking at the entire sequence at once
 - ▶ More efficient, especially on GPUs

Transformers

- ▶ “Attention Is All You Need” (Vaswani et al. 2017)
- ▶ No recurrence, relies entirely on attention (and feedforward layers) to capture global dependencies
 - ▶ Recurrent neural networks are inherently sequential, processing one word at a time
 - ▶ Transformers are more parallel, looking at the entire sequence at once
 - ▶ More efficient, especially on GPUs
 - ▶ Also scores better on many NLP tasks



- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)




- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)
- ▶ 12-24 encoder layers



- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)
- ▶ 12-24 encoder layers
 - ▶ Encoder layer = (shared) attention layer + (individual) feedforward layers



- ▶ Input layer: pre-trained word vectors (e.g. from word2vec)
- ▶ 12-24 encoder layers
 - ▶ Encoder layer = (shared) attention layer + (individual) feedforward layers





- ▶ Output layer: 2 pre-training tasks



- ▶ Output layer: 2 pre-training tasks
 - ▶ Masked LM (Cloze)



- ▶ Output layer: 2 pre-training tasks
 - ▶ Masked LM (Cloze)
 - ▶ Mask 15% of input tokens at random, predict masked words



- ▶ Output layer: 2 pre-training tasks
 - ▶ Masked LM (Cloze)
 - ▶ Mask 15% of input tokens at random, predict masked words
 - ▶ NSP (Next Sentence Prediction)



- ▶ Output layer: 2 pre-training tasks
 - ▶ Masked LM (Cloze)
 - ▶ Mask 15% of input tokens at random, predict masked words
 - ▶ NSP (Next Sentence Prediction)
 - ▶ Given sentences A and B , does B follow A ?



- ▶ Word embeddings: combinations of outputs of encoder layers



► Word embeddings: combinations of outputs of encoder layers

What is the best contextualized embedding for “Help” in that context?

For named-entity recognition task CoNLL-2003 NER

12

...

7

6

5

4

3

2

1

Help

		Dev F1 Score
First Layer	Embedding	91.0
Last Hidden Layer	12	94.9
Sum All 12 Layers		95.5
Second-to-Last Hidden Layer	11	95.6
Sum Last Four Hidden		95.9
Concat Last Four Hidden		96.1

Source

References

- ▶ Baroni, Marco, Georgiana Dinu, and Germán Kruszewski. “Don’t count, predict! a systematic comparison of context-counting vs. context-predicting semantic vectors.” Proceedings of ACL. 2014.
- ▶ Devlin, Jacob, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. “BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding.” Proceedings of NAACL-HLT. 2019.
- ▶ Mikolov, Tomas, Kai Chen, Greg Corrado, and Jeffrey Dean. “Efficient estimation of word representations in vector space.” Proceedings of ICLR. 2013.
- ▶ Mikolov, Tomas, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. “Distributed representations of words and phrases and their compositionality.” Proceedings of NeurIPS. 2013.
- ▶ Peters, Matthew E., Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. “Deep Contextualized Word Representations.” Proceedings of NAACL-HLT. 2018.
- ▶ Vaswani, Ashish, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. “Attention is all you need.” Proceedings of NeurIPS. 2017.