

760. Find Anagram Mappings (/problems/find-anagram-mappings/)

Jan. 6, 2018 | 21.3K views

Average Rating: 4.31 (16 votes)

Given two lists A and B , and B is an anagram of A . B is an anagram of A means B is made by randomizing the order of the elements in A .

We want to find an *index mapping* P , from A to B . A mapping $P[i] = j$ means the i th element in A appears in B at index j .

These lists A and B may contain duplicates. If there are multiple answers, output any of them.

For example, given

```
A = [12, 28, 46, 32, 50]
B = [50, 12, 32, 46, 28]
```

We should return

```
[1, 4, 3, 2, 0]
```

as $P[0] = 1$ because the 0th element of A appears at $B[1]$, and $P[1] = 4$ because the 1st element of A appears at $B[4]$, and so on.

Note:

1. A , B have equal lengths in range $[1, 100]$.
2. $A[i]$, $B[i]$ are integers in range $[0, 10^5]$.

Approach #1: Hash Table [Accepted]

Intuition

Articles > 760. Find Anagram Mappings ▼

Take the example $A = [12, 28, 46]$, $B = [46, 12, 28]$. We want to know where the 12 occurs in B, say at position 1; then where the 28 occurs in B, which is position 2; then where the 46 occurs in B, which is position 0.

If we had a dictionary (hash table) $D = \{46: 0, 12: 1, 28: 2\}$, then this question could be handled easily.

Algorithm

Create the hash table D as described above. Then, the answer is a list of $D[A[i]]$ for $i = 0, 1,$

...

Java

Python

Copy

```
1 class Solution(object):
2     def anagramMappings(self, A, B):
3         D = {x: i for i, x in enumerate(B)}
4         return [D[x] for x in A]
```

Complexity Analysis

- Time Complexity: $O(N)$, where N is the length of A .
- Space Complexity: $O(N)$.

Analysis written by: @awice (<https://leetcode.com/awice/>).

Rate this article:

Previous (/articles/arithmetic-slices-ii-subsequence/)

Next (/articles/bold-words-in-string/)

Comments: 55

Sort By ▼



Type comment here... (Markdown is supported)  Articles  760. Find Anagram Mappings ▾

 Preview





Post



(/narendrakoli4666)

narendrakoli4666 (narendrakoli4666) ★ 19  January 7, 2019 9:07 AM

I think this approach won't work for duplicates.
If both array contains duplicates values then this approach will fail.

14    Share  Reply

HIDE 3 REPLIES





(/beastcode)

BEastCode (beastcode) ★ 1  May 4, 2019 10:34 AM

@bertbag (<https://leetcode.com/bertbag>) Just want to point out that you can use Map.getDefault instead of an if/else statement to get some cleaner looking code.

You could replace

[Read More](#)

0    Share  Reply



(/ikelber)


ikelber (ikelber) ★ 30  January 8, 2019 3:22 PM

This solution is actually correct because there is no requirement for the indice mappings to be distinct. So every occurrence of an element `e` can map to the same index in `B`.

2    Share  Reply



(/bertbag)




bertbag (bertbag) ★ 10  January 8, 2019 6:31 AM

You are correct.

I did:


```
class Solution {  
    ...  
}
```

[Read More](#)





0    Share  Reply



(/chung_eun)

chung_eun (chung_eun) ★ 10  February 16, 2018 1:02 AM

The solution may not work if A has duplicate items.

10    Share  Reply

SHOW 1 REPLY



jiafang (jiafang) ★ 11 ⌚ February 10, 2018 11:42 PM
 Articles > 760. Find Anagram Mappings ▼

These lists A and B may contain duplicates. If there are multiple answers, output any of them.

(/jiafang)

This description is confusing, or rather wrong.

Depending on the test case:

[20,20]

Read More

9 ^ v | Share | Reply



(/javaman87)

javaman87 (javaman87) ★ 22 ⌚ September 20, 2018 6:47 PM

I'm not sure why so many people are trying to handle the duplicates when the question states that " If there are multiple answers, output any of them" meaning it doesn't matter which value you return so it's not necessary to remove the value from any map or list you put it in.

1 ^ v | Share | Reply

SHOW 4 REPLIES



(/bhaumik10)

bhaumik10 (bhaumik10) ★ 1 ⌚ September 2, 2018 1:56 AM

Alternate solution, to my surprise was accepted and beats 100% of the java solutions.

Time Complexity: $O(N^2)$, where N is the length of A.

Space Complexity: $O(N)$.

```
class Solution {
```

Read More

1 ^ v | Share | Reply

SHOW 3 REPLIES



(/rileymckenna)

rileymckenna (rileymckenna) ★ 3 ⌚ April 18, 2018 12:16 PM

```
public class Solution {
    public int[] AnagramMappings(int[] A, int[] B) {
        int[] p = new int[A.Length];
        for (int i = 0; i < A.Length; i++)
        {
```

Read More

1 ^ v | Share | Reply

SHOW 1 REPLY



(/guixl)

guixl (guixl) ★ 1 April 4, 2018 7:54 PM



Articles > 760. Find Anagram Mappings ▾

Handle duplicates:

```
public int[] anagramMappings(int[] A, int[] B) {
    Map<Integer, Queue> map = new HashMap<>();
    for (int i=0; i<B.length; i++) {
        int b = B[i];
```

Read More

1 ^ v | Share | Reply



(/skandab)

SkandaB (skandab) ★ 85 February 6, 2018 8:29 AM

This solution will print duplicate values in P.

The question is vague, doesn't specify if we can omit indexes where an element is duplicate and consider any of the indexes where the element appears.

Tried to explain in depth in my post

Read More

1 ^ v | Share | Reply



(/restart365)

restart365 (restart365) ★ 1 January 28, 2018 3:31 PM

Anyone have a solution in C? Have problem in malloc

1 ^ v | Share | Reply



(/maggie222)

maggie222 (maggie222) ★ 2 August 30, 2018 1:59 AM

handle duplicates:

Time Complexity: O(N), where NN is the length of A.

Space Complexity: O(N).

```
public int[] anagramMappings(int[] A, int[] B) {
```

Read More

0 ^ v | Share | Reply

SHOW 1 REPLY

< 1 2 3 4 5 6 >