

Printer Configuration Guide EMEA Desktop Portfolio

Revision Date: July 2019

For product sales resources please visit the Partner Portal: https://partnerportal.zebra.com

For further information and list pricing please refer to Solution Builder, accessible from the Portal

For associated barcode supplies refer to the ZipShip and EaziPrice guides accessible from the Portal

Important Note:

The information contained in this Configuration Guide is subject to change at any time in Zebra's sole and absolute discretion and is provided only as a helpful guide related to the subject matter thereof. Furthermore, the information provided in this document may be partially incomplete and / or contain errors, and Zebra Technologies disclaims any and all liability in connection with the use of such information.

©2019 Zebra Technologies Corporation and/or its affiliates. Zebra and the stylized Zebra head are trademarks of Zebra Technologies Corporation, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

Desktop Configuration Guide Changes

July 2019

Added new ZD220 and ZD230 printers

Updated part numbers for ZD4xx Serial and Ethernet upgrade kits

April 2019

First Release

ZD620™ Direct Thermal Desktop Printer



	Description							CONI	FIGURA	TION									
					Media I	Handling		Resolu	ution	Var	iant		Conne	ctivity			Opt	ions	
Model	Part Number	All Direct Thermal ZD620 printers have EPL1 Line Mode, EPL2 and ZPL firmware (SGD, XML, Unicode) and include Power Supply with UK and Euro power cord, and USB cable. All standard configurations include 256MB SDRAM (8MB user available), 512MB Flash (64MB user available), Real-Time Clock (RTC), Bluetooth Low Energy, PrintTouch, Moveable Sensor 1, USB 2.0 and USB Host. All ZD620 printers can be upgraded in the field with the appropriate module or kit to change media handling or print resolution.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Tear-Off	Peel Dispenser	Cutter, Full-Width	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Grey (standard)	Healthcare ² (<i>white</i>)	BTLE, PrintTouch & Real-Time Clock	USB, USB Host	Serial & Ethernet	Wi-Fi & Bluetooth	TCD	Lock	Linerless Tear-Off	Linerless Cutter
	ZD62042-D0EF00EZ	ZD620, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓		✓		✓	~	✓					
	ZD62042-D0EL02EZ	ZD620, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓		✓		✓	✓	~	✓				
	ZD62042-D1EF00EZ	ZD620, 4" Direct Thermal, 203 dpi, Peel Dispense, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104		✓		✓		✓		✓	✓	~					
	ZD62042-D2EF00EZ	ZD620, 4" Direct Thermal, 203 dpi, Cutter, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104			✓	✓		✓		✓	✓	~					
	ZD62142-D0EF00EZ	ZD620 LCD, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓		✓		✓	~	✓		✓			
	ZD62142-D1EF00EZ	ZD620 LCD, 4" Direct Thermal, 203 dpi, Peel Dispense, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓	✓		✓		✓		✓	✓	~		~			
	ZD62142-D0EL02EZ	ZD620 LCD, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓		✓		✓	✓	~	✓	✓			
	ZD62142-D1EL02EZ	ZD620 LCD, 4" Direct Thermal, 203 dpi, Peel Dispense, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104		✓		✓		✓		✓	✓	~	✓	~			
	ZD62142-D2EL02EZ	ZD620 LCD, 4" Direct Thermal, 203 dpi, Cutter, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104			✓	✓		✓		✓	✓	\	✓	✓			
	ZD62043-D0EF00EZ	ZD620, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104	✓				✓	✓		✓	✓	~					
ZD620	ZD62043-D2EF00EZ	ZD620, 4" Direct Thermal, 300 dpi, Cutter, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104	✓		✓		✓	✓		✓	✓	~					
20020	ZD62043-D0EL02EZ	ZD620, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	104	✓				✓	✓		✓	✓	✓	✓				
	ZD62143-D0EF00EZ	ZD620 LCD, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104	✓				✓	✓		✓	✓	~		~			
	ZD62143-D0EL02EZ	ZD620 LCD, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	104	✓				~	✓		✓	✓	\	✓	✓			
	ZD62H42-D0EF00EZ	ZD620 Healthcare LCD, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓			~	✓	✓	~		~			
	ZD62H42-D0EL02EZ	ZD620 Healthcare LCD, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓			✓	✓	✓	✓	✓	✓			
	ZD62H43-D0EF00EZ	ZD620 Healthcare LCD, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104	✓				✓		✓	✓	✓	✓		✓		1	
	ZD62H43-D0EL02EZ	ZD620 Healthcare LCD, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	104	✓				✓		✓	✓	✓	✓	✓	✓			
	ZD62L42-D0EF00EZ	ZD620 Lockable LCD, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓			✓	✓	✓	✓		✓	✓		
	ZD62L42-D0EL02EZ	ZD620 Lockable LCD, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓			✓	✓	✓	✓	✓	✓	✓		
	ZD62L43-D0EF00EZ	ZD620 Lockable LCD, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104	✓				✓		✓	✓	~	✓		✓	✓		
	ZD62L43-D0EL02EZ	ZD620 Lockable LCD, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	104	✓				✓		✓	✓	✓	✓	✓	✓	✓		
	ZD62042-D3EF00EZ	ZD620, 4" Direct Thermal, 203 dpi, Linerless Tear & Present, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	note 3			✓		✓		✓	✓	✓				✓	
	ZD62042-D3EL02EZ	ZD620, 4" Direct Thermal, 203 dpi, Linerless Tear & Present, WLAN & Bluetooth, USB, USB Host, Serial & Ethernet	203 (8)	104	note 3			✓		✓		✓	✓	✓	✓			✓	
ZD620 Linerless	ZD62042-D4EF00EZ	ZD620, 4" Direct Thermal, 203 dpi, Linerless Cut & Present, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104			note 3	✓		✓		✓	✓	✓					✓
ZDOZU LINERIESS	ZD62042-D4EL02EZ	ZD620, 4" Direct Thermal, 203 dpi, Linerless Cut & Present, WLAN & Bluetooth, USB, USB Host, Serial & Ethernet	203 (8)	104			note 3	✓		✓		✓	✓	✓	✓				✓
<u> </u>	ZD62043-D3EF00EZ	ZD620, 4" Direct Thermal, 300 dpi, Linerless Tear & Present, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104	note 3				✓	✓		✓	✓	✓				✓	
	ZD62043-D4EF00EZ	ZD620, 4" Direct Thermal, 300 dpi, Linerless Cut & Present, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	104			note 3		✓	✓		✓	✓	✓					✓

ZD620 Kits - Direct Thermal

	Part Number	Description
Connectivity	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
Media	P1080383-417	Upgrade Kit - Cutter, ZD420/ZD620, Direct Thermal
Handling	P1080383-418	Upgrade Kit - Dispenser, ZD420/ZD620, Direct Thermal
паниння	P1080383-022	Upgrade Kit - Media Core Adaptors, 1.5", 2", 3" (set of 2 each)
Printhead	P1080383-421	Upgrade Kit, Convert 203 dpi to 300 dpi, ZD420/ZD620, Direct Thermal
Conversion	P1080383-422	Upgrade Kit, Convert 300 dpi to 203 dpi, ZD420/ZD620, Direct Thermal
Battery	P1080383-603	ZD-Series Battery Pack
battery	P1080383-601	ZD-Series Battery Power Base for ZD420d/ZD620d
	P1080383-423	Mounting Plate, ZD420/ZD620, Direct Thermal
	P1080383-430	Attached Power Supply, ZD420/ZD620, Direct Thermal
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
Other	P1080383-415	Printhead Assembly, Direct Thermal, 8 dots/mm (203 dpi), ZD420/ZD620
	P1080383-416	Printhead Assembly, Direct Thermal, 12 dots/mm (300 dpi), ZD420/ZD620
	P1080383-413	Platen Kit, Direct Thermal, 8 dots/mm (203 dpi), ZD420/ZD620
	P1080383-414	Platen Kit, Direct Thermal, 12 dots/mm (300 dpi), ZD420/ZD620
	P1080383-424	Shipping Pack, ZD420/ZD620 Direct Thermal

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All Healthcare configurations have a disinfectant and UV-ready housing and IEC 60601-1 power supply.
- 3. Channel available linerless solutions require the use of genuine Zebra Linerless media. Details available upon request.

ZD620 Thermal Transfer Desktop Printer



		Description						CON	IFIGURA	TION						
					Media I	Handling		Reso	lution	Vai	riant		Conne	ctivity		Options
Model	Part Number	All ribbon roll based ZD620 printers have EPL and ZPL firmware (SGD, XML, Unicode) and Thermal Transfer and Direct Thermal print modes. Dual ribbon handling means that ZD620 printers will support 74 or 300 metre ribbon lengths. Printers include Power Supply with UK and Euro power cord, USB cable. All standard configurations include 256MB SDRAM (8MB user available), 512MB Flash (64MB user available), Moveable Sensor 1, USB 2.0 and USB Host. All ZD620 printers can be upgraded in the field with the appropriate module or kit to change media handling or print resolution.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Tear-Off	Peel Dispenser	Cutter, Full-Width	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Grey (standard)	Healthcare ² (<i>white</i>)	BTLE, PrintTouch & Real-Time Clock	USB, USB Host	Serial & Ethernet	Wi-Fi & Bluetooth	ICD
	ZD62042-T0EF00EZ	ZD620, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓		✓		✓	✓	✓		
	ZD62042-T0EL02EZ	ZD620, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓		~		✓	✓	✓	✓	
	ZD62042-T1EF00EZ	ZD620, 4" Thermal Transfer, 203 dpi, Peel Dispense, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104		✓		✓		✓		✓	✓	✓		
	ZD62042-T2EF00EZ	ZD620, 4" Thermal Transfer, 203 dpi, Cutter, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104			✓	✓		✓		✓	✓	✓		
	ZD62043-T0EF00EZ	ZD620, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108	✓				✓	✓		✓	✓	✓		
	ZD62043-T0EL02EZ	ZD620, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	108	✓				✓	✓		✓	✓	✓	✓	
	ZD62043-T1EF00EZ	ZD620, 4" Thermal Transfer, 300 dpi, Peel Dispense, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108		✓			✓	✓		✓	✓	✓		
	ZD62043-T2EF00EZ	ZD620, 4" Thermal Transfer, 300 dpi, Cutter, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108			✓		✓	✓		✓	✓	✓		
	ZD62142-T0EF00EZ	ZD620 LCD, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓		✓		✓	✓	✓		✓
	ZD62142-T0EL02EZ	ZD620 LCD, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓		✓		✓	✓	✓	✓	✓
	ZD62142-T1EF00EZ	ZD620 LCD, 4" Thermal Transfer, 203 dpi, Peel Dispense, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104		✓		✓		✓		✓	✓	✓		✓
ZD620	ZD62142-T1EL02EZ	ZD620 LCD, 4" Thermal Transfer, 203 dpi, Peel Dispense, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104		✓		✓		✓		✓	✓	✓	✓	✓
25020	ZD62142-T2EF00EZ	ZD620 LCD, 4" Thermal Transfer, 203 dpi, Cutter, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104			✓	✓		✓		✓	✓	✓		✓
	ZD62142-T2EL02EZ	ZD620 LCD, 4" Thermal Transfer, 203 dpi, Cutter, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104			✓	✓		✓		✓	✓	✓	✓	✓
	ZD62143-T0EF00EZ	ZD620 LCD, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108	✓				✓	✓		✓	✓	✓		✓
	ZD62143-T0EL02EZ	ZD620 LCD, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	108	✓				✓	✓		✓	✓	✓	✓	✓
	ZD62143-T1EF00EZ	ZD620 LCD, 4" Thermal Transfer, 300 dpi, Peel Dispense, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108		✓			✓	✓		✓	✓	✓		✓
	ZD62143-T1EL02EZ	ZD620 LCD, 4" Thermal Transfer, 300 dpi, Peel Dispense, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	108		✓			✓	✓		✓	✓	✓	✓	✓
	ZD62143-T2EF00EZ	ZD620 LCD, 4" Thermal Transfer, 300 dpi, Cutter, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108			✓		✓	✓		✓	✓	✓		✓
	ZD62143-T2EL02EZ	ZD620 LCD, 4" Thermal Transfer, 300 dpi, Cutter, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	108			✓		✓	✓		✓	✓	✓	✓	✓
	ZD62H42-T0EF00EZ	ZD620 Healthcare LCD, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, Serial & Ethernet	203 (8)	104	✓			✓			✓	✓	✓	✓		✓
	ZD62H42-T0EL02EZ	ZD620 Healthcare LCD, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	203 (8)	104	✓			✓			✓	✓	✓	✓	✓	✓
	ZD62H43-T0EF00EZ	ZD620 Healthcare LCD, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, Serial & Ethernet	152 (6)	108	✓				✓		✓	✓	✓	✓		✓
	ZD62H43-T0EL02EZ	ZD620 Healthcare with LCD, 4" Thermal Transfer, 300 dpi, with BTLE, USB, USB Host, Serial, Ethernet, WLAN & Bluetooth	152 (6)	108	✓				✓		✓	✓	✓	✓	✓	✓

ZD620 Kits - Thermal Transfer

	Part Number	Description
Connectivity	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
Media	P1080383-228	Upgrade Kit - Cutter, ZD620, Thermal Tranfer
Handling	P1080383-018	Upgrade Kit - Dispenser, ZD620, Thermal Transfer
nanuling	P1080383-022	Upgrade Kit - Media Core Adaptors, 1.5', 2", 3" (set of 2 each)
Printhead	P1080383-229	Upgrade Kit, Convert 203 dpi to 300 dpi, ZD420/ZD620, Thermal Transfer
Conversion	P1080383-230	Upgrade Kit, Convert 300 dpi to 203 dpi, ZD420/ZD620, Thermal Transfer
Battery	P1080383-603	ZD-Series Battery Pack
battery	P1080383-600	ZD-Series Battery Power Base for ZD420c/ZD420t/ZD620t
	P1080383-037	Mounting Plate, ZD420/ZD620 Thermal Transfer
	P1080383-234	Attached Power Supply, ZD420/ZD620 Thermal Transfer
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
Other	P1080383-226	Printhead Assembly, Thermal Transfer, 8 dots/mm (203 dpi), ZD420/ZD620
	P1080383-227	Printhead Assembly, Thermal Transfer, 12 dots/mm (300 dpi), ZD420/ZD620
	P1080383-222	Platen Kit, Thermal Transfer, 8 dots/mm (203 dpi), ZD420/ZD620
	P1080383-223	Platen Kit, Thermal Transfer, 12 dots/mm (300 dpi), ZD420/ZD620
	P1080383-232	Shipping Pack, ZD420/ZD620 Thermal Transfer

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All Healthcare configurations have a disinfectant and UV-ready housing and IEC 60601-1 power supply.

ZD500™ Desktop Printer



		Description				CON	IFIGURAT	TION			
					Resolution		Me	dia Hand	lling	Conne	ectivity
Model	Part Number	All ZD500 printers have ZPL firmware (SGD, XML, Unicode), Thermal Transfer and Direct Thermal print modes. All ZD500 printers include Power Supply with UK and Euro power cord, USB cable. All ZD500 standard configurations include 128MB SDRAM (4MB user available), 256MB Flash (56MB user available), Real Time Clock (RTC), Moveable Sensor 1, Serial (DB-9), Centronics Parallel, USB 2.0 and Internal 10/100 Ethernet ports with LCD Display.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Tear	Peel	Cutter	Serial, USB, Parallel & Ethernet	Wi-Fi & Bluetooth ²
	ZD50042-T0E200FZ	ZD500, 203 dpi	152 (6)	104	✓		✓			✓	
	ZD50042-T1E200FZ	ZD500, 203 dpi, Peel	152 (6)	104	✓			✓		✓	
	ZD50042-T2E200FZ	ZD500, 203 dpi, Cutter	152 (6)	104	✓				✓	✓	
	ZD50042-T0EC00FZ	ZD500, 203 dpi, WLAN 802.11a/b/g/n & Bluetooth v3.0 2	152 (6)	104	✓		✓			✓	✓
	ZD50042-T1EC00FZ	ZD500, 203 dpi, WLAN 802.11a/b/g/n & Bluetooth v3.0 2, Peel	152 (6)	104	✓			✓		✓	✓
ZD500	ZD50042-T2EC00FZ	ZD500, 203 dpi, WLAN 802.11a/b/g/n & Bluetooth v3.0 2, Cutter	152 (6)	104	✓				✓	✓	✓
20300	ZD50043-T0E200FZ	ZD500, 300 dpi	102 (4)	104		✓	✓			✓	
	ZD50043-T1E200FZ	ZD500, 300 dpi, Peel	102 (4)	104		\checkmark		✓		\checkmark	
	ZD50043-T2E200FZ	ZD500, 300 dpi, Cutter	102 (4)	104		\checkmark			✓	\checkmark	
	ZD50043-T0EC00FZ	ZD500, 300 dpi, WLAN 802.11a/b/g/n & Bluetooth v3.0 2	102 (4)	104		✓	✓			✓	✓
	ZD50043-T1EC00FZ	ZD500, 300 dpi, WLAN 802.11a/b/g/n & Bluetooth v3.0 2, Peel	102 (4)	104		✓		✓		✓	✓
	ZD50043-T2EC00FZ	ZD500, 300 dpi, WLAN 802.11a/b/g/n & Bluetooth v3.0 2, Cutter	102 (4)	104		\checkmark			✓	\checkmark	✓

ZD500™ Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
Connectivity	105850-006	USB Interface Cable 6' (A to B)
	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
	P1027135-048	Ribbon Core, 4" Thermal Transfer (set of 50)
Other	105934-038	Printhead Assembly, Thermal Transfer, 8 dots/mm (203 dpi)
	105934-039	Printhead Assembly, Thermal Transfer, 12 dots/mm (300 dpi)
	P1027135-040	Platen Kit, Thermal Transfer
	P1061022-021	Shipping Pack, ZD500

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All resolution, media handling and connectivity options are factory install only.

ZD500R™ RFID Desktop Printer & Encoder (UHF)



		Description	CONFIGURATION									
					Reso	lution	Me	dia Hand	lling	Conne	ctivity	
Model	Part Number	All ZD500R printers have ZPL firmware (SGD, XML, Unicode), Thermal Transfer and Direct Thermal print modes. All ZD500R printers include Power Supply with UK and Euro power cord, 3-inch (76mm) core adapters, USB cable. All ZD500R standard configurations include 128MB SDRAM (4MB user available), 256MB Flash (56MB user available), Real Time Clock (RTC), Moveable Sensor ¹ , Serial (DB-9), Centronics Parallel, USB 2.0 and Internal 10/100 Ethernet ports with LCD Display.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Tear	Peel	Cutter	Serial, USB, Parallel & Ethernet	Wi-Fi & Bluetooth	RFID (UHF)
	ZD50042-T0E2R2FZ	ZD500R RFID, 203 dpi	152 (6)	104	✓		✓			✓		✓
	ZD50042-T1E2R2FZ	ZD500R RFID, 203 dpi, Peel	152 (6)	104	✓			✓		✓		✓
	ZD50042-T2E2R2FZ	ZD500R RFID, 203 dpi, Cutter	152 (6)	104	✓				✓	✓		✓
	ZD50042-T0E3R2FZ	ZD500R RFID, 203 dpi, Wi-Fi & Bluetooth	152 (6)	104	✓		✓			✓	✓	✓
	ZD50042-T1E3R2FZ	ZD500R RFID, 203 dpi, Wi-Fi & Bluetooth, Peel	152 (6)	104	✓			✓		✓	✓	✓
ZD500R	ZD50042-T2E3R2FZ	ZD500R RFID, 203 dpi, Wi-Fi & Bluetooth, Cutter	152 (6)	104	✓				✓	✓	✓	✓
2D300K	ZD50043-T0E2R2FZ	ZD500R RFID, 300 dpi	102 (4)	104		✓	✓			✓		✓
	ZD50043-T1E2R2FZ	ZD500R RFID, 300 dpi, Peel	102 (4)	104		✓		✓		✓		✓
	ZD50043-T2E2R2FZ	ZD500R RFID, 300 dpi, Cutter	102 (4)	104		✓			√	√		√
	ZD50043-T0E3R2FZ	ZD500R RFID, 300 dpi, Wi-Fi & Bluetooth	102 (4)	104		✓	✓			✓	✓	✓
	ZD50043-T1E3R2FZ	ZD500R RFID, 300 dpi, Wi-Fi & Bluetooth, Peel	102 (4)	104		✓		✓		✓	✓	✓
	ZD50043-T2E3R2FZ	ZD500R RFID, 300 dpi, Wi-Fi & Bluetooth, Cutter	102 (4)	104		✓			√	√	✓	√

ZD500R™ Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
Connectivity	105850-006	USB Interface Cable 6' (A to B)
	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
Media Handling	P1061022-030	Media Core Adapters, 3", ZD500R (1 set)
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
	P1027135-048	Ribbon Core, 4" Thermal Transfer (set of 50)
Other	105934-038	Printhead Assembly, Thermal Transfer, 8 dots/mm (203 dpi)
	105934-039	Printhead Assembly, Thermal Transfer, 12 dots/mm (300 dpi)
	P1027135-040	Platen Kit, Thermal Transfer
	P1061022-021	Shipping Pack

^{1.} Adjustable full width black mark and multi-position gap sensor.

ZD510-HC Wristband Printer



		Description		CON	IFIGURA	TION	
Model	Part Number	All ZD510-HC printers have ZPL firmware (SGD, XML, Unicode), 12 dots/mm (300 dpi), Direct Thermal. All ZD510-HC printers include a Medical Grade Power Supply (IEC 60601-1) with UK and Euro power cords.	Max. Print Speed ¹ mm/s (ips)	Direct Thermal	Resolution 12 dots/mm (300 dpi)	SDRAM W	Hash Flash
ZD510-HC	ZD51013-D0EE00FZ	ZD510-HC Wristband Printer, USB, USB Host, 10/100 Ethernet, BTLE	102 (4)	✓	√	256MB	512MB
2D310-HC	ZD51013-D0EB02FZ	ZD510-HC Wristband Printer, USB, USB Host, 10/100 Ethernet, WLAN and BT	102 (4)	√	√	256MB	512MB

ZD510-HC Wristband Printer - Kits

Connectivity	Part Number	Description
Connectivity	105850-006	USB Interface Cable 6' (A to B)
	P1100266-003	Printhead Assembly, ZD510-HC, 12 dots/mm (300 dpi)
	P1100266-008	Platen Roller, ZD510-HC
	61332M	Printhead Cleaning Cards, ZD510-HC (Quantity of 10)
	P1007957	Packing Detail Kit, ZD510-HC (Shipping Pack)

ZD420™ Direct Thermal Desktop Printer



		Description						CON	FIGURAT	TION						
		All Direct Thermal ZD620 printers have EPL1 Line Mode, EPL2 and ZPL firmware (SGD, XML,			Media I	Handling		Resol	ution	Var	iant		Conn	ectivity		Option
Model	Part Number	Unicode) and include Power Supply with UK and Euro power cord, and USB cable. All standard configurations include 256MB SDRAM (8MB user available), 512MB Flash (64MB user available), Moveable Sensor ¹ , USB 2.0 and USB Host. All ZD420 printers can be upgraded in the field with the appropriate module or kit to change wired connectivity, media handling or change the resolution.	nt Sp s (ips	Maximum Print Width (mm)	Tear-Off	Peel Dispenser	Cutter, Full-Width	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Grey (standard)	Healthcare ² (<i>white</i>)	BTLE, PrintTouch & Real-Time Clock ³	USB, USB Host	Ethernet	Wi-Fi & Bluetooth	Lock
	ZD42042-D0E000EZ	ZD420, 4" Direct Thermal, 203 dpi, USB & USB Host	152 (6)	104	✓			✓		✓			✓			
	ZD42042-D0EE00EZ	ZD420, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host & Ethernet	152 (6)	104	✓			✓		✓		✓	✓	✓		
	ZD42042-D0EW02EZ	ZD420, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	152 (6)	104	✓			✓		✓		✓	✓		✓	
	ZD42043-D0E000EZ	ZD420, 4" Direct Thermal, 300 dpi, USB & USB Host	102 (4)	104	✓				✓	✓			✓			
	ZD42043-D0EE00EZ	ZD420, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host & Ethernet	102 (4)	104	✓				✓	✓		✓	✓	✓		
	ZD42043-D0EW02EZ	ZD420, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	102 (4)	104	✓				✓	✓		✓	✓		✓	
ZD420	ZD42H42-D0EE00EZ	ZD420 Healthcare, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host & Ethernet	152 (6)	104	✓			✓			✓	✓	✓	✓		
20420	ZD42H42-D0EW02EZ	ZD420 Healthcare, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	152 (6)	104	✓			✓			✓	✓	✓		✓	
	ZD42H43-D0EE00EZ	ZD420 Healthcare, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host & Ethernet	102 (4)	104	✓				✓		✓	✓	✓	✓		
	ZD42H43-D0EW02EZ	ZD420 Healthcare, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	102 (4)	104	✓				✓		✓	✓	✓		✓	
	ZD42L42-D0EE00EZ	ZD420 Lockable, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host & Ethernet	152 (6)	104	✓			✓			✓	✓	✓	✓		✓
	ZD42L42-D0EW02EZ	ZD420 Lockable, 4" Direct Thermal, 203 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	152 (6)	104	✓			✓			✓	✓	✓		✓	✓
	ZD42L43-D0EE00EZ	ZD420 Lockable, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host & Ethernet	102 (4)	104	✓				✓		✓	✓	✓	✓		✓
	ZD42L43-D0EW02EZ	ZD420 Lockable, 4" Direct Thermal, 300 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	102 (4)	104	✓				✓		✓	✓	✓	· ·	✓	✓

ZD420™ Kits - Direct Thermal

	Part Number	Description
	P1080383-442	Upgrade Kit - Ethernet Module, ZD420, Direct Thermal
Connectivity	P1080383-443	Upgrade Kit - Serial Module, ZD420, Direct Thermal
Connectivity	105850-006	USB Interface Cable 6' (A to B)
	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
Media	P1080383-417	Upgrade Kit - Cutter, ZD420/ZD620, Direct Thermal
Handling	P1080383-418	Upgrade Kit - Dispenser, ZD420/ZD620, Direct Thermal
Handing	P1080383-022	Upgrade Kit - Media Core Adaptors, 1.5", 2", 3" (set of 2 each)
Printhead	P1080383-421	Upgrade Kit, Convert 203 dpi to 300 dpi, ZD420/ZD620, Direct Thermal
Conversion	P1080383-422	Upgrade Kit, Convert 300 dpi to 203 dpi, ZD420/ZD620, Direct Thermal
Battery	P1080383-603	ZD-Series Battery Pack
Dattery	P1080383-601	ZD-Series Battery Power Base for ZD420d/ZD620d
	P1080383-423	Mounting Plate, ZD420/ZD620 Direct Thermal
	P1080383-430	Attached Power Supply, ZD420/ZD620 Direct Thermal
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
Other	P1080383-415	Printhead Assembly, Direct Thermal, 8 dots/mm (203 dpi), ZD420/ZD620
	P1080383-416	Printhead Assembly, Direct Thermal, 12 dots/mm (300 dpi), ZD420/ZD620
	P1080383-413	Platen Kit, Direct Thermal, 8 dots/mm (203 dpi), ZD420/ZD620
	P1080383-414	Platen Kit, Direct Thermal, 12 dots/mm (300 dpi), ZD420/ZD620
	P1080383-424	Shipping Pack, ZD420/ZD620 Direct Thermal

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All Healthcare configurations have a disinfectant and UV-ready housing and IEC 60601-1 power supply.
- 3. Base model ZD420 configurations do not include BTLE, PrintTouch (NFC) or Real-Time Clock. These are available in factory installed Network & Dual-Wireless configurations.

ZD420™ Thermal Transfer Desktop Printer



		Description						CON	IFIGURA	TION					
					Media I	Handling		Reso	lution	Var	riant		Conne	ctivity	
Model	Part Number	All ribbon roll based ZD420 printers have EPL and ZPL firmware (SGD, XML, Unicode) and Thermal Transfer and Direct Thermal print modes. Dual ribbon handling means that ZD420 printers will support 74 or 300 metre ribbon lengths. Printers include Power Supply with UK and Euro power cord, USB cable. All standard configurations include 256MB SDRAM (8MB user available), 512MB Flash (64MB user available), Moveable Sensor 1, USB 2.0 and USB Host. All ZD420 printers can be upgraded in the field with the appropriate module or kit to change wired connectivity, media handling or change the resolution.	. =	Maximum Print Width (mm)	Tear-Off	Peel Dispenser	Cutter, Full-Width	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Grey (standard)	Healthcare ² (<i>white</i>)	BTLE, PrintTouch & Real-Time Clock ³	USB, USB Host	Ethernet	Wi-Fi & Bluetooth
	ZD42042-T0E000EZ	ZD420, 4" Thermal Transfer, 203 dpi, USB & USB Host	152 (6)	104	✓			✓		✓			✓		
	ZD42042-T0EE00EZ	ZD420, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host & Ethernet	152 (6)	104	✓			✓		✓		✓	✓	✓	
	ZD42042-T0EW02EZ	ZD420, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	152 (6)	104	✓			✓		✓		✓	✓		✓
	ZD42043-T0E000EZ	ZD420, 4" Thermal Transfer, 300 dpi, USB & USB Host	102 (4)	108	✓				✓	✓			✓		
ZD420	ZD42043-T0EE00EZ	ZD420, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host & Ethernet	102 (4)	108	✓				✓	✓		✓	✓	✓	
20420	ZD42043-T0EW02EZ	ZD420, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	102 (4)	108	✓				✓	✓		✓	✓		✓
	ZD42H42-T0EE00EZ	ZD420 Healthcare, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host & Ethernet	152 (6)	104	✓			✓			✓	✓	✓	✓	
	ZD42H42-T0EW02EZ	ZD420 Healthcare, 4" Thermal Transfer, 203 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	152 (6)	104	✓			√			√	✓	✓	,	√
	ZD42H43-T0EE00EZ	ZD420 Healthcare, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host & Ethernet	102 (4)	108	✓				✓		✓	✓	✓	✓	
	ZD42H43-T0EW02EZ	ZD420 Healthcare, 4" Thermal Transfer, 300 dpi, BTLE, USB, USB Host, WLAN & Bluetooth	102 (4)	108	✓				√		✓	✓	✓		✓

ZD420™ Kits - Thermal Transfer

	Part Number	Description					
	P1080383-442	Upgrade Kit - Ethernet Module, ZD420, Thermal Transfer					
Connectivity	P1080383-443	Upgrade Kit - Serial Module, ZD420, Thermal Transfer					
Connectivity	105850-006	USB Interface Cable 6' (A to B)					
	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)					
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem					
Media	P1080383-228	Upgrade Kit - Cutter, ZD420, Thermal Tranfer					
Handling	P1080383-018 Upgrade Kit - Dispenser, ZD420. Thermal Transfer						
nanuling	P1080383-022	Upgrade Kit - Media Core Adaptors, 1.5', 2", 3" (set of 2 each)					
Printhead	P1080383-229	Upgrade Kit, Convert 203 dpi to 300 dpi, ZD420/ZD620, Thermal Transfer					
Conversion	P1080383-230	Upgrade Kit, Convert 300 dpi to 203 dpi, ZD420/ZD620, Thermal Transfer					
Battery	P1080383-603	ZD-Series Battery Pack					
battery	P1080383-600	ZD-Series Battery Power Base for ZD420c/ZD420t/ZD620t					
	P1080383-037	Mounting Plate, ZD420/ZD620 Thermal Transfer					
	P1080383-234	Attached Power Supply, ZD420/ZD620 Thermal Transfer					
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit					
	105950-035	Printhead Cleaning Pens (set of 12)					
Other	P1080383-226	Printhead Assembly, Thermal Transfer, 8 dots/mm (203 dpi), ZD420/ZD620					
	P1080383-227	Printhead Assembly, Thermal Transfer, 12 dots/mm (300 dpi), ZD420/ZD620					
	P1080383-222	Platen Kit, Thermal Transfer, 8 dots/mm (203 dpi), ZD420/ZD620					
	P1080383-223	Platen Kit, Thermal Transfer, 12 dots/mm (300 dpi), ZD420/ZD620					
	P1080383-232	Shipping Pack, ZD420/ZD620 Thermal Transfer					

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All Healthcare configurations have a disinfectant and UV-ready housing and IEC 60601-1 power supply.
- 3. Base model ZD420 configurations do not include BTLE, PrintTouch (NFC) or Real-Time Clock. These are available in factory installed Network & Dual-Wireless configurations.

ZD420™ Cartridge-based Desktop Printer



		Description					CON	IFIGURAT	ION				
				Media I	Handling	Reso	lution	Var	iant		Conne	ctivity	
Model	Part Number	All Cartridge-based ZD420 printers have EPL and ZPL firmware (SGD, XML, Unicode) and Thermal Transfer and Direct Thermal print modes. All ZD420 printers include Power Supply with UK and Euro power cord, USB cable. All ZD420 standard configurations include 256MB SDRAM (8MB user available), 512MB Flash (64MB user available), Moveable Sensor ¹ , USB 2.0, USB Host. All ZD420 printers can be upgraded in the field to accept Serial or 10/100 Ethernet connectivity modules, and Peel or Cutter media handling modules, or change the printhead resolution.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Tear-Off	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Grey (standard)	Healthcare ² (<i>white</i>)	USB, USB Host & BTLE	USB, USB Host	USB, USB Host, BTLE & Ethernet	USB, USB Host, BTLE, Wi-Fi & Bluetooth
	ZD42042-C0EM00EZ	ZD420, Cartridge, 203 dpi, USB, USB Host and BTLE (last order date 31 May 2019)	152 (6)	104	✓	✓		✓		✓			
	ZD42042-C0E000EZ	ZD420, Cartridge, 203 dpi, USB, USB Host (available from 15 April 2019)	152 (6)	104	✓	✓		✓			✓		
	ZD42042-C0EE00EZ	ZD420, Cartridge, 203 dpi, USB, USB Host, BTLE and 10/100 Ethernet	152 (6)	104	✓	✓		✓				✓	
	ZD42042-C0EW02EZ	ZD420, Cartridge, 203 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	152 (6)	104	✓	✓		✓					✓
	ZD42043-C0EM00EZ	ZD420, Cartridge, 300 dpi, USB, USB Host and BTLE (last order date 31 May 2019)	102 (4)	104	✓		✓	✓		✓			
ZD420	ZD42043-C0E000EZ	ZD420, Cartridge, 300 dpi, USB, USB Host (available from 15 April 2019)	102 (4)	104	✓		✓	✓			✓		
25420	ZD42043-C0EE00EZ	ZD420, Cartridge, 300 dpi, USB, USB Host, BTLE and 10/100 Ethernet	102 (4)	104	✓		✓	✓				✓	
	ZD42043-C0EW02EZ	ZD420, Cartridge, 300 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	102 (4)	104	✓		✓	✓					✓
	ZD42H42-C0EE00EZ	ZD420 Healthcare, Cartridge, 203 dpi, USB, USB Host, BTLE and 10/100 Ethernet	152 (6)	104	✓	✓			√			√	
	ZD42H42-C0EW02EZ	ZD420 Healthcare, Cartridge, 203 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	152 (6)	104	✓	✓			√				✓
	ZD42H43-C0EE00EZ	ZD420 Healthcare, Cartridge, 300 dpi, USB, USB Host, BTLE and 10/100 Ethernet	102 (4)	104	✓		✓		✓			✓	
	ZD42H43-C0EW02EZ	ZD420 Healthcare, Cartridge, 300 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	102 (4)	104	✓		✓		✓				✓

ZD420™ Kits

	Part Number	Description			
	P1080383-442	Upgrade Kit - Ethernet Module			
Connectivity	P1080383-443	Upgrade Kit - Serial Module			
Connectivity	105850-006	USB Interface Cable 6' (A to B)			
	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)			
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem			
Media P1080383-042 Upgrade Kit - Cutter, ZD420 Cartridge-based					
Handling	P1080383-018	Upgrade Kit - Dispenser, ZD420 Cartridge & ZD420/ZD620 Thermal Transfer			
папинія	P1080383-022	Upgrade Kit – Media Core Adaptors, 1.5', 2", 3" (set of 2 each), ZD420 Cartridge & ZD420/ZD620 Thermal Transfer			
Printhead	P1080383-035	Upgrade Kit, Convert 203 dpi to 300 dpi, ZD420 Cartridge			
Conversion	P1080383-036	Upgrade Kit, Convert 300 dpi to 203 dpi, ZD420 Cartridge			
Battery	P1080383-603	ZD-Series Battery Pack			
battery	P1080383-600	ZD-Series Battery Power Base for ZD420c/ZD420t/ZD620t			
	P1080383-037	Mounting Plate			
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit			
	105950-035	Printhead Cleaning Pens (set of 12)			
Other	P1080383-001	Printhead Assembly, Thermal Transfer, 8 dots/mm (203 dpi), ZD420			
Other	P1080383-007	Printhead Assembly, Thermal Transfer, 12 dots/mm (300 dpi), ZD420			
	P1080383-010	Platen Kit, Thermal Transfer, 8 dots/mm (203 dpi), ZD420			
	P1080383-016	Platen Kit, Thermal Transfer, 12 dots/mm (300 dpi), ZD420			
	P1080383-027	Shipping Pack, ZD420			

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All Healthcare configurations have a disinfectant-ready housing and IEC 60601-1 power supply.

GX420d Desktop Printer

		Description				CONFIG	JRATION			
						Conne	ectivity	Me	dia Hand	ling
Model	Part Number	All GX420d printers have EPL and ZPL firmware (SGD, XML, Unicode), Direct Thermal print mode. All GX420d printers include USB cable. All GX420d standard configurations include 8MB SDRAM (3MB user available), 4MB Flash (1.5MB user available), Auto-Sensing ¹ Serial (DB-9), Centronics Parallel and USB v1.1, Power Supply with Euro and UK power cords.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Resolution 8 dots/mm (203 dpi)	Serial, Parallel & USB	Serial, USB & Ethernet	Tear	Peel	Cutter
	GX42-202520-000	GX420d, Serial, Parallel & USB	152 (6)	104	✓	✓		✓		
	GX42-202521-000	GX420d, Serial, Parallel & USB, Peel	152 (6)	104	✓	✓			✓	
GX420d	GX42-202522-000	GX420d, Serial, Parallel & USB, Cutter	152 (6)	104	✓	✓				✓
(Direct Thermal)	GX42-202420-000	GX420d, Serial, USB & 10/100 Ethernet	152 (6)	104	✓		√	✓		
	GX42-202421-000	GX420d, Serial, USB & 10/100 Ethernet, Peel	152 (6)	104	✓		✓		✓	
	GX42-202422-000	GX420d, Serial, USB & 10/100 Ethernet, Cutter	152 (6)	104	✓		√			√

GX420d Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
Commontivity	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	P1031031	External ZebraNet 10/100 Print Server v2 ²
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	13831-002	ZebraDesigner™ Pro v2
	48766-001	ZBI 2.0 Enablement Kit (1 printer)
Other	105950-035	Printhead Cleaning Pens x 12
	105934-037	Printhead Assembly, Direct Thermal 203 dpi
	P1027135-039	Platen Kit, Direct Thermal, GK/GX
	105934-150	Shipping Pack, Direct Thermal

^{1.} Auto-sensing RS-232 Serial (DB-9) will adapt to support both straight and null modem (crossed) cables.

^{2.} Requires Centronics parallel port.

GX420t Desktop Printer

		Description				CONFIG	JRATION			
						Conne	ectivity	Me	dia Hand	ling
Model	Part Number	All GX420t printers have EPL and ZPL firmware (SGD, XML, Unicode), Thermal Transfer and Direct Thermal print modes. All GX420t printers include USB cable. All GX420t standard configurations include 8MB SDRAM (3MB user available), 4MB Flash (1.5MB user available), Auto-Sensing ¹ Serial (DB-9), Centronics Parallel and USB v1.1, Power Supply with Euro and UK power cords.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Resolution 8 dots/mm (203 dpi)	Serial, Parallel & USB	Serial, USB & Ethernet	Tear	Peel	Cutter
	GX42-102520-000	GX420t, Serial, Parallel & USB	152 (6)	104	✓	✓		✓		
	GX42-102521-000	GX420t, Serial, Parallel & USB, Peel	152 (6)	104	✓	✓			✓	
GX420t	GX42-102522-000	GX420t, Serial, Parallel & USB, Cutter	152 (6)	104	✓	✓				√
(Thermal Transfer)	GX42-102420-000	GX420t, Serial, USB & 10/100 Ethernet	152 (6)	104	√		✓	√		
	GX42-102421-000	GX420t, Serial, USB & 10/100 Ethernet, Peel	152 (6)	104	√		√	_	√	
	GX42-102422-000	GX420t, Serial, USB & 10/100 Ethernet, Cutter	152 (6)	104	√		√			√

GX420t Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
Commontivity.	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	P1031031	External ZebraNet 10/100 Print Server v2 ²
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens x 12
Other	105934-038	Printhead Assembly, Thermal Transfer, 203 dpi
Other	P1027135-040	Platen Kit, Thermal Transfer
	105934-051	Shipping Pack, Thermal Transfer
	P1027135-048	Ribbon Core, 4" Thermal Transfer (set of 50)

- 1. Auto-sensing RS-232 Serial (DB-9) will adapt to support both straight and null modem (crossed) cables.
- 2. Requires Centronics parallel port.

GX430t Desktop Printer

	•	Description				CONFIG	JRATION			
						Conne	ectivity	Me	dia Hand	ling
Model	Part Number	All GX430t printers have EPL and ZPL firmware (SGD, XML, Unicode), Thermal Transfer and Direct Thermal print modes. All GX430t printers include USB cable. All GX430t standard configurations include 8MB SDRAM (3MB user available), 4MB Flash (1.5MB user available), Auto-Sensing ¹ Serial (DB-9), Centronics Parallel and USB v1.1, Power Supply with Euro and UK power cords.	ıx. Print Spe mm/s (ips)	Maximum Print Width (mm)	Resolution 12 dots/mm (300 dpi)	Serial, Parallel & USB	Serial, USB & Ethernet	Tear	Peel	Cutter
	GX43-102520-000	GX430t, Serial, Parallel & USB	102 (4)	104	✓	✓		✓		
	GX43-102521-000	GX430t, Serial, Parallel & USB, Peel	102 (4)	104	✓	✓			✓	
GX430t	GX43-102522-000	GX430t, Serial, Parallel & USB, Cutter	102 (4)	104	✓	✓				✓
(Thermal Transfer)	GX43-102420-000	GX430t, Serial, USB & 10/100 Ethernet	102 (4)	104	√		√	✓		
	GX43-102421-000	GX430t, Serial, USB & 10/100 Ethernet, Peel	102 (4)	104	✓		✓		✓	
	GX43-102422-000	GX430t, Serial, USB & 10/100 Ethernet, Cutter	102 (4)	104	✓		✓			√

GX430t Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
Commontivity	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	P1031031	External ZebraNet 10/100 Print Server v2 ²
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens x 12
Other	105934-039	Printhead Assembly, Thermal Transfer, 300 dpi
Other	P1027135-040	Platen Kit, Thermal Transfer
	105934-051	Shipping Pack, Thermal Transfer
	P1027135-048	Ribbon Core, 4" Thermal Transfer (set of 50)

- 1. Auto-sensing RS-232 Serial (DB-9) will adapt to support both straight and null modem (crossed) cables.
- 2. Requires Centronics parallel port.

GK420™ Desktop Printer

	•	Description			CON	IFIGURA	ΓΙΟΝ		
Model	Part Number	All GK420 printers have EPL and ZPL firmware (SGD, XML, Unicode), Direct Thermal and Thermal Transfer print modes. All GK420 printers include USB cable. All GK420 standard configurations include 8MB SDRAM (3MB user available), 4MB Flash (1.5MB user available), Auto-Sensing ¹ Serial (DB-9), Centronics Parallel and USB v1.1, Power Supply with Euro and UK power cords.	rint Speed ۱/s (ips)	Maximum Print Width (mm)	Resolution 8 dots/mm (203 dpi)	Direct Thermal	Thermal Transfer app	Serial, Parallel & USB	Cctivity CSB & Ethernet
CK4304	GK42-202520-000	GK420, Direct Thermal, 203 dpi, Serial, Parallel & USB	127 (5)	104	✓	√		✓	
GK420d	GK42-202220-000	GK420, Direct Thermal, 203 dpi, USB & 10/100 Ethernet	127 (5)	104	✓	✓			✓
GK420t	GK42-102520-000	GK420, Thermal Transfer, 203 dpi, Serial, Parallel & USB	127 (5)	104	√		√	√	
GR420t	GK42-102220-000	GK420, Thermal Transfer, 203 dpi, USB & 10/100 Ethernet	127 (5)	104	√		√		√

GK420™ Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
6	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	P1031031	External ZebraNet 10/100 Print Server v2 ²
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens x 12
	105934-037	Printhead Assembly, Direct Thermal 203 dpi
	105934-038	Printhead Assembly, Thermal Transfer 203 dpi
Other	P1027135-039	Platen Kit, Direct Thermal, GK/GX
	P1027135-040	Platen Kit, Thermal Transfer
	105934-150	Shipping Pack, Direct Thermal
	105934-051	Shipping Pack, Thermal Transfer
	P1027135-048	Ribbon Core, 4" Thermal Transfer (set of 50)

- 1. Auto-sensing RS-232 Serial (DB-9) will adapt to support both straight and null modem (crossed) cables.
- 2. Requires Centronics parallel port.

ZD200 Series Desktop Printer

				CONFIGURATION								
					Media H	landling						
Model	Part Number	Description		Maximum Print Width (mm)	Tear-Off	Peel Dispenser	Cutter	USB	Ethernet	Wi-Fi & Bluetooth		
	ZD22042-D0EG00EZ	ZD220, 4" Direct Thermal, 203 dpi, EZPL, USB	102 (4)	104	✓			✓				
ZD220 ¹	ZD22042-D1EG00EZ	ZD220, 4" Direct Thermal, 203 dpi, EZPL, USB, Dispenser (Peeler)	102 (4)	104		✓		✓				
20220	ZD22042-T0EG00EZ	ZD220, 4" Thermal Transfer, 203 dpi, EZPL, USB	102 (4)	104	✓			✓				
	ZD22042-T1EG00EZ	ZD220, 4" Thermal Transfer, 203 dpi, EZPL, USB, Dispenser (Peeler)	102 (4)	104		✓		✓				
	ZD23042-D0EG00EZ	ZD230, 4" Direct Thermal, 203dpi, EZPL, USB	152 (6)	104	✓			✓				
	ZD23042-D1EG00EZ	ZD230, 4" Direct Thermal, 203dpi, EZPL, USB, Dispenser (Peeler)	152 (6)	104		✓		✓				
	ZD23042-D2EG00EZ	ZD230, 4" Direct Thermal, 203dpi, EZPL, USB, Cutter	152 (6)	104			✓	✓				
	ZD23042-D0EC00EZ	ZD230, 4" Direct Thermal, 203dpi, EZPL, USB, Ethernet	152 (6)	104	✓			✓	✓			
	ZD23042-D0ED02EZ	ZD230, 4" Direct Thermal, 203dpi, EZPL, USB, 802.11ac Wi-Fi, Bluetooth 4.1	152 (6)	104	✓			✓		✓		
ZD230 ¹	ZD23W42-D0EC00EZ	ZD230, 4" Direct Thermal, 203dpi, EZPL, (white version), EZPL, USB, Ethernet	152 (6)	104	✓			✓	✓			
ZD230	ZD23042-30EG00EZ	ZD230, 4" Thermal Transfer (74/300M), 203dpi, EZPL, USB	152 (6)	104	✓			✓				
	ZD23042-31EG00EZ	ZD230, 4" Thermal Transfer (74/300M), 203dpi, EZPL, USB, Dispenser (Peeler)	152 (6)	104		✓		✓				
	ZD23042-32EG00EZ	ZD230, 4" Thermal Transfer (74/300M), 203dpi, EZPL, USB, Cutter	152 (6)	104			✓	✓				
	ZD23042-30EC00EZ	ZD230, 4" Thermal Transfer (74/300M), 203dpi, EZPL, USB, Ethernet	152 (6)	104	✓			✓	✓			
	ZD23042-30ED02EZ	ZD230, 4" Thermal Transfer (74/300M), 203dpi, EZPL, USB, 802.11ac Wi-Fi, Bluetooth 4.1	152 (6)	104	✓			✓		✓		
	ZD23W42-30EC00EZ	ZD230, 4" Thermal Transfer (74/300M), 203dpi, EZPL, (white version), USB, Ethernet	152 (6)	104	✓			✓	✓			

ZD200 Series Kits

	Part Number	Description
	105850-006	USB Interface Cable 6' (A to B)
	P1080383-700	Kit, Platen Roller with bearings, ZD220, ZD230 Direct Thermal
Other	P1080383-701	Kit, Media Adapters for 1.5" diameter cores, 1 set, ZD220, ZD230, Direct Thermal and Thermal Transfer
	P1080383-703	Kit, Platen Roller with bearings, ZD220, ZD230 Thermal Transfer
	P1080383-704	Kit, Power Supply, 60W, 24V (power cord not included), ZD220 & ZD230 Direct Thermal and Thermal Transfer
	105950-035	Printhead Cleaning Pens (set of 12)

^{1.} Not all models are available in all countires

GC420™ Desktop Printer

		Description				CON	IFIGURA	TION			
						Print	Mode			Media I	Handling
Model	Part Number	All GC420 printers have EPL and ZPL firmware (SGD, XML, Unicode), Direct Thermal and Thermal Transfer print modes. Power Supply with UK and Euro power cord included. All GC420 configurations include 8MB SDRAM (2MB user available), 8MB Flash (6MB user available)	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Resolution 8 dots/mm (203 dpi)	Direct Thermal	Thermal Transfer	connectivity: Serial, Parallel & USB	connectivity: USB, Ethernet	Tear	Peel
	GC420-200520-000	GC420, Direct Thermal, 203 dpi, Serial, Parallel & USB	102 (4)	104	√	√		✓		✓	
GC420d	GC420-200420-000	GC420, Direct Thermal, 203 dpi, USB, 10/100 Ethernet	102 (4)	104	✓	✓			✓	✓	
	GC420-200521-000	GC420, Direct Thermal, 203 dpi, Serial, Parallel & USB, Peel	102 (4)	104	✓	✓		✓			✓
	GC420-100520-000	GC420, Thermal Transfer, 203 dpi, Serial, Parallel & USB	102 (4)	104	√		√	√		√	
GC420t	GC420-100420-000	GC420, Thermal Transfer, 203 dpi, USB, 10/100 Ethernet	102 (4)	104	✓	√			✓	✓	
	GC420-100521-000	GC420, Thermal Transfer, 203 dpi, Serial, Parallel & USB, Peel	102 (4)	104	✓		✓	✓			√

GC420™ Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	P1031031	External ZebraNet 10/100 Print Server v2 ¹
Media Handling	105810-003	Media Adpater Guide 4"
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens x 12
	G105910-048	Printhead Assembly, Direct Thermal 203 dpi
Other	G105910-053	Printhead Assembly, Thermal Transfer 203 dpi
Other	105910-001	Platen Kit, GC420d (set of 3)
	105910-055	Platen Kit, GC420t (set of 3)
	105950-050	Shipping Pack
	P1027135-048	Ribbon Core, 4" Thermal Transfer (set of 50)

^{1.} Requires Centronics parallel port.

ZD410™ Desktop Printer



		Description	CONFIGURATION										
				Media H	landling	Reso	lution	Var	iant		Conne	ectivity	
Model	Part Number	All ZD410 printers have EPL and ZPL firmware (SGD, XML, Unicode) and Direct Thermal print mode. All ZD410 printers include Power Supply with UK and Euro power cords, USB cable. All ZD410 standard configurations include 256MB SDRAM (8MB user available), 512MB Flash (64MB user available), Moveable Sensor ¹ , USB 2.0, USB Host. All ZD410 WLAN and Bluetooth configurations include standard configuration features plus dual Wi-Fi certified WLAN (IEEE 802.11ac) and MFi certified Bluetooth v4.1 radios. All ZD410 printers can be upgraded in the field to accept Serial or 10/100 Ethernet connectivity modules, and Peel or Cutter media handling modules.	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Tear-Off	8 dots/mm (203 dpi)	12 dots/mm (300 dpi)	Grey (standard)	Healthcare (<i>white</i>)	USB, USB Host & BTLE	USB, USB Host	USB, USB Host, BTLE & Ethernet	USB, USB Host, BTLE, Wi-Fi & Bluetooth
	ZD41022-D0EM00EZ	ZD410, 2" Direct Thermal, 203 dpi, USB, USB Host and BTLE (last order date 31 May 2019)	152 (6)	56	✓	✓		✓		✓			
	ZD41022-D0E000EZ	ZD410, 2" Direct Thermal, 203 dpi, USB, USB Host (available 15 April 2019)	152 (6)	56	✓	✓		✓			✓		
	ZD41022-D0EE00EZ	ZD410, 2" Direct Thermal, 203 dpi, USB, USB Host, BTLE and 10/100 Ethernet	152 (6)	56	✓	✓		✓				✓	
	ZD41022-D0EW02EZ	ZD410, 2" Direct Thermal, 203 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	152 (6)	56	✓	✓		✓					✓
	ZD41023-D0EM00EZ	ZD410, 2" Direct Thermal, 300 dpi, USB, USB Host and BTLE (last order date 31 May 2019)	102 (4)	56	✓		✓	✓		✓			
ZD410	ZD41023-D0E000EZ	ZD410, 2" Direct Thermal, 300 dpi, USB, USB Host (available 15 April 2019)	102 (4)	56	✓		✓	✓			✓		
25410	ZD41023-D0EE00EZ	ZD410, 2" Direct Thermal, 300 dpi, USB, USB Host, BTLE and 10/100 Ethernet	102 (4)	56	✓		✓	✓				✓	
	ZD41023-D0EW02EZ	ZD410, 2" Direct Thermal, 300 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	102 (4)	56	✓		✓	✓					✓
	ZD41H22-D0EE00EZ	ZD410 Healthcare, 2" Direct Thermal, 203 dpi, USB, USB Host, BTLE and 10/100 Ethernet	152 (6)	56	✓	✓			✓			✓	
	ZD41H22-D0EW02EZ	ZD410 Healthcare, 2" Direct Thermal, 203 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	152 (6)	56	✓	✓			✓				✓
	ZD41H23-D0EE00EZ	ZD410 Healthcare, 2" Direct Thermal, 300 dpi, USB, USB Host, BTLE and 10/100 Ethernet	102 (4)	56	✓		✓		√			√	
	ZD41H23-D0EW02EZ	ZD410 Healthcare, 2" Direct Thermal, 300 dpi, USB, USB Host, BTLE, WLAN (802.11ac) & Bluetooth v4.1	102 (4)	56	✓		✓		√				√

ZD410™ Kits

	Part Number	Description
	P1080383-442	Upgrade Kit - Ethernet Module
Connectivity	P1080383-443	Upgrade Kit - Serial Module
Connectivity	105850-006	USB Interface Cable 6' (A to B)
	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
Media	P1079903-021	Upgrade Kit - Cutter, ZD410
Handling	P1079903-022	Upgrade Kit - Dispenser, ZD410
Hallullig	P1079903-033	Upgrade Kit – Media Core Adaptors, 1.5', 2", 3" (set of 2 each)
Battery	P1080383-603	ZD-Series Battery Pack
Battery	P1080383-602	ZD-Series Battery Power Base for ZD410d
	P1079903-037	Mounting Plate
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
Other	P1079903-010	Printhead Assembly, Direct Thermal, 8 dots/mm (203 dpi), ZD410
	P1079903-011	Printhead Assembly, Direct Thermal, 12 dots/mm (300 dpi), ZD410
	P1079903-003	Platen Kit, Direct Thermal, ZD410
	P1079903-024	Shipping Pack, ZD410

- 1. Adjustable full width black mark and multi-position gap sensor.
- 2. All Healthcare configurations have a disinfectant-ready housing and IEC 60601-1 power supply.

TLP2824 Plus Desktop Printer

		Description		CONFIGURA							
						Med	lia Han	dling	Co	nnecti	vity
Model	Part Number	All TLP2824 Plus printers have EPL and ZPL firmware (SGD, XML, Unicode), Thermal Transfer and Direct Thermal print modes. All TLP2824 Plus standard configurations include 8MB SDRAM (3MB user available), 4MB Flash (1.5MB user available), Power Supply with UK and Euro power cords. Peel and Cutter enabled configuration include Extended Memory; 68MB Flash (65.5 user available), and Real Time Clock (RTC).	Max. Print Speed mm/s (ips)	Maximum Print Width (mm)	Resolution 8 dots/mm (203 dpi)	Tear	Peel, including 68MB Memory & RTC	Cutter, including 68MB Memory & RTC	Serial¹ & USB	Parallel	USB & Ethernet
	282P-101120-000	TLP2824 Plus, Thermal Transfer, Serial & USB	102 (4)	56	✓	✓			✓		
	282P-101121-040	TLP2824 Plus, Thermal Transfer, Serial & USB, Peel, Extended Memory & RTC	102 (4)	56	✓		✓		✓		
	282P-101122-040	TLP2824 Plus, Thermal Transfer, Serial & USB, Cutter, Extended Memory & RTC	102 (4)	56	✓			✓	√		
	282P-101220-000	TLP2824 Plus, Thermal Transfer, Parallel (Centronics)	102 (4)	56	✓	✓				✓	
TLP2824 Plus	282P-101221-040	TLP2824 Plus, Thermal Transfer, Parallel (Centronics), Peel, Extended Memory & RTC	102 (4)	56	✓		✓			\	
	282P-101222-040	TLP2824 Plus, Thermal Transfer, Parallel (Centronics), Cutter, Extended Memory & RTC	102 (4)	56	✓			✓		✓	
	282P-101520-000	TLP2824 Plus, Thermal Transfer, USB & 10/100 Ethernet	102 (4)	56	√	√					√
	282P-101521-040	TLP2824 Plus, Thermal Transfer, USB & 10/100 Ethernet, Peel, Extended Memory & RTC	102 (4)	56	√		✓				√
	282P-101522-040	TLP2824 Plus, Thermal Transfer, USB & 10/100 Ethernet, Cutter, Extended Memory & RTC	102 (4)	56	√			✓			√

TLP2824 Plus Kits

	Part Number	Description
	105850-001	Parallel Interface Cable 6' (Centronics)
Connectivity	105850-006	USB Interface Cable 6' (A to B)
Connectivity	G105850-003	Serial Interface Cable - 6' (DB-9 to DB-9)
	G105950-054	Serial Interface Cable 6' (DB-9 to DB-9) Null Modem
	P1031031	External ZebraNet 10/100 Print Server v2 ²
	ZKDU-001-00	ZKDU, Zebra Keyboard Display Unit
	105950-035	Printhead Cleaning Pens (set of 12)
Other	G105910-148	Printhead Assembly, Thermal Transfer, 8 dots/mm (203 dpi)
Other	105910-150	Platen Kit, Thermal Transfer, TLP2824 Plus
	P1012845-017	Shipping Pack, TLP2824 Plus
	105910-174	Ribbon Core, 2" Thermal Transfer (set of 50)

^{1.} Auto-sensing RS-232 Serial (DB-9) will adapt to support both straight and null modem (crossed) cables.

^{2.} Requires Centronics parallel port.