



ISP MPI Differences Between Hi3516D V300/Hi3516C V500/Hi3516A V300 and Hi3519A V100

Issue	01
Date	2019-09-15

Copyright © HiSilicon (Shanghai) Technologies Co., Ltd. 2019. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of HiSilicon (Shanghai) Technologies Co., Ltd.

Trademarks and Permissions



HISILICON, and other HiSilicon icons are trademarks of HiSilicon Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between HiSilicon and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

HiSilicon (Shanghai) Technologies Co., Ltd.

Address: New R&D Center, 49 Wuhe Road, Bantian,
Longgang District,
Shenzhen 518129 P. R. China

Website: <http://www.hisilicon.com/en/>

Email: support@hisilicon.com



About This Document

Purpose

This document describes the differences between the media processing platform programming interfaces (MPIs) of Hi3516D V300/Hi3516C V500/Hi3516A V300 and Hi3519A V100, including the modified MPIs and new MPIs. With this document, engineers that develop products based on Hi3519A V00 can quickly understand the major differences between Hi3519A V00 and Hi3516D V300/Hi3516C V500/Hi3516A V300, and therefore quickly develop products based on Hi3516D V300/Hi3516C V500/Hi3516A V300.

Related Version

The following table lists the product version related to this document.

Product Name	Version
Hi3516D	V300
Hi3516C	V500
Hi3516A	V300

Intended Audience

This document is intended for:

- Technical support engineers
- Software development engineers

Change History

Changes between document issues are cumulative. Therefore, the latest document issue contains all changes made in previous issues.

Issue 01 (2019-09-15)

This issue is the first official release, which incorporates the following changes:



Section 2.18 is added.

Issue 00B03 (2019-02-15)

This issue is the third draft release, which incorporates the following changes:

The description of Hi3516A V300 is added.

Issue 00B02 (2019-01-15)

This issue is the second draft release, which incorporates the following changes:

Sections 2.5 to 2.17 are modified.

Issue 00B01 (2018-07-15)

This issue is the first draft release.



Contents

About This Document.....	i
1 Overview.....	1
2 Module	2
2.1 Module Ctrl	2
2.2 Mesh Shading.....	2
2.3 Radial Shading	3
2.4 CA	4
2.5 DRC	4
2.6 Bayer NR.....	5
2.7 WDR	5
2.8 DE	6
2.9 Radial Crop	6
2.10 LogLut.....	7
2.11 PreLogLut.....	7
2.12 DIS	8
2.13 AF Statistics	8
2.14 Statistics Config	9
2.15 AE Stitching Statistics	9
2.16 WB Stitching Statistics.....	10
2.17 Pipe Differ	10
2.18 Calc Flicker	11



Tables

Table 2-1 Modified MPI	2
Table 2-2 Data structure with new and unsupported members	2
Table 2-3 Modified MPI	2
Table 2-4 Data structure with new members	3
Table 2-5 Modified MPIs.....	3
Table 2-6 Data structure with unsupported members	3
Table 2-7 Modified MPIs.....	4
Table 2-8 Data structure with unsupported members	4
Table 2-9 Modified MPIs.....	4
Table 2-10 Data structure with unsupported members	5
Table 2-11 Modified MPIs.....	5
Table 2-12 Data structures with new and unsupported members	5
Table 2-13 Modified MPIs.....	5
Table 2-14 Data structure with unsupported members	6
Table 2-15 New MPIs.....	6
Table 2-16 Data structure with new members	6
Table 2-17 Unsupported MPIs.....	6
Table 2-18 Data structure with unsupported members	7
Table 2-19 Unsupported MPIs.....	7
Table 2-20 Data structure with unsupported members	7
Table 2-21 Unsupported MPIs.....	7
Table 2-22 Data structure with unsupported members	8
Table 2-23 Unsupported MPIs.....	8
Table 2-24 Data structure with unsupported members	8
Table 2-25 Modified MPI	8
Table 2-26 Data structure with unsupported members	8



Table 2-27 Modified MPIs.....	9
Table 2-28 Data structure with unsupported members	9
Table 2-29 Unsupported MPI	9
Table 2-30 Data structure with unsupported members	9
Table 2-31 Unsupported MPI	10
Table 2-32 Data structure with unsupported members	10
Table 2-33 Unsupported MPIs.....	10
Table 2-34 Data structure with unsupported members	10
Table 2-35 Modified MPIs.....	11
Table 2-36 Data structure with new members	11



1 Overview

This document describes the differences between the image signal processor (ISP) MPIs of Hi3516D V300/Hi3516CV500/Hi3516A V300 and Hi3519A V100.

The differences are classified into the following types: Adding, deleting, and modifying MPI functions and public data structures. The corresponding differences include but are not limited to the following: MPI functions and data structure members (such as structure, enumeration, and union). This document briefly describes the differences between various subjects and the causes of the differences.



2 Module

2.1 Module Ctrl

Table 2-1 Modified MPI

Modified MPI	Description
HI_MPI_ISP_SetModuleControl	New or unsupported MPI parameters

Table 2-2 Data structure with new and unsupported members

Data Structure with New and Unsupported Members	Description
ISP_MODULE_CTRL_U	New member: bitBypassDE Unsupported members: <ul style="list-style-type: none">• bitBypassRadialShading• bitBypassRadialCrop• bitBypassAFStatFE

2.2 Mesh Shading

Table 2-3 Modified MPI

Modified MPI	Description
HI_MPI_ISP_SetMeshShadingGainLutAttr	The MPI parameters are added.



Table 2-4 Data structure with new members

Data Structure with New Members	Description
ISP_SHADING_LUT_ATTR_S	New member: stBNRLscGainLut

2.3 Radial Shading

Table 2-5 Modified MPIs

Modified MPIs	Description
<ul style="list-style-type: none">HI_MPI_ISP_SetRadialShadingAttrHI_MPI_ISP_GetRadialShadingAttrHI_MPI_ISP_SetRadialShadingLUTHI_MPI_ISP_GetRadialShadingLUT	Radial Shading not supported

Table 2-6 Data structure with unsupported members

Data Structures with Unsupported Members	Description
ISP_RADIAL_SHADING_ATTR_S	Unsupported members: <ul style="list-style-type: none">bEnableu16RadialStr
ISP_RADIAL_SHADING_LUT_ATTR_S	Unsupported members: <ul style="list-style-type: none">enLightModeu16BlendRatiou8LightType1u8LightType2u8RadialScaleu16CenterRXu16CenterRYu16CenterGrXu16CenterGrYu16CenterGbXu16CenterGbYu16CenterBXu16CenterBYu16OffCenterRu16OffCenterGr



Data Structures with Unsupported Members	Description
	<ul style="list-style-type: none">• u16OffCenterGb• u16OffCenterB• astRLscGainLut[3]

2.4 CA

Table 2-7 Modified MPIs

Modified MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetCAAttr• HI_MPI_ISP_GetCAAttr	The CP function is deleted, and parameters related to the CP function cannot be configured.

Table 2-8 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_CA_ATTR_S	Unsupported members: <ul style="list-style-type: none">• eCaCpEn• stCP

2.5 DRC

Table 2-9 Modified MPIs

Modified MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetDRCAAttr• HI_MPI_ISP_GetDRCAAttr	Some DRC parameters cannot be configured.



Table 2-10 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_DRC_ATTR_S	Unsupported members: <ul style="list-style-type: none">• u8FltScaleCoarse• u8FltScaleFine

2.6 Bayer NR

Table 2-11 Modified MPIs

Modified MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetNRAttr• HI_MPI_ISP_GetNRAttr	The MPI parameters are modified.

Table 2-12 Data structures with new and unsupported members

Data Structures with New and Unsupported Members	Description
ISP_NR_ATTR_S	Unsupported members: <ul style="list-style-type: none">• bLowPowerEnable• u8NrLscRatio New members: <ul style="list-style-type: none">• u8BnrLscMaxGain• u16BnrLscCmpStrength
ISP_NR_WDR_ATTR_S	New member: au8FusionFrameStr[4]

2.7 WDR

Table 2-13 Modified MPIs

Modified MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetFSWDRAttr• HI_MPI_ISP_GetFSWDRAttr	The short frame NR function in WDR mode is deleted, and parameters related to the short frame NR function cannot be configured.



Table 2-14 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_WDR_FS_ATTR_S	Unsupported member: stBnr

2.8 DE

Table 2-15 New MPIs

New MPIs	Description
<ul style="list-style-type: none">HI_MPI_ISP_SetDEAttrHI_MPI_ISP_GetDEAttr	New DE MPIs are added.

Table 2-16 Data structure with new members

Data Structure with New Members	Description
ISP_DE_ATTR_S	New members: <ul style="list-style-type: none">bEnableau16LumaGainLut[17]enOpTypestAutostManual

2.9 Radial Crop

Table 2-17 Unsupported MPIs

Unsupported MPIs	Description
<ul style="list-style-type: none">HI_MPI_ISP_SetRcAttrHI_MPI_ISP_GetRcAttr	Radial Crop is not supported.



Table 2-18 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_RC_ATTR_S	Unsupported members: <ul style="list-style-type: none">• bEnable• stCenterCoor• u32Radius

2.10 LogLut

Table 2-19 Unsupported MPIs

Unsupported MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetLogLUTAttr• HI_MPI_ISP_GetLogLUTAttr	LogLut is not supported.

Table 2-20 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_LOGLUT_ATTR_S	Unsupported member: bEnable

2.11 PreLogLut

Table 2-21 Unsupported MPIs

Unsupported MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetPreLogLUTAttr• HI_MPI_ISP_GetPreLogLUTAttr	PreLogLut is not supported.



Table 2-22 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_PRELOGLUT_ATTR_S	Unsupported member: bEnable

2.12 DIS

Table 2-23 Unsupported MPIs

Unsupported MPIs	Description
<ul style="list-style-type: none">HI_MPI_ISP_SetDISAttrHI_MPI_ISP_GetDISAttr	ISP DIS is not supported.

Table 2-24 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_DIS_ATTR_S	Unsupported member: bEnable

2.13 AF Statistics

Table 2-25 Modified MPI

Modified MPI	Description
HI_MPI_ISP_GetFocusStatistics	FE AF statistics cannot be obtained.

Table 2-26 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_AF_STATISTICS_S	Unsupported member: stFEAFStat



2.14 Statistics Config

Table 2-27 Modified MPIs

Modified MPIs	Description
<ul style="list-style-type: none">HI_MPI_ISP_SetStatisticsConfigHI_MPI_ISP_GetStatisticsConfig	Parameters related to the stitching and FE AF cannot be configured.

Table 2-28 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_STATISTICS_CTRL_U	Unsupported members: <ul style="list-style-type: none">bit1FEAeStiGloStatbit1FEAeStiLocStatbit1BEAeStiGloStatbit1BEAeStiLocStatbit1FEAfStat

2.15 AE Stitching Statistics

Table 2-29 Unsupported MPI

Unsupported MPI	Description
ISP_GetAESTitchStatistics	AE stitching statistics cannot be obtained.

Table 2-30 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_AE_STITCH_STATISTICS_S	Unsupported members: <ul style="list-style-type: none">au32FEHist1024Valueau16FEGlobalAvgau16FEZoneAvgau32BEHist1024Valueau16BEGlobalAvgau16BEZoneAvg



2.16 WB Stitching Statistics

Table 2-31 Unsupported MPI

Unsupported MPI	Description
ISP_GetWBStitchStatistics	WB stitching statistics cannot be obtained.

Table 2-32 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_WB_STITCH_STATISTICS_S	Unsupported members: <ul style="list-style-type: none">• u16ZoneRow• u16ZoneCol• au16ZoneAvgR• au16ZoneAvgG• au16ZoneAvgB• au16ZoneCountAll

2.17 Pipe Differ

Table 2-33 Unsupported MPIs

Unsupported MPIs	Description
<ul style="list-style-type: none">• HI_MPI_ISP_SetPipeDifferAttr• HI_MPI_ISP_GetPipeDifferAttr	These MPIs are not supported.

Table 2-34 Data structure with unsupported members

Data Structure with Unsupported Members	Description
ISP_PIPE_DIFF_ATTR_S	Unsupported members: <ul style="list-style-type: none">• as32Offset• au32Gain• au16ColorMatrix



2.18 Calc Flicker

Table 2-35 Modified MPIs

New MPIs	Description
HI_MPI_ISP_CalcFlickerType	This MPI is added.

Table 2-36 Data structure with new members

Data structure with new members	Description
ISP_CALCFLICKER_INPUT_S	New member: u32LinesPerSecond
ISP_CALCFLICKER_OUTPUT_S	New member: enFlickerType