



Anonymous Classes

A short-cut for classes when you want to create
only one object of the class.

Why Anonymous Class?

- Sometimes we define a class just to create only one instance of the class.

Example: a Comparator to sort strings ignoring case

```
Comparator<String> compIgnoreCase  
    = new MyComparator();
```

```
/** Compare strings ignoring case. */
```

```
class MyComparator implements Comparator<String> {  
    public int compare(String a, String b) {  
        return a.compareToIgnoreCase(b);  
    }  
}
```

Anonymous Classes (2)

- Java lets you define the class and create one object from that class **at the same time**.

The class is **anonymous** -- it doesn't have a name.

```
Comparator<String> compIgnoreCase =  
    new Comparator<String>() {  
        A class that implements Comparator  
        public int compare(String a, String b) {  
            return a.compareToIgnoreCase(b);  
        }  
    };
```

```
Collections.sort( list, compIgnoreCase );
```

How to Create Object using an Anonymous Class

- An anonymous class always extends another class or implements an interface.

Name of existing class *to extend*
or an interface *to implement*

Parenthesis after name,
but **no semi-colon**

```
new Interface_Or_SuperClass( )
```

```
{
```

```
class definition
```

```
}
```

class definition inside
of { }

Example: implement interface

Create an object that implements the Comparator interface to compare Strings *by length*.

```
/** Compare strings by length. */
Comparator<String> compByLength =
    new Comparator<String>()
    { /* definition of anonymous class */
        public int Compare(String a, String b) {
            return a.length() - b.length();
        }
    };
Arrays.sort( strings, compByLength );
```

Example: extend a class

Create an object that **extends** `MouseListener` (a class) to override one method for mouse-click events. The other methods are inherited from `MouseListener`.

```
MouseListener click = new MouseAdapter( )  
{  
    public void mouseClicked(MouseEvent event) {  
        int x = event.getX();  
        int y = event.getY();  
        System.out.printf("mouse at (%d,%d)", x, y);  
    }  
};
```

Example: interface with type param.

You can use type parameters in anonymous classes.

Example: a *Comparator* for the Color class.

```
Comparator<Color> comp
    = new Comparator<Color>( )
{
    public int compare(Color c1, Color c2) {
        return c1.getRed() - c2.getRed();
    }
};
```

Rules for Anonymous Classes

May have:

- ▣ instance attributes
- ▣ instance methods

May **not** have:

- ▣ constructor
- ▣ static attributes
- ▣ static methods

This makes sense!

... the class doesn't have a name.

Parameter for Superclass Constructor

You can supply a *parameter* to Anonymous Class.

- parameters are passed to the **superclass constructor**.
- in this case, anonymous class must extend a class.

```
// Anonymous class extends AbstractAction.  
// "ON" is passed to AbstractAction  
// constructor, like using super("ON")  
Action on = new AbstractAction("ON")  
{  
    public void actionPerformed(ActionEvent evt) {  
        //TODO perform "on" action  
    }  
};
```

Rule: accessing outer attributes

An *anonymous class* can access **attributes** from the surrounding object.

```
// message is an attribute
private String message = "Wake Up!";
void wakeUpCall(Long delay) {
    // create a TimerTask that prints a msg
    TimerTask task = new TimerTask()
    {
        public void run( ) {
            System.out.println( message );
        }
    };
    Timer timer = new Timer();
    timer.schedule( task, delay );
}
```

Rule: accessing local variables

An *anonymous class* can access local variables from the surrounding scope **only if they are final**.

```
void wakeUpCall(Long delay) {  
    final String message = "Wake Up!";  
    // create a TimerTask that prints a msg  
    TimerTask task = new TimerTask()  
    {  
        public void run( ) {  
            System.out.println( message );  
        }  
    };  
    Timer timer = new Timer();  
    timer.schedule( task, delay );  
}
```

GUI Code Builders & anonymous class

GUI code builders create anonymous classes and use the object all in one statement (no assignment to a variable).

This is a common example:

```
JButton mybutton = new JButton("Click Here!");  
// define action listener and add it to mybutton  
mybutton.addActionListener(  
    new ActionListener() {  
        public void actionPerformed(ActionEvent e) {  
            textfield.setText(  
                "Ouch! Don't press so hard.");  
        }  
    }  
);
```

JavaFX Example

All UI operations must be done on the Application thread.
For example, if you create and show a stage on an ordinary thread:

```
Stage mystage = new CounterView(counter);  
mystage.show();
```

JavaFX will throw `IllegalStateException`:

This operation is permitted on the event thread only

Start task on Application Thread

A common solution for this is to create a *Runnable* object for your JavaFX code and run it using:

```
Platform.runLater( Runnable task );
```

runLater runs the task on the JavaFX Application thread.

? How do we create a *Runnable* for our CounterView ?

Anonymous Class for Runnable

The code we want to run:

```
Counter counter = new Counter();  
Stage mystage = new CounterView(counter);  
mystage.show();
```

Anonymous class & Platform.runLater(*Runnable*):

```
Counter counter = new Counter();  
Platform.runLater( new Runnable() {  
    public void run() {  
        Stage mystage = new CounterView(counter);  
        mystage.show();  
    }  
} );
```

Lambda for Runnable

The code we want to run:

```
Counter counter = new Counter();  
Stage mystage = new CounterView(counter);  
mystage.show();
```

using a Lambda for Platform.runLater(*Runnable*):

```
Counter counter = new Counter();  
Platform.runLater(  
    () -> {  
        Stage mystage = new CounterView(counter);  
        mystage.show();  
    }  
);
```


Summary

Use anonymous classes to reduce code when...

1. only need to create one object of the class
2. class is short
3. don't need a constructor, no static fields

Guidance:

Assign anonymous object to a variable for readability.

Don't assign-and-use in one statement.

For class with a single method, a Java 8 lambda expression is usually shorter.