

Declaration of Performance

Unique identification code of the product-type: Clay Masonry Unit (Compressed Earth Brick)

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For use in facing and rendered masonry, low-rise load-bearing or non-load-bearing masonry low risk structures, including internal linings and partitions, in accordance with EN 771-1.

Use in unprotected masonry structure

Registered office:

earth4Earth Technology Ltd, 85 Great Portland Street, London, England, W1W 7LT

Attestation of Conformity System 4

Under System 4, the manufacturer is responsible for the determination of product type, factory production control, and testing in accordance with the relevant harmonised technical specification. The notified certification body SGS-CSTC Standards Technical Services Co. Ltd has carried out the product testing and has issued the corresponding UKCA certificate.

Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and tolerance (mm)	215 x 102.5 x 65	BS EN 771-1:2011+A1:2015
Tolerance	T2	BS EN 771-16
Configuration	Solid unit	BS EN 771-1
Declared Dry Density (kg/m ³)	1850	BS EN 771-13
Flatness of bed faces, maximum deviation (mm)	0.15	BS EN 771-20
Plane parallelism, maximum deviation (mm)	0.57	BS EN 771-16
Declared Compressive strength (MPa)	10	BS EN 771-1:2011
Range Category	R2	BS EN 771-1
Flexural strength (N/mm ²)	0.2	BS EN 771-1
Bond strength fixed (N/mm ²)	0.15	BS EN 998-2:2010
Active soluble salts	S2	BS EN 771-1
Reaction to fire	A1	EN 13501-1
Water absorption (%)	≤ 16%	BS EN 771-1
Water vapour permeability kg/(s·m·Pa)	1.19E-11	BS EN ISO 12572
Initial rate of water absorption kg/(m ² ·min)	1.54	EN 771-1
Thermal conductivity (λ _{10,dry}) W/mK	0.9	EN 1745
Durability against freeze-thaw	F1 (50)	BS EN 771-1
Specific heat capacity J/(g·K)	0.8392 J/(g·K)	BS EN 1745-2020
Elastic modulus MPa	1531	ASTM C469/C469M - 22
Dangerous substances	fully recyclable	2003/33/EC

The performance of the product identified above is in conformity with the declared performance.

This declaration of performance is issued, in accordance with the Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit), Regulations 2019 and Construction Products (Amendment etc.) (EU Exit), Regulations 2020 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Lei Zhang

Position: Director and R&D Manager

Place and date of issue: 07/2025

Signature: 