

浙江大学 2014 - 2015 学年冬季学期

《程序设计基础》课程期末考试试卷

课程号: 211Z0040, 开课学院: 计算机学院

考试试卷: ☒ A 卷、B 卷 (请在选定项上打 ☒)

考试形式: ☒ 闭、开卷 (请在选定项上打 ☒) , 允许带 / 入场

考试日期: 2015 年 01 月 28 日, 考试时间: 120 分钟

诚信考试, 沉着应考, 杜绝违纪.

考生姓名: _____ 学号: _____ 所属院系: _____

(注意: 答题内容必须写在答题卷上, 写在本试题卷上无效)

Section 1: Single Choice(2 marks for each item, total 20 marks)

- Which one below is **NOT** a valid identifier in the C programming language? _____.
A. printf B. _ever C. "char" D. true
- Given **a**, **b** and **c** as three double variables, which one below is **NOT** equivalent to **a/b/c**? _____.
A. (a/b)/c B. a/(b/c) C. a/(b*c) D. a/c/b
- Which function header is **NOT** correct? _____.
A. void f(void) B. void f(int i) C. void f(int i,j) D. void f(int i, int j)
- Given the code below, what will be the value of **i** after the loop? _____.
int i;
while (i<10) i++;
A. 10 B. 11 C. 9 D. None of above.
- Given the declarations: **int a[5], *p=a;** which expression is equivalent to the expression **p+1** ? _____.
A. a[1] B. &a+1 C. a+1 D. p[2]-1
- For the declarations: **int a[]={1,2,3,4,5}, *p=a+1, y;** what will be the value of variable **y** after executing **y=(*p)++**; ? _____.
A. y=1 B. y=2 C. y=3 D. Syntax error.
- For the declarations: **int *p[2], n[5];** which assignment expression is correct? _____.
A. p=n B. p=&n[0] C. p[0]=n D. p[0]=n++
- Given the following code fragment, the loop condition **str[i]!='\0'** could be replaced by which choice? _____.
char str[20]="hello, world";
for (i = 0; str[i] != '\0'; i++) putchar(str[i]);
A. str[i] B. i < 20 C. !(str[i] = '\0') D. i <= 20

9. Which function-calling statement could be used, to open a text file entitled "**abc.txt**" and located in the folder "**user**" within D diskette, which is opened for the reading and writing operation? _____.
- A. `fopen("D:\user\abc.txt","r")` B. `fopen("D:\\user\\abc.txt","r+")`
 C. `fopen("D:\user\abc.txt","rb")` D. `fopen("D:\\user\\abc.txt","w")`
10. In the following code fragments, which item is completely correct? _____.
- A. `int *p[5]; scanf("%d", p[0]);` B. `int *p; scanf("%d", p);`
 C. `int n[10], *p=n; scanf("%d", p);` D. `int n, *p; *p= &n; scanf("%d", p);`

Section 2: Fill in the blanks (2 marks for each item, total 30 marks)

1. The value of expression **3/6*2.0** is _____.
2. The value of expression '**9'-0**' is _____.
3. Given:
- ```
char c = 255;
printf("%d", c);
```
- The output should be: \_\_\_\_\_.
4. Given:
- ```
int b=50;
if ( 1<b<10 ) printf("ok") else printf("no");
```
- the output is _____.
5. The following code fragment will print out _____.
- ```
void swap(int *pa, *pb)
{
 int *t = pa;
 pa = pb;
 pb = t;
}
int a = 1, b = 2;
swap(&a, &b);
printf("%d#%d#", a, b);
```
6. The output of the code below is \_\_\_\_\_.
- ```
char *s="abc";
while ( *s++ ) if (*s) putchar(*s-1);
```
7. Given the declaration: **char *s;**, write a statement which could be used to allocate 10 bytes from the system and assign the first address to the variable **s** _____.
8. Try to use the function-call of **fscanf**, to replace the function-call of **scanf("%d",&m);** _____.
9. Given the declaration: **char *s;**, write an expression without any function-calling, which is equivalent to the expression **strlen(s)==1** _____.
10. Given the declaration: **int a[3][2]={1,2,3,4,5,6};** what is the value of expression **(a[1]+1)[0]** ? _____.

11. The value of expression `!(“2015-01-28”+5)` is _____.
12. The output of the code below is _____.

```
char x[ ]="hello,world\012345";
printf("%d#%d#", sizeof(x), strlen(x));
```
13. The output of the code below is _____.

```
char *a[3]={"one", "two", "three"}, **p=a;
printf("%s#", *(++p)+1);
printf("%c#", **p-1);
```
14. Given the declarations: **FILE *infp, *outfp**;, write a statement: it is used to write a letter, which is read from a file pointer **infp**, into the file pointer **outfp**, which points to an output file. _____.
15. Given the declaration: **char s[10]="12345678"**;, what will be the value of **strlen(s)** after executing **strcpy(s+2,s+5)**; _____.

Section 3: Read each of the following programs and answer questions (5marks for each item, total 30 marks)

1. What is the output of the following program? _____.

```
#include <stdio.h>

void swap(int *a, int b)
{
    int m, *n;

    n=&m;
    *n=*a;
    *a=b;
    b=*n;
}

int main()
{
    int x=8,y=1;

    swap(&x,y);
    printf("%d#%d#",x,y);
}
```

2. When input: **123**, what is the output of the following program_____.

```
#include <stdio.h>

int f(char s[], int b)
{
    int i=0, n=0;
```

```

        while (s[i]!='\0') {
            n=n*b+s[i]-'0';
            i++;
        }
        return n;
    }

int main()
{
    char s[20];
    int n;

    scanf("%s",s);
    printf("%d", f(s,5));
}

```

3. When the following program's input is **ing<Enter>**
This is a long test string<Enter>
the output of the program is _____.

```

#include <stdio.h>
#include <string.h>

int main()
{
    char s[100], t[100], ch, *p;
    int count, i;

    gets(s);
    gets(t);
    for (i = 0; i < strlen(s); i++) {
        count=0;
        p = t;
        while (*p != '\0') {
            if (*p == s[i]) count++;
            p++;
        }
        printf("%c %d ", s[i], count);
    }
}

```

4. The output of the following program's is _____.

```

#include <stdio.h>
#include <string.h>

void fun(char *s[], int n)
{
    char *t;
    int i,j;

```

```

        for (i=0; i<n; i++)
            for (j=i+1; j<n; j++)
                if (strlen(s[i])> strlen(s[j])) {
                    t=s[i];
                    s[i]=s[j];
                    s[j]=t;
                }
    }

int main()
{
    char *s[]={"the population of", "the city", "has reached", "top level"};

    fun(s,4);
    printf("%s,%s\n",s[0],s[3]);
}

```

5. The following program will print out _____.

```

#include <stdio.h>

void p1(int v[])
{
    int i,j,temp;

    for (i=1; i<4; i++)
        for (j=i-1; j>=0&&v[j]<v[j+1]; j--) {
            temp = v[j];
            v[j]=v[j+1];
            v[j+1]=temp;
        }
}

void p2(int v1[], int v2[])
{
    int i=0, j=0;

    while (i<4 && j<4) {
        if (v1[i]>v2[j]) {
            printf("%d ", v1[i++]);
        } else {
            printf("%d ", v2[j++]);
        }
    }
    while (i<4) printf("%d ", v1[i++]);
    while (j<4) printf("%d ", v2[j++]);
}

main()
{
    int a[2][4]={5,3,7,2},{4,1,8,6};

    p1(a[0]);
    p1(a[1]);
    p2(a[0],a[1]);
}

```

6. When input: **8 1 2 3 4 5 6 7 8**, the following program will print out _____.

```
#include <stdio.h>
#include <stdlib.h>

void F1(int *a, int n)
{
    int t, *b = a + n - 1;

    while (a < b) {
        t = *a;
        *a = *b;
        *b = t;
        a++;
        b--;
    }
}

void F2(int *a, int n)
{
    int i,t;

    if (n <= 1) return;
    for (i = 0; i < n/2; i++){
        t = *(a + i);
        *(a + i) = *(a + n - 1 - i);
        *(a + n - 1 - i) = t;
    }
}

int main(void )
{
    int i, n, *a;

    scanf("%d", &n);
    if ((a = (int*)malloc(n*sizeof(int))) == NULL) return 2;
    for (i = 0; i<n;i++) scanf("%d",&a[i]);
    F1(a + n/4, n/2);
    F2(a, n);
    for (i = 0; i < n; i++) printf("%d#",*(a + i));
    return 0;
}
```

Section 4: According to the specification, complete each program (2 marks for each blank, total 20 marks)

1. There is an increasing ordered (升序) character list in a text file **in.txt**. The following program read in this list, calculate the number of duplicates(重复) and write each character and its frequency of occurrence (>1) (大于 1 的出现次数) into the file **out.txt**. For example, if the **in.txt** contains **"abbcddddddddde"**, the list **"ab2cd12e"** will be written into **out.txt**.

```

#include <stdio.h>

main()
{
    FILE *fp1, *fp2;
    char last, c;
    int count=0;

    fp1=fopen("in.txt", "r");
    fp2=fopen("out.txt", "w");
    if ( _____(1)_____ ) return (0);
    last='\0';
    while ( _____(2)_____ ) {
        count++;
        if (c!=last) {
            if (count>1) _____(3)_____;
            count=0;
            _____(4)_____;
            last=_____(5)_____;
        }
    }
    fclose(fp1);
    fclose(fp2);
}

```

2. Function **strncat(char *ret, char *s2, int n)** copy at most **n** characters from **s2** to **ret**.

The output of the following program is:

WooMan

GoodWoMan

Please complete the program.

```

#include <stdio.h>

char *strncat(char *ret, char *s2, int n)
{
    char *s1=ret;

    if (n>0) {
        while ( _____(6)_____ );
        s1--;
        while (*s1++= _____(7)_____ ) {
            if (--n>0) continue;
            *s1= _____(8)_____;
            break;
        }
        return ret;
    } else {
        return s1;
    }
}

```

```
main()
{
    char s[100]="Good";
    char t1[100]="Woo";
    char t2[100]="Manager";

    strncat(____(9)____);
    printf("%s\n", t1);
    strncat(____(10)____);
    printf("%s\n", s);
}
```