# Namespace BOOSEapp

## Classes

AppCanvas

Implements the ICanvas interface with custom drawing functionality. Manages bitmap and graphics to render shapes and lines.

AppCircle

Custom implementation of the Circle command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

AppCommandFactory

Custom implementation of the CommandFactory to bypass BOOSE library restrictions. Acts as a central hub to return custom bridge commands instead of library defaults.

AppDrawTo

Custom implementation of the DrawTo command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

AppForm

The main user interface for the BOOSE application. Provides the entry point for commands and the canvas display area.

AppMoveTo

Custom implementation of the MoveTo command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

AppRect

Custom implementation of the Rect command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

AppTri

Custom implementation of the Tri command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

AppWrite

Custom implementation of the Write command to render text on the canvas. Acts as a bridge between the parsed user text and the AppCanvas methods.

# Class AppCanvas

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Implements the ICanvas interface with custom drawing functionality. Manages bitmap and graphics to render shapes and lines.

```
public class AppCanvas : ICanvas
```

**Inheritance**

object ← AppCanvas

**Implements**

ICanvas

**Inherited Members**

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

## Constructors

### AppCanvas(int, int)

Constructor initialises canvas and pen with specified parameters.

```
public AppCanvas(int xSize, int ySize)
```

#### Parameters

`xSize` int

Width of the canvas

`ySize` int

Height of the canvas

# Properties

## PenColour

Gets or sets the colour of the pen and brush.

```
public object PenColour { get; set; }
```

### Property Value

object

## Xpos

Gets or sets the X co-ordinate of the pen.

```
public int Xpos { get; set; }
```

### Property Value

int

## Ypos

Gets or sets the Y co-ordinate of the pen.

```
public int Ypos { get; set; }
```

### Property Value

int

# Methods

## Circle(int, bool)

Draws a circle centred on the current pen position.

```
public void Circle(int radius, bool filled)
```

### Parameters

`radius` int

The radius of the circle.

`filled` bool

Determines whether to fill in the circle with selected colour.

## Clear()

Clears the canvas setting it to the default window colour.

```
public void Clear()
```

## DrawTo(int, int)

Draws a line from the current pen position to the specified co-ordinates. Updates the pen position to the specified co-ordinates.

```
public void DrawTo(int x, int y)
```

### Parameters

`x` int

X co-ordinate.

`y` int

Y co-ordinate.

## MoveTo(int, int)

Updates the pen position to the specified co-ordinates

```
public void MoveTo(int x, int y)
```

### Parameters

`x` int

X co-ordinate.

`y` int

Y co-ordinate.

## Rect(int, int, bool)

Draws a rectangle at current pen position. Also determines whether it should be filled in or not.

```
public void Rect(int width, int height, bool filled)
```

### Parameters

`width` int

Width of the rectangle.

`height` int

Height of the rectangle.

`filled` bool

Determines whether to fill the rectangle in with the currently selected colour.

## Reset()

Resets the pen to the default position and colour.

```
public void Reset()
```

## Set(int, int)

Re-initializes the canvas with specified dimensions.

```
public void Set(int width, int height)
```

### Parameters

`width` int

Width of canvas.

`height` int

Height of canvas.

## SetColour(int, int, int)

Sets the colour of the pen (outline) and brush (fill) using RGB values.

```
public void SetColour(int red, int green, int blue)
```

### Parameters

`red` int

Colour red value, from 0-255.

`green` int

Colour green value, from 0-255.

`blue` int

Colour blue value, from 0-255.

## Tri(int, int)

Draws a triangle centred on the current pen position.

```
public void Tri(int width, int height)
```

### Parameters

`width` int

Width of triangle base.

`height` int

Height of triangle from base to tip.

## WriteText(string)

Renders text onto the canvas at the current pen position.

```
public void WriteText(string text)
```

### Parameters

`text` string

Text to display.

## getBitmap()

Gets the drawing object displayed as a bitmap. Used by UI to render canvas content to the display.

```
public object getBitmap()
```

### Returns

object

The bitmap object containing all objects drawn so far.

# Class AppCircle

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the Circle command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

```
public class AppCircle : CommandOneParameter, ICommand
```

**Inheritance**

object ← Command ← CanvasCommand ← CommandOneParameter ← AppCircle

**Implements**

ICommand

**Inherited Members**

CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.IsDouble , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

# Constructors

## AppCircle()

Constructor for the Circle command. Calls base constructor to integrate with BOOSE library structure.

```
public AppCircle()
```

# Methods

# CheckParameters(string[])

Validates the parameters before execution.

```
public override void CheckParameters(string[] parameterList)
```

## Parameters

`parameterList` string[]

The array of string parameters from the parser.

## Exceptions

CommandException

Thrown if parameters are invalid.

# Execute()

Handles the execution of the command on the canvas.

```
public override void Execute()
```

# Class AppCommandFactory

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the CommandFactory to bypass BOOSE library restrictions. Acts as a central hub to return custom bridge commands instead of library defaults.

```
public class AppCommandFactory : CommandFactory, ICommandFactory
```

**Inheritance**

object ← CommandFactory ← AppCommandFactory

**Implements**

ICommandFactory

**Inherited Members**

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

# Methods

## MakeCommand(string)

Creates and returns a command object based on the parsed input string.

```
public override ICommand MakeCommand(string commandType)
```

### Parameters

`commandType` string

The string holding the command input.

### Returns

ICommand

An implemented ICommand object to be executed by the program.

# Class AppDrawTo

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the DrawTo command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

```
public class AppDrawTo : CommandTwoParameters, ICommand
```

**Inheritance**

object ← Command ← CanvasCommand ← CommandOneParameter ← CommandTwoParameters ← AppDrawTo

**Implements**

ICommand

**Inherited Members**

CommandTwoParameters.param2 , CommandTwoParameters.param2unprocessed , CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.IsDouble , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

# Constructors

## AppDrawTo()

Constructor for the DrawTo command. Calls base constructor to integrate with BOOSE library structure.

```
public AppDrawTo()
```

# Methods

# CheckParameters(string[])

Validates the parameters before execution.

```
public override void CheckParameters(string[] parameterList)
```

## Parameters

`parameterList` string[]

The array of string parameters from the parser.

## Exceptions

CommandException

Thrown if parameters are invalid.

# Execute()

Handles the execution of the command on the canvas.

```
public override void Execute()
```

# Class AppForm

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

The main user interface for the BOOSE application. Provides the entry point for commands and the canvas display area.

```
public class AppForm : Form, IDropTarget, ISynchronizeInvoke, IWin32Window,
IBindableComponent, IComponent, IDisposable, IContainerControl
```

### Inheritance

object ← MarshalByRefObject ← Component ← Control ← ScrollableControl ← ContainerControl ← Form ← AppForm

### Implements

IDropTarget, ISynchronizeInvoke, IWin32Window, IBindableComponent, IComponent, IDisposable, IContainerControl

### Inherited Members

Form.SetVisibleCore(bool) , Form.Activate() , Form.ActivateMdiChild(Form) , Form.AddOwnedForm(Form) , Form.AdjustFormScrollbars(bool) , Form.Close() , Form.CreateAccessibilityInstance() , Form.CreateControlsInstance() , Form.CreateHandle() , Form.DefWndProc(ref Message) , Form.ProcessMnemonic(char) , Form.CenterToParent() , Form.CenterToScreen() , Form.LayoutMdi(MdiLayout) , Form.OnActivated(EventArgs) , Form.OnBackgroundImageChanged(EventArgs) , Form.OnBackgroundImageLayoutChanged(EventArgs) , Form.OnClosing(CancelEventArgs) , Form.OnClosed(EventArgs) , Form.OnFormClosing(FormClosingEventArgs) , Form.OnFormClosed(FormClosedEventArgs) , Form.OnCreateControl() , Form.OnDeactivate(EventArgs) , Form.OnEnabledChanged(EventArgs) , Form.OnEnter(EventArgs) , Form.OnFontChanged(EventArgs) , Form.OnGotFocus(EventArgs) , Form.OnHandleCreated(EventArgs) , Form.OnHandleDestroyed(EventArgs) , Form.OnHelpButtonClicked(CancelEventArgs) , Form.OnLayout(LayoutEventArgs) , Form.OnLoad(EventArgs) , Form.OnMaximizedBoundsChanged(EventArgs) , Form.OnMaximumSizeChanged(EventArgs) , Form.OnMinimumSizeChanged(EventArgs) , Form.OnInputLanguageChanged(InputLanguageChangedEventArgs) , Form.OnInputLanguageChanging(InputLanguageChangingEventArgs) , Form.OnVisibleChanged(EventArgs) , Form.OnMdiChildActivate(EventArgs) , Form.OnMenuStart(EventArgs) , Form.OnMenuComplete(EventArgs) , Form.OnPaint(PaintEventArgs) , Form.OnResize(EventArgs) ,

Form.OnDpiChanged(DpiChangedEventArgs) , Form.OnGetDpiScaledSize(int, int, ref Size) ,
Form.OnRightToLeftLayoutChanged(EventArgs) , Form.OnShown(EventArgs) ,
Form.OnTextChanged(EventArgs) , Form.ProcessCmdKey(ref Message, Keys) ,
Form.ProcessDialogKey(Keys) , Form.ProcessDialogChar(char) ,
Form.ProcessKeyPreview(ref Message) , Form.ProcessTabKey(bool) ,
Form.RemoveOwnedForm(Form) , Form.Select(bool, bool) ,
Form.ScaleMinMaxSize(float, float, bool) ,
Form.GetScaledBounds(Rectangle, SizeF, BoundsSpecified) ,
Form.ScaleControl(SizeF, BoundsSpecified) , Form.SetBoundsCore(int, int, int, int, BoundsSpecified) ,
Form.SetClientSizeCore(int, int) , Form.SetDesktopBounds(int, int, int, int) ,
Form.SetDesktopLocation(int, int) , Form.Show(IWin32Window) , Form.ShowDialog() ,
Form.ShowDialog(IWin32Window) , Form.ToString() , Form.UpdateDefaultButton() ,
Form.OnResizeBegin(EventArgs) , Form.OnResizeEnd(EventArgs) ,
Form.OnStyleChanged(EventArgs) , Form.ValidateChildren() ,
Form.ValidateChildren(ValidationConstraints) , Form.WndProc(ref Message) , Form.AcceptButton ,
Form.ActiveForm , Form.ActiveMdiChild , Form.AllowTransparency , Form.AutoScroll ,
Form.AutoSize , Form.AutoSizeMode , Form.AutoValidate , Form.BackColor ,
Form.FormBorderStyle , Form.CancelButton , Form.ClientSize , Form.ControlBox ,
Form.CreateParams , Form.DefaultImeMode , Form.DefaultSize , Form.DesktopBounds ,
Form.DesktopLocation , Form.DialogResult , Form.HelpButton , Form.Icon , Form.IsMdiChild ,
Form.IsMdiContainer , Form.IsRestrictedWindow , Form.KeyPreview , Form.Location ,
Form.MaximizedBounds , Form.MaximumSize , Form.MainMenuStrip , Form.MinimumSize ,
Form.MaximizeBox , Form.MdiChildren , Form.MdiChildrenMinimizedAnchorBottom ,
Form.MdiParent , Form.MinimizeBox , Form.Modal , Form.Opacity , Form.OwnedForms ,
Form.Owner , Form.RestoreBounds , Form.RightToLeftLayout , Form.ShowInTaskbar ,
Form.ShowIcon , Form.ShowWithoutActivation , Form.Size , Form.SizeGripStyle ,
Form.StartPosition , Form.Text , Form.TopLevel , Form.TopMost , Form.TransparencyKey ,
Form.WindowState , Form.AutoSizeChanged , Form.AutoValidateChanged ,
Form.HelpButtonClicked , Form.MaximizedBoundsChanged , Form.MaximumSizeChanged ,
Form.MinimumSizeChanged , Form.Activated , Form.Deactivate , Form.FormClosing ,
Form.FormClosed , Form.Load , Form.MdiChildActivate , Form.MenuComplete ,
Form.MenuStart , Form.InputLanguageChanged , Form.InputLanguageChanging ,
Form.RightToLeftLayoutChanged , Form.Shown , Form.DpiChanged , Form.ResizeBegin ,
Form.ResizeEnd , ContainerControl.OnAutoValidateChanged(EventArgs) ,
ContainerControl.OnMove(EventArgs) , ContainerControl.OnParentChanged(EventArgs) ,
ContainerControl.PerformAutoScale() , ContainerControl.RescaleConstantsForDpi(int, int) ,
ContainerControl.Validate() , ContainerControl.Validate(bool) ,
ContainerControl.AutoScaleDimensions , ContainerControl.AutoScaleFactor ,
ContainerControl.AutoScaleMode , ContainerControl.BindingContext ,
ContainerControl.CanEnableIme , ContainerControl.ActiveControl ,

ContainerControl.CurrentAutoScaleDimensions , ContainerControl.ParentForm ,
ScrollableControl.ScrollStateAutoScrolling , ScrollableControl.ScrollStateHScrollVisible ,
ScrollableControl.ScrollStateVScrollVisible , ScrollableControl.ScrollStateUserHasScrolled ,
ScrollableControl.ScrollStateFullDrag , ScrollableControl.GetScrollState(int) ,
ScrollableControl.OnMouseWheel(MouseEventArgs) ,
ScrollableControl.OnRightToLeftChanged(EventArgs) ,
ScrollableControl.OnPaintBackground(PaintEventArgs) ,
ScrollableControl.OnPaddingChanged(EventArgs) , ScrollableControl.SetDisplayRectLocation(int, int) ,
ScrollableControl.ScrollControlIntoView(Control) , ScrollableControl.ScrollToControl(Control) ,
ScrollableControl.OnScroll(ScrollEventArgs) , ScrollableControl.SetAutoScrollMargin(int, int) ,
ScrollableControl.SetScrollState(int, bool) , ScrollableControl.AutoScrollMargin ,
ScrollableControl.AutoScrollPosition , ScrollableControl.AutoScrollMinSize ,
ScrollableControl.DisplayRectangle , ScrollableControl.HScroll , ScrollableControl.HorizontalScroll ,
ScrollableControl.VScroll , ScrollableControl.VerticalScroll , ScrollableControl.Scroll ,
Control.GetAccessibilityObjectById(int) , Control.SetAutoSizeMode(AutoSizeMode) ,
Control.GetAutoSizeMode() , Control.GetPreferredSize(Size) ,
Control.AccessibilityNotifyClients(AccessibleEvents, int) ,
Control.AccessibilityNotifyClients(AccessibleEvents, int, int) , Control.BeginInvoke(Delegate) ,
Control.BeginInvoke(Action) , Control.BeginInvoke(Delegate, params object[]) ,
Control.BringToFront() , Control.Contains(Control) , Control.CreateGraphics() ,
Control.CreateControl() , Control.DestroyHandle() , Control.DoDragDrop(object, DragDropEffects) ,
Control.DoDragDrop(object, DragDropEffects, Bitmap, Point, bool) ,
Control.DrawToBitmap(Bitmap, Rectangle) , Control.EndInvoke(IAsyncResult) , Control.FindForm() ,
Control.GetTopLevel() , Control.RaiseKeyEvent(object, KeyEventArgs) ,
Control.RaiseMouseEvent(object, MouseEventArgs) , Control.Focus() ,
Control.FromChildHandle(nint) , Control.FromHandle(nint) ,
Control.GetChildAtPoint(Point, GetChildAtPointSkip) , Control.GetChildAtPoint(Point) ,
Control.GetContainerControl() , Control.GetNextControl(Control, bool) ,
Control.GetStyle(ControlStyles) , Control.Hide() , Control.InitLayout() , Control.Invalidate(Region) ,
Control.Invalidate(Region, bool) , Control.Invalidate() , Control.Invalidate(bool) ,
Control.Invalidate(Rectangle) , Control.Invalidate(Rectangle, bool) , Control.Invoke(Action) ,
Control.Invoke(Delegate) , Control.Invoke(Delegate, params object[]) ,
Control.Invoke<T>(Func<T>) , Control.InvokePaint(Control, PaintEventArgs) ,
Control.InvokePaintBackground(Control, PaintEventArgs) , Control.IsKeyLocked(Keys) ,
Control.IsInputChar(char) , Control.IsInputKey(Keys) , Control.IsMnemonic(char, string) ,
Control.LogicalToDeviceUnits(int) , Control.LogicalToDeviceUnits(Size) ,
Control.ScaleBitmapLogicalToDevice(ref Bitmap) , Control.NotifyInvalidate(Rectangle) ,
Control.InvokeOnClick(Control, EventArgs) , Control.OnAutoSizeChanged(EventArgs) ,
Control.OnBackColorChanged(EventArgs) , Control.OnBindingContextChanged(EventArgs) ,
Control.OnCausesValidationChanged(EventArgs) , Control.OnContextMenuStripChanged(EventArgs) ,

Control.OnCursorChanged(EventArgs) , Control.OnDataContextChanged(EventArgs) ,
Control.OnDockChanged(EventArgs) , Control.OnForeColorChanged(EventArgs) ,
Control.OnNotifyMessage(Message) , Control.OnParentBackColorChanged(EventArgs) ,
Control.OnParentBackgroundImageChanged(EventArgs) ,
Control.OnParentBindingContextChanged(EventArgs) , Control.OnParentCursorChanged(EventArgs) ,
Control.OnParentDataContextChanged(EventArgs) , Control.OnParentEnabledChanged(EventArgs) ,
Control.OnParentFontChanged(EventArgs) , Control.OnParentForeColorChanged(EventArgs) ,
Control.OnParentRightToLeftChanged(EventArgs) , Control.OnParentVisibleChanged(EventArgs) ,
Control.OnPrint(PaintEventArgs) , Control.OnTabIndexChanged(EventArgs) ,
Control.OnTabStopChanged(EventArgs) , Control.OnClick(EventArgs) ,
Control.OnClientSizeChanged(EventArgs) , Control.OnControlAdded(ControlEventArgs) ,
Control.OnControlRemoved(ControlEventArgs) , Control.OnLocationChanged(EventArgs) ,
Control.OnDoubleClick(EventArgs) , Control.OnDragEnter(DragEventArgs) ,
Control.OnDragOver(DragEventArgs) , Control.OnDragLeave(EventArgs) ,
Control.OnDragDrop(DragEventArgs) , Control.OnGiveFeedback(GiveFeedbackEventArgs) ,
Control.InvokeGotFocus(Control, EventArgs) , Control.OnHelpRequested(HelpEventArgs) ,
Control.OnInvalidated(InvalidateEventArgs) , Control.OnKeyDown(KeyEventArgs) ,
Control.OnKeyPress(KeyPressEventArgs) , Control.OnKeyUp(KeyEventArgs) ,
Control.OnLeave(EventArgs) , Control.InvokeLostFocus(Control, EventArgs) ,
Control.OnLostFocus(EventArgs) , Control.OnMarginChanged(EventArgs) ,
Control.OnMouseDoubleClick(MouseEventArgs) , Control.OnMouseClick(MouseEventArgs) ,
Control.OnMouseCaptureChanged(EventArgs) , Control.OnMouseDown(MouseEventArgs) ,
Control.OnMouseEnter(EventArgs) , Control.OnMouseLeave(EventArgs) ,
Control.OnDpiChangedBeforeParent(EventArgs) , Control.OnDpiChangedAfterParent(EventArgs) ,
Control.OnMouseHover(EventArgs) , Control.OnMouseMove(MouseEventArgs) ,
Control.OnMouseUp(MouseEventArgs) ,
Control.OnQueryContinueDrag(QueryContinueDragEventArgs) ,
Control.OnRegionChanged(EventArgs) , Control.OnPreviewKeyDown(PreviewKeyDownEventArgs) ,
Control.OnSizeChanged(EventArgs) , Control.OnChangeUICues(UICuesEventArgs) ,
Control.OnSystemColorsChanged(EventArgs) , Control.OnValidating(CancelEventArgs) ,
Control.OnValidated(EventArgs) , Control.PerformLayout() , Control.PerformLayout(Control, string) ,
Control.PointToClient(Point) , Control.PointToScreen(Point) ,
Control.PreProcessMessage(ref Message) , Control.PreProcessControlMessage(ref Message) ,
Control.ProcessKeyEventArgs(ref Message) , Control.ProcessKeyMessage(ref Message) ,
Control.RaiseDragEvent(object, DragEventArgs) , Control.RaisePaintEvent(object, PaintEventArgs) ,
Control.RecreateHandle() , Control.RectangleToClient(Rectangle) ,
Control.RectangleToScreen(Rectangle) , Control.ReflectMessage(nint, ref Message) ,
Control.Refresh() , Control.ResetMouseEventArgs() , Control.ResetText() , Control.ResumeLayout() ,
Control.ResumeLayout(bool) , Control.Scale(SizeF) , Control.Select() ,
Control.SelectNextControl(Control, bool, bool, bool, bool) , Control.SendToBack() ,

Control.SetBounds(int, int, int, int) , Control.SetBounds(int, int, int, int, BoundsSpecified) , Control.SizeFromClientSize(Size) , Control.SetStyle(ControlStyles, bool) , Control.SetTopLevel(bool) , Control.RtlTranslateAlignment(HorizontalAlignment) , Control.RtlTranslateAlignment(LeftRightAlignment) , Control.RtlTranslateAlignment(ContentAlignment) , Control.RtlTranslateHorizontal(HorizontalAlignment) , Control.RtlTranslateLeftRight(LeftRightAlignment) , Control.RtlTranslateContent(ContentAlignment) , Control.Show() , Control.SuspendLayout() , Control.Update() , Control.UpdateBounds() , Control.UpdateBounds(int, int, int, int) , Control.UpdateBounds(int, int, int, int, int, int) , Control.UpdateZOrder() , Control.UpdateStyles() , Control.OnImeModeChanged(EventArgs) , Control.AccessibilityObject , Control.AccessibleDefaultActionDescription , Control.AccessibleDescription , Control.AccessibleName , Control.AccessibleRole , Control.AllowDrop , Control.Anchor , Control.AutoScrollOffset , Control.LayoutEngine , Control.DataContext , Control.BackgroundImage , Control.BackgroundImageLayout , Control.Bottom , Control.Bounds , Control.CanFocus , Control.CanRaiseEvents , Control.CanSelect , Control.Capture , Control.CausesValidation , Control.CheckForIllegalCrossThreadCalls , Control.ClientRectangle , Control.CompanyName , Control.ContainsFocus , Control.ContextMenuStrip , Control.Controls , Control.Created , Control.Cursor , Control.DataBindings , Control.DefaultBackColor , Control.DefaultCursor , Control.DefaultFont , Control.DefaultForeColor , Control.DefaultMargin , Control.DefaultMaximumSize , Control.DefaultMinimumSize , Control.DefaultPadding , Control.DeviceDpi , Control.IsDisposed , Control.Disposing , Control.Dock , Control.DoubleBuffered , Control.Enabled , Control.Focused , Control.Font , Control.FontHeight , Control.ForeColor , Control.Handle , Control.HasChildren , Control.Height , Control.IsHandleCreated , Control.InvokeRequired , Control.IsAccessible , Control.IsAncestorSiteInDesignMode , Control.IsMirrored , Control.Left , Control.Margin , Control.ModifierKeys , Control.MouseButtons , Control.MousePosition , Control.Name , Control.Parent , Control.ProductName , Control.ProductVersion , Control.RecreatingHandle , Control.Region , Control.RenderRightToLeft , Control.ResizeRedraw , Control.Right , Control.RightToLeft , Control.ScaleChildren , Control.Site , Control.TabIndex , Control.TabStop , Control.Tag , Control.Top , Control.TopLevelControl , Control.ShowKeyboardCues , Control.ShowFocusCues , Control.UseWaitCursor , Control.Visible , Control.Width , Control.PreferredSize , Control.Padding , Control.ImeMode , Control.ImeModeBase , Control.PropagatingImeMode , Control.BackColorChanged , Control.BackgroundImageChanged , Control.BackgroundImageLayoutChanged , Control.BindingContextChanged , Control.CausesValidationChanged , Control.ClientSizeChanged , Control.ContextMenuStripChanged , Control.CursorChanged , Control.DockChanged , Control.EnabledChanged , Control.FontChanged , Control.ForeColorChanged , Control.LocationChanged , Control.MarginChanged , Control.RegionChanged , Control.RightToLeftChanged , Control.SizeChanged , Control.TabIndexChanged ,

Control.TabStopChanged, Control.TextChanged, Control.VisibleChanged, Control.Click, Control.ControlAdded, Control.ControlRemoved, Control.DataContextChanged, Control.DragDrop, Control.DragEnter, Control.DragOver, Control.DragLeave, Control.GiveFeedback, Control.HandleCreated, Control.HandleDestroyed, Control.HelpRequested, Control.Invalidated, Control.PaddingChanged, Control.Paint, Control.QueryContinueDrag, Control.QueryAccessibilityHelp, Control.DoubleClick, Control.Enter, Control.GotFocus, Control.KeyDown, Control.KeyPress, Control.KeyUp, Control.Layout, Control.Leave, Control.LostFocus, Control.MouseClick, Control.MouseDoubleClick, Control.MouseCaptureChanged, Control.MouseDown, Control.MouseEnter, Control.MouseLeave, Control.DpiChangedBeforeParent, Control.DpiChangedAfterParent, Control.MouseHover, Control.MouseMove, Control.MouseUp, Control.MouseWheel, Control.Move, Control.PreviewKeyDown, Control.Resize, Control.ChangeUICues, Control.StyleChanged, Control.SystemColorsChanged, Control.Validating, Control.Validated, Control.ParentChanged, Control.ImeModeChanged, Component.Dispose(), Component.GetService(Type), Component.Container, Component.DesignMode, Component.Events, Component.Disposed, MarshalByRefObject.GetLifetimeService(), MarshalByRefObject.InitializeLifetimeService(), MarshalByRefObject.MemberwiseClone(bool), object.Equals(object), object.Equals(object, object), object.GetHashCode(), object.GetType(), object.MemberwiseClone(), object.ReferenceEquals(object, object)

# Constructors

## AppForm()

Initialises the form and sets up the BOOSE drawing environment.

```
public AppForm()
```

# Methods

## Dispose(bool)

Clean up any resources being used.

```
protected override void Dispose(bool disposing)
```

## Parameters

`disposing` bool

true if managed resources should be disposed; otherwise, false.

# Class AppMoveTo

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the MoveTo command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

```
public class AppMoveTo : CommandTwoParameters, ICommand
```

**Inheritance**

object ← Command ← CanvasCommand ← CommandOneParameter ← CommandTwoParameters ← AppMoveTo

**Implements**

ICommand

**Inherited Members**

CommandTwoParameters.param2 , CommandTwoParameters.param2unprocessed , CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.IsDouble , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

## Constructors

### AppMoveTo()

Constructor for the MoveTo command. Calls base constructor to integrate with BOOSE library structure.

```
public AppMoveTo()
```

## Methods

# CheckParameters(string[])

Validates the parameters before execution.

```
public override void CheckParameters(string[] parameterList)
```

## Parameters

`parameterList` string[]

The array of string parameters from the parser.

## Exceptions

CommandException

Thrown if parameters are invalid.

# Execute()

Handles the execution of the command on the canvas.

```
public override void Execute()
```

# Class AppRect

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the Rect command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

```
public class AppRect : CommandTwoParameters, ICommand
```

**Inheritance**

object ← Command ← CanvasCommand ← CommandOneParameter ← CommandTwoParameters ← AppRect

**Implements**

ICommand

**Inherited Members**

CommandTwoParameters.param2 , CommandTwoParameters.param2unprocessed , CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.IsDouble , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

# Constructors

## AppRect()

Constructor for the Rect command. Calls base constructor to integrate with BOOSE library structure.

```
public AppRect()
```

# Methods

## CheckParameters(string[])

Validates the parameters before execution.

```
public override void CheckParameters(string[] parameterList)
```

### Parameters

`parameterList` string[]

The array of string parameters from the parser.

### Exceptions

CommandException

Thrown if parameters are invalid.

## Execute()

Handles the execution of the command on the canvas.

```
public override void Execute()
```

# Class AppTri

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the Tri command to bypass BOOSE library restrictions. Acts as a bridge between the parsed user input and AppCanvas methods.

```
public class AppTri : CanvasCommand, ICommand
```

**Inheritance**

object ← Command ← CanvasCommand ← AppTri

**Implements**

ICommand

**Inherited Members**

CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.IsDouble , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

## Constructors

### AppTri()

Constructor for the Tri command. Calls base constructor to integrate with BOOSE library structure.

```
public AppTri()
```

## Methods

### CheckParameters(string[])

Validates the parameters before execution.

```
public override void CheckParameters(string[] parameterList)
```

### Parameters

`parameterList` string[]

The array of string parameters from the parser.

### Exceptions

CommandException

Thrown if parameters are invalid.

## Execute()

Handles the execution of the command on the canvas.

```
public override void Execute()
```

# Class AppWrite

Namespace: BOOSEapp

Assembly: BOOSEapp.dll

Custom implementation of the Write command to render text on the canvas. Acts as a bridge between the parsed user text and the AppCanvas methods.

```
public class AppWrite : CanvasCommand, ICommand
```

**Inheritance**

object ← Command ← CanvasCommand ← AppWrite

**Implements**

ICommand

**Inherited Members**

CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.IsDouble , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

## Constructors

### AppWrite()

Constructor for the Write command. Calls base constructor to integrate with BOOSE library structure.

```
public AppWrite()
```

## Methods

### CheckParameters(string[])

Validates the parameters before execution.

```
public override void CheckParameters(string[] parameterList)
```

### Parameters

`parameterList` string[]

The array of string parameters from the parser.

### Exceptions

CommandException

Thrown if parameters are invalid.

## Execute()

Handles the execution of the command on the canvas.

```
public override void Execute()
```