

Dynamic Programming | Set 2 (Optimal Substructure Property)

As we discussed in [Set 1](#), following are the two main properties of a problem that suggest that the given problem can be solved using Dynamic programming.

- 1) Overlapping Subproblems
- 2) Optimal Substructure

We have already discussed Overlapping Subproblem property in the [Set 1](#). Let us discuss Optimal Substructure property here.


2) Optimal Substructure: A given problems has Optimal Substructure Property if optimal solution of the given problem can be obtained by using optimal solutions of its subproblems.

[Start Coding Today](#)

For example the shortest path problem has following optimal substructure property:
If a node x lies in the shortest path from a source node u to destination node v then the shortest path from u to v is combination of shortest path from u to x and shortest path from x to v . The standard All Pair Shortest Path algorithms like [Floyd–Warshall](#) and [Bellman–Ford](#) are typical examples of Dynamic Programming.

On the other hand the Longest path problem doesn't have the Optimal Substructure property. Here by Longest Path we mean longest simple path (path without cycle) between two nodes. Consider the following unweighted graph given in the [CLRS book](#).

paths, these longest paths do not have the optimal substructure property. For example, the longest path $q \rightarrow r \rightarrow t$ is not a combination of longest path from q to r and longest path from r to t , because the longest path from q to r is $q \rightarrow s \rightarrow t \rightarrow r$.



We will be covering some example problems in future posts on Dynamic Programming.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

References:

http://en.wikipedia.org/wiki/Optimal_substructure

[CLRS book](#)

Popular Posts

- [Top 10 Algorithms and Data Structures for Competitive Programming](#)
- [Top 10 algorithms in Interview Questions](#)
- [How to begin with Competitive](#)

Company Wise Coding Practice

Topic Wise

17 Comments Category: Dynamic Programming Tags: Dynamic Programming

Related Posts:

- All ways to add parenthesis for evaluation
- Count all increasing subsequences
- Count distinct occurrences as a subsequence

Programming?

- Step by Step Guide for Placement Preparation
- Reflection in Java
- Memory Layout of C Programs
- Heavy Light Decomposition
- Sorted Linked List to Balanced BST
- Generics in Java
- Aho-Corasick Algorithm for Pattern Searching
- Insertion Sort , Binary Search , QuickSort , MergeSort , HeapSort

- Longest repeating and non-overlapping substring
- Find minimum sum such that one of every three consecutive elements is taken
- Count Distinct Subsequences
- Non-crossing lines to connect points in a circle
- Count digit groupings of a number with given constraints

Previous post in category

Next post in category

(Login to Rate and Mark)

1.6

Average Difficulty : **1.6/5.0**
Based on **82** vote(s)



Add to TODO List



Mark as DONE

Writing code in comment? Please use code.geeksforgeeks.org, generate link and share the link here.

17 Comments


GeeksforGeeks

♥ Recommend **1**

🔗 Share

Join the discussion...

- Common Interview Puzzles
- Interview Experiences
- Advanced Data Structures
- Design Patterns
- Dynamic Programming
- Greedy Algorithms
- Backtracking
- Pattern Searching
- Divide & Conquer
- Geometric Algorithms
- Searching
- Sorting
- Hashing
- Analysis of Algorithms
- Mathematical Algorithms
- Randomized Algorithms
- Recursion





D. Pandey • 11 days ago

Hi,

Is it needed that for a problem to be solved by Dynamic Programn possessing Only One will be Enough? I think there exists some pr substructure and they can be solved By DP. Again, I think Longes Category, Is it?

^ | v • Reply • Share ›



Harshit Jain • a year ago

Consider finding a shortest path for travelling between two cities b substructure. That is, if the shortest route from Seattle to Los Ang Sacramento, then the shortest route from Portland to Los Angeles problem of how to get from Portland to Los Angeles is nested insi Angeles...

2 ^ | v • Reply • Share ›



shiwakant.bharti • 3 years ago

Example from wiki where the substructure may not be optimal.

<http://en.wikipedia.org/wiki/O...>


Least-cost airline fare. (Using on online flight search, we will frequ airport B involves a single connection through airport C, but the ch connection through some other airport D.)

3 ^ | v • Reply • Share ›



SDK • 5 years ago

Please can somebody clarify the difference between Greedy and



Tags

Accolite Adobe Advance Data Structures Advanced Data Structures Amazon array D-E-Shaw Directi Divide and Conquer Dynamic Programming Flipkart GATE GATE-CS-DS-&-Algo GATE-CS-Older GFacts Goldman Sachs Google Graph Greedy Algorithm Hashing Interview Experience Java MakeMyTrip MAQ Software MathematicalAlgo Matrix Microsoft Morgan Stanley Operating systems Oracle Pattern Searching Recursion Samsung SAP Labs SnapDeal stack STL Zoho

Subscribe and Never Miss an Article



Please can somebody clarify the difference between Greedy and
i.e how to decide which technique to use when by providing exam
Thank u

^ | v • Reply • Share ›



Someone → SDK • 10 months ago

Greedy is about taking the options that looks the best (local DP is about a clever way to search over *the entire solution your problem exhibits other properties) using some proper S.).

^ | v • Reply • Share ›



Anand • 5 years ago

Here is blog that has all solved DP problem frequently asked in int

<http://anandtechblog.blogspot.com/2011/01/amazon-question-dyn>

1 ^ | v • Reply • Share ›



rajesh → Anand • a year ago

In greedy algorithm we will solve the problem which are independent problems are dependent like fibonic series

^ | v • Reply • Share ›



tk • 5 years ago

As far as I know, most of the optimization problems have optimal subproblem property that helps us in deciding to choose DP. Do other than the longest path, that doesn't have the optimal substructure

Subscribe

Recent Comments

Like us on Facebook

Follow us on Twitter

Subscribe on YouTube

All Categories

other than the longest path - that doesn't have the optimal substructure

^ | v • Reply • Share ›



shawakant.bharti → tk • 3 years ago

Example from wiki where the substructure may not be optimal
[http://en.wikipedia.org/wiki/O...](http://en.wikipedia.org/wiki/Optimal_substructure)

Least-cost airline fare. (Using an online flight search, we see that the cheapest flight from airport A to airport B involves a single connection through airport C, while the cheapest flight from airport A to airport D involves a connection through some other airport.)


^ | v • Reply • Share ›



pira → shiwakant.bharti • 2 years ago

i didn't get the above example.
can anyone explain it?


^ | v • Reply • Share ›



Harshit Jain → pira • a year ago

Consider finding a shortest path for travelling from Los Angeles to Los Angeles. The shortest path is likely to exhibit optimal substructure. That is, if the shortest path from Los Angeles to Los Angeles passes through Portland and then Sacramento, then the shortest path from Los Angeles to Sacramento must pass through Sacramento to Los Angeles is nested inside the problem.

^ | v • Reply • Share ›




aj12009_3 → pira • 2 years ago

let's say you want to go from A to B, website

connection from point C. But if you think that might be costlier than the website is offering, A to C is via a point D.

Thus you can't find cheapest possible fares via connecting airports for that route.

1 ^ | v • Reply • Share ›



Vineel ➔ pira • 2 years ago

Go through the above article, to find the longest path problem, but it does not have a substructure as longest path from A to C and from C to A

^ | v • Reply • Share ›



Venki • 5 years ago

The "Optimal Substructure Property" also called as "principle of optimality" for a problem should satisfy principle of optimality. However, determining whether a problem has the property of optimality, hope some of the upcoming examples will clarify.

For example finding optimal solution to one sub-instance may preclude the optimal solution to the original problem, i.e. the optimal instances are not independent.

1 ^ | v • Reply • Share ›



rocky • 5 years ago

Nice Post! What about the Dijkstra Algorithm. Dijkstra also follows the principle of optimality.

1 ^ | v • Reply • Share ›



Jagat → rocky • 4 years ago

In case of Disjkstra, you evaluate a specific decision that r
and that is the property of a greedy algorithm.

On the other hand, when using DP, you've no idea what th
solution to all the possible sub problems.

11 ^ | v • Reply • Share ›



Shiraj Pokharel → rocky • 5 years ago

No its greedy my dear.

1 ^ | v • Reply • Share ›



Subscribe



Add Disqus to your site

Privacy

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Advertise with us!