BioHORS

Team instruction packet

FTC 2026-27 BIOBUZZ - auto, tuning, and every value left to measure

What this is. Everything the team needs to take the simulated auto to the real robot: how to rebuild the setup, how to tune Pedro Pathing v3, how to move a pose or change an action, and a list of every number that is still a placeholder.

If you want to...	Go to
Get the code running and see the auto in AdvantageScope	Section 2
Tune the drive so paths are followed on the real robot	Sections 3 and 4
Make the shooters hold speed and the pollen score	Section 5
Move where the robot drives to	Section 6
Change a speed, wait, rpm or servo position	Section 7
Know what is still a guess	Section 8

> **NOTE** Blue underlined text is a link. File names link to the file on GitHub (main branch). Use the PDF bookmarks panel, or the **Contents** link in every page footer, to jump around.

Contents

1 **Where the auto stands**

What runs today, what it scores, and what is still made up

2 **Set up and replicate**

Clone, build, run the sim, open the logs in AdvantageScope

3 **Check the wiring first**

Ten minutes before any tuning: names, directions, gear ratio

4 **Tune Pedro Pathing v3**

AutoTune web page: Mecanum, Pinpoint, Foresight, Tests

5 **Tune the mechanisms**

Shooters, gates, flower bar, intake pollen count, aim

6 **Change a pose**

Move a waypoint: Zenith, AutoPoses, the tests

7 **Change an action value**

Speeds, waits, rpm, servo positions: which file, which line

8 **Every value to measure on the robot**

The full list, grouped, with where each one lives

9 **Attached files and logs**

What is in the zip and how to use each part

10 **Links and documentation**

Every page this packet points to

1 Where the auto stands


What runs today, what it scores, and what is still made up

Two autos run the same route, and both pass every sim test on both alliances. **Pick the auto for your alliance**: the Zenith auto has one OpMode per alliance; the state-machine auto uses the **Choose Alliance** OpMode (run it before INIT; RED if never set).


OpMode name	What it is	File
Two tip (group Generated)	Zenith auto, **RED**: the route lives in `autos/two-tip.auto.json`, run by the SolversLib command runner.	`autos/two-tip.auto.json`
Two tip (BLUE) (group Generated)	Zenith auto, **BLUE**: Zenith's mirror of the RED file, written by `tools/mirror_auto.mjs`. Never edit it by hand.	`autos/two-tip-blue.auto.json`
Two Tip (state machine) (group BioHORS)	Hand-written: Pedro paths and one explicit state machine per mechanism. Easier to read and change by hand.	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/auto/TwoTipStateMachineAuto.java`
MainHORS TeleOp	Driver control; the autos pre-select it.	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/teleop/MainHorsTeleOp.java`

The route (RED; BLUE is the point mirror). Start on the south wall with 4 pollen, score them from *scoreSouth*, drive north and take pollen from the flower with the bar down, score from *scoreNorth*, come back down and sweep the garden row along the south wall with the bar stowed, drive back round the hive and score the third volley from *scoreNorth*, then park. In the sim it scores **12 of 12** pollen and tips the hive **twice**, touches nothing, and finishes in about **27.6 s** of the 30.

> **CAREFUL** **All of this is simulated.** No number on this robot is tuned yet. The poses come from FIRST's field CAD and the robot CAD, not a real field. The shot (exit angle and speed) is a what-if; the scoring spots and the auto rpm (1750) were picked in the sim to make that what-if shot land. **Filming one real shot is the most important measurement left** (Section 5d).




RED: zenith render two-tip.




BLUE: zenith render two-tip-blue, the same route turned 180 deg about the field centre.


What it looks like in AdvantageScope (frames from the physics run; the robot is the CAD model, the green line is the planned route, the orange line the driven path):




1.5 s into the auto.




4.6 s.




9.5 s.



14.5 s.



20.5 s.



23.5 s.

These frames were recorded just before the last small change (the garden sweep now goes 3.5 in further toward the corner and the flower pickup 0.35 in closer), so the robot in them stops a touch short of where it does now.

2 Set up and replicate

Clone, build, run the sim, open the logs in AdvantageScope

What you need. Android Studio (any recent one; its bundled JDK 17+ is what Gradle uses), git, and AdvantageScope 26 or newer to look at logs. Node.js 18+ only if you edit the Zenith auto.

1. Get the code.

```
git clone https://github.com/ZOGWORK/BioHORS.git
cd BioHORS
```

2. Run every test (the simulator). No robot needed; it takes about a minute. It runs both autos as full matches on both alliances, with and without ball physics, and writes logs to `TeamCode/build/sim/`.

```
# Windows PowerShell or cmd
.\gradlew.bat :TeamCode:testDebugUnitTest

# macOS / Linux / Git Bash
./gradlew :TeamCode:testDebugUnitTest
```

> **TIP** If Gradle says JAVA_HOME is not set, point it at Android Studio's JDK, e.g. `$env:JAVA_HOME = "C:\Program Files\Android\Android Studio\jbr"` in PowerShell.

3. Put it on the robot. Open the folder in Android Studio, plug in the Control Hub (or join its Wi-Fi), pick the **TeamCode** run configuration and press Run. On the Driver Station the OpModes appear under the names in Section 1.

4. Install the AdvantageScope assets (once per laptop). Open AdvantageScope once and pick the 2026-2027 FTC field so it downloads the field model, close it, then run (Python with numpy):

```
# Windows
python advantagescope/tools/build_hive_assets.py

# macOS (the script looks under APPDATA, so point it at the Mac folder)
APPDATA="$HOME/Library/Application Support" python3 advantagescope/tools/build_hive_assets.py


# Linux
APPDATA="$HOME/.config" python3 advantagescope/tools/build_hive_assets.py
```

That writes *2026-2027 Field (tipping hive)*, *Hive (Red)* and *Hive (Blue)* into AdvantageScope's `userAssets` folder (on Windows `%APPDATA%/AdvantageScope/userAssets`; AdvantageScope's **Show Assets Folder** menu item opens it on any system). Copy the folder `advantagescope/Robot_BioHORS` (the robot CAD model) into the same folder by hand, then restart AdvantageScope.

5. Open a log. Drag any `.rlog` from `TeamCode/build/sim/` (or from the attached zip) onto AdvantageScope. Add a **3D Field** tab, pick the field *2026-2027 Field (tipping hive)*, and drag these keys in:

Drag this key	As	Shows
RealOutputs/Field/Robot	Robot -> BioHORS	the robot (CAD model)
RealOutputs/Field/RobotComponents	Component (under the robot)	intake rollers spinning, flower bar moving
RealOutputs/Auto/PlannedRoute	Trajectory	the planned path (green)

Drag this key	As	Shows
RealOutputs/Auto/DrivenPath	Trajectory	where the robot really went
RealOutputs/Field/Pollen, NectarRed, NectarBlue	Game piece	every ball, flying and landing
RealOutputs/Field/HiveModelRed / Blue	Hive (Red) / Hive (Blue)	the hives, tipping



AdvantageScope with two-tip-red-physics.rlog: the keys on the left, the 3D field, and the Poses list at the bottom.

3 Check the wiring first

Ten minutes before any tuning: names, directions, gear ratio

Do this before any tuning. A motor spinning the wrong way makes every tuner give nonsense. The full checklist is section 0 of `docs/TUNING.md`.

Check	How	If wrong, change
Robot Controller config names	Must match exactly: frontLeft, backLeft, frontRight, backRight, intakeLeft, intakeRight, shooterRight (pollen), shooterLeft (nectar), gateRight (pollen), gateLeft (nectar), flowerLeft, flowerRight, pinpoint	The RC configuration on the Driver Station
Which shooter is pollen	Spin pollen alone in the Shooter Tuner; see which wheel turns. (Pollen on the right is assumed, not confirmed.)	`MechanismConstants` hardware names
Shooter directions	Both must throw the ball OUT at positive power	`POLLEN_SHOOTER_DIRECTION`, `NECTAR_SHOOTER_DIRECTION`
Shooter gear ratio	1:1 is confirmed; if it ever changes, ticksPerRev changes	`MechanismConstants.ticksPerRev`
Drive directions	Mecanum Tuner (Section 4, step 1)	`pedro/Constants` drivetrain
Flower bar servos	They face away from each other; the right one is reversed in code. Both must move the bar the same way	`FlowerBarController`
Intake	Both rollers pull IN at positive power	`IntakeController`

4 Tune Pedro Pathing v3

AutoTune web page: Mecanum, Pinpoint, Foresight, Tests

Pedro Pathing v3 tunes on the robot through **AutoTune**, a web page the robot itself serves. You do not run separate tuning OpModes any more: the procedures are listed on the page. This robot's procedures are in `TeamCode/src/main/java/org/firstinspires/ftc/teamcode/pedro/Tuning.java`; every result goes into `TeamCode/src/main/java/org/firstinspires/ftc/teamcode/pedro/Constants.java`. Official guide: https://pedropathing.com/docs/pathing/tuning.

Pedro pages to keep open while tuning: Mecanum, Pinpoint, Foresight, Tests, Constants, and what changed in Pedro 3.

Getting to the page

Step	Do
1	Deploy the code (Section 2, step 3). Fresh battery; a clear space of about 8 x 8 ft (Foresight drives fast in straight lines).
2	Connect the laptop to the Robot Controller's Wi-Fi (the same network the Driver Station uses).
3	Open http://192.168.43.1:10158 in a browser. That is the AutoTune page.
4	Pick a procedure from the list, follow its on-screen prompts, and run it with the Driver Station when it asks.
5	When it finishes, open its **Java** tab and copy the lines it gives you into `pedro/Constants.java` (the place for each is below). Redeploy before the next procedure.

The four procedures, in order

#	Procedure	What it finds	Paste into	Done when
1	Mecanum Tuner	Which way each drive motor must spin	`drivetrainConfig` motor directions	Every wheel drives the robot forward at positive power
2	Pinpoint Tuner	Pod directions and pod offsets (4-bar pods, device "pinpoint")	`localizerConfig`: xPodOffset (now -2.84, from CAD: compare), yPodOffset (0, placeholder), x/yPodDirection	Push forward: x goes up. Push left: y goes up. Spin 10 turns in place: drift under 1 in
3	Foresight Tuner	Top speeds, natural deceleration, heading P, coast/brake, brake coefficients	`foresightConfig()` and the MAX_FORWARD / MAX_STRAFE / *_DECEL constants	It finishes and prints values
4	Tests	Follows test paths with the tuned follower; includes the localization test	nothing; it checks	A 48 in line ends within 0.5 in; a 90 deg turn settles within 2 deg

> **CAREFUL** **Keep Zenith in step.** After Foresight, copy the same top speeds and decelerations into `autos/robot.json` (*kinematics*: maxForwardVelInPerS, maxStrafeVelInPerS, forwardDecelInPerS2, strafeDecelInPerS2) and change their provenance to CALIBRATED FROM ROBOT. Zenith's time estimate uses them, and the sim drive model reads them too.

> **TIP** Also copy the Pinpoint pod offsets into the sim, `X/Y_POD_OFFSET_IN` in `TeamCode/src/test/.../sim/BioHorsSim.java`, so the simulator matches the robot.

Then, once the robot drives real paths: record a few auto runs, and refit Zenith's acceleration and settle time from the *robot* traces (not the sim ones) with `npx zenith calibrate --write`.

5 Tune the mechanisms

Shooters, gates, flower bar, intake pollen count, aim

Each step has a full write-up in `docs/TUNING.md` (the section number is given). All values live in `TeamCode/src/main/java/org/firstinspires/ftc/teamcode/subsystems/MechanismConstants.java` unless the table says otherwise.

5a. Shooters (TUNING.md section 3)

Run the **Shooter Tuner** OpMode (group *Tuning*), robot on blocks, no pollen, fresh battery. It tunes pollen, then nectar, then checks both together, and prints lines. Paste them into each shooter's "tuned values" block in MechanismConstants. It sets kS, the feedforward reference and kP; it does **not** pick the target rpm.

5b. Target rpm (field test)

Teleop pollen target is 1600 rpm (the team's test value); the auto uses `AUTO_POLLEN_RPM` = 1750 (picked in the sim). Shoot from the auto's spots and trim in the teleop: **dpad left/right** trims pollen, **left bumper / A** trims nectar, 50 rpm a press. Write the rpm that lands 10 of 10 back into the file.

5c. Gates, flower bar, intake (sections 4, 4b, 4c)

What	How to find it	Values
Gates	Move each gate servo by hand in small steps (e.g. with a servo tester or a short test OpMode); write down where it fully blocks and fully clears a pollen.	POLLEN/NECTAR_GATE_OPEN 0.67, CLOSED 0.485
Flower bar	STOWED: folded back so nothing sticks past the frame (the auto drives 0.13 in off the wall!). DOWN: bar tip seats in the flower. SHOOTING: clear of the shot.	FLOWER_BAR_STOWED 0.05, DOWN 0.80, SHOOTING 0.65
Intake pollen count	Run the intake empty, read the speed (free); load the hopper, read it again (loaded). The auto counts pollen from how much the intake slows.	INTAKE_FREE_TICKS_PER_S 2800, INTAKE_LOADED_TICKS_PER_S 2100, settle 0.4 s, filter 0.3

5d. The shot (section 9a): the most important measurement left

Film one pollen shot from the side at 1750 rpm, with a ruler in frame. Measure the exit angle and the ball speed. Put them in the sim's ShotModel (`TeamCode/src/test/.../sim/`), rerun `ShotSweepTest`, and it reports the rpm and distance that seat a pollen. Only then move the scoring spots (Section 6) and set AUTO_POLLEN_RPM.

> **CAREFUL** With the CAD exit angle (44 deg) no spot inside the field scores at any rpm in the sim. The auto scores today only because of the what-if 70 deg shot. Do not trust the scoring spots until a shot is filmed.

5e. Aim (section 8)

In `TeamCode/src/main/java/org/firstinspires/ftc/teamcode/aim/AimController.java`: confirm the shooter fires out of the robot's front (SHOOTER_FACING_OFFSET_RAD = 0), then tune kP (1.2) until the robot turns onto the hive without oscillating; MIN_YAW (0.06) is the smallest command that still moves it.

6 Change a pose

Move a waypoint: Zenith, AutoPoses, the tests

A **pose** is a point and a heading on the field: x and y in inches, heading in radians. The auto drives between named poses called **waypoints**.

The field frame (used everywhere: auto, aim, sim)

Origin	Centre of the field
+X	Toward the audience's right (the BLUE side)
+Y	Away from the audience
Heading	Radians, counter-clockwise from +X. 90 deg = pi/2 = 1.5708 faces +Y (north); 180 deg = pi = 3.1416 faces -X (west); -90 deg faces south
Units	Inches. The walls are at x, y = +/-70.674 (FIRST CAD)
Alliances	Write RED only. BLUE is the point mirror: (x, y, h) -> (-x, -y, h + pi). The state-machine auto mirrors in code; the Zenith BLUE file is written by `tools/mirror_auto.mjs`

The waypoints today (RED)

Waypoint	x in	y in	heading	What it is
start	-13	-62.87	90 deg	Back to the south wall, facing the hive
scoreSouth	-13	-48	90 deg	First volley
scoreNorth	-13	48	-90 deg	Second and third volley
flowerNorthApproach	-24	42	90 deg	Lines up below the flower
flowerNorthPickup	-24	52.75	90 deg	Bar down, its tip at the flower
aboveGardenLane	-36	-54.7	180 deg	Above the garden row
gardenSweepStart	-40	-61.17	180 deg	Start of the sweep, by the south wall
gardenSweepEnd	-59.6	-61.62	180 deg	Front roller over the corner pollen
offGardenLane	-50	-50	180 deg	Back off the wall after the sweep
park	-54.7	36	180 deg	End of the auto

How to move one

The two autos keep their own copy of the points. Change both; a test fails if they disagree.

Step	Do this	Where
1	Edit the waypoint's xIn / yIn / headingRad, and update its *provenance* text (say what you measured and when). Easiest in the Zenith desktop app: `npx zenith open`, drag the point, save. Or edit the JSON by hand.	`autos/waypoints.json`
2	Check it: no wall, hive or flower in the way, and it fits in 30 s.	`npx zenith validate` `npx zenith estimate autos/two-tip.auto.json`

3	Write the BLUE auto again (Zenith's mirror of the RED one), copy both to the robot and refresh the generated Java. BlueAutoMirrorTest fails if you skip this.	`node tools/mirror_auto.mjs`
		`npx zenith deploy`
		`npx zenith codegen two-tip`
		`npx zenith codegen two-tip-blue`

4	Copy the same number into the state-machine auto's pose (named in CAPITALS, e.g. `GARDEN_SWEEP_END`).	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/auto/AutoPoses.java`
4b	Changed *start*? Also set the teleop's fallback start, used when the teleop runs without an auto before it: `DEFAULT_START_X_IN`, `DEFAULT_START_Y_IN`, `DEFAULT_START_HEADING_RAD`. Otherwise aim works from the old spot.	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/teleop/MainHorsTeleOp.java`
5	Run the tests. AutoPosesTest checks the two copies are equal; the match tests check both autos still score, tip, avoid contact and finish on time on both alliances.	`.\gradlew.bat :TeamCode:testDebugUnitTest`
6	Open `TeamCode/build/sim/two-tip-red.rlog` in AdvantageScope and watch it.	Section 2
7	Branch, commit, open a PR (never push to main).	GitHub

> **NOTE** **Curved legs.** Some legs are Bezier curves whose heading is split into short linear pieces (Pedro 3.0.2 cannot follow a tangent heading inside a piecewise heading without spinning). If you move a waypoint at the end of a curve, the heading pieces in `two-tip.auto.json` and `AutoPoses` were generated by `tools/zenith_headings.py`; regenerate them the same way, or the robot may twist on that leg.

> **TIP** **Measuring a waypoint on the real field:** put the robot where it should be, run the teleop, and read the Pinpoint pose off the telemetry (after it was started at the real start pose). That number, in the field frame, is the waypoint.

7 Change an action value

Speeds, waits, rpm, servo positions: which file, which line

An **action value** is anything the robot does rather than where it goes: how fast it drives a leg, how long it waits, the shooter rpm, a servo position. Each one is a named constant near the top of its file.

To change...	Edit	File
Shooter rpm in auto	`AUTO_POLLEN_RPM` (1750)	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/subsystems/MechanismConstants.java`
Shooter rpm in teleop	`POLLEN_SHOOTER.targetRpm` / nectar (1600)	same
Gate / flower bar positions	`*_GATE_OPEN/CLOSED`, `FLOWER_BAR_*`	same
Drive speed on a leg (state machine)	`DEFAULT_SPEED` 0.8, `PICKUP_SPEED` 0.3, `GARDEN_SWEEP_SPEED` 0.2, `SLIDE_SPEED` 0.3, `OFF_LANE_SPEED` 0.6	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/auto/TwoTipStateMachineAuto.java`
Waits (state machine)	`FLOWER_WAIT_S` 1.0, `GARDEN_WAIT_S` 0.8, `SPIN_UP_AFTER_S` 0.5, `SWEEP_TIMEOUT_S` 3.0	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/auto/TwoTipStateMachineAuto.java`
Drive speed / waits (Zenith auto)	a path step's *speedFraction*, a wait step's *timeoutS* / *seconds* (or in the Zenith app); then `zenith validate`, `deploy`, `codegen`	`autos/two-tip.auto.json`
Volley timing (both autos)	`SPINUP_TIMEOUT_S` 2.0, `FEED_S_PER_PIECE` 0.4, `FEED_EXTRA_S` 0.2	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/zenith/ScoreCommand.java`
Teleop stick feel	`STICK_DEADBAND`, `*_EXPO`, `MAX_*`	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/subsystems/DriveController.java`
Intake power	`INTAKE_POWER` 1.0, `OUTTAKE_POWER` -1.0	`TeamCode/src/main/java/org/firstinspires/ftc/teamcode/subsystems/IntakeController.java`
Zenith's idea of the robot	speeds, accel, settle times, footprint, mouth	`autos/robot.json`

Every time you change a value

1. Label it	Every number has a provenance comment. Change PLACEHOLDER to MEASURED / CALIBRATED FROM ROBOT / SET BY HAND, and say how you got it. Never present a guess as measured.
2. Test it	`.\gradlew.bat :TeamCode:testDebugUnitTest`: if a match test fails, the sim thinks the change breaks the auto. Read why before overriding.
3. Ship it	Branch, commit, PR. Greptile reviews it; merge when it is clean.

CAREFUL The sim tests use a few made-up plant numbers too (the shot, motor time constants). Do not change a PLACEHOLDER shot or sim constant just to make the auto score higher in the sim.

8 Every value to measure on the robot

The full list, grouped, with where each one lives

Everything below is a guess, a spec sheet number or a sim result. Work down the list roughly in this order: wiring, Pedro, shooters, mechanisms, then the field. The full generated list (every line with a PLACEHOLDER / NEEDS MEASUREMENT / SET FROM SIM label) is in the zip as `open-values.txt`.

Group	Value (file)	Now	Label	How to measure
Field	All 10 waypoints (waypoints.json + AutoPoses)	Section 6	SET BY HAND / SET FROM SIM	Drive there on a real field, read the Pinpoint
Field	Teleop start pose (MainHorsTeleOp DEFAULT_START_X/Y)	-13, -62.87	NEEDS MEASUREMENT	Same as the auto start
Pinpoint	yPodOffset (pedro/Constants)	0	PLACEHOLDER	Pinpoint Tuner
Pinpoint	xPodOffset	-2.84	MEASURED FROM CAD	Pinpoint Tuner: compare
Pinpoint	x/y pod directions	FORWARD	PLACEHOLDER	Pinpoint Tuner
Drive	MAX_FORWARD / MAX_STRAFE in/s	60 / 50	SET FROM SIM	Foresight Tuner
Drive	FORWARD / STRAFE_DECEL in/s^2	60 / 50	SET FROM SIM	Foresight Tuner
Drive	coast / brake kV, heading P	0.02 / 0.05, 3.0	SET FROM SIM	Foresight Tuner
Drive	heading / linear / quadratic brake coefficients	example	PLACEHOLDER	Foresight Tuner
Drive	translational P (fwd, strafe)	0.12/0.04, 0.15/0.06	SET FROM SIM	Tests: 48 in line within 0.5 in
Zenith	robot.json speeds and decels	60/50/60/50	SET FROM SIM	Copy from Foresight
Zenith	robot.json accelInPerS2, settleS	220, 0.4	CALIBRATED FROM SIM	zenith calibrate on robot traces
Zenith	robot.json maxAngularVelRadPerS	5	PLACEHOLDER	Spin at full yaw, read the Pinpoint
Zenith	robot.json shooter settleS	0.25	PLACEHOLDER	Time from at-speed to first good shot
Shooter	kP, kI, kD, kF, kS (MechanismConstants)	0.001, 0.0005, 0, 1, 0	PLACEHOLDER	Shooter Tuner
Shooter	ffReferenceMaxTicksPerSec	2800	SPEC (no load)	Shooter Tuner
Shooter	integralLimit, derivative/rpm/power alphas	50, 0.9, 0.72, 0.5	PLACEHOLDER	Leave unless noisy
Shooter	rpmTolerance	75 rpm	PLACEHOLDER	Shot-to-shot spread vs rpm
Shooter	Pollen / nectar targetRpm	1600 / 1600	SET BY HAND	Field test (5b)
Shooter	AUTO_POLLEN_RPM	1750	PLACEHOLDER, SET FROM SIM	After the shot is filmed (5d)
Shooter	Pollen motor = shooterRight	-	assumed	Section 3
Shooter	Shooter directions	FORWARD	PLACEHOLDER	Section 3
Gates	POLLEN/NECTAR_GATE_OPEN / CLOSED	0.67 / 0.485	PLACEHOLDER	Move by hand (5c)
Flower bar	FLOWER_BAR_STOWED / DOWN / SHOOTING	0.05 / 0.80 / 0.65	PLACEHOLDER	Move by hand (5c)
Intake	INTAKE_POWER / OUTTAKE_POWER	1.0 / -1.0	PLACEHOLDER	Collect test
Intake	INTAKE_FREE / LOADED_TICKS_PER_S	2800 / 2100	PLACEHOLDER	Read empty and full (5c)

Group	Value (file)	Now	Label	How to measure
Intake	INTAKE_SENSE_SETTLE_S, FILTER_ALPHA	0.4, 0.3	PLACEHOLDER	Watch the count on telemetry
Aim	SHOOTER_FACING_OFFSET_RAD	0	PLACEHOLDER	Which way the shot leaves
Aim	kP, MAX_YAW, MIN_YAW, tolerance	1.2, 0.7, 0.06, 2 deg	PLACEHOLDER	Aim on the field (5e)
Teleop	STICK_DEADBAND, TRANSLATION/YAW_EXPO, MAX_*	0.05, 1.6/1.8, 1.0/0.85	PLACEHOLDER	Driver preference
Auto	SPINUP_TIMEOUT_S, FEED_S_PER_PIECE, FEED_EXTRA_S	2.0, 0.4, 0.2	PLACEHOLDER	Time a real volley
Auto	State machine speeds (DEFAULT ... OFF_LANE)	0.8 .. 0.2	SET BY HAND	Run the auto; slow down where it misses
Auto	FLOWER_WAIT_S, GARDEN_WAIT_S, SWEEP_TIMEOUT_S	1.0, 0.8, 3.0	SET BY HAND	Run the auto
Sim	ShotModel exit angle and grip (test side)	70 deg, 0.8	WHAT-IF	Film a shot (5d)
Sim	X/Y_POD_OFFSET_IN (BioHorsSim)	0, 0	copy	Copy from the robot

9 Attached files and logs

What is in the zip and how to use each part

The zip **BioHORS_team_packet.zip** holds everything needed to see what the sim saw, without building anything. It is too big for git, so it is shared alongside this PDF; to build a fresh one from your own checkout (after running the tests, Section 2), run:

```
python docs/packet/make_zip.py      # writes build/BioHORS_team_packet.zip
```

Folder in the zip	What	Use it to
BioHORS_Team_Packet.pdf	This packet	Read
logs/*.rlog	Every sim run: two-tip-red / two-tip-blue (Zenith autos), two-tip-red-physics / two-tip-blue-physics (real ball physics), state-machine-red / blue, physics-tip-demo(-blue), mechanisms-demo, teleop-aim, ...	Drag onto AdvantageScope (Section 2, step 5)
logs/*.trace.json	Per-step timing traces of the Zenith auto	npx zenith sim / calibrate
videos/*.mp4	Screen recordings of the auto in AdvantageScope	Show the team
autos/	robot.json, waypoints.json, two-tip.auto.json, two-tip-blue.auto.json, the field file, zenith.json	Open in the Zenith app; the source of the route
advantagescope/	Robot_BioHORS model + config, the hive asset tools	Install the 3D assets
docs/	TUNING.md (the long tuning brief), ROBOT_CAD.md, two-tip.png	Detail behind Sections 4-5
open-values.txt	Every placeholder line in the code, with file and line number	The checklist
screenshots/	The images in this PDF at full size	Slides, posters

> **NOTE** The logs are regenerated every time the tests run. To make a fresh one after a change, run the tests and look in `TeamCode/build/sim/`.

Which test writes which log

Log	Test	What it proves
two-tip-red / blue	ZenithAutoMatchTest	12 scored, 2 tips, no contact, under 30 s, both alliances
two-tip-red / blue-physics	ZenithAutoMatchTest (physics)	The same with real ball flight and landing
(no log)	BlueAutoMirrorTest	The BLUE Zenith file is the mirror of the RED one
state-machine-red / blue	StateMachineAutoMatchTest	The hand-written auto does the same
physics-tip-demo	PhysicsTipDemoTest	The hive tips when the balls land, not before
mechanisms-demo	MechanismsDemoTest	Intake spins, flower bar moves
teleop-aim	MainHorsTeleOpSimTest	Teleop aim turns the chassis onto the hive

10 Links and documentation

Every page this packet points to

What	Link
Our repository	https://github.com/ZOGWORK/BioHORS
Tuning brief (long version of Sections 3-5)	https://github.com/ZOGWORK/BioHORS/blob/main/docs/TUNING.md
Robot CAD notes	https://github.com/ZOGWORK/BioHORS/blob/main/docs/ROBOT_CAD.md
Agent / sim rules for this repo	https://github.com/ZOGWORK/BioHORS/blob/main/AGENTS.md
Pedro Pathing docs	https://pedropathing.com/docs
What is new in Pedro 3	https://pedropathing.com/docs/pathing/pedro3
Tuning overview	https://pedropathing.com/docs/pathing/tuning
Mecanum tuning	https://pedropathing.com/docs/pathing/tuning/drivetrain/mecanum
Localization	https://pedropathing.com/docs/pathing/tuning/localization
Pinpoint	https://pedropathing.com/docs/pathing/tuning/localization/pinpoint
Foresight	https://pedropathing.com/docs/pathing/tuning/foresight
Constants	https://pedropathing.com/docs/pathing/tuning/constants
Tests	https://pedropathing.com/docs/pathing/tuning/test
AutoTune (only while on the robot's Wi-Fi)	http://192.168.43.1:10158
Pedro path visualizer	https://visualizer.pedropathing.com/
Pedro Javadoc	https://javadoc.io/doc/com.pedropathing
Pedro GitHub / Discord	github.com/Pedro-Pathing / discord.gg/bqRdAjEmjk
Zenith (auto planner)	https://zenith.horizon36596.org/
SimLoop (the simulator)	https://libraries.horizon36596.org/simloop/
SimLoop: what it does not do	https://libraries.horizon36596.org/simloop/limits/
SimLoop: troubleshooting	https://libraries.horizon36596.org/simloop/troubleshooting/
AdvantageScope	https://docs.advantagescope.org/
FTC SDK docs	https://ftc-docs.firstinspires.org/
goBILDA Pinpoint	gobilda.com: Pinpoint odometry computer

> **TIP** Stuck? In this order: the Pedro Discord for drive tuning; `docs/TUNING.md` for our mechanisms; the SimLoop limits page before blaming the sim.