ZOTAC ZBOX PRO SERIES

ZOTAC

S35W3 / S35W3DX

SKU ZP-S35W3 / ZP-S35W3DX

FANLESS EMBEDDED PC · INTEL CORE 3 304 · EDGE AI

概要 – OVERVIEW

Intel Core 3 プロセッサー 304（組み込み向け CPU）を搭載した、3.5 インチ SBC ベースの 0.82L ファンレス組み込み PC「ZBOX PRO S35W3 / S35W3DX」。HDMI 2.0 ×3 の独立 3 画面、RS-232/422/485 と 8 ビット GPIO の端子台、2.5GbE、DC 9〜36V 入力を備え、-20〜+45°C での 24 時間運用を想定した設計です。内蔵 NPU で 15 TOPS、DX モデルは DeepX DX-M1 NPU モジュールを加えて合計 40 TOPS のエッジ AI 処理に対応します。



ファンレス
0.82L・全金属筐体

15 / 40 TOPS
内蔵 NPU ／ DX は DX-M1 を搭載

HDMI 2.0 ×3
独立 3 画面出力

−20〜+45°C
DC 9〜36V ワイドレンジ入力









Wi-Fi 7 | **2.5GbE** LAN | **RS-232** / 422 / 485 | **8-bit** GPIO | **DDR5**-6400 | **M.2** NVMe ×2

技術仕様 – TECHNICAL SPECIFICATIONS

■ プロセッサー

Intel Core 3 Processor 304
5 コア / 最大 4.3GHz / 組み込み向け

■ グラフィックス

Intel Graphics
最大 2.3GHz

■ AI 性能

内蔵 NPU 15 TOPS
DX モデル: DeepX DX-M1（25 TOPS）
合計 40 TOPS
OpenVINO / WindowsML / ONNX Runtime

■ メモリー

1 × DDR5-6400 SO-DIMM
最大 64GB

■ ストレージ

2 × M.2 2280 NVMe Gen4
各 2 レーン

■ 映像出力

3 × HDMI 2.0
独立 3 画面

■ ネットワーク

1 × 2.5 Gigabit Ethernet
Wi-Fi 7 802.11be
Bluetooth 5.4

■ インターフェース

2 × USB 3.2 Type-A
3 × USB 2.0
RS-232 / RS-422 / RS-485・8 × GPIO
2×9 ピン端子台

■ 冷却 / 電源 / 動作温度

ファンレス（全金属筐体）
DC 9〜36V
本体 −20〜+45°C

■ 外形寸法

164.0 × 110.8 × 45.0 mm
W × D × H ／ 0.82L

■ 対応OS

Windows 11
Ubuntu Linux

■ 構成

ベアボーン
メモリー・SSD・OS は別途
構成はお問い合わせください

Manufactured by PCP SOLUTIONS (PC Partner Limited) and offered in Japan as ZBOX PRO. Product information ©2026 PC Partner Limited; Japanese edition by ZOTAC NIPPON. All company and/or product names may be trade names, trademarks and/or registered trademarks of the respective owners. Specifications are subject to change without notice. Intel, Intel Core and OpenVINO are trademarks of Intel Corporation. DeepX and DX-M1 are trademarks of DEEPX Co., Ltd. The terms HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks of HDMI Licensing Administrator, Inc.

製品情報　お問い合わせ