


Unless noted otherwise:
– Resistors: 0603, Thick Film
– Capacitors: 0603, Ceramic, 50V, X7R, 10%



Power



File: power.kicad_sch

Logic



File: logic.kicad_sch

Glastra

Sheet: /
File: stabielator.kicad_sch

Title: **Stabielator**

Size: A4	Date: 2026-09-07	Rev: v0.1.0
KiCad E.D.A. 10.0.3		Id: 1/3

[illegible]

Push-pull, active-high latched RESET
 Active-low push-button input
 KILL debounce/duration = 500 ms
 Clpt = 4n7 = 2s long-press time
 Clpt = open = 50ms short press-time

The schematic diagram illustrates the electrical connections for the USB4105-GF-A module. The module's pinout is as follows:

- Top Pins (A4, B4, A9, B9):** All connected to VBUS.
- Top Pins (A6, B6):** Connected to DP1 and DP2.
- Top Pins (A7, B7):** Connected to DN1 and DN2.
- Top Pins (A5, B5):** Connected to CC1 and CC2.
- Bottom Pins (A8, B8):** Connected to SBU1 and SBU2.
- Bottom Pins (A1, A12, B1, B12):** All connected to GND.
- Left Pins (S1, S2, S3, S4):** Connected to a common ground point.

External components and connections include:

- Power:** A 5V supply is connected to the VBUS line through a 1A Polyfuse (F1). A 5V_DEBUG test point (TP11) is also connected to this line.
- USB-C Connector:** A USBLC6-2SC6 connector is used. Pins 1 and 3 are connected to DP1 and DP2. Pins 2 and 4 are connected to DN1 and DN2. Pins 5 and 6 are connected to CC1 and CC2. Pins 7 and 8 are connected to SBU1 and SBU2. Pins 9 and 10 are connected to GND.
- Resistors:** R24 (1M) is connected between the common ground point and the module's ground. R26 (22R) and R27 (22R) are connected between the USB-C pins 1/3 and 2/4 respectively and the module's ground. R22 (5k1) and R25 (5k1) are connected between the module's ground and the USB-C pins 5/6 and 7/8 respectively.
- Test Points:** TP13 (GND_DEBUG) is connected to the module's ground.

VBAT

R66
300k 0.1%

R67
100k 0.1%

GND

BATTERY

C53
100n

GND

Rev: v0.1.0
Id: 2/3

