

DROP FORGED TURNBUCKLES

JAW & EYE · JAW & JAW · ROD END EYE & EYE · HOT GALVANIZED OR SELF-COLORED · WLL 500 TO 10,000 LBS.




BENEFITS & FEATURES

- Drop forged steel — eye, jaw and hook fittings are heat treated
- Recommended for straight or in-line pull only**
- Meets or exceeds all requirements of **ASME B30.26** including identification, ductility, design factor, proof load and temperature requirements
- Meets the performance requirements of Federal Specification **F1145 Type 1 Form 1** and **ASTM FF-T-791B**
- Available with hot galvanized or self-colored finish
- Jaw types supplied with round pins and cotter keys unless nuts and bolts are specified
- Locking nuts available for all sizes
- Material traceability through the Product Identification Code (PIC) system

⚠ Turnbuckles are recommended for straight or in-line pull only. Loads are based on a design factor of 5 to 1.

JAW & EYE DIMENSIONS



HOT GALVANIZED TURNBUCKLES — JAW & EYE AND JAW & JAW

DIAMETER & TAKE-UP	JAW & EYE — HOT GALVANIZED			JAW & JAW — HOT GALVANIZED		
	PART NO.	CLOSED LENGTH	WEIGHT PER 100	PART NO.	CLOSED LENGTH	WEIGHT PER 100
1/4" x 4"	02605 5	8-1/4"	37.5	03055 7	8-1/2"	40
5/16" x 4-1/2"	02610 9	9-1/8"	52.5	03060 1	9-1/4"	52.5
3/8" x 6"	02615 4	11-1/2"	96.5	03065 6	11-1/2"	97.5
1/2" x 2"	02620 8	8-3/4"	109	03070 0	8-7/8"	119
1/2" x 6"	02623 9	13-1/4"	160	03073 1	13-1/2"	170
1/2" x 9"	02626 0	16-1/4"	198.5	03076 2	16-1/2"	202.5
1/2" x 12"	02629 1	19-1/4"	225	03079 3	19-1/2"	227.5
5/8" x 6"	02634 5	14-5/8"	257.5	03084 7	15-3/4"	260.5
5/8" x 9"	02637 6	17-7/8"	330	03087 8	18-3/4"	330
5/8" x 12"	02640 6	21-1/8"	402	03090 8	21-3/4"	407
5/8" x 18"	02643 7	27-1/8"	581	03093 9	27-3/4"	607
3/4" x 6"	02648 2	15-5/8"	402.5	03098 4	16-1/2"	417.5
3/4" x 9"	02651 2	18-3/4"	522.5	03101 1	19-1/2"	545
3/4" x 12"	02654 3	22"	602.5	03104 2	22-1/2"	619.5
3/4" x 18"	02657 4	28"	702	03107 3	28-1/2"	753
7/8" x 6"	02662 8	19"	655	03112 7	19-1/2"	668
7/8" x 12"	02665 9	23-1/2"	842.5	03115 8	24-1/2"	862.5
7/8" x 18"	02668 0	29-1/2"	1252	03118 9	30-1/2"	1281
1" x 6"	02673 4	19-1/8"	872	03123 3	20-3/16"	911
1" x 12"	02676 5	25-1/4"	1137.5	03126 4	25-1/2"	1165
1" x 18"	02679 6	31-1/4"	1463	03129 5	31-1/2"	1518

ROD END EYE & EYE

SELF-COLORED			
DIAMETER & TAKE-UP	PART NO.	CLOSED LENGTH	WEIGHT PER 100
1/2" x 6"	03373 2	13"	131
5/8" x 6"	03384 8	13-1/4"	205
3/4" x 6"	03398 5	13-1/2"	293
7/8" x 6"	03412 8	14"	456
1" x 6"	03423 4	14-1/8"	589

JAW DIMENSIONS & STRENGTH

A	B	C	D	E*	F	H**	P	WLL (LBS.)†
1/4"	7/32"	5/16"	25/32"	3/8"	5/8"	9/32"	1/4"	500
5/16"	1/4"	5/16"	7/8"	15/32"	5/8"	9/32"	1/4"	800
3/8"	9/32"	13/32"	1"	1/2"	13/16"	11/32"	5/16"	1,200
1/2"	5/16"	1/2"	1-9/32"	5/8"	1"	15/32"	7/16"	2,200
5/8"	3/8"	21/32"	1-21/32"	7/8"	1-5/16"	35/64"	1/2"	3,500
3/4"	1/2"	13/16"	1-27/32"	15/16"	1-5/8"	43/64"	5/8"	5,200
7/8"	9/16"	29/32"	1-31/32"	1-5/32"	1-7/8"	25/32"	3/4"	7,200
1"	11/16"	1-1/16"	2-13/32"	1-3/16"	2"	15/16"	7/8"	10,000

EYE DIMENSIONS & STRENGTH

A	C	D	E	WLL (LBS.)†
1/4"	1/2"	1"	7/32"	500
5/16"	5/8"	1-1/4"	9/32"	800
3/8"	3/4"	1-1/2"	11/32"	1,200
1/2"	1"	2"	7/16"	2,200
5/8"	1-1/4"	2-5/16"	17/32"	3,500
3/4"	1-1/2"	2-3/4"	5/8"	5,200
7/8"	1-3/4"	3-1/2"	7/8"	7,200
1"	2"	3-3/4"	7/8"	10,000

All dimensions in inches. * At parting line; includes 7° draft. ** Hole size. † Loads are based on a design factor of 5 to 1. Eye, jaw and hook fittings are heat treated. Jaw types are supplied with round pins and cotter keys unless nuts and bolts are specified; locking nuts are available for all sizes.

CALL FOR CUSTOMIZED CONFIGURATIONS

866-848-2032 · murphylift.com · Lock nuts, self-colored finish & custom assemblies available