

ALLOY FITTINGS · GRADE 100

MURPHYLIFT.COM

GRADE 100 ALLOY FITTINGS — CLEVIS

CONNECTING LINKS · SLING, GRAB, FOUNDRY & SELF-LOCKING HOOKS · CHAIN 7/32" TO 1-1/4" · WLL TO 90,400 LBS.

CLX — CONNECTING LINK



PART #	CHAIN SIZE	WLL (LBS.)	A	C	O	R	P	S	WEIGHT (LBS.)
CLX06	7/32-1/4	3,000	0.55	0.71	0.71	1.77	0.31	0.30	0.15
CLX07	9/32	4,300	0.70	0.79	0.81	1.99	0.40	0.35	0.31
CLX08	5/16	5,700	0.75	1.00	0.93	2.44	0.45	0.39	0.44
CLX10	3/8	8,800	0.94	1.18	1.08	2.83	0.50	0.50	0.77
CLX13	1/2	15,000	1.10	1.42	1.31	3.44	0.75	0.66	1.63
CLX16	5/8	22,600	1.35	1.59	1.56	4.13	0.81	0.81	2.56
CLX20	3/4	35,300	1.65	1.81	1.81	4.45	1.10	0.98	5.51
CLX22	7/8	42,700	1.93	2.17	2.28	5.24	1.14	1.10	6.83
CLX26	1	59,700	2.24	3.35	2.76	7.56	1.57	1.18	14.99
CLX32	1-1/4	90,400	3.15	3.33	3.70	8.11	1.85	1.38	25.35

CBX_SF — CLEVIS SLING HOOK WITH FORGED LATCH



PART #	CHAIN SIZE	WLL (LBS.)	A	A1	B	C	G	H	R	P X L	WEIGHT (LBS.)
CBX06SF	7/32-1/4	3,000	1.02	0.75	0.28	0.31	0.59	0.79	2.72	0.30 x 0.69	0.68
CBX07SF	9/32	4,300	1.34	1.02	0.37	0.39	0.75	1.10	3.74	0.35 x 0.89	1.41
CBX08SF	5/16	5,700	1.34	1.02	0.37	0.39	0.75	1.10	3.74	0.39 x 0.89	1.36
CBX10SF	3/8	8,800	1.57	1.22	0.47	0.53	0.98	1.30	4.33	0.51 x 1.16	2.59
CBX13SF	1/2	15,000	2.01	1.57	0.59	0.67	1.18	1.57	5.35	0.63 x 1.46	4.66
CBX16SF	5/8	22,600	2.20	1.77	0.71	0.87	1.46	1.89	6.10	0.79 x 2.05	7.67
CBX20SF	3/4	35,300	2.36	2.09	0.91	1.02	2.01	2.05	7.28	0.94 x 2.87	14.99
CBX22SF	7/8	42,700	2.76	2.44	1.02	1.14	1.97	2.48	8.27	1.02 x 2.83	20.08

CFX — CLEVIS GRAB HOOK WITH SADDLE



PART #	CHAIN SIZE	WLL (LBS.)	A	B	C	G	H	R	M	P X L	WEIGHT (LBS.)
CFX06	7/32-1/4	3,000	0.31	0.29	0.35	0.87	0.87	2.03	1.40	0.30 x 0.69	0.44
CFX07	9/32	4,300	0.39	0.39	0.45	1.18	1.10	2.62	1.85	0.35 x 0.89	0.97
CFX08	5/16	5,700	0.39	0.39	0.43	1.18	1.10	2.60	1.85	0.39 x 0.89	0.97
CFX10	3/8	8,800	0.51	0.51	0.59	1.73	1.34	3.15	2.17	0.51 x 1.24	2.12
CFX13	1/2	15,000	0.67	0.63	0.69	2.09	1.85	4.15	3.19	0.63 x 1.65	4.63
CFX16	5/8	22,600	0.75	0.75	0.72	2.52	2.36	4.40	3.62	0.83 x 2.03	7.50
CFX20	3/4	35,300	0.93	0.91	0.87	3.35	2.56	4.65	3.94	0.94 x 2.42	11.46
CFX22	7/8	42,700	1.02	1.02	0.98	3.62	2.68	6.06	4.72	1.02 x 2.83	17.2

CFX_S — CLEVIS GRAB HOOK WITH SADDLE & LATCH



PART #	CHAIN SIZE	WLL (LBS.)	A	B	C	G	H	R	M	P X L	WEIGHT (LBS.)
CFX06S	7/32-1/4	3,000	0.31	0.31	0.35	0.87	0.87	1.99	1.40	0.30 x 0.69	0.44
CFX07S	9/32	4,300	0.39	0.39	0.45	1.18	1.10	2.62	1.85	0.35 x 0.89	0.97
CFX08S	5/16	5,700	0.39	0.39	0.43	1.18	1.10	2.60	1.85	0.39 x 0.89	0.97
CFX10S	3/8	8,800	0.51	0.51	0.59	1.73	1.34	3.15	2.17	0.51 x 1.24	2.12
CFX13S	1/2	15,000	0.67	0.63	0.69	2.09	1.85	4.15	3.19	0.63 x 1.65	4.63
CFX16S	5/8	22,600	0.75	0.75	0.72	2.52	2.36	4.40	3.62	0.83 x 2.03	7.50

CYFX — CLEVIS FOUNDRY HOOK



PART #	CHAIN SIZE	WLL (LBS.)	A	B	C	G	H	R	P X L	WEIGHT (LBS.)
CYFX06	7/32-1/4	3,000	2.11	0.33	0.26	0.87	1.02	3.58	0.30 x 0.69	1.54
CYFX07	9/32	4,300	2.52	0.39	0.45	1.02	1.22	4.74	0.35 x 0.89	2.43
CYFX08	5/16	5,700	2.52	0.39	0.45	1.02	1.22	4.74	0.39 x 0.89	2.43
CYFX10	3/8	8,800	2.99	0.51	0.59	1.18	1.34	5.16	0.51 x 1.24	3.75
CYFX13	1/2	15,000	3.50	0.67	0.69	1.57	1.75	5.83	0.63 x 1.65	7.94
CYFX16	5/8	22,600	3.98	0.75	0.85	1.77	1.99	7.81	0.83 x 2.03	12.35

CRFX — CLEVIS SELF LOCKING HOOK



PART #	CHAIN SIZE	WLL (LBS.)	A	B	C	G	H	R	T	P X L	WEIGHT (LBS.)
CRFX06	7/32-1/4	3,000	1.10	0.28	0.31	0.63	0.83	3.70	1.38	0.30 x 0.69	1.10
CRFX07	9/32	4,300	1.34	0.35	0.39	0.79	1.02	4.84	1.69	0.35 x 0.89	2.09
CRFX08	5/16	5,700	1.34	0.35	0.39	0.79	1.02	4.84	1.69	0.39 x 0.89	2.09
CRFX10	3/8	8,800	1.77	0.47	0.55	0.98	1.18	5.63	2.20	0.51 x 1.24	3.53
CRFX13	1/2	15,000	2.01	0.59	0.67	1.38	1.57	7.09	2.72	0.63 x 1.65	7.05
CRFX16	5/8	22,600	2.36	0.75	0.75	1.42	1.97	8.46	3.15	0.83 x 2.03	13.23
CRFX20	3/4	35,300	2.76	0.91	1.02	2.36	2.64	9.96	3.54	0.94 x 2.87	21.61
CRFX22	7/8	42,200	3.23	1.02	1.26	2.44	2.76	11.30	3.94	1.02 x 2.83	31.75

Grade 100 alloy steel, heat treated. All dimensions in inches, weights in pounds. Working load limits are based on a 4:1 design factor and apply to a straight in-line pull. Fittings must be matched to the chain size shown — the rated capacity of an assembly is limited by its lowest-rated component. Do not exceed the rated WLL. Inspect before each use and remove from service if deformed, cracked or worn.

CALL FOR GRADE 100 CHAIN & FITTINGS

866-848-2032 · murphylift.com · Grade 100 chain, master links & sling assemblies in stock

ALLOY FITTINGS · GRADE 100

MURPHYLIFT.COM

GRADE 100 ALLOY FITTINGS — EYE & SWIVEL

SLING, FOUNDRY, GRAB & SELF-LOCKING HOOKS · SWIVEL SELF-LOCKING · CHAIN 7/32" TO 1-1/4" · WLL TO 90,400 LBS.

CAX_SF — EYE SLING HOOK WITH FORGED LATCH



PART #	CHAIN SIZE	WLL (LBS.)	A	A1	D	G	H	O	R	WEIGHT (LBS.)
CAX06SF	7/32-1/4	3,000	1.02	0.75	0.39	0.63	0.79	0.79	3.19	0.55
CAX08SF	9/32-5/16	5,700	1.30	1.02	0.43	0.75	1.14	0.98	3.98	1.10
CAX10SF	3/8	8,800	1.57	1.22	0.63	1.02	1.30	1.34	5.16	2.14
CAX13SF	1/2	15,000	2.01	1.57	0.75	1.30	1.65	1.69	6.26	4.19
CAX16SF	5/8	22,600	2.20	1.77	0.96	1.57	1.97	1.97	7.20	7.28
CAX20SF	3/4	35,300	2.36	2.05	1.06	1.89	2.09	2.17	7.99	9.92
CAX22SF	7/8	42,700	2.76	2.44	1.14	1.97	2.36	2.36	8.82	15.65
CAX26SF	1	59,700	3.03	2.87	1.38	2.36	2.95	2.76	10.12	26.46
CAX32SF	1-1/4	90,400	4.02	3.70	1.65	2.87	3.58	3.31	13.19	61.06

CYX — EYE FOUNDRY HOOK



PART #	CHAIN SIZE	WLL (LBS.)	A	D	G	H	O	R	WEIGHT (LBS.)
CYX06	7/32-1/4	3,000	2.11	0.45	0.87	1.02	0.59	4.04	1.34
CYX08	9/32-5/16	5,700	2.44	0.53	0.98	1.14	0.94	5.04	2.03
CYX10	3/8	8,800	2.99	0.55	0.90	1.18	1.26	5.91	3.90
CYX13	1/2	15,000	3.50	0.75	1.50	1.57	1.06	6.81	6.22
CYX16	5/8	22,600	4.02	0.94	1.77	1.89	1.85	8.27	11.09
CYX20	3/4	35,300	4.49	1.10	2.13	2.36	2.20	10.24	16.76
CYX22	7/8	42,700	5.00	1.26	2.48	2.76	2.17	10.83	27.12
CYX26	1	59,700	5.35	1.38	2.83	3.15	2.44	12.01	39.46
CYX32	1-1/4	90,400	6.02	1.50	3.31	3.74	2.76	12.99	60.19

CROX — EYE SELF LOCKING HOOK



PART #	CHAIN SIZE	WLL (LBS.)	A	D	G	H	O	R	T	WEIGHT (LBS.)
CROX06	7/32-1/4	3,000	1.10	0.43	0.63	0.83	0.83	4.29	1.38	1.10
CROX08	9/32-5/16	5,700	1.34	0.47	0.79	1.02	1.06	5.31	1.69	2.12
CROX10	3/8	8,800	1.77	0.63	0.98	1.18	1.34	6.61	2.20	3.64
CROX13	1/2	15,000	2.01	0.79	1.38	1.57	1.57	8.07	2.72	7.17
CROX16	5/8	22,600	2.36	1.06	1.42	1.97	1.97	9.88	3.15	13.45
CROX20	3/4	35,300	2.76	1.18	2.36	2.64	2.36	11.42	3.54	21.61
CROX22	7/8	42,700	3.15	1.26	2.44	2.76	2.76	12.68	3.94	31.75

CDX — EYE GRAB HOOK WITH SADDLE



PART #	CHAIN SIZE	WLL (LBS.)	A	D	G	H	O	R	M	WEIGHT (LBS.)
CDX06	7/32-1/4	3,000	0.31	0.33	0.87	0.87	0.53	2.11	1.40	0.40
CDX08	9/32-5/16	5,700	0.39	0.43	1.18	1.10	0.67	2.76	1.85	0.88
CDX10	3/8	8,800	0.51	0.59	1.73	1.34	0.87	3.41	2.17	1.94
CDX13	1/2	15,000	0.67	0.71	2.09	1.85	1.02	4.35	3.19	4.30
CDX16	5/8	22,600	0.75	0.83	2.52	2.36	1.26	5.08	3.62	7.05
CDX20	3/4	35,300	0.93	0.91	3.35	2.52	1.50	6.04	3.94	10.80
CDX22	7/8	42,700	1.02	1.18	3.43	2.80	1.65	7.24	4.53	16.53
CDX26	1	59,700	1.20	1.42	3.94	3.54	2.17	8.39	5.00	28.66
CDX32	1-1/4	90,400	1.52	1.73	6.30	4.41	2.36	9.65	7.87	67.24

CRGX — SWIVEL SELF LOCKING HOOK



PART #	CHAIN SIZE	WLL (LBS.)	R	A	B	O	D	G	H	T	WEIGHT (LBS.)
CRGX06	7/32-1/4	3,000	6.30	1.10	1.06	1.42	0.51	0.63	0.83	1.38	1.32
CRGX08	9/32-5/16	5,700	7.17	1.34	1.06	1.42	0.51	0.79	1.02	1.69	2.43
CRGX10	3/8	8,800	8.54	1.77	1.38	1.77	0.63	0.98	1.18	2.20	4.41
CRGX13	1/2	15,000	10.67	2.13	1.77	1.97	0.83	1.38	1.57	2.72	8.82
CRGX16	5/8	22,600	12.60	2.44	2.28	2.44	0.94	1.50	1.97	3.15	14.99

Grade 100 alloy steel, heat treated. All dimensions in inches, weights in pounds. Working load limits are based on a 4:1 design factor and apply to a straight in-line pull. Fittings must be matched to the chain size shown — the rated capacity of an assembly is limited by its lowest-rated component. Do not exceed the rated WLL. Inspect before each use and remove from service if deformed, cracked or worn.

CALL FOR CUSTOM SLING ASSEMBLIES

866-848-2032 · murphylift.com · Grade 100 chain, master links & sling assemblies in stock