



CZ UNIVERSAL PLATE CLAMP

VERTICAL LIFTING & 180° TURNING · JAW CAPACITY TO 5" · DESIGN FACTOR 4:1 · WLL 120 TO 66,000 LBS.

CZ plate clamps can be used on all hot rolled structural steel plates and sections up to a surface hardness of **300 Brinell (32 HRC)**.

BENEFITS & FEATURES

- Body of clamp is welded construction
- Lifts a plate from horizontal to vertical position and vice versa through **180°**
- Clamp jaws and pads manufactured from high-tensile steel
- Fitted with a hold-open and lock-closed lever. A spring gives an initial bite on the material; if the plate starts to slip, the cam shape of the jaw turns with the material and increases gripping force
- Cam handle is ergonomically designed with a flat surface for ease of operation while wearing protective gloves
- Cam handle connects to the cam via a robust square drive
- Designed with a sloping slot, which increases grip on the load when the clamp is in the horizontal position
- **Design factor 4:1**



INSPECTION, CARE & USE

- DO NOT** side load the clamp more than 15° — use a type CY or CX clamp for side loading
- DO NOT** lift plates with a temperature greater than 120°C / 250°F

- DO NOT** use to lift stainless steel, lead or copper — for stainless steel plates use an LJ or HG clamp
- DO NOT** use on a double, triple or quad sling. When using two clamps to lift a steel plate, a lifting beam must be used between the two clamps so they operate in a vertical position. Use a CY or CX clamp for slings with more than one leg

RATED CAPACITIES & DIMENSIONS

PRODUCT CODE	WORKING LOAD LIMIT		JAW CAPACITY (IN.)	DIMENSIONS (IN.)								WEIGHT (LBS.)
	MIN. (LBS.)	MAX. (LBS.)		A	B	C	D	E	F	G	H	
92 500	120	1,100	0 to 5/8	3.898	7.677	1.142	1.299	1.850	1.969	0.393	0.433	3.3
92 1500	350	3,300	0 to 3/4	4.961	8.858	1.969	1.929	2.756	3.228	0.472	0.472	6.6
92 2000	450	4,400	0 to 1-1/4	7.559	12.283	3.150	2.953	3.780	3.937	0.787	0.787	17.6
92 3000	675	6,600	0 to 1-1/4	7.559	12.283	3.150	2.953	3.780	3.937	0.787	1.181	22.0
CZ4	1,100	8,800	0 to 1-1/4	7.756	14.606	3.150	2.677	3.661	5.079	0.787	1.181	26.5
CZ4L	1,100	8,800	1-1/8 to 2-3/8	8.976	15.354	3.150	2.677	3.661	5.079	0.787	1.181	39.7
CZ6	1,600	13,200	0 to 2	11.535	19.055	3.504	3.740	5.630	5.079	0.984	1.378	46.3
CZ8	2,150	17,600	0 to 2	11.535	19.370	3.504	3.740	5.630	5.079	0.984	1.654	57.3
CZ8L	2,150	17,600	2 to 4	14.252	20.630	3.504	4.488	5.630	5.079	0.984	1.654	70.5
CZ10	3,350	22,000	0 to 2	11.535	21.457	4.331	3.740	5.630	5.472	0.984	1.772	66.1
CZ10L*	3,350	22,000	2 to 4	14.252	21.457	4.331	4.488	5.630	5.472	0.984	1.772	81.6
CZ15	6,650	33,000	0 to 2	14.173	24.134	5.118	4.921	6.378	8.031	1.772	2.165	165.3
CZ15L*	6,650	33,000	2 to 4	18.110	26.693	5.118	6.890	6.378	8.031	1.772	2.165	194.0
CZ20*	8,850	44,000	0 to 2-1/2	18.189	29.724	5.118	6.496	8.268	9.252	1.772	2.559	271.2
CZ20L*	8,850	44,000	2-1/2 to 5	22.047	31.693	5.118	7.677	8.268	9.252	1.772	2.559	299.8
CZ30*	13,250	66,000	0 to 2-1/2	18.189	28.819	2.362	6.496	8.268	11.614	2.559	—	429.9

* Not stocked — available on request. Design factor 4:1. For use on hot rolled structural steel plates and sections up to 300 Brinell (32 HRC).

CALL FOR SIZING & APPLICATION SUPPORT

866-848-2032 · murphylift.com · CY, CX, LJ & HG clamps also available