

ENDLESS ROUNDSLINGS

POLYESTER · COLOR CODED BY CAPACITY · VERTICAL, CHOKER & BASKET HITCHES



HOW TO MEASURE

Length



⚠ Always protect roundslings from corners, edges, or protrusions. Refer to the Sling Protection section of this catalog to choose the right protection product for your lift.

Endless roundslings are continuous loop slings made of load-bearing polyester yarn encased in a protective double-wall cover. Color coding identifies rated capacity at a glance per **ASME B30.9**.

Can be used in vertical, choker, and basket hitch configurations. Flexible design conforms to irregular loads and minimizes load damage.

RATED CAPACITIES & SPECIFICATIONS

PART NUMBER	COLOR	RATED CAPACITY (LBS)				APPROXIMATE MEASUREMENTS				
		VERTICAL	CHOKER	BASKET @ 90°	BASKET @ 45°	MIN. LENGTH (FT)	WEIGHT (LBS/FT)	BODY DIA. RELAXED (IN.)	BODY WIDTH @ LOAD (IN.)	MIN. HDWR DIA.** (IN.)
ENR1	Purple	2,600	2,100	5,200	3,600	3'	0.30	0.625	1.00	0.44
ENR2	Green	5,300	4,200	10,600	7,400	3'	0.40	0.875	1.38	0.63
ENR3	Yellow	8,400	6,700	16,800	11,800	3'	0.50	1.125	1.75	0.75
ENR4	Tan	10,600	8,500	21,200	14,000	3'	0.60	1.125	1.88	0.88
ENR5	Red	13,200	10,600	26,400	18,000	3'	0.80	1.375	2.00	1.00
ENR6	White	16,800	13,400	33,600	23,000	6'	0.90	1.375	2.13	1.13
ENR7	Blue	21,200	17,000	42,400	29,000	6'	1.30	1.625	2.63	1.19
ENR8	Orange	25,000	20,000	50,000	35,000	6'	1.60	1.750	3.00	1.25
ENR9	Orange	31,000	24,800	62,000	43,000	6'	2.00	2.125	3.25	1.50
ENR10	Orange	40,000	32,000	80,000	56,000	6'	2.60	2.350	3.75	1.62
ENR11	Orange	53,000	42,400	106,000	74,000	8'	3.40	3.150	4.00	2.00
ENR12	Orange	66,000	52,800	132,000	93,000	8'	4.30	3.950	4.63	2.13
ENR13	Orange	90,000	72,000	180,000	127,000	8'	5.90	4.800	5.25	2.50

** Minimum recommended diameter for the connection hardware to be used for a vertical hitch. All rated capacities in lbs. Color coding per ASME B30.9. Polyester yarn construction.

FEATURES

- Polyester yarn core with double-wall protective sleeve
- Color coded by capacity per ASME B30.9
- Flexible — conforms to irregular load shapes
- Lightweight and easy to handle
- Non-marring surface protects finished loads
- Rated capacities from 2,600 to 200,000 lbs (basket)

HOW TO ORDER

- Specify part number and length in feet
- Custom lengths available
- Always use proper sling protection on edges

CALL FOR CUSTOM LENGTHS & BULK PRICING

866-848-2032 · murphylift.com · Same day shipping · Custom configurations available