

GRADE 100 WELDED MASTER LINKS

SINGLE LINKS › SUB-LINK ASSEMBLIES › CRANE HOOK ASSEMBLIES › TRADE SIZES 1/2" TO 2-3/4" › WLL TO 271,000 LBS.

Grade 100 welded alloy master links form the top connection of chain, wire rope and synthetic sling assemblies. Single links serve one- and two-leg slings; sub-link assemblies carry three- and four-leg slings; oversized master links suit large crane hooks. Working load limits are listed at both a **4:1 design factor** (chain slings) and a **5:1 design factor** (wire rope and synthetic slings).



WELDED MASTER LINK

TRADE SIZE (IN.)	WLL 4:1 (LBS.)*	WLL 5:1 (LBS.)**	WEIGHT (LBS.)	INSIDE DIMENSIONS (IN.)			CHAIN SIZE (IN.)	
				I-LENGTH	I-WIDTH	DIA.	1 LEG	2 LEG
1/2"	6,000	4,800	0.75	4.33	2.36	0.51	7/32 + 9/32 + 5/16	7/32
5/8"	8,750	7,000	1.47	5.51	3.15	0.63	5/16	9/32
3/4"	13,750	11,000	2.02	5.91	3.54	0.71	3/8	5/16
7/8"	17,600	14,080	3.30	6.30	3.54	0.87	1/2	3/8
1"	32,500	26,000	5.06	7.09	3.94	1.02	5/8	1/2
1-1/4"	45,200	36,160	8.58	7.87	4.33	1.26	3/4	5/8
1-1/2"	70,600	56,480	19.80	11.81	6.30	1.57	7/8	3/4
1-3/4"	85,400	68,320	28.16	13.39	7.09	1.77	1	7/8
2"	119,400	95,520	37.84	13.78	7.48	2.01	1-1/4	1
2-1/4"	180,800	144,640	53.24	15.75	7.87	2.24	—	1-1/4
2-1/2"	200,000	160,000	73.85	16.93	8.27	2.48	—	—
2-3/4"	271,000	216,800	101.41	18.11	9.84	2.80	—	—

MASTER LINK ASSEMBLIES WITH EXTRA LARGE SUB-LINKS

TRADE SIZE (IN.)	WLL 4:1 (LBS.)*	WLL 5:1 (LBS.)**	WEIGHT (LBS.)	INSIDE DIM. — MASTERS (IN.)			INSIDE DIM. — SUBS (IN.)			FOR CHAIN (IN.)
				I-LENGTH	I-WIDTH	DIA.	I-LENGTH	I-WIDTH	DIA.	
3/4"	12,900	10,320	3.52	5.91	3.54	0.71	4.33	2.36	0.51	7/32 + 9/32"
7/8"	17,100	13,680	5.63	6.30	3.54	0.87	4.33	2.36	0.63	9/32" + 5/16"
1"	26,400	21,120	8.58	7.09	3.94	1.02	5.31	2.95	0.71	3/8"
1-1/4"	45,000	36,000	15.18	7.87	4.33	1.26	6.30	3.55	0.87	1/2"
1-1/2"	67,800	54,240	24.09	10.24	5.51	1.42	7.09	3.94	1.02	5/8"
1-3/4"	105,900	84,720	67.24	13.39	7.09	1.75	11.81	6.3	1.63	3/4"

MASTER LINK ASSEMBLIES FOR LARGE CRANE HOOKS

TRADE SIZE (IN.)	WLL 4:1 (LBS.)*	WLL 5:1 (LBS.)**	WEIGHT (LBS.)	INSIDE DIM. — MASTERS (IN.)			INSIDE DIM. — SUBS (IN.)			CHAIN SIZE (IN.)
				I-LENGTH	I-WIDTH	DIA.	I-LENGTH	I-WIDTH	DIA.	
1-1/8"	17,100	13,680	14.37	13.40	7.10	1.18	4.33	2.36	0.63	9/32 - 5/16
1-1/8"	26,400	21,120	15.55	13.40	7.10	1.18	5.31	2.95	0.71	3/8
1-1/2"	45,000	36,000	28.60	13.40	7.10	1.57	6.30	3.54	0.87	1/2
1-1/2"	67,800	54,240	32.10	13.40	7.10	1.57	7.09	3.94	1.02	5/8

* For use with chain slings. ** For use with wire rope and synthetic slings. A dash indicates the configuration is not offered in that size. Grade 100 welded alloy steel.

CALL FOR CUSTOM SLING ASSEMBLIES

866-848-2032 · murphylift.com · Grade 100 chain, hooks & fittings in stock