

STAINLESS STEEL SHEAVES

TYPE 304 STAINLESS · PRECISION CAST · BRASS BUSHING · SHEAVE DIAMETERS 1" TO 5"




Precision cast type 304 stainless steel sheaves fitted with a brass bushing for smooth rotation and long service life. Corrosion resistant throughout, they suit marine, architectural and outdoor applications, and serve as replacement wheels for blocks, davits and running rigging.

BENEFITS & FEATURES

- **Type 304 stainless steel** — precision cast for consistent groove profile
- Fitted with a **brass bushing** for smooth, low-friction rotation
- Corrosion resistant for marine, outdoor and washdown service
- Sheave diameters from 1" through 5"
- Separate groove profiles for fibre rope and for wire cable
- Replacement sheaves for blocks, davits and running rigging

DIMENSIONS



FOR FIBRE ROPE

ITEM NO.	A — SHEAVE DIA. (IN.)	B — ROPE DIA. (IN.)	C (IN.)	D (IN.)	WEIGHT (LBS.)
3130S-25	1"	1/4"	0.32"	0.55"	0.20
3130S-32	1-1/4"	5/16"	0.32"	0.55"	0.24
3130S-50	2"	3/8"	0.40"	0.78"	0.50
3130S-75	3"	1/2"	0.52"	0.78"	0.80
3130S-75-A	3"	5/8"	0.52"	1.10"	0.85
3130S-100	4"	5/8"	0.66"	1"	1.20
3130S-100-A	4"	3/4"	0.66"	1.32"	1.26
3130S-125	5"	3/4"	0.68"	1"	1.50

FOR WIRE CABLE

ITEM NO.	A — SHEAVE DIA. (IN.)	B — CABLE DIA. (IN.)	C (IN.)	D (IN.)	WEIGHT (LBS.)
BLOC-SHFO-0005	3"	3/16"	0.52"	0.78"	0.88
BLOC-SHFO-0001	4"	1/4"	0.62"	0.87"	1.30
BLOC-SHFO-0003	5"	5/16"	0.62"	0.98"	2.25

APPLICATIONS

- Marine & sailboat running rigging
- Architectural cable systems
- Davits, hoists & block rebuilds
- Stage & theatre rigging
- Awning & canopy systems
- General light-duty pulley service

HOW TO ORDER

- Specify item number and rope or cable diameter
- Groove profile differs between rope and cable — order to match
- -A suffix denotes a wider groove on the same sheave diameter
- Wire cable sheaves are listed under their own SKUs
- Blocks, snatch blocks & swivel blocks also available

Type 304 stainless steel, precision cast with brass bushing. Dimensions in inches; A = sheave outside diameter, B = rope or cable diameter, C = bore, D = hub width. Sheaves are supplied without axle or side plates. No working load limit is published for these components — select the block or assembly rating for the application. Imported.

CALL FOR BLOCKS, PULLEYS & REPLACEMENT SHEAVES

866-848-2032 · murphylift.com · Snatch blocks, swivel blocks & stainless rigging in stock