

TURNBUCKLE BODIES & STUB ENDS


DROP FORGED • SELF-COLORED • ASTM F1145 • SIZES 3/8" TO 2-1/2" • WLL 1,200 TO 60,000 LBS.

BENEFITS & FEATURES

- Drop forged turnbuckle bodies and stub ends
- Meets the performance requirements of **ASTM F1145**
- Self-colored finish — some bodies available hot galvanized
- Order bodies separately to build custom assemblies with your choice of end fittings
- Stub ends supplied for welding or machining to suit the application
- Sizes 3/8" through 2-1/2" • take-ups 6" through 24"
- Working load limits from 1,200 to 60,000 lbs.
- **Recommended for straight or in-line pull only**



⚠ Turnbuckle bodies are recommended for straight or in-line pull only. Dimension F is measured in the closed position.



RATED CAPACITIES & DIMENSIONS

SIZE (IN.) DIA. (A) X TAKE-UP (B)	WORKING LOAD LIMIT (LBS.)	APPROX. WEIGHT EACH (LBS.)		DIMENSIONS (IN.)			
		BODY ONLY	STUB END	C	D	E	F*
3/8" x 6"	1,200	0.3	0.7	7.13	0.56	4.44	16.00
1/2" x 6"	2,200	0.6	1.4	7.50	0.75	4.25	16.00
1/2" x 9"	2,200	0.8	1.7	10.50	0.75	4.25	19.00
1/2" x 12"	2,200	1.0	1.8	13.50	0.75	4.25	22.00
5/8" x 6"	3,500	1.0	2.0	7.88	0.94	4.06	16.00
5/8" x 9"	3,500	1.2	2.5	10.88	0.94	4.06	19.00
5/8" x 12"	3,500	1.4	3.1	13.88	0.94	4.06	22.00
3/4" x 6"	5,200	1.2	3.3	8.25	1.13	4.38	17.00
3/4" x 9"	5,200	1.6	4.0	11.25	1.13	4.38	20.00
3/4" x 12"	5,200	2.1	4.8	14.25	1.13	4.38	23.00
3/4" x 18"	5,200	3.2	5.8	20.25	1.13	4.38	29.00
7/8" x 6"	7,200	1.8	4.5	8.63	1.31	4.69	18.00
7/8" x 12"	7,200	2.7	6.4	14.63	1.31	4.69	24.00
7/8" x 18"	7,200	3.8	—	20.63	1.31	—	—
1" x 6"	10,000	2.5	6.3	9.00	1.50	5.00	19.00
1" x 12"	10,000	4.2	8.9	15.00	1.50	5.00	25.00
1" x 18"	10,000	7.0	11.4	21.00	1.50	5.00	31.00
1" x 24"	10,000	7.4	—	27.00	1.50	—	—
1-1/8" x 6"	12,400	5.0	—	9.13	1.56	—	—
1-1/8" x 12"	12,400	5.4	—	15.13	1.56	—	—
1-1/4" x 6"	15,200	5.0	10.2	9.13	1.56	5.44	20.00
1-1/4" x 12"	15,200	5.4	13.6	15.13	1.56	5.44	26.00
1-1/4" x 18"	15,200	8.0	—	21.10	1.56	—	—
1-1/4" x 24"	15,200	10.2	—	27.13	1.56	—	—
1-3/8" x 6"	18,000	6.0	13.9	9.75	1.88	5.38	20.50
1-1/2" x 6"	21,400	5.7	15.1	9.75	1.88	5.38	20.50
1-1/2" x 12"	21,400	8.5	20.5	15.75	1.88	5.38	26.50
1-1/2" x 18"	21,400	11.0	—	21.75	1.88	—	—
1-1/2" x 24"	21,400	13.7	—	27.75	1.88	—	—
1-5/8" x 6"	25,000	8.2	—	10.38	2.19	—	—
1-3/4" x 6"	28,000	10.3	22.5	10.38	2.19	5.80	22.00
2" x 6"	37,000	14.2	34.0	11.00	2.50	6.00	23.00
2" x 24"	37,000	30.0	—	29.00	2.50	—	—
2-1/2" x 6"	60,000	33.0	68.0	13.50	3.75	6.25	26.00

* Closed position. Meets the performance requirements of ASTM F1145. Self-colored finish; some bodies available hot galvanized. Drop forged. A dash indicates the size is not offered in that configuration.

CALL FOR CUSTOMIZED CONFIGURATIONS

866-848-2032 • murphylift.com • End fittings, hot galvanized bodies & custom assemblies available