

4-LEG BRIDLE WIRE ROPE SLINGS

With Eye Hoist Hooks



M-Sling 4-leg all-purpose bridles, designed for general lifting purposes where attachment may be made directly to the load, such as hooking into lifting eyes or placing loops over lugs.

Rated capacities based on design factor of **5 to 1**.

Horizontal sling angles less than 30° shall not be used.

* In some cases, oblong master links are larger in capacity than required, but are sized to accommodate heavy duty thimbles. If thimbles are not required, a smaller master link can sometimes be used.

** Does not include hardware.

60°

ANGLE TO HORIZ.

45°

ANGLE TO HORIZ.

30°

ANGLE TO HORIZ.

RATED CAPACITIES & SPECIFICATIONS

ROPE DIA.	EIPS CAPACITIES (TONS) (Angle to Horizontal)			ALLOY OBLONG MASTER LINK* DIA. (IN.)	EYE HOOK (TONS)	MINIMUM SLING LENGTH**
	60°	45°	30°			
1/4"	2.2	1.8	1.3	3/4	1T	1'3"
3/8"	5	4.1	2.9	3/4	2T	1'8"
1/2"	8.8	7.1	5.1	1	3T	2'
5/8"	14	11	7.8	1-1/4	5T	2'4"
3/4"	19	16	11	1-1/2	7T	2'9"
7/8"	26	21	15	1-3/4	11T	3'3"
1"	34	28	20	2	11T	3'6"
1-1/8"	42	34	24	2	15T	4'
1-1/4"	51	42	30	2-1/4	15T	4'6"
1-3/8"	62	50	36	(Pear Link) 2-3/4	22T	5'
1-1/2"	73	60	42	(Pear Link) 2-3/4	22T	5'6"
1-3/4"	98	80	57	(Pear Link) 3	30T	6'6"
2"	127	104	73	(Pear Link) 3-1/4	37T	8'

FEATURES

- * In some cases, oblong master links are larger in capacity than required, but are sized to accommodate heavy duty thimbles. If thimbles are not required, a smaller master link can sometimes be used.
- Eye hooks on bottom. Thimbles on top.
- Eye hooks on bottom. Thimbles on top.
- Flemished eye splice, not a Texas tucked or turn back eye splice
- Heavy gauge stainless steel tag per ASME B30.9 and API RP2D
- Quality controlled swaging process with paint verification
- 6x19 class IWRC EIP bright wire rope standard on 1/4" – 1-1/8"
- 6x37 class IWRC EIP bright wire rope standard on 1-1/4" and larger
- Proof testing available upon request
- Design factor 5 to 1

HOW TO ORDER

- Specify part number and length in feet when ordering

CALL FOR CUSTOMIZED CONFIGURATIONS

866-848-2032 · murphylift.com · Custom lengths, fittings & multi-leg assemblies available