


DROP FORGED WIRE ROPE CLIPS

HOT DIP GALVANIZED • FEDERAL SPECIFICATION FF-C-450D, TYPE 1, CLASS 1 • SIZES 1/8"–3"



DIMENSION REFERENCE



Wire rope clips clamp the dead end of a wire rope back onto the live end to form a secure loop. Drop forged from one continuous piece of steel and hot dip galvanized for corrosion resistance.

FEATURES

- Drop forged from one continuous piece of steel for maximum strength
- Hot dip galvanized — U-bolt, saddle & nuts
- Meets Federal Specification **FF-C-450D, Type 1, Class 1**
- The only wire rope clip type approved for overhead lifting
- Available in sizes 1/8" through 3"
- Use with a thimble to extend wire rope service life

WARNING: Improper use or installation can result in serious injury or death. Forged clips are the only wire rope clip approved for lifting purposes.

SIZES, APPLICATION DATA & DIMENSIONS

PART NO.	SIZE	MIN. CLIPS	ROPE TURN BACK	TORQUE (FT. LBS.)*	DIMENSIONS (IN.)							APPROX. WT. (LBS.)
					A	B	C	D	E	F	G	
435000	1/8"***	2	3-1/4"	4.5	0.19	0.81	0.38	0.44	0.44	0.75	0.94	0.05
435025	3/16"***	2	3-3/4"	7.5	0.25	0.94	0.50	0.56	0.56	0.94	1.19	0.10
435050	1/4"	2	4-3/4"	15	0.31	1.19	0.63	0.56	0.56	1.06	1.50	0.18
435075	5/16"	2	5-1/4"	30	0.38	1.31	0.75	0.75	0.75	1.44	1.69	0.31
435100	3/8"	2	6-1/2"	45	0.44	1.56	0.88	0.75	0.75	1.50	1.94	0.46
435125	7/16"	3	7"	65	0.50	1.81	1.00	1.00	1.00	1.88	2.31	0.73
435150	1/2"	3	11-1/2"	65	0.50	1.81	1.06	1.00	1.00	1.88	2.31	0.73
435175	9/16"	3	12"	95	0.56	2.06	1.13	1.25	1.25	2.38	2.50	0.96
435200	5/8"	3	12"	95	0.56	2.06	1.25	1.25	1.25	2.38	2.50	1.00
435225	3/4"	4	18"	130	0.63	2.31	1.38	1.38	1.38	2.75	2.75	1.50
435250	7/8"	4	19"	225	0.75	2.63	1.69	1.44	1.44	3.19	3.31	2.44
435275	1"	5	26"	225	0.75	2.63	1.75	1.75	1.75	3.63	3.47	2.70
435300	1-1/8"	6	34"	225	0.75	2.81	1.88	2.00	2.00	4.00	3.56	3.10
435325	1-1/4"	7	44"	360	0.88	3.25	2.06	2.25	2.25	4.38	4.06	4.60
435350	1-3/8"	7	44"	360	0.88	3.44	2.25	2.31	2.31	4.63	4.25	5.20
435375	1-1/2"	8	54"	360	0.88	3.50	2.50	2.38	2.38	4.94	4.38	5.90
435400	1-5/8"	8	58"	430	1.00	3.61	2.66	2.62	2.62	5.31	4.75	7.34
435425	1-3/4"	8	61"	590	1.13	3.75	2.88	2.75	2.75	5.88	5.25	9.80
435450	2"	8	71"	750	1.25	4.44	3.38	3.00	3.00	6.50	5.81	13.75
435475	2-1/4"	8	73"	750	1.25	4.50	3.81	3.31	3.31	7.13	6.31	15.70
435500	2-1/2"	9	84"	750	1.25	4.50	4.25	3.38	3.38	7.75	6.44	17.90
435525	2-3/4"	10	100"	750	1.25	5.00	5.00	3.50	3.50	8.31	6.75	22.00
435550	3"	10	106"	1,200	1.50	5.31	5.25	3.88	3.88	9.19	7.56	32.00

*Based on clean, unlubricated threads; minimum torque required to reach maximum holding power. **U-bolts and nuts zinc plated. Dimensions may vary.

APPLICATION & INSTALLATION

- 1 Apply the first clip one base width from the dead end of the wire rope. The base or saddle must bear on the **live** end — U-bolt on the short (dead) end. Tighten nuts firmly.
- 2 Attach the second clip as close to the loop as possible. Tighten the nuts, but not firmly.
- 3 Space the balance of clips equally between the first two. Tighten all nuts completely, apply initial load, then inspect and retighten. Inspect all clips periodically.

Clip quantities are based on right regular or Lang lay wire rope, 6x19 or 6x37 class, fibre core, IWRC, IPS or XIPS. They also apply to right regular lay wire rope, 8x19 and 18x7 class, fibre core, IPS or XIPS, in sizes 1-1/2" and smaller.

For Seale construction or similar large outer wire construction in the 6x19 class in sizes 1" and larger, add one additional clip. For other classes not listed, additional clips may be required. If more clips are used than shown, increase the rope turn back proportionately.

CALL FOR CUSTOM ASSEMBLIES & BULK PRICING

866-848-2032 • murphylift.com • Thimbles, wire rope & sleeves also available