

# JAW & JAW TURNBUCKLE ASSEMBLIES



DROP-FORGED CARBON STEEL • SELF-COLORED OR HOT-DIP GALVANIZED • 500–10,000 LB RATED CAPACITY



⚠ Inspect before each use and never exceed the rated capacity. Apply load through the jaw end fittings only — do not side-load.

Drop-forged carbon steel turnbuckle assemblies with **jaw & jaw** end fittings, for adjustable tensioning of rigging, guy wire, and structural assemblies. Available **self-colored** or **hot-dip galvanized (HDG)** — both finishes share identical dimensions and rated capacities.

- Drop-forged carbon steel body & jaw fittings
- Self-colored or hot-dip galvanized finish
- Take-up lengths from 4" to 12"
- Diameters 1/4" through 1"
- Rated capacities 500–10,000 lbs
- Forged and assembled in the U.S.A.

**500–10,000**

RATED CAP. (LBS.)

**1/4"–1"**

DIAMETER RANGE

**U.S.A.**

DROP-FORGED

## RATED CAPACITIES & DIMENSIONS

| PART NO.           |                  | DIAMETER & THREAD | TAKE-UP (IN.) | OAL • CLOSED LENGTH (IN.) | WEIGHT (LBS.) | RATED CAP. (LBS.) |
|--------------------|------------------|-------------------|---------------|---------------------------|---------------|-------------------|
| SELF-COLORED       | GALVANIZED (HDG) |                   |               |                           |               |                   |
| <b>TB101-4-J-J</b> | TB101-4-J-J-ZN*  | 1/4-20            | 4             | 9                         | 0.49          | <b>500</b>        |
| <b>TB102-J-J</b>   | TB102-J-J-HDG    | 5/16-18           | 4 1/2         | 10 1/4                    | 0.60          | <b>800</b>        |
| <b>TB103-J-J</b>   | TB103-J-J-HDG    | 3/8-16            | 6             | 12 3/8                    | 1.07          | <b>1,200</b>      |
| <b>TB105-3-J-J</b> | TB105-3-J-J-HDG  | 1/2-13            | 3             | 10 3/8                    | 1.53          | <b>2,200</b>      |
| <b>TB105-4-J-J</b> | TB105-4-J-J-HDG  | 1/2-13            | 4             | 11 3/16                   | 1.57          | <b>2,200</b>      |
| <b>TB105-J-J</b>   | TB105-J-J-HDG    | 1/2-13            | 6             | 12 3/8                    | 1.69          | <b>2,200</b>      |
| <b>TB105-9-J-J</b> | TB105-9-J-J-HDG  | 1/2-13            | 9             | 16 3/4                    | 3.28          | <b>2,200</b>      |
| <b>TB105-J-J-J</b> | TB105-J-J-J-HDG  | 1/2-13            | 12            | 19 3/4                    | 2.44          | <b>2,200</b>      |
| <b>TB107-3-J-J</b> | TB107-3-J-J-HDG  | 5/8-11            | 3             | 13 9/16                   | 2.57          | <b>3,500</b>      |
| <b>TB107-4-J-J</b> | TB107-4-J-J-HDG  | 5/8-11            | 4             | 14 5/8                    | 2.75          | <b>3,500</b>      |
| <b>TB107-J-J</b>   | TB107-J-J-HDG    | 5/8-11            | 6             | 15 5/8                    | 3.02          | <b>3,500</b>      |
| <b>TB107-9-J-J</b> | TB107-9-J-J-HDG  | 5/8-11            | 9             | 18 7/8                    | 4.60          | <b>3,500</b>      |
| <b>TB107-J-J-J</b> | TB107-J-J-J-HDG  | 5/8-11            | 12            | 21 7/8                    | 5.28          | <b>3,500</b>      |
| <b>TB108-J-J</b>   | TB108-J-J-HDG    | 3/4-10            | 6             | 16 3/4                    | 4.78          | <b>5,200</b>      |
| <b>TB108-9-J-J</b> | TB108-9-J-J-HDG  | 3/4-10            | 9             | 19 3/4                    | 5.64          | <b>5,200</b>      |
| <b>TB108-J-J-J</b> | TB108-J-J-J-HDG  | 3/4-10            | 12            | 22 5/8                    | 6.41          | <b>5,200</b>      |
| <b>TB109-J-J</b>   | TB109-J-J-HDG    | 7/8-9             | 6             | 22                        | 7.11          | <b>7,200</b>      |
| <b>TB109-J-J-J</b> | TB109-J-J-J-HDG  | 7/8-9             | 12            | 25 3/8                    | 9.42          | <b>7,200</b>      |
| <b>TB110-J-J</b>   | TB110-J-J-HDG    | 1-8               | 6             | 20 3/16                   | 9.51          | <b>10,000</b>     |
| <b>TB110-J-J-J</b> | TB110-J-J-J-HDG  | 1-8               | 12            | 25 5/8                    | 11.69         | <b>10,000</b>     |

Self-colored and galvanized (HDG) assemblies share identical dimensions, weights, and rated capacities. \*1/4" galvanized is zinc-plated (not hot-dip) and is not tapped oversized — part No. TB101-4-J-J-ZN. All dimensions in inches; weights and rated capacities in lbs. Drop-forged carbon steel. Inspect before each use and remove from service if damaged.

**FROM COMMON TO CUSTOM — WE DO IT ALL**

866-848-2032 • murphylift.com • 80% of orders ship same day • Free shipping on orders \$50+