

EYE & EYE FLAT WEB SLINGS



POLYESTER · 1-4 PLY · 1" TO 12" WEB WIDTH · VERTICAL, CHOKER & BASKET HITCHES

M-SLING EYE & EYE WEB SLING



⚠ Always protect web slings from corners, edges, or protrusions. Refer to the Sling Protection section of this catalog to choose the right protection product for your lift.

Eye & eye flat web slings are made from high-strength polyester webbing with a flat loop eye formed at each end. The wide bearing surface spreads load over the lift point, protecting finished and coated surfaces.

Available in one, two, three and four ply constructions to suit the capacity required. Every sling carries a durable label listing rated capacities for **vertical, choker and basket** hitches per **ASME B30.9**.

RATED CAPACITIES & SPECIFICATIONS

PART NUMBER	WEB WIDTH	RATED CAPACITY (LBS.)			EYE DIMENSIONS (IN.)		MIN. STANDARD LENGTH (FT.)	APPROX. WEIGHT (LBS.)	
		VERTICAL	CHOKER	VERTICAL BASKET	WIDTH	LENGTH		BASE	ADDER / FT.
ONE PLY									
EE191	1"	1,600	1,250	3,200	1	9	3'	0.4	0.06
EE192	2"	3,200	2,560	6,400	2	9	4'	0.9	0.12
EE193	3"	4,800	3,840	9,600	1-1/2	9	4'	1.4	0.18
EE194	4"	6,400	5,120	12,800	2	12	4'	1.9	0.24
EE196	6"	9,600	7,680	19,200	2	14	5'	3.4	0.36
EE198	8"	12,800	10,240	25,600	3	18	6'	5.3	0.48
EE1910	10"	16,000	12,800	32,000	4	22	8'	8.0	0.60
EE1912	12"	19,200	15,360	38,400	5	26	8'	9.8	0.72
TWO PLY									
EE291	1"	3,200	2,560	6,400	1	9	3'	0.4	0.13
EE292	2"	6,400	5,120	12,800	2	9	3'	0.9	0.25
EE293	3"	9,300	7,440	18,600	1-1/2	12	4'	1.7	0.38
EE294	4"	11,500	9,200	23,000	2	12	4'	2.3	0.50
EE296	6"	16,500	13,200	33,000	2	14	6'	4.9	0.76
EE298	8"	22,750	18,200	45,500	3	18	6'	6.5	1.0
EE2910	10"	28,400	22,720	56,800	4	22	7'	9.4	1.3
EE2912	12"	34,100	27,280	68,200	5	26	8'	13	1.5
THREE PLY									
EE391	1"	4,100	3,280	8,200	1	12	4'	1.0	0.20
EE392	2"	8,300	6,640	16,600	2	12	4'	2.1	0.40
EE393	3"	12,500	10,000	25,000	1-1/2	18	5'	3.7	0.59
EE394	4"	16,000	12,800	32,000	2	18	5'	5.0	0.79
EE396	6"	23,000	18,400	46,000	3	20	5'	7.6	1.2
EE398	8"	30,700	24,560	61,400	4	24	7'	13	1.6
EE3910	10"	36,800	29,440	73,600	5	28	7'	16	2.0
EE3912	12"	44,000	35,200	88,000	6	32	7'	20	2.4
FOUR PLY									
EE491	1"	6,200	4,960	12,400	1	12	4'	1.1	0.26
EE492	2"	12,400	9,920	24,800	2	12	4'	2.2	0.53
EE493	3"	17,000	13,600	34,000	1-1/2	18	5'	4.1	0.79
EE494	4"	22,000	17,600	44,000	2	18	5'	5.5	1.1
EE496	6"	33,000	26,400	66,000	3	20	5'	8.3	1.6
EE498	8"	44,000	35,200	88,000	4	24	7'	15	2.1
EE4910	10"	55,000	44,000	110,000	5	28	7'	19	2.6
EE4912	12"	66,000	52,800	132,000	6	32	7'	23	3.2

All rated capacities in pounds, based on a 5:1 design factor. Capacities apply to polyester webbing at the ply and width shown. Basket capacity shown is for a vertical (90°) basket hitch — reduce for any other angle. Approximate sling weight = base weight plus the per-foot adder times the sling length. Meets ASME B30.9 and WSTD-WB-1. Before ordering slings for use in a chemically active environment, call for a recommendation.

FEATURES

- Polyester webbing — high strength with controlled stretch
- Flat eye & eye design for vertical, choker and basket hitches
- Available in one, two, three and four ply constructions
- Web widths from 1" through 12"
- Abrasion-resistant, non-marring against finished loads
- Color-coded label with rated capacities for all three hitches
- Meets or exceeds ASME B30.9 and WSTD-WB-1 standards
- 5:1 design factor · proof tested

HOW TO ORDER

- Specify part number and overall length in feet
- Length is measured bearing point to bearing point
- Custom lengths, widths & ply counts available
- Add sleeves or edge guards for abrasive loads
- Always use proper sling protection on corners & edges

CALL FOR CUSTOM LENGTHS & BULK PRICING

866-848-2032 · murphylift.com · Same day shipping · Custom configurations available