

Week6 Assignment

Task1:

Considering the same example you solved in the previous assignment (radiative heat transfer between two parallel plates), how many shields with $\epsilon=0.1$ should you add in order to have the new heat transfer rate to be 1% of the case without shields?

Answer:

$$q_{12} = \frac{Q_{12}}{A} = \frac{A\sigma (T_1^4 - T_2^4)}{\frac{1}{\epsilon_1} + \frac{1}{\epsilon_2} - 1} \div A = \frac{5.67 \times 10^{-8} \times (800^4 - 500^4)}{\frac{1}{0.2} + \frac{1}{0.7} - 1} \approx 3625.3491 \text{ W}$$

$$\begin{aligned} q'_{12\text{shield}} &= \frac{Q_{12\text{shield}}}{A} \\ &= \frac{A\sigma (T_1^4 - T_2^4)}{(\frac{1}{\epsilon_1} + \frac{1}{\epsilon_2} - 1)(\frac{1}{\epsilon_{3.1}} + \frac{1}{\epsilon_{3.2}} - 1) \dots (\frac{1}{\epsilon_{n.1}} + \frac{1}{\epsilon_{n.2}} - 1)} \div A \\ &= \frac{\sigma (T_1^4 - T_2^4)}{(\frac{1}{\epsilon_1} + \frac{1}{\epsilon_2} - 1)(\frac{1}{\epsilon_{3.1}} + \frac{1}{\epsilon_{3.2}} - 1) \dots (\frac{1}{\epsilon_{n.1}} + \frac{1}{\epsilon_{n.2}} - 1)} \end{aligned}$$

$$\epsilon_1 = \epsilon_2 = \epsilon_3 = \dots = \epsilon_{n-1} = \epsilon_n = 0.1$$

$$\begin{aligned} q'_{12\text{shield}} &= \frac{\sigma (T_1^4 - T_2^4)}{(\frac{1}{\epsilon_1} + \frac{1}{\epsilon_2} - 1)(\frac{1}{\epsilon_{3.1}} + \frac{1}{\epsilon_{3.2}} - 1) \dots (\frac{1}{\epsilon_{n.1}} + \frac{1}{\epsilon_{n.2}} - 1)} \\ &= \frac{\sigma (T_1^4 - T_2^4)}{(n+1)(\frac{1}{0.1} + \frac{1}{0.1} - 1)} = \frac{1}{100} \times \frac{\sigma (T_1^4 - T_2^4)}{(\frac{1}{0.2} + \frac{1}{0.7} - 1)} \end{aligned}$$

$$\rightarrow n = 28$$


So we need 28 shields with $\epsilon=0.1$ in order to have the new heat transfer rate to be 1% of the case without shields.

Task2:


You should create a pdf file with screenshots of all the steps we went through (clearly from your own file) and explain briefly the reason behind the use of each step (in your own words)

Answer:


1. At first, draw the outline and shape of the building in Sketchup.




2. Use the command “Creat spaces from diagram” to creat a three floors building.




3. By using the command “Info tool”, you can see the material information about the building.




4. Then click the command “Surface matching”.





5. Find “User input” and build windows by using “Windows to Wall Ratio “.




6. Find “Surface search”, you can use Surface Orientation to build the windows on other side.




7. Next step is make overhangs by using “ Projection Factor” .




8. Open “Default Tray”.








9. Choose the space of each thermal zone .




10. Using “ Set Attributes for Selected Spaces” to set parent thermal zone’s thermostat.











11. Saving the model.



12. Run the “Launch Open Studio” and add the design date .



13. Click the “Run Simulation”.



14. You can see the Result Summary .

